

Atlas Copco

Model: ZBP 2000

AC Input: 120V 15A Max 50/60Hz

AC Output: 120V 20A Max(total) 50/60Hz

Or 120V 15A Max(total) 50/60Hz (when input is connected with AC mains together)

USB TYPE A+TYPE C Output: 5.0Vdc 2.0A 10.0W

Capacity: 45Ah 2160Wh

USB TYPE A Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max

USB TYPE C Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max

Charge Temp.: 0°C~45°C Discharge Temp.: -20°C~45°C Produced in 2023.10

Atlas Copco(Wuxi) Compressor Co.,Ltd. No 45 Ximei Road, Xinwu District,Wuxi, P.R.C



S/N: WUP 600324

Solar Input: 12-60Vdc 15A Max

IP55 IK09



FCC ID:2BBHM-ZBP2000
IC:30663-ZBP2000



Atlas Copco

Model: ZBP 2000 PREDEFINED

AC Input: 120V 15A Max 50/60Hz

AC Output: 120V 20A Max(total) 50/60Hz

Or 120V 15A Max(total) 50/60Hz (when input is connected with AC mains together)

USB TYPE A+TYPE C Output: 5.0Vdc 2.0A 10.0W

Capacity: 45Ah 2160Wh

USB TYPE A Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max

USB TYPE C Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max

Charge Temp.: -20°C~45°C Discharge Temp.: -20°C~45°C Produced in 2023.10

Atlas Copco(Wuxi) Compressor Co.,Ltd. No 45 Ximei Road, Xinwu District,Wuxi, P.R.C



S/N: WUP 600324

Solar Input: 12-60Vdc 15A Max

IP55 IK09




FCC ID:2BBHM-ZBP2000
IC:30663-ZBP2000





Model: ZBP 2000
 AC Input: 120V 15A Max 50/60Hz
 AC Output: 120V 20A Max(total) 50/60Hz
 Or 120V 15A Max(total) 50/60Hz (when input is connected with AC mains together)
 USB TYPE A+TYPE C Output: 5.0Vdc 2.0A 10.0W Capacity: 45Ah 2160Wh
 USB TYPE A Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max
 USB TYPE C Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max
 Charge Temp.: 0°C~45°C Discharge Temp.: -20°C~45°C Produced in 2023.10
 Atlas Copco(Wuxi) Compressor Co.,Ltd. No 45 Ximei Road, Xinwu District,Wuxi, P.R.C


S/N: WUP 600324
 Solar Input: 12-60Vdc 15A Max
 IP55 IK09



Model: ZBP 2000 PREDEFINED
 AC Input: 120V 15A Max 50/60Hz
 AC Output: 120V 20A Max(total) 50/60Hz
 Or 120V 15A Max(total) 50/60Hz (when input is connected with AC mains together)
 USB TYPE A+TYPE C Output: 5.0Vdc 2.0A 10.0W Capacity: 45Ah 2160Wh
 USB TYPE A Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max
 USB TYPE C Output: 5.0Vdc 3.0A/9.0Vdc 2.0A/12.0Vdc 1.5A 18.0W Max
 Charge Temp.: -20°C~45°C Discharge Temp.: -20°C~45°C Produced in 2023.10
 Atlas Copco(Wuxi) Compressor Co.,Ltd. No 45 Ximei Road, Xinwu District,Wuxi, P.R.C



S/N: WUP 600324
 Solar Input: 12-60Vdc 15A Max
 IP55 IK09





WARNING Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.
MAVERTISSEMENT: Ne pas surcharger la batterie interne. Consultez le manuel d'utilisation. Il ne faut pas fumer, allumer une allumette ou produire des étincelles à proximité du bloc d'alimentation. Charger la batterie uniquement dans un endroit bien aéré.

200W 100W Max Output
AC Output: 120V~2.0A Max Output
USB Type-A Output: 5.0V/3.0A & 5.0V/2.0A
USB Type-C Output: 5.0V/3.0A & 5.0V/2.0A
SIN: WUP 400026
Date of Birth: 2023/03/12
Rev: 1.0
Model: WUP 4000
Capacity: 126Wh
Max. Charge Power: 120W
Max. Discharge Power: 100W
Max. Charge Current: 2.0A
Max. Discharge Current: 2.0A
Max. Charge Voltage: 12.8V
Max. Discharge Voltage: 11.8V
Max. Charge Time: 6h
Max. Discharge Time: 10h
Max. Operating Time: 10h
Max. Storage Time: 30 days
Max. Shelf Life: 3 years
Max. Operating Temperature: 0°C to 40°C
Max. Storage Temperature: -20°C to 60°C
Max. Humidity: 5% to 95%
Max. Altitude: 3000m
Max. Transport Weight: 5.5kg
Max. Packing Weight: 5.8kg
Max. Dimensions: 350x250x280mm
FC
CE
RoHS

Label Location