

RF Exposure evaluation

Product Name : Barcode scanner
FCC ID : 2BBKD-G2-B
Test Standard : KDB447498 D04 General RF Exposure Guidance v01

According to 447498 D04 Interim General RF Exposure Guidance v01

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

BLE:Ant gain = **-1.36** dBi
MAX output power : **-1.805dBm@2402MHz**
ERP=-1.805-1.36-2.15=-5.315dBm
WORSE CASE:
 $10^{-0.1805} = 0.66\text{mW} < 2.715 \text{ mW}$

Then SAR evaluation is not required

2.4G:

$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2/30$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{((\text{dBuV/m})/20)}/10^6$

d = measurement distance in meters (m)---3m

So $\text{pt} = (\text{EXd})^2/30 \times \text{gt}$

Ant gain = 0 dBi [-2.15dBd]

Field strength = 93.79 dB μ V/m @3m @2440MHz

So $\text{Pt} = \{ [10^{(93.79/20)}/10^6 \times 3]^2/30 \} \times 1000 \text{ mW} = 0.7230\text{mW} < 2.781\text{mW}$

So $\text{ERP} = 0.7230 \times 0.61 = 0.44 < 2.781\text{mW}$

Then SAR evaluation is not required