

RF TEST REPORT

FCC ID: 2BBLK-WL2079T

Test Report No.....: RF230809011-01-001

Product(s) Name.....: WiFi+BT Module

Model(s).....: WL00024

Trade Mark.....: MTK

Applicant.....: Huizhou Speed Wireless Technology Co., Ltd

Address.....: No. 138 Huize Road, Hi-Tech Industrial Park of East River, Zhongkai
Hi-tech District, Huizhou City, Guangdong Province, China

Receipt Date.....: 2023.08.09

Test Date.....: 2023.10.08~2023.10.21

Issued Date.....: 2023.10.21

Standards.....: 47 CFR FCC Part 15, Subpart C(Section 15.247)
ANSI C63.10:2013

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Black Ding	Tim Zhang	Misue Su	
<i>Black Ding</i>	<i>Tim.zhang</i>	<i>Misue Su</i>	

Table of Contents

History of this test report.....	4
1. General Information	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Basic Description of Equipment Under Test.....	5
1.4 Transmit Operating Mode	6
2. Summary of Test Results	7
2.1 Summary of Test Items	7
2.2 Application of Standard.....	7
2.3 Test Instruments	8
2.4 Test Mode	9
2.5 Test Condition	10
2.6 Duty Cycle of Test Signal	10
2.7 Measurement Uncertainty.....	14
2.8 Test Location.....	14
2.9 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED ..	14
2.10 Description of Support Units	14
2.11 Deviation from Standards	14
3. Test Procedure And Results	15
3.1 AC Power Line Conducted Emission	15
3.1.1 Limit.....	15
3.1.2 Test Procedure	15
3.1.3 Test Setup	15
3.1.4 Test Result.....	16
3.2 Radiated Emission and Band Edge	18
3.2.1 Limit.....	18
3.2.2 Test Procedure	18
3.2.3 Test Setup	19
3.2.4 Test Result.....	21
3.3 Spurious Emission at Antenna Port	53

3.3.1	Limit	53
3.3.2	Test Procedure	53
3.3.3	Test Setup	54
3.3.4	The Result	55
3.4	6dB Bandwidth.....	121
3.4.1	Limit	121
3.4.2	Test Procedure	121
3.4.3	Test Setup	121
3.4.4	Test Result.....	122
3.5	Maximum conducted output power	160
3.5.1	Limit	160
3.5.2	Test Procedure	160
3.5.3	Test Setup	160
3.5.4	Table of Parameters of Text Software Setting.....	161
3.5.5	The Result	162
3.6	Power Spectral Density.....	164
3.6.1	Limit.....	164
3.6.2	Test Procedure	164
3.6.3	Test Setup	164
3.6.4	The Result	165

History of this test report

Original Report Issue Date: 2023.10.21

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. General Information

1.1 Applicant

Huizhou Speed Wireless Technology Co., Ltd

No. 138 Huize Road, Hi-Tech Industrial Park of East River, Zhongkai Hi-tech District, Huizhou City, Guangdong Province, China

1.2 Manufacturer

Huizhou Speed Wireless Technology Co., Ltd

No. 138 Huize Road, Hi-Tech Industrial Park of East River, Zhongkai Hi-tech District, Huizhou City, Guangdong Province, China

1.3 Basic Description of Equipment Under Test

Report No.	POC230809011-S001	
Report Name	WiFi+BT Module	
Model Name	WL00024	
Trade Mark	MTK	
Power Supply	DC 3.3V~12V	
Operate temperature	0℃-60℃	
EUT Stage	○ Product Unit	● Final-Sample
Operating Band and Conducted Output Power (Max power)	2400MHz ~ 2483.5MHz	●IEEE 802.11b: 21.39dBm
Product Type	IEEE 802.11b: WLAN (2TX) IEEE 802.11g: WLAN (2TX) IEEE 802.11n: WLAN (2TX) IEEE 802.11ax: WLAN (2TX)	
Nominal Bandwidth	20MHz / 40MHz	
Modulation	IEEE 802.11b: DSSS (DBPSK / DQPSK / CCK) IEEE 802.11g: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ax: OFDMA (BPSK / QPSK / 16QAM / 64QAM)	
Data Rate (Mbps)	IEEE 802.11b mode: DSSS (1/2/5.5/11) IEEE 802.11g mode: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n mode: up to 300 Mbps IEEE 802.11ax mode: up to 573.6 Mbps	
Antenna gain	Ant1: 3.6dBi, Ant2: 2.4dBi	
Antenna type	PCB antenna	

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz), 802.11ax (20MHz):

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400MHz ~ 2483.5 MHz	01	2412MHz	07	2442MHz
	02	2417MHz	08	2447MHz
	03	2422MHz	09	2452MHz
	04	2427MHz	10	2457MHz
	05	2432MHz	11	2462MHz
	06	2437MHz	/	/

Seven channels are provided for 802.11n (40MHz), 802.11ax (40MHz):

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400MHz ~ 2483.5 MHz	03	2422 MHz	07	2442MHz
	04	2427MHz	08	2447MHz
	05	2432MHz	09	2452MHz
	06	2437MHz	/	/

Note: For 802.11ax mode only support full RU mode.

1.4 Transmit Operating Mode

Transmit Operating Mode					Transmit Multiple Antennas					
☐	Operating mode 1 (single antenna)				☐	1TX				
☒	Operating mode 2 (multiple antenna, no beam forming)				☒	2TX	☐	3TX	☐	4TX
☐	Operating mode 3 (multiple antenna, with beam forming)				☐	2TX	☐	3TX	☐	4TX
☒	802.11b	Operating mode	☐	1TX	☒	2TX	☐	3TX		
☒	802.11g	Operating mode	☐	1TX	☒	2TX	☐	3TX		
☒	802.11n(20MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX		
☒	802.11n(40MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX		
☒	802.11ax(20MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX		
☒	802.11ax(40MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX		

2. Summary of Test Results

2.1 Summary of Test Items

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Test item	FCC Clause	Results	Remarks
AC Power Conducted Emission	15.207	Pass	Meet the requirement of the limit
Radiated Emission and Band Edge Measurement	15.205/15.209 /15.247(d)	Pass	Meet the requirement of the limit
Spurious Emission at Antenna Port	15.247(d)	Pass	Meet the requirement of the limit
6dB Bandwidth	15.247(a)(2)	Pass	Meet the requirement of the limit
Maximum Conducted Power	15.247(b)	Pass	Meet the requirement of the limit
Power Spectral Density	15.247(e)	Pass	Meet the requirement of the limit
Antenna Requirements	15.203	Compliance	Note
Note: The EUT has 2 PCB antennas arrangement which was permanently attached.			

2.2 Application of Standard

47 CFR FCC Part 15, Subpart C (Section 15.247)

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10:2013

2.3 Test Instruments

Radiated Emissions						
No.	Equipment	Manufacturer	Type No.	Serial No.	Cal. date (yyyy/mm/dd)	Cal. Due date (yyyy/mm/dd)
1	Test receiver	Rohde&Schwarz	ESU	100184	2023/5/3	2024/5/2
2	Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-127 3	2023/4/23	2024/4/22
3	Low frequency amplifier	Unknown	LNA 0920N	2014	2023/5/3	2024/5/2
4	High frequency amplifier	Schwarzbeck	BBV 9718	284	2023/5/3	2024/5/2
5	Loop Antenna	Schwarzbeck	FMZB1519 B	00029	2022/7/4	2025/7/3
6	Log periodic antenna	Schwarzbeck	VULB 9168	1151	2023/4/23	2024/4/22
7	Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-127 3	2022/5/5	2025/5/4
8	Horn Antenna	Schwarzbeck	BBHA 9170	9170#685	2022/7/4	2025/7/3
9	Temp&Humidity Recorder	Meideshi	JR900	/	2023/5/3	2024/5/2
10	RF cable(966 chamber)9kHz-1 GHz	Unknown	Unknown	Unknown	2023/5/3	2024/5/2
11	RF cable(966 chamber)1GHz- 18GHz	Unknown	Unknown	Unknown	2023/5/3	2024/5/2
12	RF cable(966 chamber)18GHz -40GHz	Unknown	Unknown	Unknown	2023/5/3	2024/5/2
13	Test software	Farad Technology Co., Ltd	EZ-EMC	/	/	/
Conducted Emission						
1	Test receiver	Rohde&Schwarz	ESCI	100718	2023/5/3	2024/5/2
2	LISN	Rohde&Schwarz	ENV216	100075	2023/5/3	2024/5/2
3	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	2023/5/3	2024/5/2
4	RF cable (9kHz-30MHz)	Unknown	Unknown	Unknown	2023/5/3	2024/5/2
5	Test software	Farad Technology Co., Ltd	EZ-EMC	/	/	/
RF Conducted Emission						
1	MXA Signal Analyzer	Keysight	N9021B	MY600801 69	2023/4/23	2024/4/22
2	RF Control Unit	dsusoft	JS0806-2	21G806044 9	2023/4/23	2024/4/22
3	power supply unit	dsusoft	JS0806-4A DC	N/A	2023/4/23	2024/4/22
4	VXG Signal Generator	Keysight	M9384B	MY612707 87	2023/4/23	2024/4/22
5	EXG Analog Signal Generator	Keysight	N5173B	MY591012 82	2023/4/23	2024/4/22
6	Test software	dsusoft	JS1120-3	/	/	/

2.4 Test Mode

Frequency Range : 2400~2483.5 MHz				
Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emission	Simultaneous transmitting	-	-	-
Radiated Emission and Band Edge Measurement	802.11b	1Mbps	01/06/11	1&2
	802.11g	6Mbps	01/06/11	1&2
	802.11n(20MHz)	MCS0	01/06/11	1&2
	802.11n(40MHz)	MCS0	03/06/09	1&2
	802.11ax(20MHz)	MCS0	01/06/11	1&2
	802.11ax(40MHz)	MCS0	03/06/09	1&2
Spurious Emission at Antenna Port	802.11b	1Mbps	01/06/11	1&2
	802.11g	6Mbps	01/06/11	1&2
	802.11n(20MHz)	MCS0	01/06/11	1&2
	802.11n(40MHz)	MCS0	03/06/09	1&2
	802.11ax(20MHz)	MCS0	01/06/11	1&2
	802.11ax(40MHz)	MCS0	03/06/09	1&2
6dB Bandwidth	802.11b	1Mbps	01/06/11	1&2
	802.11g	6Mbps	01/06/11	1&2
	802.11n(20MHz)	MCS0	01/06/11	1&2
	802.11n(40MHz)	MCS0	03/06/09	1&2
	802.11ax(20MHz)	MCS0	01/06/11	1&2
	802.11ax(40MHz)	MCS0	03/06/09	1&2
Maximum Conducted Power	802.11b	1Mbps	01/06/11	1&2
	802.11g	6Mbps	01/06/11	1&2
	802.11n(20MHz)	MCS0	01/06/11	1&2
	802.11n(40MHz)	MCS0	03/06/09	1&2
	802.11ax(20MHz)	MCS0	01/06/11	1&2
	802.11ax(40MHz)	MCS0	03/06/09	1&2
Power Spectral Density	802.11b	1Mbps	01/06/11	1&2
	802.11g	6Mbps	01/06/11	1&2
	802.11n(20MHz)	MCS0	01/06/11	1&2
	802.11n(40MHz)	MCS0	03/06/09	1&2
	802.11ax(20MHz)	MCS0	01/06/11	1&2
	802.11ax(40MHz)	MCS0	03/06/09	1&2

2.5 Test Condition

Applicable to	Environmental conditions	Input Power	Tested by
AC Power Conducted Emission	23.3°C, 52% RH	AC 120V/60Hz	Albert Fan
Radiated Emission and Band Edge Measurement	24.2°C, 55% RH	AC 120V/60Hz	Albert Fan
Spurious Emission at Antenna Port	24.2°C, 52% RH	DC 5V	Jason Huang
6dB Bandwidth	24.2°C, 52% RH	DC 5V	Jason Huang
Maximum Conducted Power	24.2°C, 52% RH	DC 5V	Jason Huang
Power Spectral Density	24.2°C, 52% RH	DC 5V	Jason Huang

Note: Adapter supply voltage AC 120V/60Hz.

The applicant declare the operating environment of EUT as below:

Normal conditions: 5V DC, 0~60°C

2.6 Duty Cycle of Test Signal

If duty cycle is $\geq 98\%$, duty factor is not required.

If duty cycle is $< 98\%$, duty factor shall be considered.

All the duty factor of other test mode have been considered.

Test Mode	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle[%]
11B-CDD	2412	8.38	8.66	96.77
11G-CDD	2412	1.39	1.66	83.73
11N20MIMO	2412	1.30	1.54	84.42
11N40MIMO	2422	0.64	0.89	71.91
11AX20MIMO	2412	0.20	0.41	48.78
11AX40MIMO	2422	0.21	0.43	48.84


11B-CDD_2412



11G-CDD_2412




11N20MIMO_2412




11N40MIMO_2422



11AX20MIMO_2412



11AX40MIMO_2422



2.7 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 143.88\text{kHz}$
Power Spectral Density	$\pm 0.743\text{dB}$
Conducted Spurious Emission	$\pm 1.328\text{dB}$
RF power conducted	$\pm 0.384\text{dB}$
Conducted emission(9kHz~30MHz) AC main	$\pm 2.72\text{dB}$
Radiated emission(9kHz~30MHz)	$\pm 2.66\text{dB}$
Radiated emission (30MHz~1GHz)	$\pm 4.62\text{dB}$
Radiated emission (1GHz~18GHz)	$\pm 4.86\text{dB}$
Radiated emission (18GHz~40GHz)	$\pm 3.80\text{dB}$

2.8 Test Location

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier	CN0145
A2LA Certificate Number	6823.01
Telephone:	0755-26024411

2.9 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.10 Description of Support Units

Support Equipment				
No.	Equipment	Brand Name	Model Name	Remarks
1	mini PC	/	S10	DC:12V/4A
2	Adapter	TEKA	TEKA-TE120250US	OUTPUT: DC:12V/2.5A

2.11 Deviation from Standards

None

3. Test Procedure And Results

3.1 AC Power Line Conducted Emission

3.1.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3.1.2 Test Procedure

Test Method	
☒ Conducted Measurement	☐ Radiated Measurement
Test Channels	
☐ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme

Note: ● : Test ○ : No Test

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

3.1.3 Test Setup




3.1.4 Test Result

Note:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Measurement = Reading + Correct Factor.
3. Over = Measurement – Limit

We only recorded the data of the worst mode. Please see the following:

150kHz~30MHz	Worst Case Operating Mode: 11B-CDD Channel 01
--------------	---




150kHz~30MHz

Worst Case Operating Mode: 11B-CDD Channel 01

Neutral

Conducted Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1740	20.88	19.88	40.76	64.77	-24.01	QP	
2		0.1740	6.71	19.88	26.59	54.77	-28.18	AVG	
3		0.2340	14.32	19.88	34.20	62.31	-28.11	QP	
4		0.2340	4.06	19.88	23.94	52.31	-28.37	AVG	
5		0.4820	16.25	19.88	36.13	56.30	-20.17	QP	
6	*	0.4820	8.46	19.88	28.34	46.30	-17.96	AVG	
7		1.5180	10.76	19.90	30.66	56.00	-25.34	QP	
8		1.5180	3.62	19.90	23.52	46.00	-22.48	AVG	
9		4.2420	8.80	19.91	28.71	56.00	-27.29	QP	
10		4.2420	0.42	19.91	20.33	46.00	-25.67	AVG	
11		8.5740	4.22	19.94	24.16	60.00	-35.84	QP	
12		8.5740	-1.23	19.94	18.71	50.00	-31.29	AVG	

3.2 Radiated Emission and Band Edge

3.2.1 Limit

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Distance Meters(m)	Field Strength Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 – 0.49	300	$2400/\text{F}(\text{kHz})$	-
0.490 – 1.705	30	$24000/\text{F}(\text{kHz})$	-
1.705 – 30	30	30	-
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

- Note: (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.2.2 Test Procedure

Test Method	
☐ Conducted Measurement	☒ Radiated Measurement
Test Channels	
☒ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme
Note: ☒ : Test ☐ : No Test	


- a) The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b) The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c) The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of

the antenna are set to make the measurement.


- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e) The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f) The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g) All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h) All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i) For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.2.3 Test Setup


(A) Radiated Emission Test Set-Up Frequency Below 30 MHz



(B) Radiated Emission Test Set-Up Frequency 30 MHz-1000 MHz



(C) Radiated Emission Test Set-Up Frequency Above 1 GHz



3.2.4 Test Result

1) Radiated emission: 9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

2) Radiated emission: 30MHz-1G

Note:


1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit

We only recorded the data of the worst mode. Please see the following:

Below 1G (30MHz~1GHz)

Worst Case Operating Mode: 11B-CDD Channel 01


VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		36.2540	35.28	-11.36	23.92	40.00	-16.08	peak		
2	*	90.5374	43.61	-14.64	28.97	43.50	-14.53	peak		
3		103.0800	40.76	-13.10	27.66	43.50	-15.84	peak		
4		133.6188	32.43	-10.10	22.33	43.50	-21.17	peak		
5		164.3301	27.07	-9.60	17.47	43.50	-26.03	peak		
6		319.9370	26.15	-7.81	18.34	46.00	-27.66	peak		

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	34.6385	34.26	-11.68	22.58	40.00	-17.42	peak		
2		90.5374	37.57	-14.64	22.93	43.50	-20.57	peak		
3		107.1337	36.46	-12.58	23.88	43.50	-19.62	peak		
4		131.7577	27.96	-10.21	17.75	43.50	-25.75	peak		
5		263.8190	25.99	-9.26	16.73	46.00	-29.27	peak		
6		377.2590	26.89	-6.30	20.59	46.00	-25.41	peak		



3) Radiated emission: Above 1G

Note:

1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit


Above 1G (1GHz~18GHz)	Test mode:11B-CDD	Test Channel:1
-----------------------	-------------------	----------------

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	51.43	-1.88	49.55	74.00	-24.45	peak		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	45.40	0.19	45.59	74.00	-28.41	peak		
2		2390.000	63.11	0.41	63.52	74.00	-10.48	peak		
3	*	2390.000	52.82	0.41	53.23	54.00	-0.77	AVG		

Above 1G (1GHz~18GHz)


Test mode: 11B-CDD

Test Channel: 6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11B-CDD

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4924.000	51.24	-1.29	49.95	74.00	-24.05	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2483.500	47.51	1.09	48.60	74.00	-25.40	peak		
2		2500.000	44.44	1.22	45.66	74.00	-28.34	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	4924.000	52.16	-1.29	50.87	74.00	-23.13	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2483.500	67.21	1.09	68.30	74.00	-5.70	peak		
2	*	2483.500	52.37	1.09	53.46	54.00	-0.54	AVG		
3		2500.000	45.33	1.22	46.55	74.00	-27.45	peak		


Above 1G (1GHz~18GHz)

Test mode:11G-CDD

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	50.17	-1.88	48.29	74.00	-25.71	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	44.46	0.19	44.65	74.00	-29.35	peak		
2	*	2390.000	52.33	0.41	52.74	74.00	-21.26	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	51.59	-1.88	49.71	74.00	-24.29	peak		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	45.13	0.19	45.32	74.00	-28.68	peak		
2		2390.000	69.49	0.41	69.90	74.00	-4.10	peak		
3	*	2390.000	52.44	0.41	52.85	54.00	-1.15	AVG		

Above 1G (1GHz~18GHz)


Test mode: 11G-CDD

Test Channel: 6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11G-CDD

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4924.000	49.91	-1.29	48.62	74.00	-25.38	peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	56.59	1.09	57.68	74.00	-16.32	peak		
2	*	2483.500	44.01	1.09	45.10	54.00	-8.90	AVG		
3		2500.000	44.12	1.22	45.34	74.00	-28.66	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4924.000	50.64	-1.29	49.35	74.00	-24.65	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	67.02	1.09	68.11	74.00	-5.89	peak		
2	*	2483.500	50.64	1.09	51.73	54.00	-2.27	AVG		
3		2500.000	43.93	1.22	45.15	74.00	-28.85	peak		


Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	51.45	-1.88	49.57	74.00	-24.43	peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	44.80	0.19	44.99	74.00	-29.01	peak		
2	*	2390.000	52.20	0.41	52.61	74.00	-21.39	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	52.44	-1.88	50.56	74.00	-23.44	peak		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	44.69	0.19	44.88	74.00	-29.12	peak		
2		2390.000	69.47	0.41	69.88	74.00	-4.12	peak		
3	*	2390.000	51.86	0.41	52.27	54.00	-1.73	AVG		

Above 1G (1GHz~18GHz)


Test mode: 11N20MIMO

Test Channel: 6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	4924.000	49.58	-1.29	48.29	74.00	-25.71	peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	2483.500	52.60	1.09	53.69	74.00	-20.31	peak		
2		2500.000	43.58	1.22	44.80	74.00	-29.20	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4924.000	51.26	-1.29	49.97	74.00	-24.03	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	67.52	1.09	68.61	74.00	-5.39	peak		
2	*	2483.500	50.69	1.09	51.78	54.00	-2.22	AVG		
3		2500.000	43.07	1.22	44.29	74.00	-29.71	peak		

Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:3


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4844.000	49.52	-1.77	47.75	74.00	-26.25	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	44.50	0.19	44.69	74.00	-29.31	peak		
2	*	2390.000	53.31	0.41	53.72	74.00	-20.28	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4844.000	50.67	-1.77	48.90	74.00	-25.10	peak		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	45.13	0.19	45.32	74.00	-28.68	peak		
2		2390.000	65.25	0.41	65.66	74.00	-8.34	peak		
3	*	2390.000	50.81	0.41	51.22	54.00	-2.78	AVG		

Above 1G (1GHz~18GHz)


Test mode: 11N40MIMO

Test Channel: 6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:9


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4904.000	50.05	-1.41	48.64	74.00	-25.36	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	56.73	1.09	57.82	74.00	-16.18	peak		
2	*	2483.500	42.48	1.09	43.57	54.00	-10.43	AVG		
3		2500.000	44.42	1.22	45.64	74.00	-28.36	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4904.000	52.39	-1.41	50.98	74.00	-23.02	peak		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	65.17	1.09	66.26	74.00	-7.74	peak		
2	*	2483.500	51.34	1.09	52.43	54.00	-1.57	AVG		
3		2500.000	55.10	1.22	56.32	74.00	-17.68	peak		
4		2500.000	43.15	1.22	44.37	54.00	-9.63	AVG		


Above 1G (1GHz~18GHz)

Test mode: 11AX20MIMO

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	50.52	-1.88	48.64	74.00	-25.36	peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	44.79	0.19	44.98	74.00	-29.02	peak		
2		2390.000	55.16	0.41	55.57	74.00	-18.43	peak		
3	*	2390.000	42.86	0.41	43.27	54.00	-10.73	AVG		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	51.63	-1.88	49.75	74.00	-24.25	peak		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	44.97	0.19	45.16	74.00	-28.84	peak		
2		2390.000	65.40	0.41	65.81	74.00	-8.19	peak		
3	*	2390.000	52.23	0.41	52.64	54.00	-1.36	AVG		

Above 1G (1GHz~18GHz)

Test mode: 11AX20MIMO

Test Channel: 6

VERTICAL



HORIZONTAL

