

FCC SAR Test Report

Applicant : **Bedigital S.A.**

Address : **Parque Industrial Santa Lucia Km 3.3 Via
Funza Siberia Bodega 13A, Bogota, Colombia**

Product Name : **KSW 80**

Report Date : **June 13, 2023**

Shenzhen Anbotech Compliance Laboratory Limited



Contents

1	Statement of Compliance	6
2	General Information.....	7
2.1	Client Information	7
2.2	Description of Equipment Under Test (EUT).....	7
2.3	Device Category and SAR Limits	8
2.4	Applied Standard	8
2.5	Environment of Test Site.....	8
2.6	Test Configuration.....	8
3	Specific Absorption Rate (SAR)	9
3.1	Introduction.....	9
3.2	SAR Definition	9
4	SAR Measurement System	10
4.1	E-Field Probe.....	11
4.2	Data Acquisition Electronics (DAE).....	11
4.3	Robot.....	12
4.4	Measurement Server	12
4.5	Phantom	13
4.6	Device Holder.....	14
4.7	Data Storage and Evaluation.....	14
5	Test Equipment List.....	17
6	Tissue Simulating Liquids.....	18
7	System Verification Procedures	20
8	EUT Testing Position.....	22
8.1	Front-of-face and Limbs.....	22
9	Measurement Procedures	23
9.1	Spatial Peak SAR Evaluation	23
9.2	Power Reference Measurement.....	24
9.3	Area Scan Procedures	24
9.4	Zoom Scan Procedures.....	24
9.5	Volume Scan Procedures	25
9.6	Power Drift Monitoring	25
10	Conducted Power	26
11	SAR Test Results Summary.....	46
11.1	SAR Results	47
11.2	SAR Measurement Variability	50
12	Simultaneous Transmission Analysis	51
13	Measurement Uncertainty	52
Appendix A.	EUT Photos and Test Setup Photos.....	56
Appendix B.	Plots of SAR System Check	57



Appendix C.	Plots of SAR Test Data.....	62
Appendix D.	DASY System Calibration Certificate.....	84



TEST REPORT

Applicant : Bedigital S.A.
Manufacturer : ShenZhen Holawin Technology Co.,Ltd.
Product Name : KSW-80
Model No. : KSW-80
Trade Mark : esenses
Rating(s) : Input: 5V 2A(with DC 3.7V, 450mAh battery inside)

Test Standard(s) : IEC 62209-2:2010; IEEE 1528:2013; FCC 47 CFR Part 2.1093;

ANSI/IEEE C95.1:2005; Reference FCC KDB 447498; KDB 248227;
KDB 616217; KDB 941225; KDB 865664

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the IEEE 1528-2013, FCC 47 CFR Part 2.1093, ANSI/IEEE C95.1:2005 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

May 25, 2023

Date of Test

May 26, 2023 – June 06, 2023

Prepared By



(Ella Liang)

Approved & Authorized Signer



(Kingkong Jin)



Version

Version No.	Date	Description
R00	June 13, 2023	Original



1 Statement of Compliance

<Highest SAR Summary>

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013. The maximum results of Specific Absorption Rate (SAR) found during testing are as follows.

<Highest SAR Summary>

FrequencyBand	Highest Reported 1g-SAR(W/Kg)	
	Face up(10mm)	Limbs(0mm)
GSM 850	0.343	0.774
GSM1900	0.489	1.049
WCDMA Band II	0.650	0.916
WCDMA Band V	0.219	0.506
LTE Band 2	0.568	0.790
LTE Band 4	0.481	0.649
LTE Band 5	0.172	0.205
LTE Band 7	0.532	1.063
LTE Band 12	0.289	0.410
LTE Band 13	0.317	0.509
LTE Band 17	0.224	0.363
Simultaneous Reported SAR (W/Kg)	N/A	N/A
SAR Test Limit (W/Kg)	1.6	4.0
Test Result	PASS	

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.



2 General Information

2.1 Client Information

Applicant	:	Bedigital S.A.
Address	:	Parque Industrial Santa Lucia Km 3.3 Via Funza Siberia Bodega 13A, Bogota, Colombia
Manufacturer	:	ShenZhen Holawin Technology Co.,Ltd.
Address	:	Room 619,Building A,HuaFeng ZhiGu Intelligent Technology Zone,No.4 YinTian Road,Xi'Xiang,Bao'An,ShenZhen,China

2.2 Description of Equipment Under Test (EUT)

Product Name	:	KSW 80
Model No.	:	KSW-80
Listed Models	:	T47, T49, T47W, A13, H9 Pro Max, S9 Ultra, A10, LT21, S19, I10
Trade Mark	:	esenses
Test Power Supply	:	DC 3.7V battery inside
Test Sample No.	:	1-2-1(Engineering Sample)
Tx Frequency	:	GSM 850: TX: 824.2~848.8MHz PCS 1900: TX: 1850.2~1909.8MHz UMTS Band 2: TX: 1852.4~1907.6MHz UMTS Band 5: TX: 826.4~846.6MHz LTE-FDD Band 2: TX: 1850~1909MHz LTE-FDD Band 4: TX: 1710~1755MHz LTE-FDD Band 5: TX: 824~849MHz LTE-FDD Band 7: TX: 2500~2570MHz LTE-FDD Band 12: TX: 699~716MHz LTE-FDD Band 13: TX: 777~787MHz LTE-FDD Band 17: TX: 704~716MHz
Type of Modulation	:	GSM:GMSK, 8PSK WCDMA:QPSK,16QAM LTE:QPSK,16QAM
Category of device	:	Portable device
Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.		



2.3 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

2.4 Applied Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093:2013)
- ANSI/IEEE C95.1:2005
- IEEE Std 1528:2013
- KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- KDB 865664 D02 RF Exposure Reporting v01r02
- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- KDB 941225 D01 3G SAR Procedures v03r01
- KDB 941225 D05 SAR for LTE Devices v02r05
- KDB 941225 D06 Hotspot SAR v02r01
- KDB 648474 D04 Handset SAR v01r03

2.5 Environment of Test Site

Items	Required	Actual
Temperature (°C)	18-25	22~23
Humidity (%RH)	30-70	55~65

2.6 Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests. For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.



3 Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by


$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.



4 SAR Measurement System



DASY System Configurations

The DASYsystem for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

components are described in details in the following sub-sections.



4.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

➤ E-Field Probe Specification

<EX3DV4 Probe>

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 W/kg; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Photo of EX3DV4

➤ E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

4.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



**Photo of DAE**

4.3 Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX60XL) type from Stäubli SA (France). For the 6-axis controllersystem, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäublirobot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

**Photo of DASY5**

4.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.





Photo of Server for DASY5

4.5 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
Measurement Areas	Left Hand, Right Hand, Flat Phantom



Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI4 Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)
Filling Volume	Approx. 30 liters
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm




Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.



4.6 Device Holder

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Device Holder

4.7 Data Storage and Evaluation

➤ Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an



incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [W/kg]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

➤ Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm _i , a _{i0} , a _{i1} , a _{i2}
	- Conversion factor	ConvF _i
	- Diode compression point	dcp _i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i, (i = x, y, z)

U_i = input signal of channel i, (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated:



$$\text{E-field Probes: } E_i = \frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}$$

$$\text{H-field Probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with V_i = compensated signal of channel i , ($i = x, y, z$)

Norm_i = sensor sensitivity of channel i , ($i = x, y, z$), $\mu\text{V}/(\text{V/m})^2$ for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in W/kg

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm^3

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.



5 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1118	Jun. 08,2021	Jun. 07,2024
SPEAG	835MHz System Validation Kit	D835V2	4d154	Jun. 16,2021	Jun. 15,2024
SPEAG	1750MHz System Validation Kit	D1750V2	1021	Jul. 01,2021	Jun. 30,2024
SPEAG	1900MHz System Validation Kit	D1900V2	5d175	Jun. 15,2022	Jun. 14,2025
SPEAG	2450MHz System Validation Kit	D2450V2	910	Jun. 15,2021	Jun. 14,2024
SPEAG	2600MHz System Validation Kit	D2600V2	1058	Jun. 19,2021	Jun. 18,2024
Rohde & Schwarz	UNIVERSAL RADIO COMMUNICATION TESTER	CMW500	1201.0002K50-104209-JC	Nov.10, 2021	Nov.09, 2022
SPEAG	Data Acquisition Electronics	DAE4	387	Sept.06,2022	Sept.05,2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7396	May 06,2023	May 05,2024
Agilent	ENA Series Network Analyzer	E5071C	MY46317418	Oct.26, 2022	Oct.25, 2023
SPEAG	DAK	DAK-3.5	1226	NCR	NCR
SPEAG	SAM Twin Phantom	QD000P40CD	1802	NCR	NCR
SPEAG	ELI Phantom	QDOVA004AA	2058	NCR	NCR
AR	Amplifier	ZHL-42W	QA1118004	NCR	NCR
Agilent	Power Meter	N1914A	MY50001102	Oct.26, 2022	Oct.25, 2023
Agilent	Power Sensor	N8481H	MY51240001	Oct.26, 2022	Oct.25, 2023
R&S	Spectrum Analyzer	N9020A	MY51170037	Oct.26, 2022	Oct.25, 2023
Agilent	Signal Generation	N5182A	MY48180656	Oct.26, 2022	Oct.25, 2023
Worken	Directional Coupler	0110A05601O-10	COM5BNW1A2	Oct.26, 2022	Oct.25, 2023

Note:

1. The calibration certificate of DASY can be referred to appendix C of this report.
2. The dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The Insertion Loss calibration of Dual Directional Coupler and Attenuator were characterized via the network analyzer and compensated during system check.
4. The dielectric probe kit was calibrated via the network analyzer, with the specified procedure (calibrated in pure water) and calibration kit (standard) short circuit, before the dielectric measurement. The specific procedure and calibration kit are provided by Agilent.
5. In system check we need to monitor the level on the power meter, and adjust the power amplifier level to have precise power level to the dipole; the measured SAR will be normalized to 1W input power according to the ratio of 1W to the input power to the dipole. For system check, the calibration of the power amplifier is deemed not critically required for correct measurement; the power meter is critical and we do have calibration for it



6 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown as followed:




Photo of Liquid Height for Head SAR




Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800,1900,2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800,1900,2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	65.5	0	0	0	0	31.5	2.16	52.5



The following table shows the measuring results for simulating liquid.

Measured Frequency (MHz)	Target Tissue		Measured Tissue				Liquid Temp.	Test Data
	ϵ_r	σ	ϵ_r	Dev. (%)	σ	Dev. (%)		
750	41.9	0.89	43.144	2.97%	0.916	-0.40%	22.5	05/31/2023
835	41.5	0.90	41.637	0.33%	0.903	-2.31%	22.6	05/26/2023
1750	40.1	1.37	39.960	-0.35%	1.365	0.47%	22.4	06/02/2023
1900	40.0	1.40	40.092	0.23%	1.403	-2.29%	22.5	05/30/2023
2600	39.0	1.96	39.008	0.02%	1.960	-1.11%	22.8	06/06/2023



7 System Verification Procedures


Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

➤ Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

➤ System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



System Setup for System Evaluation






Photo of Dipole Setup

➤ **Validation Results**

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10%. The table below shows the target SAR and measured SAR after normalized to 1W input power. It indicates that the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Power fed onto reference dipole (mW)	Targeted SAR (W/kg)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
05/31/2023	750	250	8.76	2.18	8.74	-0.25%
05/26/2023	835	250	9.57	2.42	9.69	1.25%
06/02/2023	1750	250	36.7	9.38	37.52	2.24%
05/30/2023	1900	250	40.1	10.17	40.69	1.47%
06/06/2023	2600	250	56.8	14.54	58.17	2.41%


Target and Measurement SAR after Normalized



8 EUT Testing Position

8.1 Front-of-face and Limbs

Transmitters that are built-in within a wrist watch or similar wrist-worn devices typically operate in speaker mode for voice communication, with the device worn on the wrist and positioned next to the mouth. Next to the mouth exposure requires 1-g SAR and the wrist-worn condition requires 10-g extremity SAR. The 10-g extremity and 1-g SAR test exclusions may be applied to the wrist and face exposure conditions. When SAR evaluation is required, next to the mouth use is evaluated with the front of the device positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium. The wrist bands should be strapped together to represent normal use conditions. SAR for wrist exposure is evaluated with the back of the device positioned in direct contact against a flat phantom filled with body tissue-equivalent medium. The wrist bands should be unstrapped and touching the phantom.



9 Measurement Procedures

The measurement procedures are as follows:

- Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the middle channel.
- Keep EUT to radiate maximum output power or 100% duty factor (if applicable)
- Measure output power through RF cable and power meter.
- Place the EUT in the positions as setup photos demonstrates.
- Set scan area, grid size and other setting on the DASY software.
- Measure SAR transmitting at the middle channel for all applicable exposure positions.
- Identify the exposure position and device configuration resulting the highest SAR
- Measure SAR at the lowest and highest channels at the worst exposure position and device configuration if applicable.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- Extraction of the measured data (grid and values) from the Zoom Scan
- Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- Generation of a high-resolution mesh within the measured volume
- Interpolation of all measured values from the measurement grid to the high-resolution grid
- Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- Calculation of the averaged SAR within masses of 1g and 10g



9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan Procedures

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan Procedures

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.



			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm * 4 – 6 GHz: ≤ 4 mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.



10 Conducted Power

<GSM Conducted power>

Band GSM850	Burst Average Power (dBm)				Frame-Average Power (dBm)		
TX Channel	Tune-up	128	190	251	128	190	251
Frequency (MHz)		824.2	836.6	848.8	824.2	836.6	848.6
GSM (GMSK, 1 Tx slot)	33±1	32.87	33.07	32.74	/	/	/
GPRS (GMSK, 1 Tx slot)	33±1	32.76	33.01	32.47	23.73	23.98	23.44
GPRS (GMSK, 2 Tx slots)	30±1	30.62	30.99	30.47	24.60	24.97	24.45
GPRS (GMSK, 3 Tx slots)	29±1	28.67	29.03	28.53	24.41	24.77	24.27
GPRS (GMSK, 4 Tx slots)	28±1	26.69	27.02	26.51	23.68	24.01	23.50
Band PCS1900	Burst Average Power (dBm)				Frame-Average Power (dBm)		
TX Channel	Tune-up	512	661	810	512	661	810
Frequency (MHz)		1850.2	1880.0	1909.8	1850.2	1880.0	1909.8
GSM (GMSK, 1 Tx slot)	30±1	30.59	29.54	30.05	/	/	/
GPRS (GMSK, 1 Tx slot)	30±1	30.56	29.81	29.92	21.53	20.78	20.89
GPRS (GMSK, 2 Tx slots)	28±1	28.22	27.37	27.64	22.20	21.35	21.62
GPRS (GMSK, 3 Tx slots)	26±1	26.56	25.68	25.97	22.30	21.42	21.71
GPRS (GMSK, 4 Tx slots)	24±1	24.51	23.62	23.92	21.50	20.61	20.91

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) – 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) – 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) – 3.01 dB

Note:

1. Per KDB 447498 D01, the maximum output power channel is used for SAR testing and for further SAR test reduction
2. For Data mode SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS 2 Tx slots for GSM850 and GPRS 3 Tx slots PCS1900 due to its highest frame-average power.



<WCDMA Conducted Power>

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81
Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$. Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference. Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$. Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$. Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g. Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.													

Setup Configuration

<WCDMA Conducted Power>

WCDMA	Band II (dBm)				Band V (dBm)			
TX Channel	Tune-up	9262	9400	9538	Tune-up	4132	4183	4233
Frequency (MHz)		1852.4	1880.0	1907.6	power	826.4	836.6	846.6
RMC 12.2Kbps	23±1	23.53	23.49	23.61	23±1	23.50	23.53	23.56
HSDPA Subtest-1	22±1	22.94	22.95	22.95	22±1	22.93	22.97	22.98
HSDPA Subtest-2	21±1	21.89	21.84	21.82	21±1	21.88	21.81	21.86
HSDPA Subtest-3	20±1	20.70	20.71	20.82	20±1	20.73	20.75	20.71
HSDPA Subtest-4	20±1	20.75	20.33	20.78	20±1	20.03	19.93	20.09
HSUPA Subtest-1	22±1	22.71	22.84	22.72	22±1	22.85	22.85	22.78
HSUPA Subtest-2	21±1	21.81	21.88	21.82	21±1	21.87	21.83	21.81
HSUPA Subtest-3	21±1	21.72	21.59	21.56	21±1	21.79	21.71	21.83
HSUPA Subtest-4	20±1	20.85	20.87	20.88	20±1	20.84	20.85	20.85
HSUPA Subtest-5	20±1	20.19	20.05	20.19	20±1	20.11	20.07	20.12
HSPA+	21±1	21.77	21.60	21.42	21±1	21.85	21.91	21.59

General Note

1. Per KDB 941225 D01 v02, RMC 12.2kbps setting is used to evaluate SAR. If AMR 12.2kbps power is < 0.25dB higher than RMC 12.2kbps, SAR tests with AMR 12.2kbps can be excluded.
2. By design, AMR and HSDPA/HSUPA RF power will not be larger than RMC 12.2kbps, detailed information is included in Tune-up Procure exhibit.
3. It is expected by the manufacturer that MPR for some HSDPA/HSUPA subtests may differ from the specification of 3GPP, according to the chipset implementation in this model. The implementation and expected deviation are detailed in tune-up procedure exhibit.



<LTE Conducted Power>

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band2	1.4MHz	18607	1RB#0	23.28	22.45	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18607	1RB#2	23.30	22.18	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18607	1RB#5	22.95	22.22	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18607	3RB#0	23.01	22.05	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18607	3RB#1	22.27	21.83	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18607	3RB#3	22.54	21.67	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18607	6RB#0	22.72	21.31	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	1RB#0	23.28	22.45	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	1RB#2	22.94	21.85	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	1RB#5	22.88	22.23	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	3RB#0	23.43	21.99	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	3RB#1	23.10	21.48	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	3RB#3	22.77	21.69	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	18900	6RB#0	23.00	21.91	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	1RB#0	23.28	22.45	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	1RB#2	23.14	21.86	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	1RB#5	22.73	21.83	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	3RB#0	23.14	21.92	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	3RB#1	22.41	21.97	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	3RB#3	22.95	21.36	22.5±1.0	22.0±1.0
NTNV	Band2	1.4MHz	19193	6RB#0	23.21	22.56	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	1RB#0	23.15	22.44	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	1RB#8	22.97	21.91	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	1RB#14	22.87	22.09	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	8RB#0	22.57	21.46	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	8RB#4	22.82	21.90	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	8RB#7	22.64	21.77	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18615	15RB#0	22.05	21.43	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	1RB#0	23.08	22.41	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	1RB#8	23.04	22.45	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	1RB#14	23.42	22.15	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	8RB#0	22.78	21.78	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	8RB#4	22.98	21.83	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	8RB#7	22.91	22.14	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	18900	15RB#0	22.94	21.57	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	19185	1RB#0	22.57	21.66	22.5±1.0	22.0±1.0



NTNV	Band2	3MHz	19185	1RB#8	22.70	21.96	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	19185	1RB#14	23.08	22.10	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	19185	8RB#0	22.12	21.55	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	19185	8RB#4	22.24	21.85	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	19185	8RB#7	22.74	22.32	22.5±1.0	22.0±1.0
NTNV	Band2	3MHz	19185	15RB#0	22.42	21.10	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	1RB#0	23.01	22.15	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	1RB#12	22.60	22.08	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	1RB#24	22.68	22.18	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	12RB#0	22.94	21.68	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	12RB#6	22.67	21.86	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	12RB#13	22.97	21.89	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18625	25RB#0	22.71	21.72	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	1RB#0	23.39	22.19	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	1RB#12	22.32	21.34	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	1RB#24	22.33	21.43	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	12RB#0	22.87	21.98	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	12RB#6	22.03	21.56	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	12RB#13	22.30	21.63	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	18900	25RB#0	22.69	21.84	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	1RB#0	23.28	22.14	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	1RB#12	22.48	21.03	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	1RB#24	22.61	21.68	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	12RB#0	22.24	21.52	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	12RB#6	22.36	21.58	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	12RB#13	22.56	21.54	22.5±1.0	22.0±1.0
NTNV	Band2	5MHz	19175	25RB#0	22.57	21.56	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	1RB#0	22.47	21.86	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	1RB#24	23.00	22.23	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	1RB#49	22.60	21.70	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	25RB#0	22.28	21.38	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	25RB#12	22.96	21.84	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	25RB#25	22.65	21.71	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18650	50RB#0	22.21	21.63	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18900	1RB#0	23.24	22.27	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18900	1RB#24	22.32	21.48	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18900	1RB#49	23.41	22.33	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18900	25RB#0	22.70	22.03	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18900	25RB#12	22.32	21.45	22.5±1.0	22.0±1.0



NTNV	Band2	10MHz	18900	25RB#25	23.08	21.94	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	18900	50RB#0	22.85	21.93	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	1RB#0	22.93	22.12	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	1RB#24	22.27	21.70	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	1RB#49	22.96	22.24	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	25RB#0	22.14	21.34	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	25RB#12	22.37	21.69	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	25RB#25	22.35	21.39	22.5±1.0	22.0±1.0
NTNV	Band2	10MHz	19150	50RB#0	22.12	21.05	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	1RB#0	23.30	22.34	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	1RB#38	23.18	22.57	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	1RB#74	23.32	22.81	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	38RB#0	22.90	22.34	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	38RB#18	23.28	21.85	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	38RB#37	22.68	21.86	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18675	75RB#0	23.01	21.54	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	1RB#0	22.83	22.34	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	1RB#38	22.87	22.04	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	1RB#74	22.59	21.74	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	38RB#0	22.86	21.70	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	38RB#18	22.58	22.00	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	38RB#37	22.49	21.86	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	18900	75RB#0	22.53	21.63	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	1RB#0	23.05	21.75	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	1RB#38	22.74	21.85	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	1RB#74	22.80	21.64	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	38RB#0	22.29	21.39	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	38RB#18	22.56	21.63	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	38RB#37	22.39	21.69	22.5±1.0	22.0±1.0
NTNV	Band2	15MHz	19125	75RB#0	22.21	21.80	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	1RB#0	22.57	21.71	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	1RB#49	22.96	22.58	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	1RB#99	22.55	22.04	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	50RB#0	22.16	21.28	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	50RB#25	22.74	21.83	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	50RB#50	22.46	21.67	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18700	100RB#0	22.67	21.44	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18900	1RB#0	23.34	22.25	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18900	1RB#49	22.98	22.48	22.5±1.0	22.0±1.0



NTNV	Band2	20MHz	18900	1RB#99	23.30	22.20	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18900	50RB#0	22.65	21.89	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18900	50RB#25	22.73	21.56	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18900	50RB#50	23.04	22.04	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	18900	100RB#0	22.70	22.12	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	1RB#0	22.68	22.03	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	1RB#49	22.70	22.10	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	1RB#99	22.87	21.90	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	50RB#0	22.25	21.31	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	50RB#25	22.35	21.45	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	50RB#50	22.68	21.93	22.5±1.0	22.0±1.0
NTNV	Band2	20MHz	19100	100RB#0	22.64	21.38	22.5±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band4	1.4MHz	19957	1RB#0	23.03	22.35	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	19957	1RB#2	22.81	22.09	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	19957	1RB#5	22.69	21.97	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	19957	3RB#0	22.36	21.68	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	19957	3RB#1	22.26	21.56	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	19957	3RB#3	22.21	21.50	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	19957	6RB#0	22.12	21.43	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	1RB#0	23.32	22.63	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	1RB#2	23.05	22.28	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	1RB#5	23.33	22.65	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	3RB#0	23.13	22.41	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	3RB#1	22.71	21.96	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	3RB#3	23.09	22.37	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20175	6RB#0	22.55	21.80	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	1RB#0	23.39	22.69	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	1RB#2	23.46	22.70	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	1RB#5	23.25	22.61	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	3RB#0	23.04	22.27	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	3RB#1	22.88	22.23	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	3RB#3	23.04	22.33	22.5±1.0	22.0±1.0
NTNV	Band4	1.4MHz	20393	6RB#0	23.15	22.47	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	19965	1RB#0	23.02	22.28	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	19965	1RB#8	23.07	22.35	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	19965	1RB#14	23.11	22.49	22.5±1.0	22.0±1.0



NTNV	Band4	3MHz	19965	8RB#0	22.57	21.86	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	19965	8RB#4	22.85	22.10	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	19965	8RB#7	22.50	21.84	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	19965	15RB#0	22.31	21.67	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	1RB#0	22.68	22.06	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	1RB#8	22.90	22.26	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	1RB#14	23.24	22.62	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	8RB#0	22.09	21.43	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	8RB#4	22.11	21.38	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	8RB#7	22.47	21.83	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20175	15RB#0	22.39	21.76	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	1RB#0	23.36	22.66	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	1RB#8	23.45	22.78	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	1RB#14	23.11	22.41	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	8RB#0	22.99	22.28	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	8RB#4	22.82	22.09	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	8RB#7	23.19	22.46	22.5±1.0	22.0±1.0
NTNV	Band4	3MHz	20385	15RB#0	22.20	21.48	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	1RB#0	23.18	22.47	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	1RB#12	23.34	22.64	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	1RB#24	23.28	22.61	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	12RB#0	23.04	22.29	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	12RB#6	23.08	22.32	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	12RB#13	23.38	22.73	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	19975	25RB#0	22.61	21.91	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	1RB#0	23.36	22.61	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	1RB#12	22.40	21.77	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	1RB#24	23.07	22.32	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	12RB#0	22.62	21.94	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	12RB#6	22.31	21.58	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	12RB#13	23.09	22.34	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20175	25RB#0	22.20	21.49	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	1RB#0	23.44	22.78	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	1RB#12	23.34	22.64	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	1RB#24	23.36	22.70	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	12RB#0	23.13	22.43	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	12RB#6	22.68	22.04	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	12RB#13	22.90	22.22	22.5±1.0	22.0±1.0
NTNV	Band4	5MHz	20375	25RB#0	23.06	22.33	22.5±1.0	22.0±1.0



NTNV	Band4	10MHz	20000	1RB#0	23.17	22.51	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20000	1RB#24	23.40	22.75	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20000	1RB#49	22.87	22.12	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20000	25RB#0	22.96	22.27	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20000	25RB#12	22.90	22.17	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20000	25RB#25	21.99	21.23	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20000	50RB#0	23.00	22.28	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	1RB#0	22.98	22.27	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	1RB#24	23.07	22.28	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	1RB#49	23.47	22.74	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	25RB#0	22.81	22.14	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	25RB#12	23.00	22.25	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	25RB#25	22.71	21.98	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20175	50RB#0	22.28	21.63	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	1RB#0	23.42	22.69	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	1RB#24	22.83	22.12	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	1RB#49	22.93	22.26	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	25RB#0	23.13	22.46	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	25RB#12	22.56	21.84	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	25RB#25	22.31	21.56	22.5±1.0	22.0±1.0
NTNV	Band4	10MHz	20350	50RB#0	22.71	22.06	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	1RB#0	22.86	22.23	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	1RB#38	23.30	22.61	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	1RB#74	23.50	22.84	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	38RB#0	22.87	22.18	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	38RB#18	22.38	21.66	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	38RB#37	22.80	22.13	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20025	75RB#0	22.19	21.48	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	1RB#0	23.29	22.66	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	1RB#38	23.19	22.43	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	1RB#74	22.56	21.76	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	38RB#0	22.79	22.01	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	38RB#18	22.76	22.10	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	38RB#37	22.48	21.75	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20175	75RB#0	22.44	21.82	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20325	1RB#0	23.48	22.78	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20325	1RB#38	22.86	22.21	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20325	1RB#74	22.77	22.01	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20325	38RB#0	23.33	22.61	22.5±1.0	22.0±1.0



NTNV	Band4	15MHz	20325	38RB#18	22.84	22.13	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20325	38RB#37	22.68	21.94	22.5±1.0	22.0±1.0
NTNV	Band4	15MHz	20325	75RB#0	22.71	22.00	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	1RB#0	22.31	21.62	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	1RB#49	23.33	22.60	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	1RB#99	22.89	22.11	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	50RB#0	22.44	21.80	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	50RB#25	22.95	22.19	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	50RB#50	22.76	21.98	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20050	100RB#0	22.63	21.97	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	1RB#0	22.52	21.81	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	1RB#49	23.07	22.37	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	1RB#99	22.57	21.88	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	50RB#0	22.76	22.07	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	50RB#25	22.81	22.07	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	50RB#50	22.30	21.57	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20175	100RB#0	22.08	21.39	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	1RB#0	22.62	22.00	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	1RB#49	23.07	22.37	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	1RB#99	23.09	22.35	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	50RB#0	22.57	21.83	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	50RB#25	23.26	22.56	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	50RB#50	22.31	21.53	22.5±1.0	22.0±1.0
NTNV	Band4	20MHz	20300	100RB#0	22.70	21.97	22.5±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band5	1.4MHz	20407	1RB#0	23.66	22.23	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20407	1RB#2	22.85	21.43	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20407	1RB#5	23.95	22.58	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20407	3RB#0	23.28	22.03	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20407	3RB#1	22.61	21.51	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20407	3RB#3	23.34	21.72	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20407	6RB#0	23.63	22.40	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20525	1RB#0	23.51	22.18	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20525	1RB#2	23.33	22.23	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20525	1RB#5	23.25	22.05	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20525	3RB#0	22.90	21.20	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20525	3RB#1	22.91	21.66	23.0±1.0	22.0±1.0



NTNV	Band5	1.4MHz	20525	3RB#3	22.50	21.50	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20525	6RB#0	22.51	21.32	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	1RB#0	23.12	22.34	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	1RB#2	22.99	21.22	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	1RB#5	23.64	22.56	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	3RB#0	23.06	22.13	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	3RB#1	22.62	21.48	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	3RB#3	23.21	21.98	23.0±1.0	22.0±1.0
NTNV	Band5	1.4MHz	20643	6RB#0	22.49	21.53	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	1RB#0	22.63	21.25	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	1RB#8	22.67	21.44	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	1RB#14	23.29	21.92	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	8RB#0	22.47	21.03	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	8RB#4	22.61	21.43	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	8RB#7	23.34	21.96	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20415	15RB#0	22.17	21.51	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	1RB#0	23.00	21.90	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	1RB#8	23.21	22.21	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	1RB#14	22.59	21.48	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	8RB#0	22.43	21.37	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	8RB#4	23.44	21.83	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	8RB#7	22.48	21.36	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20525	15RB#0	22.75	21.17	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	1RB#0	22.94	21.79	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	1RB#8	23.98	22.46	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	1RB#14	23.11	21.45	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	8RB#0	22.98	22.02	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	8RB#4	23.05	22.06	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	8RB#7	22.37	21.32	23.0±1.0	22.0±1.0
NTNV	Band5	3MHz	20635	15RB#0	22.83	21.36	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	1RB#0	23.12	21.73	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	1RB#12	23.14	22.19	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	1RB#24	23.71	22.31	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	12RB#0	23.20	21.87	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	12RB#6	23.25	21.43	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	12RB#13	23.08	21.81	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20425	25RB#0	22.84	21.41	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20525	1RB#0	23.19	21.80	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20525	1RB#12	23.55	21.95	23.0±1.0	22.0±1.0



NTNV	Band5	5MHz	20525	1RB#24	22.57	21.58	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20525	12RB#0	22.38	21.59	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20525	12RB#6	22.90	21.34	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20525	12RB#13	22.14	21.20	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20525	25RB#0	22.44	21.21	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	1RB#0	23.22	21.69	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	1RB#12	22.65	21.38	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	1RB#24	23.32	22.06	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	12RB#0	22.85	21.43	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	12RB#6	22.19	21.33	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	12RB#13	23.40	21.90	23.0±1.0	22.0±1.0
NTNV	Band5	5MHz	20625	25RB#0	22.79	21.24	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	1RB#0	23.57	22.16	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	1RB#24	22.66	21.60	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	1RB#49	23.05	22.17	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	25RB#0	23.65	22.01	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	25RB#12	22.56	21.56	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	25RB#25	22.81	21.67	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20450	50RB#0	22.93	21.60	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	1RB#0	23.43	22.38	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	1RB#24	23.83	22.70	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	1RB#49	23.68	22.41	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	25RB#0	22.84	21.97	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	25RB#12	23.5	22.31	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	25RB#25	23.33	21.93	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20525	50RB#0	22.66	21.39	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	1RB#0	22.76	21.55	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	1RB#24	23.16	21.59	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	1RB#49	23.04	21.82	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	25RB#0	22.54	21.34	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	25RB#12	22.55	21.78	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	25RB#25	22.43	21.11	23.0±1.0	22.0±1.0
NTNV	Band5	10MHz	20600	50RB#0	22.63	21.36	23.0±1.0	22.0±1.0



Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band7	5MHz	20775	1RB#0	23.32	22.30	23±1.0	22.0±1.0
NTNV	Band7	5MHz	20775	1RB#12	23.17	22.09	23±1.0	22.0±1.0
NTNV	Band7	5MHz	20775	1RB#24	23.33	21.98	23±1.0	22.0±1.0
NTNV	Band7	5MHz	20775	12RB#0	23.21	22.28	23±1.0	22.0±1.0
NTNV	Band7	5MHz	20775	12RB#6	23.01	21.60	23±1.0	22.0±1.0
NTNV	Band7	5MHz	20775	12RB#13	22.89	21.88	23±1.0	22.0±1.0
NTNV	Band7	5MHz	20775	25RB#0	22.91	21.68	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	1RB#0	22.77	21.77	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	1RB#12	23.40	22.14	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	1RB#24	23.63	22.77	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	12RB#0	22.41	21.09	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	12RB#6	23.51	21.72	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	12RB#13	23.21	21.94	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21100	25RB#0	22.34	21.50	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	1RB#0	23.44	22.18	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	1RB#12	22.90	21.55	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	1RB#24	23.71	22.66	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	12RB#0	22.51	21.32	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	12RB#6	23.04	22.00	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	12RB#13	22.99	21.61	23±1.0	22.0±1.0
NTNV	Band7	5MHz	21425	25RB#0	22.53	21.54	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	1RB#0	23.12	21.79	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	1RB#24	22.94	21.38	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	1RB#49	22.91	21.65	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	25RB#0	22.82	21.38	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	25RB#12	22.47	21.06	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	25RB#25	23.07	22.21	23±1.0	22.0±1.0
NTNV	Band7	10MHz	20800	50RB#0	22.78	21.72	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	1RB#0	22.67	21.85	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	1RB#24	22.82	22.05	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	1RB#49	23.20	22.11	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	25RB#0	22.51	21.67	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	25RB#12	22.24	21.14	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	25RB#25	23.20	21.99	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21100	50RB#0	22.78	21.31	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21400	1RB#0	23.46	22.06	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21400	1RB#24	23.38	22.50	23±1.0	22.0±1.0



NTNV	Band7	10MHz	21400	1RB#49	22.69	21.50	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21400	25RB#0	22.97	21.64	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21400	25RB#12	23.24	21.91	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21400	25RB#25	22.59	21.11	23±1.0	22.0±1.0
NTNV	Band7	10MHz	21400	50RB#0	22.40	21.51	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	1RB#0	23.53	22.37	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	1RB#38	22.83	21.79	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	1RB#74	23.34	22.06	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	38RB#0	23.00	21.82	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	38RB#18	22.47	21.18	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	38RB#37	23.07	21.87	23±1.0	22.0±1.0
NTNV	Band7	15MHz	20825	75RB#0	22.64	21.49	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	1RB#0	23.18	21.72	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	1RB#38	23.10	21.82	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	1RB#74	23.57	22.68	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	38RB#0	23.09	21.87	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	38RB#18	22.52	21.00	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	38RB#37	23.75	22.46	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21100	75RB#0	22.55	21.80	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	1RB#0	23.45	21.87	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	1RB#38	23.14	22.11	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	1RB#74	23.54	22.41	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	38RB#0	22.53	21.84	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	38RB#18	22.99	21.67	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	38RB#37	23.31	21.83	23±1.0	22.0±1.0
NTNV	Band7	15MHz	21375	75RB#0	22.82	21.78	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	1RB#0	23.27	22.15	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	1RB#49	22.46	21.76	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	1RB#99	22.48	21.32	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	50RB#0	23.31	22.56	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	50RB#25	22.49	21.16	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	50RB#50	22.59	21.30	23±1.0	22.0±1.0
NTNV	Band7	20MHz	20850	100RB#0	23.19	22.04	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21100	1RB#0	22.31	21.42	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21100	1RB#49	23.39	22.24	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21100	1RB#99	22.93	21.71	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21100	50RB#0	22.82	21.34	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21100	50RB#25	23.07	21.90	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21100	50RB#50	22.65	21.26	23±1.0	22.0±1.0



NTNV	Band7	20MHz	21100	100RB#0	22.24	21.19	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	1RB#0	22.79	21.30	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	1RB#49	23.06	22.05	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	1RB#99	23.26	22.15	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	50RB#0	22.54	21.49	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	50RB#25	23.03	21.99	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	50RB#50	22.82	21.67	23±1.0	22.0±1.0
NTNV	Band7	20MHz	21350	100RB#0	22.39	21.31	23±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band12	1.4MHz	23017	1RB#0	23.15	22.47	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	1RB#2	22.54	21.89	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	1RB#5	23.20	22.65	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	3RB#0	23.24	22.34	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	3RB#1	22.21	21.47	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	3RB#3	22.90	22.10	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	6RB#0	22.60	22.05	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	1RB#0	22.74	21.97	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	1RB#2	23.06	21.98	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	1RB#5	22.75	22.12	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	3RB#0	22.63	21.64	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	3RB#1	22.82	21.85	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	3RB#3	22.51	21.50	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	6RB#0	22.22	21.53	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	1RB#0	22.96	22.10	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	1RB#2	22.74	21.61	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	1RB#5	23.21	22.36	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	3RB#0	22.72	22.01	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	3RB#1	22.22	21.66	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	3RB#3	22.78	21.95	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	6RB#0	22.74	21.65	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	1RB#0	22.31	21.43	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	1RB#8	22.56	21.78	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	1RB#14	23.30	22.33	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	8RB#0	22.17	21.15	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	8RB#4	22.45	21.90	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	8RB#7	22.47	21.86	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	15RB#0	22.54	21.34	23.0±1.0	22.0±1.0



NTNV	Band12	3MHz	23095	1RB#0	22.59	21.80	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	1RB#8	22.97	22.00	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	1RB#14	22.80	21.62	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	8RB#0	22.20	21.69	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	8RB#4	22.38	21.93	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	8RB#7	22.51	21.43	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	15RB#0	22.43	21.49	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	1RB#0	23.00	21.96	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	1RB#8	23.30	22.82	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	1RB#14	22.60	22.11	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	8RB#0	22.61	21.75	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	8RB#4	23.30	22.07	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	8RB#7	22.81	21.58	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	15RB#0	22.16	21.65	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	1RB#0	23.31	21.81	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	1RB#12	23.14	22.14	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	1RB#24	23.08	22.63	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	12RB#0	22.85	22.15	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	12RB#6	22.78	22.03	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	12RB#13	22.90	21.86	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	25RB#0	22.56	21.67	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	1RB#0	22.48	22.21	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	1RB#12	22.76	22.48	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	1RB#24	22.56	21.39	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	12RB#0	22.46	21.28	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	12RB#6	22.91	21.63	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	12RB#13	22.11	21.09	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	25RB#0	22.44	21.86	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	1RB#0	22.42	22.13	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	1RB#12	22.48	21.37	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	1RB#24	23.40	22.55	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	12RB#0	22.33	21.53	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	12RB#6	22.27	21.28	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	12RB#13	22.72	22.35	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	25RB#0	22.51	21.37	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	1RB#0	23.19	22.49	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	1RB#24	22.42	21.69	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	1RB#49	23.22	22.06	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	25RB#0	22.93	22.14	23.0±1.0	22.0±1.0



NTNV	Band12	10MHz	23060	25RB#12	22.11	21.68	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	25RB#25	22.77	21.99	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	50RB#0	22.54	21.99	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	1RB#0	22.58	22.16	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	1RB#24	23.11	22.53	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	1RB#49	23.47	22.76	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	25RB#0	22.27	21.86	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	25RB#12	22.81	22.36	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	25RB#25	23.25	22.12	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	50RB#0	22.83	21.47	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	1RB#0	22.85	21.75	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	1RB#24	22.61	21.91	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	1RB#49	22.58	21.82	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	25RB#0	22.12	21.58	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	25RB#12	22.13	21.44	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	25RB#25	22.18	21.05	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	50RB#0	22.27	21.70	23.0±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band13	5MHz	23205	1RB#0	22.27	21.69	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23205	1RB#12	23.07	22.46	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23205	1RB#24	22.90	22.12	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23205	12RB#0	22.18	21.33	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23205	12RB#6	22.92	22.36	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23205	12RB#13	23.16	22.38	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23205	25RB#0	22.49	21.82	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	1RB#0	23.20	22.57	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	1RB#12	23.73	22.95	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	1RB#24	22.58	21.53	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	12RB#0	22.72	21.85	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	12RB#6	23.19	21.85	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	12RB#13	22.11	21.62	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23230	25RB#0	22.44	21.51	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23255	1RB#0	22.67	22.13	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23255	1RB#12	22.99	22.40	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23255	1RB#24	23.04	22.19	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23255	12RB#0	22.71	22.06	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23255	12RB#6	23.02	21.51	23±1.0	22.0±1.0



NTNV	Band13	5MHz	23255	12RB#13	22.47	21.77	23±1.0	22.0±1.0
NTNV	Band13	5MHz	23255	25RB#0	22.34	21.41	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	1RB#0	23.19	22.23	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	1RB#24	22.42	22.55	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	1RB#49	23.22	22.17	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	25RB#0	22.93	21.81	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	25RB#12	22.11	22.10	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	25RB#25	22.77	22.18	23±1.0	22.0±1.0
NTNV	Band13	10MHz	23230	50RB#0	22.54	21.96	23±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band17	5MHz	23755	1RB#0	22.61	21.72	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	1RB#12	23.48	22.24	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	1RB#24	22.93	22.34	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	12RB#0	22.89	22.06	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	12RB#6	22.47	21.60	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	12RB#13	23.18	22.30	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	25RB#0	23.15	22.46	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	1RB#0	23.61	22.64	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	1RB#12	23.46	22.12	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	1RB#24	22.70	21.79	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	12RB#0	23.01	22.15	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	12RB#6	22.92	22.04	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	12RB#13	22.58	21.67	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	25RB#0	22.74	22.37	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	1RB#0	22.42	22.13	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	1RB#12	22.48	21.37	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	1RB#24	23.40	22.55	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	12RB#0	22.33	21.53	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	12RB#6	22.27	21.28	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	12RB#13	22.72	22.35	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	25RB#0	22.51	21.37	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	1RB#0	23.48	22.33	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	1RB#24	22.41	21.74	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	1RB#49	22.70	21.60	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	25RB#0	22.99	22.59	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	25RB#12	23.46	22.88	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	25RB#25	22.72	21.94	23.0±1.0	22.0±1.0



NTNV	Band17	10MHz	23780	50RB#0	23.07	22.12	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	1RB#0	22.69	22.25	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	1RB#24	22.32	21.83	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	1RB#49	22.87	22.17	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	25RB#0	22.55	22.14	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	25RB#12	23.64	22.87	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	25RB#25	22.44	21.77	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	50RB#0	23.38	22.33	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	1RB#0	23.00	22.29	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	1RB#24	22.59	21.47	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	1RB#49	22.41	21.47	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	25RB#0	22.72	21.76	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	25RB#12	23.28	22.41	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	25RB#25	22.69	21.96	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	50RB#0	22.89	22.30	23.0±1.0	22.0±1.0



11 SAR Test Results Summary

General Note:

1.Per KDB 447498 D01v05r01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.

Scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Reported SAR(W/kg)= Measured SAR(W/kg) Scaling Factor*

2.Per KDB 447498 D01v05r01, for each exposure position, if the highest output channel reported $SAR \leq 0.8 W/kg$, other channels SAR testing are not necessary

3.Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.

4.Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.

5.Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are $\leq 0.8 W/kg$. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is $> 1.45 W/kg$, the remaining required test channels must also be tested.

6.Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is $\leq 1.45 W/kg$; Per KDB 941225 D05, 16QAM SAR testing is not required.

7.Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is $\leq 1.45 W/kg$; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.

8.Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8 W/Kg$; if the deviation among the repeated measurement is $\leq 20\%$, and the measured SAR $< 1.45 W/Kg$, only one repeated measurement is required.

9.When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



11.1 SAR Results**Face Up SAR****<GSM>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
#1	GSM850	GSM Voice	Front	10	190	836.6	33.07	34.00	1.239	-0.08	0.277	0.343
#2	PCS1900	GSM Voice	Front	10	512	1850.2	30.59	31.00	1.099	0.01	0.445	0.489

<WCDMA>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
#3	WCDMA Band II	RMC 12.2K	Front	10	9538	1907.6	23.61	24.00	1.094	0.05	0.594	0.650
#4	WCDMA Band V	RMC 12.2K	Front	10	4233	846.6	23.56	24.00	1.107	-0.11	0.198	0.219

<LTE>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
#5	LTE Band 2	20MHz/1RB	Front	10	18900	1880	23.34	23.5	1.038	0.02	0.519	0.538
	LTE Band 2	20MHz/50RB	Front	10	18900	1880	23.04	23.5	1.112	-0.10	0.511	0.568
#6	LTE Band 4	20MHz/1RB	Front	10	20050	1720	23.33	23.5	1.040	0.03	0.463	0.481
	LTE Band 4	20MHz/50RB	Front	10	20300	1745	23.26	23.5	1.057	0.05	0.454	0.480
#7	LTE Band 5	10MHz/1RB	Front	10	20525	836.5	23.83	24.0	1.040	-0.10	0.165	0.172
	LTE Band 5	10MHz/25RB	Front	10	20450	844	23.65	24.0	1.084	-0.11	0.158	0.171
#8	LTE Band 7	20MHz/1RB	Front	10	21100	2535	23.39	24.0	1.151	0.07	0.462	0.532
	LTE Band 7	20MHz/50RB	Front	10	20850	2510	23.31	24.0	1.172	-0.05	0.447	0.524
#9	LTE Band 12	10MHz/1RB	Front	10	23095	707.5	23.47	24.0	1.130	0.02	0.256	0.289
	LTE Band 12	10MHz/50RB	Front	10	23095	707.5	23.25	24.0	1.189	-0.09	0.237	0.282
#10	LTE Band 13	10MHz/1RB	Front	10	23230	782	23.22	24.0	1.197	0.04	0.254	0.304
	LTE Band 13	10MHz/50RB	Front	10	23230	782	22.93	24.0	1.279	-0.11	0.248	0.317
	LTE Band 17	10MHz/1RB	Front	10	23780	709	23.48	24.0	1.127	-0.09	0.199	0.224



#11	LTE Band 17	10MHz/50RB	Front	10	23790	710	23.64	24.0	1.086	0.05	0.203	0.221
-----	-------------	------------	-------	----	-------	-----	-------	------	-------	------	--------------	-------

Limbs SAR

<GSM>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
#12	GSM850	GSM Voice	Back	0	190	836.6	33.07	34.00	1.239	-0.13	0.625	0.774
	GSM850	GPRS 2TX slot	Back	0	190	836.6	30.99	31.00	1.002	0.05	0.567	0.568
#13	PCS1900	GSM Voice	Back	0	512	1850.2	30.59	31.00	1.099	0.09	0.857	0.942
	PCS1900	GSM Voice	Back	0	661	1880.0	29.54	31.00	1.400	0.06	0.734	1.027
	PCS1900	GSM Voice	Back	0	810	1909.8	30.05	31.00	1.245	0.11	0.843	1.049
	PCS1900	GPRS 3TX slot	Back	0	512	1850.2	26.56	27.00	1.107	0.05	0.769	0.851
	PCS1900	GPRS 3TX slot	Back	0	661	1880.0	25.68	27.00	1.355	-0.05	0.717	0.972
	PCS1900	GPRS 3TX slot	Back	0	810	1909.8	25.97	27.00	1.268	-0.03	0.729	0.924

<WCDMA>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
#14	WCDMA Band II	RMC 12.2K	Back	0	9538	1907.6	23.61	24.00	1.094	0.11	0.898	0.982
	WCDMA Band II	RMC 12.2K	Back	0	9400	1880.0	23.49	24.00	1.125	0.08	0.814	0.915
	WCDMA Band II	RMC 12.2K	Back	0	9262	1852.4	23.53	24.00	1.114	-0.11	0.822	0.916
#15	WCDMA Band V	RMC 12.2K	Back	0	4233	846.6	23.56	24.00	1.107	0.10	0.457	0.506



<LTE>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
#16	LTE Band 2	20MHz/1RB	Back	0	18900	1880	23.34	23.5	1.038	-0.06	0.758	0.786
	LTE Band 2	20MHz/50RB	Back	0	18900	1880	23.04	23.5	1.112	0.03	0.711	0.790
#17	LTE Band 4	20MHz/1RB	Back	0	20050	1720	23.33	23.5	1.040	0.05	0.624	0.649
	LTE Band 4	20MHz/50RB	Back	0	20300	1745	23.26	23.5	1.057	-0.10	0.605	0.639
#18	LTE Band 5	10MHz/1RB	Back	0	20525	836.5	23.83	24.0	1.040	0.05	0.197	0.205
	LTE Band 5	10MHz/25RB	Back	0	20450	844	23.65	24.0	1.084	-0.12	0.183	0.198
#19	LTE Band 7	20MHz/1RB	Back	0	21100	2535	23.39	24.0	1.151	-0.05	0.887	1.021
	LTE Band 7	20MHz/1RB	Back	0	20850	2510	23.27	24.0	1.183	0.03	0.865	1.023
	LTE Band 7	20MHz/1RB	Back	0	21350	2560	23.26	24.0	1.186	0.05	0.862	1.022
	LTE Band 7	20MHz/50RB	Back	0	20850	2510	23.31	24.0	1.172	-0.11	0.879	1.030
	LTE Band 7	20MHz/50RB	Back	0	21100	2535	23.07	24.0	1.239	-0.12	0.858	1.063
	LTE Band 7	20MHz/50RB	Back	0	21350	2560	23.03	24.0	1.250	0.08	0.850	1.063
#20	LTE Band 12	10MHz/1RB	Back	0	23095	707.5	23.47	24.0	1.130	0.03	0.351	0.397
	LTE Band 12	10MHz/50RB	Back	0	23095	707.5	23.25	24.0	1.189	-0.18	0.345	0.410
#21	LTE Band 13	10MHz/1RB	Back	0	23230	782	23.22	24.0	1.197	0.04	0.407	0.487
	LTE Band 13	10MHz/50RB	Back	0	23230	782	22.93	24.0	1.279	-0.05	0.398	0.509
	LTE Band 17	10MHz/1RB	Back	0	23780	709	23.48	24.0	1.127	-0.10	0.321	0.362
#22	LTE Band 17	10MHz/50RB	Back	0	23790	710	23.64	24.0	1.086	-0.11	0.334	0.363

Note:

1. Per KDB 865664 D01V01, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/Kg.
2. Per KDB 865664 D01V01, if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/Kg, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/Kg.
4. The ratio is the difference in percentage between original and repeated measured SAR.



11.2 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. The following procedures are applied to determine if repeated measurements are required.

- 1 Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2 When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3 Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

SAR Measurement Variability

Band	Mode	Test Position	Spacing (mm)	Ch.	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
PCS1900	GSM Voice	Back	0	512	0.857	0.779	1.100	N/A
PCS1900	GSM Voice	Back	0	810	0.843	0.753	1.120	N/A
WCDMA Band II	RMC 12.2K	Back	0	9538	0.898	0.898	1.000	N/A
WCDMA Band II	RMC 12.2K	Back	0	9400	0.814	0.702	1.160	N/A
WCDMA Band II	RMC 12.2K	Back	0	9262	0.822	0.806	1.020	N/A
LTE Band 7	20MHz/1RB	Back	0	21100	0.887	0.814	1.090	N/A
LTE Band 7	20MHz/1RB	Back	0	20850	0.865	0.801	1.080	N/A
LTE Band 7	20MHz/1RB	Back	0	21350	0.862	0.750	1.150	N/A
LTE Band 7	20MHz/50RB	Back	0	20850	0.879	0.870	1.010	N/A
LTE Band 7	20MHz/50RB	Back	0	21100	0.858	0.780	1.100	N/A
LTE Band 7	20MHz/50RB	Back	0	21350	0.850	0.794	1.070	N/A



12 Simultaneous Transmission Analysis

EUT will choose either GSM/WCDMA/ LTE according to the network signal condition; therefore, GSM/WCDMA / LTE cannot transmit simultaneously.



13 Measurement Uncertainty

Measurement uncertainty evaluation for SAR test

NO	Source	Uncert. ai (%)	Prob. Dist.	Div. k	ci (1g)	ci (10g)	Stand.U ncert. ui (1g)	Stand.U ncert. ui (10g)	Veff
1	Repeat	0.4	N	1	1	1	0.4	0.4	9
Instrument									
2	Probe calibration	7	N	2	1	1	3.5	3.5	∞
3	Axial isotropy	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
4	Hemispherical isotropy	9.4	R	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
5	Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
7	Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
8	Readout electronics	0.3	N	1	1	1	0.3	0.3	∞
9	Response time	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
10	Integration time	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
11	Ambient noise	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
12	Ambient reflections	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Probe positioner mech. restrictions	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
14	Probe positioning with respect to phantom shell	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
15	Max.SAR evaluation	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞



Test sample related									
16	Device positioning	3.8	N	1	1	1	3.8	3.8	99
17	Device holder	5.1	N	1	1	1	5.1	5.1	5
18	Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up									
19	Phantom uncertainty	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
20	Liquid conductivity (target)	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
21	Liquid conductivity (meas)	2.5	N	1	0.64	0.43	1.6	1.2	∞
22	Liquid Permittivity (target)	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.5	∞
23	Liquid Permittivity (meas)	2.5	N	1	0.6	0.49	1.5	1.2	∞
Combined standard			RSS	$U_c = \sqrt{\sum_{i=1}^n C_i^2 U_i^2}$			11.4%	11.3%	236
Expanded uncertainty(P=95%)		$U = k U_c$,k=2					22.8%	22.6%	

Measurement uncertainty evaluation for System Check (0.3-3GHz)

No.	Error Description	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement System									
1	Probe calibration	6.05%	N	1	1	1	6.05%	6.05%	∞
2	Axial isotropy	0.00%	R	$\sqrt{3}$	0.7	0.7	0.00%	0.00%	∞
3	Hemispherical isotropy	0.00%	R	$\sqrt{3}$	0.7	0.7	0.00%	0.00%	∞
4	Boundary Effects	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
5	Probe Linearity	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
6	System Detection Limits	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
7	Modulation response	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
8	Readout electronics	0.00%	N	1	1	1	0.00%	0.00%	∞
9	Response time	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
10	Integration time	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
11	RF Ambient Noise	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
12	RF Ambient Reactions	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
13	Probe Positioner	0.02%	R	$\sqrt{3}$	1	1	0.01%	0.01%	∞
14	Probe Positioning	0.40%	R	$\sqrt{3}$	1	1	0.23%	0.23%	∞
15	Max. SAR Eval.	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
System check source (dipole)									
16	Dev. of experimental dipole	0.00%	N	1	1	1	0.00%	0.00%	∞



17	Dipole Axis to Liquid Dist.	2.00%	R	$\sqrt{3}$	1	1	1.15%	1.15%	∞
18	Input power & SAR drift	5.00%	R	$\sqrt{3}$	1	1	2.89%	2.89%	∞
Phantom and Setup									
19	Phantom uncertainty	7.20%	R	$\sqrt{3}$	1	1	4.16%	4.16%	∞
20	SAR correction	0.00%	N	1	1	0.84	0.00%	0.00%	∞
21	Liquid conductivity (meas.)	2.50%	N	1	0.78	0.71	1.95%	1.78%	∞
22	Liquid permittivity (meas.)	2.50%	N	1	0.23	0.26	0.58%	0.65%	∞
23	Temp. unc. - Conductivity	3.60%	R	$\sqrt{3}$	0.78	0.71	1.62%	1.48%	∞
24	Temp. unc. - Permittivity	0.50%	R	$\sqrt{3}$	0.23	0.26	0.07%	0.08%	∞
Combined standard uncertainty			RSS				8.65%	8.57%	
Expanded uncertainty (confidence interval of 95%)			K=2				17.30%	17.14%	

Measurement uncertainty evaluation for System Check (3-6GHz)



No.	Error Description	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement System									
1	Probe calibration	6.65%	N	1	1	1	6.65%	6.65%	∞
2	Axial isotropy	0.00%	R	$\sqrt{3}$	0.7	0.7	0.00%	0.00%	∞
3	Hemispherical isotropy	0.00%	R	$\sqrt{3}$	0.7	0.7	0.00%	0.00%	∞
4	Boundary Effects	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
5	Probe Linearity	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
6	System Detection Limits	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
7	Modulation response	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
8	Readout electronics	0.00%	N	1	1	1	0.00%	0.00%	∞
9	Response time	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
10	Integration time	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
11	RF Ambient Noise	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
12	RF Ambient Reactions	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
13	Probe Positioner	0.04%	R	$\sqrt{3}$	1	1	0.02%	0.02%	∞
14	Probe Positioning	0.80%	R	$\sqrt{3}$	1	1	0.46%	0.46%	∞
15	Max. SAR Eval.	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
System check source (dipole)									
16	Dev. of experimental dipole	0.00%	N	1	1	1	0.00%	0.00%	∞
17	Dipole Axis to Liquid Dist.	2.00%	R	$\sqrt{3}$	1	1	1.15%	1.15%	∞
18	Input power & SAR drift	5.00%	R	$\sqrt{3}$	1	1	2.89%	2.89%	∞
Phantom and Setup									
19	Phantom uncertainty	7.60%	R	$\sqrt{3}$	1	1	4.39%	4.39%	∞
20	SAR correction	0.00%	N	1	1	0.84	0.00%	0.00%	∞
21	Liquid conductivity (meas.)	2.50%	N	1	0.78	0.71	1.95%	1.78%	∞



22	Liquid permittivity (meas.)	2.50%	N	1	0.23	0.26	0.58%	0.65%	∞
23	Temp. unc. - Conductivity	3.60%	R	$\sqrt{3}$	0.78	0.71	1.62%	1.48%	∞
24	Temp. unc. - Permittivity	0.50%	R	$\sqrt{3}$	0.23	0.26	0.07%	0.08%	∞
Combined standard uncertainty			RSS				9.25%	9.18%	
Expanded uncertainty (confidence interval of 95%)			K=2				18.51%	18.36%	



Appendix A. EUT Photos and Test Setup Photos

	
Front(10mm)	Back(0mm)



Appendix B. Plots of SAR System Check

750MHz Head System Check

Date:05/31/2023

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1163



Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 750 \text{ MHz}$; $\sigma = 0.916 \text{ S/m}$; $\epsilon_r = 43.144$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Area Scan (81x81x1): Measurement grid: $dx=15.00 \text{ mm}$, $dy=15.00 \text{ mm}$ Maximum value of SAR (interpolated) = 2.52 W/kg **Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 53.81 V/m ; Power Drift = 0.02 dB Peak SAR (extrapolated) = 3.55 W/kg **SAR(1 g) = 2.18 W/kg ; SAR(10 g) = 1.40 W/kg** Maximum value of SAR (measured) = 2.52 W/kg  $0 \text{ dB} = 2.52 \text{ W/kg} = 4.01 \text{ dBW/kg}$

System Performance Check 750MHz 250mW



Report No.:18220WC30109101

FCC ID: 2BBNN-KSW-80

Page 58 of 142

835MHz Head System Check

Date: 05/26/2023

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d154



Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 41.637$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05,06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Area Scan (61x91x1): Measurement grid: $dx=15.00 \text{ mm}$, $dy=15.00 \text{ mm}$ Maximum value of SAR (interpolated) = 2.875 W/kg **Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 50.286 V/m ; Power Drift = -0.11 dB Peak SAR (extrapolated) = 3.175 W/kg **SAR(1 g) = 2.42 W/kg ; SAR(10 g) = 1.55 W/kg** Maximum value of SAR (measured) = 2.574 W/kg 0 dB = $2.52 \text{ W/kg} = 4.01 \text{ dBW/kg}$

System Performance Check 835MHz 250mW



Report No.:18220WC30109101

FCC ID: 2BBNN-KSW-80

Page 59 of 142

1750MHz Head System Check

Date: 06/02/2023

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1021

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1750$ MHz; $\sigma = 1.365$ S/m; $\epsilon_r = 39.960$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.61, 8.61, 8.61); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Area Scan (81x81x1): Measurement grid: dx=15.00 mm, dy=15.00 mm

Maximum value of SAR (interpolated) = 8.07 W/kg



Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 73.69 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 13.1 W/kg

SAR(1 g) = 9.38 W/kg; SAR(10 g) = 5.26 W/kg

Maximum value of SAR (measured) = 7.84 W/kg



0 dB = 7.84 W/kg = 8.94 dBW/kg

System Performance Check 1750MHz 250mW

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn



Report No.:18220WC30109101

FCC ID: 2BBNN-KSW-80

Page 60 of 142

1900MHz Head System Check

Date: 05/30/2023

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d175

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1900$ MHz; $\sigma = 1.403$ S/m; $\epsilon_r = 40.092$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05.06.2022;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;

Phantom: SAM 1; Type: SAM;

Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Area Scan (81x81x1): Measurement grid: $dx=15.00$ mm, $dy=15.00$ mm

Maximum value of SAR (interpolated) = 7.10W/kg



Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 69.43 V/m; Power Drift = -0.01dB

Peak SAR (extrapolated) = 11.9 W/kg

SAR(1 g) = 10.17 W/kg; SAR(10 g) = 5.38 W/kg

Maximum value of SAR (measured) = 7.07 W/kg



0 dB = 7.07 W/kg = 8.49 dBW/kg

System Performance Check 1900MHz 250mW



Report No.:18220WC30109101

FCC ID: 2BBNN-KSW-80

Page 61 of 142

2600MHz Head System Check

Date: 06/06/2023

DUT: Dipole 2600 MHz; Type: D2600V2;

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2600$ MHz; $\sigma = 1.960$ S/m; $\epsilon_r = 39.008$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 – SN7396; ConvF(7.38, 7.38, 7.38); Calibrated: 05.06.2022;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06.2022
- Phantom: SAM; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Area Scan (101x101x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 14.5 W/kg



Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 84.05 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 27.9 W/kg

SAR(1 g) = 14.54 W/kg; SAR(10 g) = 6.29 W/kg

Maximum value of SAR (measured) = 15.5 W/kg



0 dB = 15.5 W/kg = 11.90 dBW/kg

System Performance Check 2600MHz 250mW



Appendix C. Plots of SAR Test Data

#1

Date: 05/26/2023

GSM850_GSM Voice_Face Up_CH190

Communication System: UID 0, GSM (0); Frequency: 836.6MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.885$ S/m; $\epsilon_r = 41.195$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.411 W/kg


Front /Zoom Scan (5x5x7)/Cube 0:Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 13.56 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.498 W/kg

SAR(1 g) = 0.277 W/kg; SAR(10 g) = 0.166 W/kg

Maximum value of SAR (measured) =0.377 W/kg



#2

Date: 05/30/2023

GSM1900_GSM Voice_Face Up_CH512

Communication System: UID 0, GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.414$ S/m; $\epsilon_r = 39.51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05,06.2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Front /Area Scan (61x61x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (measured) = 0.712 W/kg


Front /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.50 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.807 W/kg

SAR(1 g) = 0.445 W/kg; SAR(10 g) = 0.235 W/kg

Maximum value of SAR (measured) = 0.627 W/kg



#3

Date: 05/30/2023

WCDMA 1900_RMC 12.2K_Fack Up_Ch9538



Communication System: UID 0, Generic WCDMA (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908 \text{ MHz}$; $\sigma = 1.45 \text{ S/m}$; $\epsilon_r = 39.68$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05,06.2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$ Maximum value of SAR (measured) = 1.33 W/kg **Front /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 16.52 V/m ; Power Drift = 0.05 dB Peak SAR (extrapolated) = 1.50W/kg **SAR(1 g) = 0.594W/kg ; SAR(10 g) = 0.298 W/kg** Maximum value of SAR (measured) = 1.18 W/kg 

#4

Date: 05/26/2023

WCDMA 850_RMC 12.2K_Face Up_Ch4233


Communication System: UID 0, Generic WCDMA (0); Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 847\text{Hz}$; $\sigma = 0.901\text{ S/m}$; $\epsilon_r = 41.27$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05,06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$ Maximum value of SAR (measured) = 0.291 W/kg **Front /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 13.18 V/m ; Power Drift = -0.11 dB Peak SAR (extrapolated) = 0.364 W/kg **SAR(1 g) = 0.198 W/kg ; SAR(10 g) = 0.117 W/kg** Maximum value of SAR (measured) = 0.275 W/kg 

Date: 05/30/2023

LTE Band 2_ Face Up _1RB_Ch18900

Communication System: UID 0, Generic LTE (0); Frequency: 1880.0 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880.0$ MHz; $\sigma = 1.414$ S/m; $\epsilon_r = 39.47$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05,06,2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Front /Area Scan (51x51x1):Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 1.49 W/kg


Front /Zoom Scan (5x5x7)/Cube 0:Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.68 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.64 W/kg

SAR(1 g) = 0.519 W/kg; SAR(10 g) = 0.211 W/kg

Maximum value of SAR (measured) = 1.28 W/kg



#6

Date: 06/02/2023

LTE Band 4_ Face Up _1RB_ Ch20050

Communication System: UID 0, Generic LTE (0); Frequency: 1720 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1720$; $\sigma = 1.347$ S/m; $\epsilon_r = 39.01$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.61, 8.61, 8.61); Calibrated: 05,06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (51x51x1):Measurement grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 1.12 W/kg



Front /Zoom Scan (5x5x7)/Cube 0:Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 14.72 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.463 W/kg; SAR(10 g) = 0.199 W/kg

Maximum value of SAR (measured) = 1.02 W/kg



LTE Band 5_ Face Up _1RB_Ch20525

Communication System: UID 0, Generic LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 837$ MHz; $\sigma = 0.880$ S/m; $\epsilon_r = 41.24$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.226 W/kg


Front /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 13.75 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.293 W/kg

SAR(1 g) = 0.165 W/kg; SAR(10 g) = 0.098 W/kg

Maximum value of SAR (measured) = 0.220 W/kg



LTE Band 7_ Face Up _1RB_Ch21100

Communication System: UID 0, Generic LTE (0); Frequency: 2535 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2535$ MHz; $\sigma = 1.924$ S/m; $\epsilon_r = 38.03$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 – SN7396; ConvF(7.38, 7.38, 7.38); Calibrated: 05.06.2022;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06.2022
- Phantom: SAM; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (51x51x1):Measurement grid: dx=1.200mm, dy=1.200mm

Maximum value of SAR (interpolated) = 1.26 W/kg



Front /Zoom Scan (7x7x7)/Cube 0:Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.19 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.462 W/kg; SAR(10 g) = 0.101 W/kg

Maximum value of SAR (measured) = 1.28 W/kg



#9

Date: 05/31/2023

LTE Band 12_ Face Up _1RB_Ch23095


Communication System: UID 0, Generic LTE (0); Frequency: 707.5 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 708 \text{ MHz}$; $\sigma = 0.85 \text{ S/m}$; $\epsilon_r = 43.42$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05,06,2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$ Maximum value of SAR (interpolated) = 0.401 W/kg **Front /Zoom Scan (5x5x7)/Cube 0:**Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 13.35 V/m ; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.436 W/kg **SAR(1 g) = 0.256 W/kg ; SAR(10 g) = 0.157 W/kg** Maximum value of SAR (measured) = 0.358 W/kg 

#10

Date: 05/31/2023

LTE Band 13_ Face Up _1RB_Ch23230


Communication System: UID 0, Generic LTE (0); Frequency: 782 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.90 \text{ S/m}$; $\epsilon_r = 43.81$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$ Maximum value of SAR (interpolated) = 0.426 W/kg **Front /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 16.58 V/m ; Power Drift = 0.04 dB Peak SAR (extrapolated) = 0.293 W/kg **SAR(1 g) = 0.254 W/kg ; SAR(10 g) = 0.115 W/kg** Maximum value of SAR (measured) = 0.293 W/kg 

LTE Band 17_ Face Up _50RB_Ch23790

Communication System: UID 0, Generic LTE (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 710 \text{ MHz}$; $\sigma = 0.82 \text{ S/m}$; $\epsilon_r = 43.39$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

Front /Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (measured) = 0.305 W/kg


Front /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.69 V/m ; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.364 W/kg

SAR(1 g) = 0.203 W/kg ; SAR(10 g) = 0.121 W/kg

Maximum value of SAR (measured) = 0.278 W/kg



#12

Date: 05/26/2023

GSM850_GSM Voice_Limbs_Ch190

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:1.99986

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.885$ S/m; $\epsilon_r = 41.195$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05,06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1):Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) =1.45W/kg



BACK /Zoom Scan (5x5x7)/Cube 0:Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 27.78 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.97 W/kg

SAR(1 g) = 0.625 W/kg; SAR(10 g) = 0.238 W/kg

Maximum value of SAR (measured) =1.43W/kg



#13

Date: 05/30/2023

GSM1900_GSM Voice_Limbs_Ch512

Communication System: UID 0, GPRS(4 Tx slots) (0); Frequency: 1850.2MHz;Duty Cycle: 1:1.99986

Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.414 \text{ S/m}$; $\epsilon_r = 39.51$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05,06.2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

BACK /Area Scan (61x61x1):Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (measured) =2.19 W/kg



BACK/Zoom Scan (5x5x7)/Cube 0:Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.01 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.53 W/kg

SAR(1 g) = 0.857 W/kg; SAR(10 g) = 0.353 W/kg

Maximum value of SAR (measured) = 1.95 W/kg



#14

Date: 05/30/2023

WCDMA 1900_RMC 12.2K_Limbs_Ch9538


Communication System: UID 0, Generic WCDMA (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908 \text{ MHz}$; $\sigma = 1.45 \text{ S/m}$; $\epsilon_r = 39.68$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05,06.2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

BACK/Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$ Maximum value of SAR (measured) = 2.51 W/kg **BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 30.59 V/m ; Power Drift = 0.11 dB Peak SAR (extrapolated) = 2.91 W/kg **SAR(1 g) = 0.898 W/kg ; SAR(10 g) = 0.468 W/kg** Maximum value of SAR (measured) = 2.26 W/kg 

#15

Date: 05/26/2023

WCDMA 850_RMC 12.2K_Limbs_Ch4233

Communication System: UID 0, Generic WCDMA (0); Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 847$ MHz; $\sigma = 0.901$ S/m; $\epsilon_r = 41.27$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05,06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK/Area Scan (61x61x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (measured) = 0.838 W/kg



BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.49 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.10 W/kg

SAR(1 g) = 0.457 W/kg; SAR(10 g) = 0.230 W/kg

Maximum value of SAR (measured) = 0.803 W/kg



Date: 05/30/2023

LTE Band 2_ Limbs _1RB_Ch18900

Communication System: UID 0, Generic LTE (0); Frequency: 1880.0 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880.0$ MHz; $\sigma = 1.414$ S/m; $\epsilon_r = 39.47$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.13, 8.13, 8.13); Calibrated: 05,06,2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1):Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) =3.89 W/kg


BACK /Zoom Scan (5x5x7)/Cube 0:Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.32 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 4.34 W/kg

SAR(1 g) = 0.758 W/kg; SAR(10 g) =0.325 W/kg

Maximum value of SAR (measured) = 3.14W/kg



Date: 06/02/2023

LTE Band 4_Limbs_1RB_Ch20050

Communication System: UID 0, Generic LTE (0); Frequency: 1720.0 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1720.0$ MHz; $\sigma = 1.347$ S/m; $\epsilon_r = 39.01$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(8.61, 8.61, 8.61); Calibrated: 05,06,2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 1.83 W/kg


BACK /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.518 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.12W/kg

SAR(1 g) = 0.624 W/kg; SAR(10 g) = 0.338 W/kg

Maximum value of SAR (measured) = 1.60W/kg



LTE Band 5_ Limbs_1RB_Ch20525

Communication System: UID 0, Generic LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 837$ MHz; $\sigma = 0.880$ S/m; $\epsilon_r = 41.24$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.71, 9.71, 9.71); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 0.286 W/kg



BACK /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.94 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.335 W/kg

SAR(1 g) = 0.197 W/kg; SAR(10 g) = 0.085 W/kg

Maximum value of SAR (measured) = 0.251 W/kg



Date: 06/06/2023

LTE Band 7_ Limbs_1RB_Ch21100

Communication System: UID 0, Generic LTE (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2535$ MHz; $\sigma = 1.924$ S/m; $\epsilon_r = 38.03$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(7.38, 7.38, 7.38); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1): Measurement grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.286 W/kg


BACK /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 19.95 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 3.39 W/kg

SAR(1 g) = 0.887 W/kg; SAR(10 g) = 0.387 W/kg

Maximum value of SAR (measured) = 2.48 W/kg



LTE Band 12_ Limbs_1RB_Ch23095

Communication System: UID 0, Generic LTE (0); Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 708 \text{ MHz}$; $\sigma = 0.85 \text{ S/m}$; $\epsilon_r = 43.42$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (interpolated) = 0.311 W/kg



BACK /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.45 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.415 W/kg

SAR(1 g) = 0.351 W/kg ; SAR(10 g) = 0.112 W/kg

Maximum value of SAR (measured) = 0.452 W/kg



LTE Band 13_ Limbs_1RB_Ch23230

Communication System: UID 0, Generic LTE (0); Frequency: 782 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.90 \text{ S/m}$; $\epsilon_r = 43.81$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK/Area Scan (31x41x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (measured) = 0.754 W/kg



BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.87 V/m ; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.957 W/kg

SAR(1 g) = 0.407 W/kg ; SAR(10 g) = 0.221 W/kg

Maximum value of SAR (measured) = 0.753 W/kg



LTE Band 17_ Limbs_50RB_Ch23790

Communication System: UID 0, Generic LTE (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 710 \text{ MHz}$; $\sigma = 0.82 \text{ S/m}$; $\epsilon_r = 43.39$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7396; ConvF(9.82, 9.82, 9.82); Calibrated: 05.06.2022;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn387; Calibrated: Sep.06,2022;
- Phantom: SAM 1; Type: SAM;
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.10 (7164)

BACK /Area Scan (61x61x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 1.12 W/kg



BACK /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.56 V/m ; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 0.334 W/kg ; SAR(10 g) = 0.104 W/kg

Maximum value of SAR (measured) = 0.850 W/kg



Appendix D. DASY System Calibration Certificate

In Collaboration with
s p e a g
CALIBRATION LABORATORY中国认可
国际互认
校准
CALIBRATION
CNAS L0570Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Client

Anbotek (Auden)

Certificate No: Z23-98671

CALIBRATION CERTIFICATE

Object EX3DV4 - SN:7396

Calibration Procedure(s) FF-Z12-006-08
Calibration Procedures for Dosimetric E-field Probes

Calibration date: May 06, 2023

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	20-Jun-22 (CTTL, No.J22 X07447)	Jun-21
Power sensor NRP-Z91	101547	20-Jun-22 (CTTL, No.J22 X07447)	Jun-21
Power sensor NRP-Z91	101548	20-Jun-22 (CTTL, No.J22 X07447)	Jun-21
Reference10dBAttenuator	18N50W-10dB	13-Mar-23(CTTL,No.J23X01547)	Mar-22
Reference20dBAttenuator	18N50W-20dB	13-Mar-23(CTTL, No.J23X01548)	Mar-22
Reference Probe EX3DV4	SN 7433	26-Sep-22(SPEAG,No.EX3-7433_Sep22)	Sep-21
DAE4	SN 549	13-Dec-22(SPEAG, No.DAE4-549_Dec22)	Dec -21
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGeneratorMG3700A	6201052605	27-Jun-22 (CTTL, No.J22X04776)	Jun-21
Network Analyzer E5071C	MY46110673	13-Jan-23 (CTTL, No.J23X00285)	Jan -22

	Name	Function
Calibrated by:	Yu Zongying	SAR Test Engineer
Reviewed by:	Lin Hao	SAR Test Engineer
Approved by:	Qi Dianyuan	SAR Project Leader

Signature

Issued: May06, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z23-98671

Page 1 of 11





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
 Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
 E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A,B,C,D	modulation dependent linearization parameters
Polarization Φ	Φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i $\theta=0$ is normal to probe axis

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\theta=0$ ($f \leq 900\text{MHz}$ in TEM-cell; $f > 1800\text{MHz}$: waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}; A,B,C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800\text{MHz}$) and inside waveguide using analytical field distributions based on power measurements for $f > 800\text{MHz}$. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from $\pm 50\text{MHz}$ to $\pm 100\text{MHz}$.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).





In Collaboration with

s p e a g**CALIBRATION LABORATORY**

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Probe EX3DV4

SN: 7396

Calibrated: May 06, 2023

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cttl@chinaatl.com [Http://www.chinaatl.cn](http://www.chinaatl.cn)

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7396**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.54	0.53	0.50	±10.0%
DCP(mV) ^B	97.8	104.5	102.5	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB μV	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	199.9	±2.4%
		Y	0.0	0.0	1.0		203.3	
		Z	0.0	0.0	1.0		195.0	

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X, Y, Z do not affect the E²-field uncertainty inside TSL (see Page 5 and Page 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
 Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
 E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7396

Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	9.82	9.82	9.82	0.30	0.85	±12.1%
835	41.5	0.90	9.71	9.71	9.71	0.15	1.36	±12.1%
900	41.5	0.97	9.87	9.87	9.87	0.16	1.37	±12.1%
1750	40.1	1.37	8.61	8.61	8.61	0.25	1.04	±12.1%
1900	40.0	1.40	8.13	8.13	8.13	0.24	1.01	±12.1%
2100	39.8	1.49	8.14	8.14	8.14	0.24	1.04	±12.1%
2300	39.5	1.67	7.85	7.85	7.85	0.40	0.75	±12.1%
2450	39.2	1.80	7.57	7.57	7.57	0.50	0.75	±12.1%
2600	39.0	1.96	7.38	7.38	7.38	0.64	0.68	±12.1%
5250	35.9	4.71	5.33	5.33	5.33	0.45	1.30	±13.3%
5600	35.5	5.07	4.89	4.89	4.89	0.45	1.35	±13.3%
5750	35.4	5.22	4.92	4.92	4.92	0.45	1.45	±13.3%

^C Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequency below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.





In Collaboration with

s p e a g**CALIBRATION LABORATORY**

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2218

Fax: +86-10-62304633-2209

E-mail: cttl@chinattl.com

Http://www.chinattl.cn

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7396

Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz] ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	10.09	10.09	10.09	0.30	0.90	± 12.1%
835	55.2	0.97	9.88	9.88	9.88	0.19	1.32	± 12.1%
900	55.0	1.05	9.82	9.82	9.82	0.23	1.15	± 12.1%
1750	53.4	1.49	8.24	8.24	8.24	0.24	1.06	± 12.1%
1900	53.3	1.52	7.97	7.97	7.97	0.19	1.24	± 12.1%
2100	53.2	1.62	8.18	8.18	8.18	0.19	1.39	± 12.1%
2300	52.9	1.81	7.88	7.88	7.88	0.55	0.80	± 12.1%
2450	52.7	1.95	7.53	7.53	7.53	0.46	0.89	± 12.1%
2600	52.5	2.16	7.38	7.38	7.38	0.52	0.80	± 12.1%
5250	48.9	5.36	4.93	4.93	4.93	0.45	1.80	± 13.3%
5600	48.5	5.77	4.19	4.19	4.19	0.48	1.90	± 13.3%
5750	48.3	5.94	4.52	4.52	4.52	0.48	1.95	± 13.3%

^C Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequency below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.






In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 7.4\%$ ($k=2$)

