

Maximum Permissible Exposure Report

Product Information

EUT : VITURE One Neckband
 Model Number : V1218
 Model Declaration : N/A
 Test Model : V1218
 Power Supply : 1,DC 3.85V by battery;2,Input: DC 5V
 Hardware version : SMB.370.09
 Software version : V1.1.230224.231304
 Sample ID : TZ230504409-2#&TZ230504409-4#

Bluetooth

Bluetooth Version : V5.0
 Operation Frequency : 2402- 2480 MHz
 Channel Number : 79 Channels for Bluetooth BR/EDR(DSS)
 : 40 Channels for BLE (DTS)
 Modulation Technology : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth BR/EDR (DSS)
 : GFSK for BLE (DTS)
 Data Rates : Bluetooth BR/EDR (DSS): 1/2/3Mbps
 : BLE (DTS): 1Mbps
 Antenna Type And Gain : Internal Antenna 1:
 : 0.57dBi

WiFi

WLAN : Supported IEEE 802.11a/b/g/n/ac
 IEEE 802.11b:2412-2462MHz
 IEEE 802.11g:2412-2462MHz
 IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz
 WLAN FCC Operation : IEEE 802.11n HT40: 2422-2452MHz / 5190-5230MHz / 5755-5795MHz
 Frequency : IEEE 802.11a: 5180-5240MHz / 5745-5825MHz
 : IEEE 802.11ac VHT20: 5180-5240MHz / 5745-5825MHz
 : IEEE 802.11ac VHT40: 5190-5230MHz / 5755-5795MHz
 : IEEE 802.11ac VHT80: 5210MHz / 5775MHz
 WLAN Channel Number : 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20)
 : 7 Channels for 2422-2452MHz(IEEE 802.11n HT40)
 : 4 Channels for 5180-5240MHz (IEEE 802.11a/ac VHT20/n HT20)
 : 2 Channels for 5190-5230MHz (IEEE 802.11ac VHT40/n HT40)
 : 1 Channels for 5210MHz (IEEE 802.11ac VHT80)
 : 5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20)
 : 2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40)
 : 1 Channels for 5775MHz(IEEE 802.11ac VHT80)
 WLAN Modulation : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
 Technology : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
 : IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 : IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
 : IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
 Antenna Type And Gain : Antenna 1:
 : 0.57dBi (Max.), for TX/RX (WLAN 2.4G Band)
 : 1.97dBi (Max.), for TX/RX (WLAN 5.2G Band)
 : 1.73dBi (Max.), for TX/RX (WLAN 5.8G Band)

Antenna 2:
-0.02dBi (Max.), for TX/RX (WLAN 2.4G Band)
1.61dBi (Max.), for TX/RX (WLAN 5.2G Band)
-0.44dBi (Max.), for TX/RX (WLAN 5.8G Band)

Note 1: Antenna position refer to EUT Photos.

Note 2: the above information was supplied by the applicant.

2. Limit and method

3.1 Refer evaluation method

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ "[max. power of channel, including tune-up tolerance, mW]/ (min. test separation distance, mm)] • [√f (GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Antenna Information

This Product can only use antennas certificated as follows provided by manufacturer;

Antenna Gain and type refer to Product information

4. Conducted Power

2.4G Band:
Bluetooth(BDR+EDR)

TestMode	Antenna	Channel	Result[dBm]
DH5	Ant1	2402	1.67
		2441	2.22
		2480	2.22
2DH5	Ant1	2402	2.62
		2441	2.86
		2480	2.58
3DH5	Ant1	2402	2.28
		2441	2.22
		2480	2.66

Bluetooth(BLE)

TestMode	Antenna	Channel	Result[dBm]
BLE_1M	Ant1	2402	1.56
		2440	3.1
		2480	3.5

WiFi 2.4GHz Band

TestMode	Antenna	Channel	Result[dBm]
11B	Ant1	2412	1.66
	Ant2	2412	1.03
	Ant1	2437	2.82
	Ant2	2437	1.33
	Ant1	2462	1.71
	Ant2	2462	0.73
11G	Ant1	2412	2.43
	Ant2	2412	0.00
	Ant1	2437	2.04
	Ant2	2437	0.70
	Ant1	2462	1.01
	Ant2	2462	-0.27
11N20MIMO	Ant1	2412	-3.36
	Ant2	2412	-2.08
	total	2412	0.34
	Ant1	2437	-2.51
	Ant2	2437	-1.49
	total	2437	1.04
	Ant1	2462	-3.37
	Ant2	2462	-2.23
	total	2462	0.25
11N40MIMO	Ant1	2422	-1.78
	Ant2	2422	-0.63
	total	2422	1.84
	Ant1	2437	-2.26
	Ant2	2437	-1.93
	total	2437	0.92
	Ant1	2452	-2.57
	Ant2	2452	-2.51
	total	2452	0.47

5G Band
UNII-1 Band

TestMode	Antenna	Channel	Result[dBm]
11A	Ant1	5180	-2.82
	Ant2	5180	-4.42
	Ant1	5200	-2.62
	Ant2	5200	-4.66
	Ant1	5240	-2.79
	Ant2	5240	-4.35
11N20MIMO	Ant1	5180	-5.36
	Ant2	5180	-7.56
	total	5180	-3.31
	Ant1	5200	-5.45
	Ant2	5200	-7.52
	total	5200	-3.35
	Ant1	5240	-4.96
	Ant2	5240	-7.00
11N40MIMO	total	5240	-2.85
	Ant1	5190	-5.19
	Ant2	5190	-7.47
	total	5190	-3.17
	Ant1	5230	-5.16
	Ant2	5230	-7.58
11AC20MIMO	total	5230	-3.19
	Ant1	5180	-5.55
	Ant2	5180	-7.57
	total	5180	-3.43
	Ant1	5200	-4.70
	Ant2	5200	-6.81
	total	5200	-2.62
	Ant1	5240	-4.82
11AC40MIMO	Ant2	5240	-6.74
	total	5240	-2.66
	Ant1	5190	-4.80
	Ant2	5190	-7.32
	total	5190	-2.87
	Ant1	5230	-5.32
11AC80MIMO	Ant2	5230	-7.35
	total	5230	-3.21
	Ant1	5210	-5.41
	Ant2	5210	-6.89
	total	5210	-3.08

UNII-3 Band

TestMode	Antenna	Channel	Result[dBm]
11A	Ant1	5745	-4.36
	Ant2	5745	-4.94
	Ant1	5785	-5.17
	Ant2	5785	-4.69
	Ant1	5825	-5.54
	Ant2	5825	-4.19
11N20MIMO	Ant1	5745	-6.11
	Ant2	5745	-7.07
	total	5745	-3.55
	Ant1	5785	-7.12
	Ant2	5785	-6.83
	total	5785	-3.96
	Ant1	5825	-7.68
	Ant2	5825	-6.29
	total	5825	-3.92
11N40MIMO	Ant1	5755	-6.44
	Ant2	5755	-7.03
	total	5755	-3.71
	Ant1	5795	-7.49
	Ant2	5795	-6.77
	total	5795	-4.10
11AC20MIMO	Ant1	5745	-6.28
	Ant2	5745	-6.93
	total	5745	-3.58
	Ant1	5785	-7.15
	Ant2	5785	-6.69
	total	5785	-3.90
	Ant1	5825	-7.84
	Ant2	5825	-6.33
	total	5825	-4.01
11AC40MIMO	Ant1	5755	-6.29
	Ant2	5755	-6.95
	total	5755	-3.60
	Ant1	5795	-7.48
	Ant2	5795	-6.74
	total	5795	-4.08
11AC80MIMO	Ant1	5775	-6.85
	Ant2	5775	-6.82
	total	5775	-3.82

5. Manufacturing Tolerance

Bluetooth(BDR+EDR)

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.5	1.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	2.5	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	1.5	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Bluetooth(BLE)

GFSK(1Mbps) (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	1.0	2.5	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

WiFi 2.4GHz Band – Antenna 1

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	1.0	2.5	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	2.0	1.5	0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	-4.0	-3.0	-4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	-2.5	-3.0	-3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

WiFi 2.4GHz Band – Antenna 2

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	0.5	1.0	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	-0.5	0.0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	-2.5	-2.0	-2.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	-1.0	-2.5	-3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

UNII-1 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-3.5	-3.5	-3.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-6.0	-6.0	-5.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-6.0	-5.0	-5.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	-5.5	-5.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	-5.5	-6.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	-6.0	--	--
Tolerance $\pm$ (dB)	1.0	--	--

UNII-1 Band – Antenna 2

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-5.0	-5.0	-5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-8.0	-8.0	-7.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-8.0	-7.5	-7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	-8.0	-8.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	-8.0	-8.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	-7.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

UNII-3 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	-5.0	-5.5	-6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	-6.5	-7.5	-8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	-7.0	-7.5	-8.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	-7.0	-8.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	-10.5	-10.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	--	--
Target (dBm)	-10.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

UNII-3 Band – Antenna 2

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	-5.5	-5.0	-4.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	-7.5	-7.5	-7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	-7.5	-7.0	-7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	-7.5	-7.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	-10.5	-10.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	--	--
Target (dBm)	-10.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

6. Measurement Results

6.1 Standalone Evaluation Result

Bluetooth(BDR+ED
R)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
GFSK	2.5	1.7783	0.57	1.1402	5	0.629	3.000	Yes
$\pi/4$ -DQPSK	3.5	2.2387	0.57	1.1402	5	0.791	3.000	Yes
8-DPSK	3.0	1.9953	0.57	1.1402	5	0.705	3.000	Yes

Bluetooth(BLE)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
GFSK(1Mbps)	4.0	2.5119	0.57	1.1402	5	0.888	3.000	Yes
GFSK(2Mbps)	0.0	1.0000	0.57	1.1402	5	0.353	3.000	Yes

WiFi 2.4GHz Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
IEEE 802.11b	3.5	2.2387	0.57	1.1402	5	0.793	3.000	Yes
IEEE 802.11g	3.0	1.9953	0.57	1.1402	5	0.707	3.000	Yes
IEEE 802.11n HT20	-2.0	0.6310	0.57	1.1402	5	0.223	3.000	Yes
IEEE 802.11n HT40	-1.5	0.7079	0.57	1.1402	5	0.251	3.000	Yes

WiFi 2.4GHz Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
IEEE 802.11b	2.0	1.5849	-0.02	0.9954	5	0.721	3.000	Yes
IEEE 802.11g	1.0	1.2589	-0.02	0.9954	5	0.573	3.000	Yes

IEEE 802.11n HT20	-1.0	0.7943	-0.02	0.9954	5	0.362	3.000	Yes
IEEE 802.11n HT40	0.0	1.0000	-0.02	0.9954	5	0.455	3.000	Yes

UNII-1 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
IEEE 802.11a	-2.0	0.6310	1.93	1.5596	5	0.448	3.000	Yes
IEEE 802.11n HT20	-4.5	0.3548	1.93	1.5596	5	0.252	3.000	Yes
IEEE 802.11ac VHT20	-4.0	0.3981	1.93	1.5596	5	0.283	3.000	Yes
IEEE 802.11n HT40	-4.5	0.3548	1.93	1.5596	5	0.252	3.000	Yes
IEEE 802.11ac VHT40	-4.5	0.3548	1.93	1.5596	5	0.252	3.000	Yes
IEEE 802.11ac VHT80	1.0	1.2590	1.93	1.5596	5	0.894	3.000	Yes

UNII-1 Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
IEEE 802.11a	-4.0	0.3981	1.61	1.4488	5	0.263	3.000	Yes
IEEE 802.11n HT20	-6.5	0.2239	1.61	1.4488	5	0.148	3.000	Yes
IEEE 802.11ac VHT20	-6.0	0.2512	1.61	1.4488	5	0.166	3.000	Yes
IEEE 802.11n HT40	-7.0	0.1995	1.61	1.4488	5	0.132	3.000	Yes
IEEE 802.11ac VHT40	-7.0	0.1995	1.61	1.4488	5	0.132	3.000	Yes
IEEE 802.11ac VHT80	1.0	1.2590	1.61	1.4488	5	0.830	3.000	Yes

UNII-3 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
IEEE 802.11a	-4.0	0.3981	1.73	1.4894	5	0.270	3.000	Yes

IEEE 802.11n HT20	-5.5	0.2818	1.73	1.4894	5	0.191	3.000	Yes
IEEE 802.11ac VHT20	-6.0	0.2512	1.73	1.4894	5	0.170	3.000	Yes
IEEE 802.11n HT40	-6.0	0.2512	1.73	1.4894	5	0.170	3.000	Yes
IEEE 802.11ac VHT40	-6.0	0.2512	1.73	1.4894	5	0.170	3.000	Yes
IEEE 802.11ac VHT80	1.0	1.2590	1.73	1.4894	5	0.854	3.000	Yes

UNII-3 Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	separation distance (mm)	Calculation Value	SAR Test Exclusion Threshold	SAR Test Exclusion
	dBm	mW						
IEEE 802.11a	-3.5	0.4467	-0.44	0.9036	5	0.203	3.000	Yes
IEEE 802.11n HT20	-6.0	0.2512	-0.44	0.9036	5	0.114	3.000	Yes
IEEE 802.11ac VHT20	-6.0	0.2512	-0.44	0.9036	5	0.114	3.000	Yes
IEEE 802.11n HT40	-6.5	0.2239	-0.44	0.9036	5	0.102	3.000	Yes
IEEE 802.11ac VHT40	-6.0	0.2512	-0.44	0.9036	5	0.114	3.000	Yes
IEEE 802.11ac VHT80	1.0	1.2590	-0.44	0.9036	5	0.573	3.000	Yes

Note: Calculation Value = $P \sqrt{F} / D$

P=Maximum turn-up power plus Antenna Gain in mW

F=Channel frequency in GHz

D=Minimum test separation distance in mm

Remark:

1. Output power including tune-up tolerance;
2. evaluate distance is 5mm from user manual provide by manufacturer;

6.2 Simultaneous Transmission

The highest estimated SAR(1g)		Summary Calculation Value	Limit	Conclusion
Ant.1(W/kg)	Ant.2(W/kg)			
0.119	0.111	0.144	≤1	Pass

The highest estimated SAR = the max Calculation Value / 7.5

Summary Calculation Value = $\sum$ of (the highest measured or estimated SAR_{Ant.1}+SAR_{Ant.2})/1.6

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06, No SAR is required.

-----THE END OF REPORT-----