



# FCC Test Report

**Test Report  
On Behalf of  
TRUSTSTONE GROUP, LLC  
For  
TRAVEL TUMBLER WARMER & CHARGING STATION  
Model No.: PY-TRTMB-BLK, PY-TRMG-BLK, HG-PY-TRTMB-BLK,  
HG-PY-TRMG-BLK**

**FCC ID: 2BBPL-PY-TRTMB-BLK**

**Prepared For :** TRUSTSTONE GROUP, LLC  
1370 Broadway 9th floor, New York, NY 10018, United States

**Prepared By :** Shenzhen HUAK Testing Technology Co., Ltd.  
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,  
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**Date of Test:** Sept. 26, 2024 ~ Oct. 23, 2024

**Date of Report:** Oct. 23, 2024

**Report Number:** HK2409265635-2E



### Test Result Certification

**Applicant's Name**..... : TRUSTSTONE GROUP, LLC

Address..... : 1370 Broadway 9th floor, New York, NY 10018, United States

**Manufacturer's Name** ..... : TRUSTSTONE GROUP, LLC

Address..... : 1370 Broadway 9th floor, New York, NY 10018, United States

#### Product Description

Trade Mark ..... : XO POPPY

Product Name..... : TRAVEL TUMBLER WARMER &CHARGING STATION

Model and/or Type Reference : PY-TRTMB-BLK, PY-TRMG-BLK, HG-PY-TRTMB-BLK, HG-PY-TRMG-BLK

**Standards** ..... : FCC CFR 47 PART 15, KDB 680106 D01

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test**..... :

Date (s) of Performance of Tests ..... : **Sept. 26, 2024 ~ Oct. 23, 2024**

Date of Issue..... : **Oct. 23, 2024**

Test Result..... : **Pass**

Testing Engineer

Len Liao

Technical Manager

Sliver Wan

Authorized Signatory

Jason Zhou



Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Frequency Band: 112-205KHz

| Channel List |                 |         |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (KHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01           | 165             | 02      | 165             |         |                 |         |                 |
|              |                 |         |                 |         |                 |         |                 |
|              |                 |         |                 |         |                 |         |                 |
|              |                 |         |                 |         |                 |         |                 |

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.

## 2. Summary of Test Results

### 2.1. Test procedures according to the technical standards:

FCC KDB 680106 D01 Wireless Power Transfer v04

| FCC CFR 47                                       |                                   |          |        |
|--|-----------------------------------|----------|--------|
| Standard Section                                 | Test Item                         | Judgment | Remark |
| FCC CFR 47 part1,<br>1.1310 KDB 680106<br>D01v04 | Electric Field Strength (E) (V/m) | PASS     |        |
|  | Magnetic Field Strength (H) (A/m) | PASS     |        |

### 2.2. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                                      | Uncertainty             |
|-----|---|-------------------------|
| 1   | All Emissions, Radiated(<30M)(9KHz-30MHz) | $\pm 3.90\text{dB}$     |
| 2   | Temperature                               | $\pm 0.5^\circ\text{C}$ |
| 3   | Humidity                                  | $\pm 2\%$               |



**2.3. Test Instruments**

| Description                          | Brand | Model No. | S/N        | Calibrated Date | Calibrated Until |
|--------------------------------------|-------|-----------|------------|-----------------|------------------|
| Electric and Magnetic Field Analyzer | narda | EHP-200AC | 180ZX11028 | Feb. 20, 2024   | Feb. 19, 2025    |

NOTE: 1. The calibration interval of the above test instruments is 12 months.



2.4. Test Mode

| Test Item      | Test Mode | Description  |
|----------------|-----------|--|
| MPE Test Cases | Mode 1    | AC/DC Adapter + EUT + mobile phone (Full Load) + Mug (Full Load) |
|                | Mode 2    | AC/DC Adapter + EUT + mobile phone (Full Load) + Mug (Half Load) |
|                | Mode 3    | AC/DC Adapter + EUT + mobile phone (Full Load) + Mug (Null Load) |
|                | Mode 4    | AC/DC Adapter + EUT + mobile phone (Half Load) + Mug (Full Load) |
|                | Mode 5    | AC/DC Adapter + EUT + mobile phone (Half Load) + Mug (Half Load) |
|                | Mode 6    | AC/DC Adapter + EUT + mobile phone (Half Load) + Mug (Null Load) |
|                | Mode 7    | AC/DC Adapter + EUT + mobile phone (Null Load) + Mug (Full Load) |
|                | Mode 8    | AC/DC Adapter + EUT + mobile phone (Null Load) + Mug (Half Load) |
|                | Mode 9    | AC/DC Adapter + EUT + mobile phone (Null Load) + Mug (Null Load) |
|                | Mode 10   | AC/DC Adapter + EUT + mobile phone (Full Load)                   |
|                | Mode 11   | AC/DC Adapter + EUT + mobile phone (Half Load)                   |
|                | Mode 12   | AC/DC Adapter + EUT + mobile phone (Null Load)                   |
|                | Mode 13   | AC/DC Adapter + EUT + Mug (Full Load)                            |
|                | Mode 14   | AC/DC Adapter + EUT + Mug (Half Load)                            |
|                | Mode 15   | AC/DC Adapter + EUT + Mug (Null Load)                            |
|                | Mode 16   | AC/DC Adapter + EUT (Null Load)                                  |

Note:

1. All modes and configurations above have been tested, Only the result of the worst case was recorded in the report, the worst-case configuration is Mode 1.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The Mobile Phone is provided by Lab, and the Mug is the product accessory.
4. According to the manufacturer's design principle, the wireless charging power will reach its maximum when the client device's battery level is between 1% and 10%.



### 3. Maximum Permissible Exposure

#### Limit of Maximum Permissible Exposure

| Limits for Occupational / Controlled Exposure         |                                   |                                   |  |   |
|---|-----------------------------------|-----------------------------------|--|---|
| Frequency Range (MHz)                                 | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
| 0.3-3.0   | 614                               | 1.63                              | (100)*                                   | 6   |
| 3.0-30  | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6   |
| 30-300  | 61.4                              | 0.163                             | 1.0                                      | 6   |
| 300-1500  |                                   |                                   | F/300                                    | 6   |
| 1500-100,000  |                                   |                                   | 5  | 6   |
| Limits for General Population / Uncontrolled Exposure |                                   |                                   |  |   |
| Frequency Range (MHz)                                 | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
| 0.3-1.34  | 614                               | 1.63                              | (100)*                                   | 30  |
| 1.34-30   | 824/f                             | 2.19/f                            | (180 / f)*                               | 30  |
| 30-300  | 27.5                              | 0.073                             | 0.2                                      | 30  |
| 300-1500  |                                   |                                   | F/1500                                   | 30  |
| 1500-100,000  |                                   |                                   | 1  | 30  |

Note 1: f = frequency in MHz; \*Plane-wave equivalent power density.

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 Wireless Power Transfer v04.


Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

## 4. Test Procedure

a. For devices designed for typical desktop applications, such as wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of (H-field & E-field strengths for all sides is 20cm).

E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 20 cm measured from the center of the probe(s) to the edge of the device.

### 4.1 Test Setup



### 4.2 Result of Maximum Permissible Exposure



All test modes complete the test. Only the full load test was the worst results reported below:

**ANT 1:**

E-Field Strength at 20 cm from the edges surrounding the EUT (V/m)

| Field strength | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Limits (V/m) |
|----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|
| V/m            | 2.2061          | 2.2461          | 2.2446          | 2.2461          | 2.2344          | 614          |

H-Field Strength at 20 cm from the edges surrounding the EUT (A/m)

| Field strength | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Limits (A/m) |
|----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|
| A/m            | 0.0110          | 0.0138          | 0.0174          | 0.0149          | 0.0129          | 1.63         |

**ANT 2:**

E-Field Strength at 20 cm from the edges surrounding the EUT (V/m)

| Field strength | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Limits (V/m) |
|----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|
| V/m            | 2.7078          | 2.8851          | 2.9183          | 2.8189          | 2.6314          | 614          |

H-Field Strength at 20 cm from the edges surrounding the EUT (A/m)

| Field strength | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Limits (A/m) |
|----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|
| A/m            | 0.0167          | 0.0215          | 0.0223          | 0.0207          | 0.0153          | 1.63         |





**ANT 1 + ANT 2:**

**E-Field Strength at 20 cm from the edges surrounding the EUT (V/m)**

| Field strength | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Limits (V/m) |
|----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|
| V/m            | 3.4983          | 3.6100          | 3.6544          | 3.5848          | 3.4661          | 614          |

**H-Field Strength at 20 cm from the edges surrounding the EUT (A/m)**

| Field strength | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Limits (A/m) |
|----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|
| A/m            | 0.0191          | 0.0206          | 0.0224          | 0.0191          | 0.0150          | 1.63         |



Remark: According KDB 680106 D01 Wireless Power Transfer v04, section 5.2). The aggregate H-field strengths at 20 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. The E- field evaluation conducted assuming a user separation distance of 20 cm according to the KDB 680106 D01 Wireless Power Transfer v04, section 5.2).


Result: The device comply with the RF exposure requirement according to 680106 D01 v04, section 5.2):

- (1) The power transfer frequency is below 1MHz.
  - The device operate in the frequency range for 112KHz~ 205KHz.
- (2) The output power from each transmitting element (e .g., coil) is less than or equal to 15 watts.
  - The maximum output power is 10W.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
  - The EUT is placed directly in contact with the transmitter.
- (4) Only 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover 2.093-porable exposure conditions).
  - Yes, mobile device only.
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
  - The EUT meet the conditions.
- (6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.
  - The transfer system including a charging system with two primary coils, the coil pairs can be powered on at the same time.




Photographs of Test

A



B



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Addr: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



C



D




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Address: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



E



※※※※THE END※※※※