FCC ID: 2BBQ4-W5U

## **RF Exposure Evaluation**

#### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in KDB 447498 D01 V06 and 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposures									
0.3–3.0	614	1.63	*(100)	6					
3.0–30	1842/f	4.89/f	*(900/f²)	6					
30–300	61.4	0.163	1.0	6					
300–1500			f/300	6					
1500–100,000			5	6					
(B) Limits for General Population/Uncontrolled Exposure									
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500			f/1500	30					
1500–100,000			1.0	30					

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

#### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

# Test Result of RF Exposure Evaluation

wifi 2.4G mode

Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
802.11b	15.483	35.3427	0.01648	1.0	PASS
802.11g	13.589	22.8507	0.01066	1.0	PASS
802.11n HT20	14.675	29.3427	0.01368	1.0	PASS
802.11n HT40	14.1	25.7040	0.01199	1.0	PASS

Remark: antenna gain=3.7dBi

### wifi 5G mode:

Band	Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
Band 1	802.11a	12.102	16.2256	0.00659	1.0	PASS
	802.11n HT20	12.185	16.5386	0.00672	1.0	PASS
	802.11n HT40	11.387	13.7626	0.00559	1.0	PASS
Band 4	802.11a	11.65	14.6218	0.00594	1.0	PASS
	802.11n HT20	11.603	14.4644	0.00588	1.0	PASS
	802.11n HT40	11.51	14.1579	0.00575	1.0	PASS

Remark: antenna gain=3.1dBi