

TEST REPORT

Reference No...... : WTX23X06018267W001
FCC ID..... : 2BBQ9-BBKS
Applicant..... : Wuhu Youfan E-Commerce Co.,Ltd.
Address..... : No. 369 industrial Road, Anhui Xinwu Economic Development Zone (In Fulong E-commerce Industrial Park), Wuhu County
Product Name..... : Bluetooth Battery Kill Switch
Test Model..... : BBKS-2023-250A
Standards..... : FCC Part 15.247
Date of Receipt sample..... : June 6, 2023
Date of Test..... : June 6~18, 2023
Date of Issue..... : June 18, 2023
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tested by:

Jack Huang

Jack Huang

Approved & Authorized By:

Silin Chen

Silin Chen

TABLE OF CONTENTS

1. GENERAL INFORMATION 4

 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

 1.2 TEST STANDARDS 5

 1.3 TEST METHODOLOGY 5

 1.4 TEST FACILITY 5

 1.5 EUT SETUP AND TEST MODE 6

 1.6 MEASUREMENT UNCERTAINTY 6

 1.7 TEST EQUIPMENT LIST AND DETAILS 7

2. SUMMARY OF TEST RESULTS 9

3. ANTENNA REQUIREMENT 10

 3.1 STANDARD APPLICABLE 10

 3.2 EVALUATION INFORMATION 10

4. POWER SPECTRAL DENSITY 11

 4.1 STANDARD APPLICABLE 11

 4.2 TEST SETUP BLOCK DIAGRAM 11

 4.3 TEST PROCEDURE 11

 4.4 SUMMARY OF TEST RESULTS/PLOTS 11

5. DTS BANDWIDTH 12

 5.1 STANDARD APPLICABLE 12

 5.2 TEST SETUP BLOCK DIAGRAM 12

 5.3 TEST PROCEDURE 12

 5.3 SUMMARY OF TEST RESULTS/PLOTS 12

6. RF OUTPUT POWER 13

 6.1 STANDARD APPLICABLE 13

 6.2 TEST SETUP BLOCK DIAGRAM 13

 6.3 TEST PROCEDURE 13

 6.4 SUMMARY OF TEST RESULTS/PLOTS 13

7. FIELD STRENGTH OF SPURIOUS EMISSIONS 14

 7.1 STANDARD APPLICABLE 14

 7.2 TEST PROCEDURE 14

 7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION 16

 7.4 SUMMARY OF TEST RESULTS/PLOTS 16

8. OUT OF BAND EMISSIONS 20

 8.1 STANDARD APPLICABLE 20

 8.2 TEST PROCEDURE 20

 8.3 SUMMARY OF TEST RESULTS/PLOTS 21

9. CONDUCTED EMISSIONS 25

 9.1 TEST PROCEDURE 25

 9.2 BASIC TEST SETUP BLOCK DIAGRAM 25

 9.3 TEST RECEIVER SETUP 25

 9.4 SUMMARY OF TEST RESULTS/PLOTS 25

APPENDIX SUMMARY 26

APPENDIX A 27

APPENDIX B 29

APPENDIX C 31

APPENDIX D 32

APPENDIX E 33

APPENDIX PHOTOGRAPHS 36

Report version

| Version No. | Date of issue | Description |
|-------------|---------------|-------------|
| Rev.00 | June 18, 2023 | Original |
| / | / | / |

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Wuhu Youfan E-Commerce Co.,Ltd.
 Address of applicant: No. 369 industrial Road, Anhui Xinwu Economic Development Zone (In Fulong E-commerce Industrial Park), Wuhu County

Manufacturer: Wuhu Youfan E-Commerce Co.,Ltd.
 Address of manufacturer: No. 369 industrial Road, Anhui Xinwu Economic Development Zone (In Fulong E-commerce Industrial Park), Wuhu County

| General Description of EUT | |
|---|--------------------------------|
| Product Name: | Bluetooth Battery Kill Switch |
| Brand Name: | / |
| Model No.: | BBKS-2023-250A |
| Adding Model(s): | BBKS-2023-200A, BBKS-2023-120A |
| Rated Voltage: | DC 12V |
| Power Adapter: | / |
| Software Version: | / |
| Hardware Version: | / |
| Serial Number: | S-001 |
| <i>Note: The test data is gathered from a production sample provided by the manufacturer.</i> | |

| Technical Characteristics of EUT | |
|----------------------------------|--------------|
| Bluetooth Version: | V5.0 BLE |
| Frequency Range: | 2402-2480MHz |
| RF Output Power: | -4.15dBm |
| Data Rate: | 1Mbps |
| Modulation: | GFSK |
| Quantity of Channels: | 40 |
| Channel Separation: | 2MHz |
| Type of Antenna: | PCB |
| Antenna Gain: | 1.9dBi |

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List | | |
|----------------|-------------|---------|
| Test Mode | Description | Remark |
| TM1 | Low | 2402MHz |
| TM2 | Middle | 2440MHz |
| TM3 | High | 2480MHz |

| Test software(Fix the Tx frequency) | Power level(Testing) |
|-------------------------------------|----------------------|
| Name | level |
| EMI_Test_Tool | Index |

| Test Conditions | |
|--------------------|-----------|
| Temperature: | 22~25 °C |
| Relative Humidity: | 50~55 %. |
| ATM Pressure: | 1019 mbar |

| EUT Cable List and Details | | | |
|----------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| | | | |

| Special Cable List and Details | | | |
|--------------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| | | | |

| Auxiliary Equipment List and Details | | | |
|--------------------------------------|--------------|-------|---------------|
| Description | Manufacturer | Model | Serial Number |
| | | | |

1.6 Measurement Uncertainty

| Measurement uncertainty | | | |
|-----------------------------|------------|--------------------|--|
| Parameter | Conditions | Uncertainty | |
| RF Output Power | Conducted | ±0.42dB | |
| Occupied Bandwidth | Conducted | ±1.5% | |
| Power Spectral Density | Conducted | ±1.8dB | |
| Conducted Spurious Emission | Conducted | ±2.17dB | |
| Conducted Emissions | Conducted | 9-150kHz ±3.74dB | |
| | | 0.15-30MHz ±3.34dB | |

| | | |
|--------------------------------|----------|------------------------|
| Transmitter Spurious Emissions | Radiated | 30-200MHz \pm 4.52dB |
| | | 0.2-1GHz \pm 5.56dB |
| | | 1-6GHz \pm 3.84dB |
| | | 6-18GHz \pm 3.92dB |

1.7 Test Equipment List and Details

| No. | Description | Manufacturer | Model | Serial No. | Cal Date | Due. Date |
|-----------|-------------------------|------------------------|-----------------------|-------------|------------|------------|
| SEMT-1075 | Communication Tester | Rohde & Schwarz | CMW500 | 148650 | 2023-03-27 | 2024-03-26 |
| SEMT-1063 | GSM Tester | Rohde & Schwarz | CMU200 | 114403 | 2023-03-27 | 2024-03-26 |
| SEMT-1072 | Spectrum Analyzer | Agilent | E4407B | MY41440400 | 2023-03-27 | 2024-03-26 |
| SEMT-1079 | Spectrum Analyzer | Agilent | N9020A | US47140102 | 2023-03-27 | 2024-03-26 |
| SEMT-1080 | Signal Generator | Agilent | 83752A | 3610A01453 | 2023-03-27 | 2024-03-26 |
| SEMT-1081 | Vector Signal Generator | Agilent | N5182A | MY47070202 | 2023-03-27 | 2024-03-26 |
| SEMT-1028 | Power Divider | Weinschel | 1506A | PM204 | 2023-03-27 | 2024-03-26 |
| SEMT-1082 | Power Divider | RF-Lambda | RFLT4W5M18G | 14110400027 | 2023-03-27 | 2024-03-26 |
| SEMT-1031 | Spectrum Analyzer | Rohde & Schwarz | FSP30 | 836079/035 | 2023-03-27 | 2024-03-26 |
| SEMT-1007 | EMI Test Receiver | Rohde & Schwarz | ESVB | 825471/005 | 2023-03-27 | 2024-03-26 |
| SEMT-1008 | Amplifier | Agilent | 8447F | 3113A06717 | 2023-04-12 | 2024-04-11 |
| SEMT-1043 | Amplifier | C&D | PAP-1G18 | 2002 | 2023-04-12 | 2024-04-11 |
| SEMT-1069 | Loop Antenna | Schwarz beck | FMZB 1516 | 9773 | 2023-03-19 | 2025-03-18 |
| SEMT-1068 | Broadband Antenna | Schwarz beck | VULB9163 | 9163-333 | 2023-03-19 | 2025-03-18 |
| SEMT-1042 | Horn Antenna | ETS | 3117 | 00086197 | 2023-03-19 | 2025-03-18 |
| SEMT-1121 | Horn Antenna | Schwarzbeck | BBHA 9170 | BBHA9170582 | 2023-03-27 | 2024-03-26 |
| SEMT-1169 | Pre-amplifier | Direction Systems Inc. | PAP-2640 | 14145-14153 | 2023-03-27 | 2024-03-26 |
| SEMT-1163 | Spectrum Analyzer | Rohde & Schwarz | FSP40 | 100612 | 2023-03-27 | 2024-03-26 |
| SEMT-1166 | Power Limiter | Agilent | N9356B | MY45450376 | 2023-03-27 | 2024-03-26 |
| SEMT-1076 | RF Switcher | Top Precision | RCS03-A2 | / | 2023-03-19 | 2025-03-18 |
| SEMT-1096 | Power Sensor | Agilent | U2021XA | MY54250019 | 2023-03-27 | 2024-03-26 |
| SEMT-C001 | Cable | Zheng DI | LL142-07-07-10M(A) | / | / | / |
| SEMT-C002 | Cable | Zheng DI | ZT40-2.92J-2.92J-6M | / | / | / |
| SEMT-C003 | Cable | Zheng DI | ZT40-2.92J-2.92J-2.5M | / | / | / |
| SEMT-C004 | Cable | Zheng DI | 2M0RFC | / | / | / |

| | | | | | | |
|-----------|-------|----------|--------|---|---|---|
| SEMT-C005 | Cable | Zheng DI | 1M0RFC | / | / | / |
| SEMT-C006 | Cable | Zheng DI | 1M0RFC | / | / | / |

| Software List | | | |
|--|--------------|--------|---------|
| Description | Manufacturer | Model | Version |
| EMI Test Software (Radiated Emission)* | Farad | EZ-EMC | RA-03A1 |
| EMI Test Software (Conducted Emission)* | Farad | EZ-EMC | RA-03A1 |

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test Item | Result |
|---------------------------|-----------------------------------|---------------|
| §2.1093 | RF Exposure | Compliant |
| §15.203; §15.247(b)(4)(i) | Antenna Requirement | Compliant |
| §15.205 | Restricted Band of Operation | Compliant |
| §15.207(a) | Conducted Emission | N/A |
| §15.247(e) | Power Spectral Density | Compliant |
| §15.247(a)(2) | DTS Bandwidth | Compliant |
| §15.247(b)(3) | RF Output Power | Compliant |
| §15.209(a) | Radiated Emission | Compliant |
| §15.247(d) | Band Edge (Out of Band Emissions) | Compliant |

N/A: not applicable

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has a PCB antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.4 Summary of Test Results/Plots


Please refer to Appendix A

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) The maximum peak conducted output power may be measured using a broadband peak RF power meter.
- b) The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
- c) Record the measurement data.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


7.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



| | | |
|--------------------------|------------------------------|------------------------------|
| Frequency :9kHz-30MHz | Frequency :30MHz-1GHz | Frequency :Above 1GHz |
| RBW=10KHz, | RBW=120KHz, | RBW=1MHz, |
| VBW =30KHz | VBW=300KHz | VBW=3MHz(Peak), 10Hz(AV) |
| Sweep time= Auto | Sweep time= Auto | Sweep time= Auto |
| Trace = max hold | Trace = max hold | Trace = max hold |
| Detector function = peak | Detector function = peak, QP | Detector function = peak, AV |

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\begin{aligned}\text{Result} &= \text{Indicated Reading} + \text{Correct} \\ \text{Correct} &= \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}\end{aligned}$$


The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Result} - \text{FCC Part 15 Limit}$$

7.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

➤ Spurious Emissions Below 1GHz





➤ Spurious Emissions Above 1GHz

| Frequency (MHz) | Reading (dBuV) | Correct dB/m | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polar H/V | Detector |
|------------------------|-------------------|-----------------|--------------------|-------------------|----------------|--------------|----------|
| Low Channel-2402MHz | | | | | | | |
| 4802 | 59.28 | -3.49 | 55.79 | 74 | -18.21 | H | PK |
| 4802 | 38.96 | -3.49 | 35.47 | 54 | -18.53 | H | AV |
| 7206 | 59.09 | -0.47 | 58.62 | 74 | -15.38 | H | PK |
| 7206 | 38.37 | -0.47 | 37.9 | 54 | -16.1 | H | AV |
| 4802 | 59.83 | -3.49 | 56.34 | 74 | -17.66 | V | PK |
| 4802 | 38.28 | -3.49 | 34.79 | 54 | -19.21 | V | AV |
| 7206 | 60.27 | -0.47 | 59.8 | 74 | -14.2 | V | PK |
| 7206 | 40.43 | -0.47 | 39.96 | 54 | -14.04 | V | AV |
| Middle Channel-2440MHz | | | | | | | |
| 4880 | 59.47 | -3.49 | 55.98 | 74 | -18.02 | H | PK |
| 4880 | 39.15 | -3.49 | 35.66 | 54 | -18.34 | H | AV |
| 7320 | 59.28 | -0.47 | 58.81 | 74 | -15.19 | H | PK |
| 7320 | 38.56 | -0.47 | 38.09 | 54 | -15.91 | H | AV |
| 4880 | 60.02 | -3.49 | 56.53 | 74 | -17.47 | V | PK |
| 4880 | 38.47 | -3.49 | 34.98 | 54 | -19.02 | V | AV |
| 7320 | 60.46 | -0.47 | 59.99 | 74 | -14.01 | V | PK |
| 7320 | 40.62 | -0.47 | 40.15 | 54 | -13.85 | V | AV |
| High Channel-2480MHz | | | | | | | |
| 4960 | 59.69 | -3.41 | 56.28 | 74 | -17.72 | H | PK |
| 4960 | 38.76 | -3.41 | 35.35 | 54 | -18.65 | H | AV |
| 7440 | 57.27 | -0.42 | 56.85 | 74 | -17.15 | H | PK |
| 7440 | 37.54 | -0.42 | 37.12 | 54 | -16.88 | H | AV |
| 4960 | 60.43 | -3.41 | 57.02 | 74 | -16.98 | V | PK |
| 4960 | 39.1 | -3.41 | 35.69 | 54 | -18.31 | V | AV |
| 7440 | 59.25 | -0.42 | 58.83 | 74 | -15.17 | V | PK |
| 7440 | 37.18 | -0.42 | 36.76 | 54 | -17.24 | V | AV |

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW \geq [3 \times RBW].
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

| Frequency | RBW |
|--------------------|--------------------|
| 9 kHz to 150 kHz | 200 Hz to 300 Hz |
| 0.15 MHz to 30 MHz | 9 kHz to 10 kHz |
| 30 MHz to 1000 MHz | 100 kHz to 120 kHz |
| >1000 MHz | 1 MHz |


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots


➤ Radiated test

| | | | |
|--------------|-----|-----------|-------------------------|
| Test Channel | Low | Polarity: | Horizontal (worst case) |
|--------------|-----|-----------|-------------------------|



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|-----------------|----------------|-----------------|----------------|-------------|---------------|
| 1 | 2310.000 | 44.44 | -18.19 | 26.25 | 54.00 | -27.75 | Ave Detector |
| | 2310.000 | 56.86 | -18.19 | 38.67 | 74.00 | -35.33 | Peak Detector |
| 2 | 2390.000 | 44.68 | -18.23 | 26.45 | 54.00 | -27.55 | Ave Detector |
| | 2390.000 | 57.44 | -18.23 | 39.21 | 74.00 | -34.79 | Peak Detector |
| 3 | 2402.986 | 79.70 | -18.23 | 61.47 | / | / | Ave Detector |
| | 2403.788 | 111.83 | -18.23 | 93.60 | / | / | Peak Detector |

| | | | |
|--------------|------|-----------|-------------------------|
| Test Channel | High | Polarity: | Horizontal (worst case) |
|--------------|------|-----------|-------------------------|



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|-----------------|----------------|-----------------|----------------|-------------|---------------|
| 1 | 2479.910 | 77.17 | -18.04 | 59.13 | / | / | Ave Detector |
| | 2479.359 | 107.16 | -18.04 | 89.12 | / | / | Peak Detector |
| 2 | 2483.500 | 50.25 | -18.03 | 32.22 | 54.00 | -21.78 | Ave Detector |
| | 2483.500 | 70.46 | -18.03 | 52.43 | 74.00 | -21.57 | Peak Detector |

Reference No.: WTX23X06018267W001

➤ Conducted test

Please refer to Appendix D and E


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

9.2 Basic Test Setup Block Diagram



9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

| | |
|-----------------------------------|---------|
| Start Frequency..... | 150 kHz |
| Stop Frequency..... | 30 MHz |
| Sweep Speed..... | Auto |
| IF Bandwidth..... | 10 kHz |
| Quasi-Peak Adapter Bandwidth..... | 9 kHz |
| Quasi-Peak Adapter Mode..... | Normal |

9.4 Summary of Test Results/Plots

Not applicable, The EUT is DC supply.

APPENDIX SUMMARY

| | | | |
|-------------------|--------------------|---------------|------------|
| Project No. | WTX23X06018267W001 | Test Engineer | Jack Huang |
| Start date | 2023/06/06 | Finish date | 2023/06/18 |
| Temperature | 24.9°C | Humidity | 48% |
| RF specifications | BT-BLE | | |

| APPENDIX | Description of Test Item | Result |
|-----------------|-------------------------------------|---------------|
| A | Power Spectral Density | Compliant |
| B | DTS Bandwidth | Compliant |
| C | RF Output Power | Compliant |
| D | Conducted Out of Band Emissions and | Compliant |
| E | Conducted Spurious Emissions | Compliant |


APPENDIX A

| Power Spectral Density | | | |
|------------------------|--------------|------------------------------------|-------------------|
| Test Mode | Test Channel | Power Spectral Density dBm/3kHz | Limit dBm/3kHz |
| GFSK(BLE) | Low | -19.17 | 8 |
| | Middle | -18.31 | 8 |
| | High | -17.73 | 8 |

| | |
|---|--|
| <p style="text-align: center;">Low</p> | |
| <p style="text-align: center;">Middle</p> | |
| <p style="text-align: center;">High</p> | |

APPENDIX B


| DTS Bandwidth | | | |
|---------------|--------------|-----------------------|--------------|
| Test Mode | Test Channel | 6 dB Bandwidth kHz | Limit kHz |
| GFSK(BLE) | Low | 0.73 | ≥ 500 |
| | Middle | 0.74 | ≥ 500 |
| | High | 0.73 | ≥ 500 |



APPENDIX C




| RF Output Power | | | |
|-----------------|--------------|----------------|--------------|
| Test Mode | Test Channel | Reading dBm | Limit dBm |
| GFSK(BLE) | Low | -4.27 | 30 |
| | Middle | -4.15 | 30 |
| | High | -4.41 | 30 |

APPENDIX D






APPENDIX E




Low



Middle



High



APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****