



RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Test Result of RF Exposure Evaluation

2.4G WIFI mode								
Mode	Output power to antenna (dBm)		Output power to antenna (mW)		Power Density at R=20cm (mW/cm ²)		Limit (mW/cm ²)	Result
802.11b	14.89		30.83		0.016433		1.0	PASS
802.11g	13.72		23.55		0.012552		1.0	PASS
802.11n20	15.71		37.24		0.019848		1.0	PASS
802.11n40	15.57		36.06		0.019219		1.0	PASS
802.11n20	ANT1 13.60	ANT2 13.69	ANT1 22.91	ANT2 23.39	ANT1 0.007848	ANT2 0.008012	1.0	PASS
802.11n20 (MIMO)	16.66		46.34		0.049513		1.0	PASS
802.11n40	ANT1 13.42	ANT2 13.33	ANT1 21.98	ANT2 21.53	ANT1 0.007529	ANT2 0.007374	1.0	PASS
802.11n40 (MIMO)	16.39		43.55		0.046529		1.0	PASS

2.4G WIFI Antenna1/2 Gain = 4.28dBi ; MIMO Gain = 7.30dBi