



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Innovative Eyewear, Inc.

Address: 11900 Biscayne Bl, # 630, North Miami Florida United States 33181

FCC ID: 2BBYK-LCD00Z

Product Name: Active noise cancelling stereo Bluetooth headphone

Standard(s): 47 CFR Part 15, Subpart C(15.247)

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR231168726-00A

Date Of Issue: 2024/1/4

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	17
3.2.5 Corrected Amplitude & Margin Calculation.....	17
3.3 MINIMUM 6 DB BANDWIDTH.....	18
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure	18
3.4 MAXIMUM CONDUCTED OUTPUT POWER.....	19
3.4.1 Applicable Standard.....	19
3.4.2 EUT Setup.....	19
3.4.3 Test Procedure	19
3.5 MAXIMUM POWER SPECTRAL DENSITY.....	20
3.5.1 Applicable Standard.....	20
3.5.2 EUT Setup.....	20
3.5.3 Test Procedure	20
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	21
3.6.1 Applicable Standard.....	21
3.6.2 EUT Setup.....	21
3.6.3 Test Procedure	21
3.7 DUTY CYCLE	22
3.7.1 EUT Setup.....	22
3.7.2 Test Procedure	22

3.8 ANTENNA REQUIREMENT..... 23
 3.8.1 Applicable Standard.....23
 3.8.2 Judgment.....23

4. Test DATA AND RESULTS 24
 4.1 AC LINE CONDUCTED EMISSIONS..... 24
 4.2 RADIATION SPURIOUS EMISSIONS 25
 4.3 6 dB EMISSION BANDWIDTH 55
 4.4 MAXIMUM CONDUCTED OUTPUT POWER..... 60
 4.5 MAXIMUM POWER SPECTRAL DENSITY 62
 4.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE..... 68
 4.7 DUTY CYCLE 73

5. RF EXPOSURE EVALUATION 76
 5.1 APPLICABLE STANDARD..... 76
 5.2 MEASUREMENT RESULT 76

6. EUT PHOTOGRAPHS 77

7. TEST SETUP PHOTOGRAPHS 78

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231168726-00A	Original Report	2024/1/4

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Active noise cancelling stereo Bluetooth headphone
EUT Model:	LCD00Z
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	1.39dBm(Left side mirror legs) 0.59dBm(Right side mirror legs)
Modulation Type:	GFSK
Rated Input Voltage:	DC 3.7V from battery or DC 5V from charging contact
Serial Number:	RE: 2DVE-1 RF: 2DVE-2
EUT Received Date:	2023/11/20
EUT Received Status:	Good

Operation Frequency Detail: For BLE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2402
Middle	2440
Highest	2480

Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Chip Antenna	50	2.4~2.5GHz	-3.86dBi(Left side mirror legs) -4.56dBi(Right side mirror legs)

The Method of §15.203 Compliance:

- Antenna was permanently attached to the unit.
- Antenna use a unique type of connector to attach to the EUT.
- Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter 1	Unknown	XY-0033B	Input:100-240V~50/60Hz 0.15A Max Output:5.0V 1000mA
Adapter 2	Unknown	XY-0033B	Input:100-240V~50/60Hz 0.15A Max Output:5.0V 1000mA
Power Cable	Unknown	Unknown	0.8m

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For BLE:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:	No		
EUT Exercise Software:	BT FCC Tool V2.24		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
1Mbps	5	5	5
2Mbps	5	5	5
Note: The prototype has Left side mirror legs and Riht side mirror legs. The two mirror legs can transmit wireless signals simultaneously			

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

1.2.4 Block Diagram of Test Setup

Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 4.12dB, 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.203	Antenna Requirement	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


3.2.2 EUT Setup

9kHz-30MHz:



30MHz- 1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1000 MHz

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300 Hz	1 kHz	200 Hz	QP
150 kHz – 30 MHz	10 kHz	30 kHz	9 kHz	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum Conducted Output Power

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013, section 11.9.1.3

- a). Place the EUT on a bench and set it in transmitting mode.
- b). Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to measuring equipment.


3.5 Maximum power spectral density

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.7 Duty Cycle

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Not Applicable, the device was powered by battery when operating.

4.2 Radiation Spurious Emissions

Serial Number:	2DVE-1	Test Date:	2023/12/27~2023/12/28
Test Site:	966-2,966-1	Test Mode:	Transmitting
Tester:	Jeff Luo, coco Tian	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23~24.5	Relative Humidity: (%)	45~57	ATM Pressure: (kPa)	101.6~101.9
----------------------	---------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Below					
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
BACL	Loop Antenna	1313-1P	3092721	2023/10/20	2026/10/19
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600- UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600- UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
High					
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2023/2/22	2026/2/21
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1- 1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1- 2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2023/11/8	2024/11/7
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536- JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362- 200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

Note: The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

0.009MHz-30MHz false emission is more than 20dB below the limit value. No test results were recorded.

After pre-scan in the X, Y and Z axes of orientation in BLE test results, the worst case is below: X.

Provides BLE 1MHz test results at 30MHz-1GHz (highest power for Conducted Output Power).

Radiation Spurious Emissions from 1 to 25GHz provides test results and test plots(Only the test plot with the smallest harmonic margin is provided) for sideband and harmonics of the X-axis of the Left side mirror legs and Right side mirror legs mirror legs.


1) 30MHz-1GHz

Left side mirror legs:

BLE 1Mbps – Low Channel:

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: horizontal
 Note: Transmitting(BLE)


Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	27.78	-4.78	23.00	40.00	17.00	Peak
2	37.548	27.30	-9.82	17.48	40.00	22.52	Peak
3	119.436	28.00	-11.86	16.14	43.50	27.36	Peak
4	154.821	29.04	-12.32	16.72	43.50	26.78	Peak
5	588.905	28.69	-5.69	23.00	46.00	23.00	Peak
6	833.317	28.33	-1.99	26.34	46.00	19.66	Peak

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: vertical
 Note: Transmitting(BLE)

Date: 2023-12-28




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	28.36	-4.78	23.58	40.00	16.42	Peak
2	37.285	28.44	-9.66	18.78	40.00	21.22	Peak
3	77.865	30.55	-17.63	12.92	40.00	27.08	Peak
4	129.923	27.89	-11.62	16.27	43.50	27.23	Peak
5	463.970	28.12	-6.99	21.13	46.00	24.87	Peak
6	721.726	29.48	-3.63	25.85	46.00	20.15	Peak

BLE 1Mbps Middle Channel:

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: horizontal
 Note: Transmitting(BLE)


Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	32.864	29.28	-6.33	22.95	40.00	17.05	Peak
2	41.422	27.34	-12.53	14.81	40.00	25.19	Peak
3	125.007	28.32	-11.69	16.63	43.50	26.87	Peak
4	153.200	28.61	-12.27	16.34	43.50	27.16	Peak
5	668.142	27.79	-4.43	23.36	46.00	22.64	Peak
6	866.088	28.22	-1.55	26.67	46.00	19.33	Peak

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: vertical
 Note: Transmitting(BLE)

Date: 2023-12-28




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	27.25	-4.36	22.89	40.00	17.11	Peak
2	36.637	26.83	-9.18	17.65	40.00	22.35	Peak
3	75.182	30.25	-17.37	12.88	40.00	27.12	Peak
4	129.015	27.92	-11.63	16.29	43.50	27.21	Peak
5	312.179	28.92	-10.90	18.02	46.00	27.98	Peak
6	638.369	28.61	-4.88	23.73	46.00	22.27	Peak

BLE 1Mbps High Channel:

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: horizontal
 Note: Transmitting(BLE)


Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.424	27.84	-4.45	23.39	40.00	16.61	Peak
2	36.509	28.63	-9.08	19.55	40.00	20.45	Peak
3	129.015	28.30	-11.63	16.67	43.50	26.83	Peak
4	201.393	28.77	-12.66	16.11	43.50	27.39	Peak
5	494.199	28.04	-6.45	21.59	46.00	24.41	Peak
6	755.387	28.79	-3.24	25.55	46.00	20.45	Peak

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: vertical
 Note: Transmitting(BLE)

Date: 2023-12-28




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	27.16	-4.12	23.04	40.00	16.96	Peak
2	70.337	30.31	-16.95	13.36	40.00	26.64	Peak
3	115.321	28.39	-12.22	16.17	43.50	27.33	Peak
4	202.810	28.66	-12.72	15.94	43.50	27.56	Peak
5	564.639	28.17	-5.98	22.19	46.00	23.81	Peak
6	801.786	28.21	-2.39	25.82	46.00	20.18	Peak

right side mirror legs:
BLE 1Mbps – Low Channel:

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: horizontal
 Note: Transmitting(BLE 1Mbps Mode)


Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.211	27.84	-4.28	23.56	40.00	16.44	Peak
2	39.715	27.79	-11.50	16.29	40.00	23.71	Peak
3	122.834	28.08	-11.75	16.33	43.50	27.17	Peak
4	297.224	28.37	-11.17	17.20	46.00	28.80	Peak
5	494.199	29.11	-6.45	22.66	46.00	23.34	Peak
6	711.674	29.64	-3.76	25.88	46.00	20.12	Peak

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: vertical
 Note: Transmitting(BLE 1Mbps Mode)

Date: 2023-12-28




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.424	27.81	-4.45	23.36	40.00	16.64	Peak
2	38.888	27.63	-10.86	16.77	40.00	23.23	Peak
3	74.396	30.16	-17.34	12.82	40.00	27.18	Peak
4	121.123	28.73	-11.80	16.93	43.50	26.57	Peak
5	513.633	28.35	-6.30	22.05	46.00	23.95	Peak
6	711.674	31.56	-3.76	27.80	46.00	18.20	Peak

BLE 1Mbps Middle Channel:

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: horizontal
 Note: Transmitting(BLE 1Mbps Mode)


Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.211	27.52	-4.28	23.24	40.00	16.76	Peak
2	36.381	27.60	-8.99	18.61	40.00	21.39	Peak
3	128.563	28.05	-11.63	16.42	43.50	27.08	Peak
4	300.367	28.62	-11.05	17.57	46.00	28.43	Peak
5	463.970	28.10	-6.99	21.11	46.00	24.89	Peak
6	719.200	28.90	-3.65	25.25	46.00	20.75	Peak

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: vertical
 Note: Transmitting(BLE 1Mbps Mode)

Date: 2023-12-28




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.510	28.79	-5.26	23.53	40.00	16.47	Peak
2	38.616	28.27	-10.64	17.63	40.00	22.37	Peak
3	78.139	30.49	-17.65	12.84	40.00	27.16	Peak
4	118.601	28.38	-11.94	16.44	43.50	27.06	Peak
5	462.346	27.92	-7.03	20.89	46.00	25.11	Peak
6	714.173	28.62	-3.73	24.89	46.00	21.11	Peak

BLE 1Mbps High Channel:

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: horizontal
 Note: Transmitting(BLE 1Mbps Mode)


Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.211	27.40	-4.28	23.12	40.00	16.88	Peak
2	39.162	27.72	-11.07	16.65	40.00	23.35	Peak
3	130.379	28.76	-11.64	17.12	43.50	26.38	Peak
4	207.850	28.85	-12.90	15.95	43.50	27.55	Peak
5	463.970	28.21	-6.99	21.22	46.00	24.78	Peak
6	711.674	29.19	-3.76	25.43	46.00	20.57	Peak

Project No.: CR231168726-RF
 Tester: Jeff Luo
 Polarization: vertical
 Note: Transmitting(BLE 1Mbps Mode)

Date: 2023-12-28



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	27.57	-4.12	23.45	40.00	16.55	Peak
2	36.766	27.35	-9.28	18.07	40.00	21.93	Peak
3	70.584	29.51	-16.98	12.53	40.00	27.47	Peak
4	138.874	28.00	-12.01	15.99	43.50	27.51	Peak
5	473.835	28.13	-6.80	21.33	46.00	24.67	Peak
6	729.358	29.29	-3.57	25.72	46.00	20.28	Peak

**2) 1-25GHz:
BLE 1Mbps-Left side mirror legs:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2390.000	34.03	PK	H	31.71	65.74	74.00	8.26
2390.000	18.56	AV	H	31.71	50.27	54.00	3.73
2390.000	35.20	PK	V	31.71	66.91	74.00	7.09
2390.000	19.21	AV	V	31.71	50.92	54.00	3.08
4804.000	36.28	PK	H	11.19	47.47	74.00	26.53
4804.000	25.78	AV	H	11.19	36.97	54.00	17.03
4804.000	35.58	PK	V	11.19	46.77	74.00	27.23
4804.000	24.91	AV	V	11.19	36.10	54.00	17.90
7206.000	35.93	PK	H	15.03	50.96	74.00	23.04
7206.000	26.76	AV	H	15.03	41.79	54.00	12.21
7206.000	37.52	PK	V	15.03	52.55	74.00	21.45
7206.000	27.52	AV	V	15.03	42.55	54.00	11.45
Middle Channel: 2440 MHz							
4880.000	37.33	PK	H	11.48	48.81	74.00	25.19
4880.000	25.60	AV	H	11.48	37.08	54.00	16.92
4880.000	34.91	PK	V	11.48	46.39	74.00	27.61
4880.000	24.33	AV	V	11.48	35.81	54.00	18.19
7320.000	38.19	PK	H	15.58	53.77	74.00	20.23
7320.000	26.86	AV	H	15.58	42.44	54.00	11.56
7320.000	37.28	PK	V	15.58	52.86	74.00	21.14
7320.000	28.92	AV	V	15.58	44.50	54.00	9.50
High Channel: 2480 MHz							
2483.500	27.88	PK	H	32.19	60.07	74.00	13.93
2483.500	18.32	AV	H	32.19	50.51	54.00	3.49
2483.500	27.81	PK	V	32.19	60.00	74.00	14.00
2483.500	18.09	AV	V	32.19	50.28	54.00	3.72
4960.000	37.09	PK	H	11.77	48.86	74.00	25.14
4960.000	26.21	AV	H	11.77	37.98	54.00	16.02
4960.000	36.15	PK	V	11.77	47.92	74.00	26.08
4960.000	25.39	AV	V	11.77	37.16	54.00	16.84
7440.000	36.41	PK	H	15.98	52.39	74.00	21.61
7440.000	27.02	AV	H	15.98	43.00	54.00	11.00
7440.000	36.82	PK	V	15.98	52.80	74.00	21.20
7440.000	28.91	AV	V	15.98	44.89	54.00	9.11

BLE 2Mbps-Left side mirror legs:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2390.000	28.73	PK	H	31.71	60.44	74.00	13.56
2390.000	18.68	AV	H	31.71	50.39	54.00	3.61
2390.000	29.76	PK	V	31.71	61.47	74.00	12.53
2390.000	18.45	AV	V	31.71	50.16	54.00	3.84
4804.000	32.22	PK	H	11.19	43.41	74.00	28.59
4804.000	23.10	AV	H	11.19	34.29	54.00	17.71
4804.000	32.99	PK	V	11.19	44.18	74.00	27.82
4804.000	23.98	AV	V	11.19	35.17	54.00	16.83
7206.000	33.39	PK	H	15.03	48.42	74.00	23.58
7206.000	24.63	AV	H	15.03	39.66	54.00	12.34
7206.000	34.16	PK	V	15.03	49.19	74.00	22.81
7206.000	27.75	AV	V	15.03	42.78	54.00	11.22
Middle Channel: 2440 MHz							
4880.000	35.50	PK	H	11.48	46.98	74.00	27.02
4880.000	25.85	AV	H	11.48	37.33	54.00	16.67
4880.000	35.61	PK	V	11.48	47.09	74.00	26.91
4880.000	25.66	AV	V	11.48	37.14	54.00	16.86
7320.000	37.41	PK	H	15.58	52.99	74.00	21.01
7320.000	28.18	AV	H	15.58	43.76	54.00	10.24
7320.000	37.30	PK	V	15.58	52.88	74.00	21.12
7320.000	28.86	AV	V	15.58	44.44	54.00	9.56
High Channel: 2480 MHz							
2483.500	30.01	PK	H	32.19	62.20	74.00	11.80
2483.500	18.72	AV	H	32.19	50.91	54.00	3.09
2483.500	29.68	PK	V	32.19	61.87	74.00	12.13
2483.500	19.24	AV	V	32.19	51.43	54.00	2.57
4960.000	34.00	PK	H	11.77	45.77	74.00	28.23
4960.000	22.87	AV	H	11.77	34.64	54.00	19.36
4960.000	34.11	PK	V	11.77	45.88	74.00	28.12
4960.000	24.19	AV	V	11.77	35.96	54.00	18.04
7440.000	36.01	PK	H	15.98	51.99	74.00	22.01
7440.000	27.21	AV	H	15.98	43.19	54.00	10.81
7440.000	34.20	PK	V	15.98	50.18	74.00	23.82
7440.000	25.13	AV	V	15.98	41.11	54.00	12.89

BLE 1Mbps-Right side mirror legs:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2390.000	33.75	PK	H	31.71	65.46	74.00	8.54
2390.000	18.93	AV	H	31.71	50.64	54.00	3.36
2390.000	35.16	PK	V	31.71	66.87	74.00	7.13
2390.000	19.25	AV	V	31.71	50.96	54.00	3.04
4804.000	37.39	PK	H	11.19	48.58	74.00	25.42
4804.000	26.87	AV	H	11.19	38.06	54.00	15.94
4804.000	36.71	PK	V	11.19	47.90	74.00	26.10
4804.000	26.30	AV	V	11.19	37.49	54.00	16.51
7206.000	37.02	PK	H	15.03	52.05	74.00	21.95
7206.000	27.85	AV	H	15.03	42.88	54.00	11.12
7206.000	36.56	PK	V	15.03	51.59	74.00	22.41
7206.000	28.54	AV	V	15.03	43.57	54.00	10.43
Middle Channel: 2440 MHz							
4880.000	38.35	PK	H	11.48	49.83	74.00	24.17
4880.000	26.68	AV	H	11.48	38.16	54.00	15.84
4880.000	35.98	PK	V	11.48	47.46	74.00	26.54
4880.000	25.20	AV	V	11.48	36.68	54.00	17.32
7320.000	39.19	PK	H	15.58	54.77	74.00	19.23
7320.000	27.66	AV	H	15.58	43.24	54.00	10.76
7320.000	37.39	PK	V	15.58	52.97	74.00	21.03
7320.000	30.00	AV	V	15.58	45.58	54.00	8.42
High Channel: 2480 MHz							
2483.500	27.99	PK	H	32.19	60.18	74.00	13.82
2483.500	18.12	AV	H	32.19	50.31	54.00	3.69
2483.500	28.01	PK	V	32.19	60.20	74.00	13.80
2483.500	18.19	AV	V	32.19	50.38	54.00	3.62
4960.000	37.28	PK	H	11.77	49.05	74.00	24.95
4960.000	26.28	AV	H	11.77	38.05	54.00	15.95
4960.000	36.25	PK	V	11.77	48.02	74.00	25.98
4960.000	25.50	AV	V	11.77	37.27	54.00	16.73
7440.000	36.46	PK	H	15.98	52.44	74.00	21.56
7440.000	27.04	AV	H	15.98	43.02	54.00	10.98
7440.000	36.89	PK	V	15.98	52.87	74.00	21.13
7440.000	28.95	AV	V	15.98	44.93	54.00	9.07

BLE 2Mbps-Right side mirror legs:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2390.000	28.63	PK	H	31.71	60.34	74.00	13.66
2390.000	18.76	AV	H	31.71	50.47	54.00	3.53
2390.000	29.75	PK	V	31.71	61.46	74.00	12.54
2390.000	18.42	AV	V	31.71	50.13	54.00	3.87
4804.000	35.30	PK	H	11.19	46.49	74.00	27.51
4804.000	26.17	AV	H	11.19	37.36	54.00	16.64
4804.000	36.02	PK	V	11.19	47.21	74.00	26.79
4804.000	27.05	AV	V	11.19	38.24	54.00	15.76
7206.000	36.43	PK	H	15.03	51.46	74.00	22.54
7206.000	27.67	AV	H	15.03	42.70	54.00	11.30
7206.000	37.22	PK	V	15.03	52.25	74.00	21.75
7206.000	28.79	AV	V	15.03	43.82	54.00	10.18
Middle Channel: 2440 MHz							
4880.000	36.51	PK	H	11.48	47.99	74.00	26.01
4880.000	26.80	AV	H	11.48	38.28	54.00	15.72
4880.000	36.68	PK	V	11.48	48.16	74.00	25.84
4880.000	26.72	AV	V	11.48	38.20	54.00	15.80
7320.000	38.44	PK	H	15.58	54.02	74.00	19.98
7320.000	29.26	AV	H	15.58	44.84	54.00	9.16
7320.000	38.42	PK	V	15.58	54.00	74.00	20.00
7320.000	29.90	AV	V	15.58	45.48	54.00	8.52
High Channel: 2480 MHz							
2483.500	29.91	PK	H	32.19	62.10	74.00	11.90
2483.500	18.75	AV	H	32.19	50.94	54.00	3.06
2483.500	28.82	PK	V	32.19	61.01	74.00	12.99
2483.500	18.93	AV	V	32.19	51.12	54.00	2.88
4960.000	35.79	PK	H	11.77	47.56	74.00	26.44
4960.000	24.18	AV	H	11.77	35.95	54.00	18.05
4960.000	35.14	PK	V	11.77	46.91	74.00	27.09
4960.000	25.79	AV	V	11.77	37.56	54.00	16.44
7440.000	37.11	PK	H	15.98	53.09	74.00	20.91
7440.000	28.20	AV	H	15.98	44.18	54.00	9.82
7440.000	35.26	PK	V	15.98	51.24	74.00	22.76
7440.000	26.19	AV	V	15.98	42.17	54.00	11.83


Worst Test plots

Left side mirror legs(BLE 1M High channel):



Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: vertical
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4960.000	25.39	11.77	37.16	54.00	16.84	Average
2	4960.000	36.15	11.77	47.92	74.00	26.08	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: horizontal
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7440.000	27.02	15.98	43.00	54.00	11.00	Average
2	7440.000	36.41	15.98	52.39	74.00	21.61	Peak
3	17745.600	16.34	31.42	47.76	54.00	6.24	Average
4	17745.600	30.19	31.42	61.61	74.00	12.39	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: vertical
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7440.000	28.91	15.98	44.89	54.00	9.11	Average
2	7440.000	36.82	15.98	52.80	74.00	21.20	Peak
3	17772.000	16.37	31.52	47.89	54.00	6.11	Average
4	17772.000	30.14	31.52	61.66	74.00	12.34	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: Horizontal
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	20499.000	39.36	4.99	44.35	54.00	9.65	Average
2	20499.000	52.13	4.99	57.12	74.00	16.88	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: Vertical
 Note: BLE

Date: 2023-12-27




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	23150.600	38.87	5.50	44.37	54.00	9.63	Average
2	23150.600	51.23	5.50	56.73	74.00	17.27	Peak

Right side mirror legs(BLE 1M Middle channel):

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: horizontal
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4880.000	26.68	11.48	38.16	54.00	15.84	Average
2	4880.000	38.35	11.48	49.83	74.00	24.17	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: vertical
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4880.000	25.20	11.48	36.68	54.00	17.32	Average
2	4880.000	35.98	11.48	47.46	74.00	26.54	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: horizontal
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7320.000	27.66	15.58	43.24	54.00	10.76	Average
2	7320.000	39.19	15.58	54.77	74.00	19.23	Peak
3	17848.800	15.74	31.91	47.65	54.00	6.35	Average
4	17848.800	29.54	31.91	61.45	74.00	12.55	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: vertical
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7320.000	30.00	15.58	45.58	54.00	8.42	Average
2	7320.000	37.39	15.58	52.97	74.00	21.03	Peak
3	17560.800	17.33	30.34	47.67	54.00	6.33	Average
4	17560.800	30.73	30.34	61.07	74.00	12.93	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: Horizontal
 Note: BLE


Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	21663.800	38.53	4.82	43.35	54.00	10.65	Average
2	21663.800	51.63	4.82	56.45	74.00	17.55	Peak

Project No.: CR231168726-RF
 Tester: coco Tian
 Polarization: Vertical
 Note: BLE

Date: 2023-12-27



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	23432.000	38.95	5.40	44.35	54.00	9.65	Average
2	23432.000	51.62	5.40	57.02	74.00	16.98	Peak

4.3 6 dB Emission Bandwidth

Serial Number:	2DVE-2	Test Date:	2023/11/28~2023/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24-25	Relative Humidity: (%)	31-48	ATM Pressure: (kPa)	100.28-101.54
----------------------	-------	------------------------------	-------	------------------------	---------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101590	2023/11/16	2024/11/15
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Left side mirror legs:**Test Data:**

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
BLE 1Mbps	2402	0.729	≥ 0.5
	2440	0.735	≥ 0.5
	2480	0.726	≥ 0.5
BLE 2Mbps	2402	1.176	≥ 0.5
	2440	1.176	≥ 0.5
	2480	1.176	≥ 0.5

Right side mirror legs:**Test Data:**


Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
BLE 1Mbps	2402	0.729	≥ 0.5
	2440	0.726	≥ 0.5
	2480	0.726	≥ 0.5
BLE 2Mbps	2402	1.188	≥ 0.5
	2440	1.242	≥ 0.5
	2480	1.188	≥ 0.5

Left side mirror legs:




6dB Emission Bandwidth

BLE 2Mbps
Lowest Channel




ProjectNo.:CR231168726-RF-L Tester:Lingling Li
Date: 19.DEC.2023 13:25:40

BLE 2Mbps
Middle Channel




ProjectNo.:CR231168726-RF-L Tester:Lingling Li
Date: 19.DEC.2023 13:29:31

BLE 2Mbps
Highest Channel




ProjectNo.:CR231168726-RF-L Tester:Lingling Li
Date: 19.DEC.2023 13:34:15

Right side mirror legs:




6dB Emission Bandwidth


BLE 2Mbps
Lowest Channel



BLE 2Mbps
Middle Channel



BLE 2Mbps
Highest Channel



4.4 Maximum Conducted Output Power

Serial Number:	2DVE-2	Test Date:	2023/11/28~2023/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24-25	Relative Humidity: (%)	31-48	ATM Pressure: (kPa)	100.28-101.54
----------------------	-------	------------------------------	-------	------------------------	---------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Left side mirror legs:**Test Data:**

Test Modes	Test Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limit (dBm)
BLE 1Mbps	2402	1.39	≤30
	2440	0.9	≤30
	2480	1.01	≤30
BLE 2Mbps	2402	1.12	≤30
	2440	0.72	≤30
	2480	0.88	≤30

Right side mirror legs:**Test Data:**

Test Modes	Test Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limit (dBm)
BLE 1Mbps	2402	0.59	≤30
	2440	0.3	≤30
	2480	0.38	≤30
BLE 2Mbps	2402	0.44	≤30
	2440	0.16	≤30
	2480	0.27	≤30

4.5 Maximum power spectral density

Serial Number:	2DVE-2	Test Date:	2023/11/28~2023/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24-25	Relative Humidity: (%)	31-48	ATM Pressure: (kPa)	100.28-101.54
----------------------	-------	------------------------------	-------	------------------------	---------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101590	2023/11/16	2024/11/15
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Left side mirror legs:**Test Data:**

Test Modes	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1Mbps	2402	-15.26	≤8.00
	2440	-15.53	≤8.00
	2480	-15.47	≤8.00
BLE 2Mbps	2402	-18.43	≤8.00
	2440	-18.87	≤8.00
	2480	-18.79	≤8.00

Right side mirror legs:**Test Data:**


Test Modes	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1Mbps	2402	-15.74	≤8.00
	2440	-15.95	≤8.00
	2480	-16.02	≤8.00
BLE 2Mbps	2402	-19.08	≤8.00
	2440	-19.27	≤8.00
	2480	-19.21	≤8.00

Left side mirror legs:




Maximum power spectral density


BLE 2Mbps
Lowest Channel




BLE 2Mbps
Middle Channel



BLE 2Mbps
Highest Channel




Right side mirror legs:




Maximum power spectral density

BLE 2Mbps
Lowest Channel




ProjectNo.:CR231168726-RF Tester:Lingling Li
Date: 28.NOV.2023 13:07:53

BLE 2Mbps
Middle Channel



ProjectNo.:CR231168726-RF Tester:Lingling Li
Date: 28.NOV.2023 13:10:49

BLE 2Mbps
Highest Channel



ProjectNo.:CR231168726-RF Tester:Lingling Li
Date: 28.NOV.2023 13:14:15

4.6 100 kHz Bandwidth of Frequency Band Edge

Serial Number:	2DVE-2	Test Date:	2023/11/28~2023/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24-25	Relative Humidity: (%)	31-48	ATM Pressure: (kPa)	100.28-101.54
----------------------	-------	------------------------------	-------	------------------------	---------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101590	2023/11/16	2024/11/15
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Left side mirror legs:


100 kHz Bandwidth of Frequency Band Edge

BLE 1Mbps
Lowest Band edge



ProjectNo.:CR231168726-RF-L Tester:Lingling Li
Date: 19.DEC.2023 13:16:12


BLE 1Mbps
Highest Band edge




ProjectNo.:CR231168726-RF-L Tester:Lingling Li
Date: 19.DEC.2023 13:23:14

100 kHz Bandwidth of Frequency Band Edge

BLE 2Mbps
Lowest Band edge




BLE 2Mbps
Highest Band edge




Right side mirror legs:

100 kHz Bandwidth of Frequency Band Edge

BLE 1Mbps
Lowest Band edge




BLE 1Mbps
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

BLE 2Mbps
Lowest Band edge



BLE 2Mbps
Highest Band edge



4.7 Duty Cycle

Serial Number:	2DVE-2	Test Date:	2023/11/28~2023/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	24-25	Relative Humidity: (%)	31-48	ATM Pressure: (kPa)	100.28-101.54
----------------------	-------	------------------------------	-------	------------------------	---------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101590	2023/11/16	2024/11/15
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Left side mirror legs:**Test Data:**

Test Modes	Test Frequency (MHz)	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (kHz)
BLE 1Mbps	2440	2.125	2.505	84.83	470.59	1.0
BLE 2Mbps	2440	1.075	1.255	85.66	930.23	1.0


Right side mirror legs:**Test Data:**

Test Modes	Test Frequency (MHz)	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (kHz)
BLE 1Mbps	2440	2.125	2.505	84.83	470.59	1.0
BLE 2Mbps	2440	1.075	1.255	85.66	930.23	1.0

Left side mirror legs:



Right side mirror legs:



5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

5.2 Measurement Result

Left side mirror legs:

The max conducted power including tune-up tolerance is 2dBm (1.58mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 1.58/5 \cdot (\sqrt{2.480}) = 0.50 < 3.0$

Right side mirror legs:

The max conducted power including tune-up tolerance is 1dBm (1.26mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 1.26/5 \cdot (\sqrt{2.480}) = 0.40 < 3.0$

Two legs transmit simultaneously max conducted power including tune-up tolerance is 5dBm(3.16mW)

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 3.16/5 \cdot (\sqrt{2.480}) = 0.995 < 3.0$

Result: Compliant. The stand-alone SAR evaluation is not necessary.

6. EUT PHOTOGRAPHS

Please refer to the attachment CR231168726-EXP EUT EXTERNAL PHOTOGRAPHS and CR231168726-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR231168726-00A-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====