



RF MEASUREMENT REPORT

FCC ID: 2BBYQPCWL-0510

Applicant: PicoCELA Inc

Product: WiFi 6 (802.11ax) 4x4 MU-MIMO Tri Band Access point

Model No.: PCWL-0510

Brand Name: PicoCELA

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part 15 Subpart C (Section 15.247)

Result: Complies

Received Date: 2023-05-10

Test Date: 2023-05-17 ~ 2023-08-29

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2305RSU028-U1	V01	Initial Report	2023-07-25	Invalid
2305RSU028-U1	V02	Added test data	2023-08-29	Valid

Note: This report added PSD and conducted spurious verification data for panel antennas.

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information.....	6
1.5. Radio Specification under Test	6
1.6. Working Frequencies	7
1.7. Description of Available Antennas.....	8
2. Test Configuration	9
2.1. Test Mode.....	9
2.2. Test System Connection Diagram.....	10
2.3. Test Software	11
2.4. Applied Standards.....	11
2.5. Test Environment Condition	11
3. Antenna Requirements	12
4. Measuring Instrument	13
5. Decision Rules and Measurement Uncertainty	15
5.1. Decision Rules	15
5.2. Measurement Uncertainty	15
6. Test Result.....	16
6.1. Summary	16
6.2. 6dB Bandwidth Measurement.....	17
6.2.1. Test Limit	17
6.2.2. Test Procedure	17
6.2.3. Test Setting	17
6.2.4. Test Setup	17
6.2.5. Test Result	17
6.3. Output Power Measurement	18
6.3.1. Test Limit	18
6.3.2. Test Procedure	18
6.3.3. Test Setting	18
6.3.4. Test Setup	18
6.3.5. Test Result	18
6.4. Power Spectral Density Measurement	19
6.4.1. Test Limit	19

6.4.2.	Test Procedure	19
6.4.3.	Test Setting	19
6.4.4.	Test Setup	19
6.4.5.	Test Result	20
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement	21
6.5.1.	Test Limit	21
6.5.2.	Test Procedure	21
6.5.3.	Test Setting	21
6.5.4.	Test Setup	21
6.5.5.	Test Result	22
6.6.	Radiated Spurious Emission Measurement.....	23
6.6.1.	Test Limit	23
6.6.2.	Test Procedure	23
6.6.3.	Test Setting	23
6.6.4.	Test Setup	25
6.6.5.	Test Result	26
6.7.	Radiated Restricted Band Edge Measurement	27
6.7.1.	Test Limit	27
6.7.2.	Test Procedure	28
6.7.3.	Test Setting	28
6.7.4.	Test Setup	29
6.7.5.	Test Result	29
6.8.	AC Conducted Emissions Measurement	30
6.8.1.	Test Limit	30
6.8.2.	Test Setup	30
6.8.3.	Test Result	30
Appendix A – Test Result.....		31
A.1	Duty Cycle Test Result	31
A.2	6dB Bandwidth Test Result	33
A.3	Output Power Test Result	37
A.4	Power Spectral Density Test Result.....	40
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	66
A.6	Radiated Spurious Emission Test Result.....	120
A.7	Radiated Restricted Band Edge Test Result.....	134
A.8	AC Conducted Emissions Test Result	342
Appendix B – Test Setup Photograph		344
Appendix C – EUT Photograph		345

1. General Information

1.1. Applicant

PicoCELA Inc

2-34-5 Nihonbashi Ningyo-cho Chuo-ku Tokyo 103-0013 JAPAN

1.2. Manufacturer

PicoCELA Inc

2-34-5 Nihonbashi Ningyo-cho Chuo-ku Tokyo 103-0013 JAPAN

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China Laboratory Accreditations A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020 ☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104
☐	Test Site – MRT Shenzhen Laboratory Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China Laboratory Accreditations A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) Laboratory Accreditations TAF: 3261 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	WiFi 6 (802.11ax) 4x4 MU-MIMO Tri Band Access point
Model No.	PCWL-0510
EUT Identification No.	20230510Sample#02
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Antenna Information	Refer to Section 1.7
Power Supply	AC/DC Adapter or PoE Adapter
Accessories	
AC/DC Adapter	Model: PSAC60W-120 Input: 100-240V, 1.6A Output: 12V, 5A
Note 1: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer. Note 2: AC/DC Adapter was not sold with the product.	

1.5. Radio Specification under Test

Frequency Range	802.11b/g/n-HT20/ax-HE20: 2412 ~ 2462MHz 802.11n-HT40/ax-HE40: 2422 ~ 2452MHz	
Channel Number	802.11b/g/n-HT20/ax-HE20: 11 802.11n-HT40/ax-HE40: 7	
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax: OFDMA	
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps 802.11ax: up to 1147.2Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

1.7. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	Tx Paths	Max Antenna Gain (dBi)	Directional Gain (dBi)		Beamforming Directional Gain (dBi)
				For Power	For PSD	
Wi-Fi Antenna 1# (Model No.: PIC04-220080(AP))						
Omni-Directional	2400 ~ 2500	4	4.50	4.50	10.52	10.52
Omni-Directional	5150 ~ 5875	4	7.00	7.00	13.02	13.02
Wi-Fi Antenna 2# (Model No.: SAA04-222060)						
Directional Panel	2400 ~ 2500	4	13.50	13.50	19.52	19.52
Directional Panel	5150 ~ 5875	4	15.50	15.50	21.52	21.52
Remark:						
1. The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated. For CDD transmissions, directional gain is calculated as follows. Directional gain = $G_{ANT\ Max} + \text{Array Gain}$, where Array Gain is as follows. - For power spectral density (PSD) measurements on all devices, $\text{Array Gain} = 10 \log (N_{ANT}/ N_{SS}) \text{ dB};$ - For power measurements on IEEE 802.11 devices, $\text{Array Gain} = 0 \text{ dB for } N_{ANT} \leq 4;$						
2. The EUT also supports Beam Forming mode, and the Beam Forming supports 802.11n/ac/ax, not include 802.11a/b/g. Beamforming Directional gain = $G_{ANT\ Max} + 10 \log (N_{ANT}/ N_{SS}).$						
3. For the two antenna types, we evaluated “Output Power”, “Power Spectral Density”, “Radiated Spurious Emission” and “Radiated Restricted Band Edge” separately, and other test items were evaluated with Antenna 1# with higher power levels.						

2. Test Configuration


2.1. Test Mode

Mode 1: Transmit by 802.11b (1Mbps)
Mode 2: Transmit by 802.11g (6Mbps)
Mode 3: Transmit by 802.11n-HT20 (MCS0)
Mode 4: Transmit by 802.11n-HT40 (MCS0)
Mode 5: Transmit by 802.11ax-HE20 (MCS0)
Mode 6: Transmit by 802.11ax-HE40 (MCS0)
Remark: 1. For radiated spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. This device supports 4 Nss and power level is the same of spatial multiplexing. The worst case is Nss=1. 3. After preliminary scan designated by the manufacturer, CDD mode is determined to be the worst case compared to Beamforming mode, hence, all the radiated test is performed in CDD mode. 4. For beamforming operation, manufacturer automatically backs power down based on CDD power. Therefore, only the CDD mode was evaluated in this report.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram



Cable Type		Cable Description	
A	LAN Cable	Non shielded, > 10m	
B	Power Cable	Non shielded, 1.25m	
Product		Manufacturer	Model No.
1	Notebook	Dell	Latitude 5491

2.3. Test Software

The test utility software used during testing was “telnet”, and the commands were provided by the manufacturer.

Note: Final power setting please refer to operational description.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013
- KDB 662911 D01v02r01

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2023-12-28	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2023-08-22	WZ-AC1
Preamplifier	Agilent	83017A	MRTSUE06076	1 year	2024-05-07	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2023-06-21	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2024-06-09	WZ-AC1
Anechoic Chamber	TDK	WZ-AC1	MRTSUE06212	1 year	2024-04-20	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE06403	1 year	2023-06-06	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE06403	1 year	2024-05-31	WZ-AC1
Signal Analyzer	Keysight	N9010B	MRTSUE06607	1 year	2023-12-28	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11039	1 year	2023-11-01	WZ-AC1
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2023-12-28	WZ-AC1
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2023-09-29	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2023-11-05	WZ-AC1
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2024-01-12	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2024-05-15	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2023-06-04	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2024-05-23	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2023-11-27	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2023-10-13	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2024-05-07	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2024-04-20	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11038	1 year	2023-11-01	WZ-AC2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2023-06-04	WZ-SR2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2024-05-23	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2023-06-06	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2024-05-31	WZ-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06615	1 year	2023-10-08	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2023-10-27	WZ-SR2
Temperature Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2023-10-08	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2023-06-06	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2024-05-31	WZ-TR3
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2023-06-04	WZ-TR3
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2024-05-23	WZ-TR3
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2023-06-04	WZ-TR3

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2024-05-23	WZ-TR3
Attenuator	MVE	MVE2213	MRTSUE11089	1 year	2023-06-08	WZ-TR3
Attenuator	MVE	MVE2213	MRTSUE11089	1 year	2024-06-08	WZ-TR3

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_MF 7802	2.03C	RE Antenna & Turntable
Controller_MF 7802	1.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.
(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Disturbance
Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 9kHz~30MHz: 2.60dB 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.28dB 1GHz~40GHz: 4.98dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.3dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 1.5dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.3dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 3.2%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure


ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


6.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
8. Sweep time = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.
If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW $\geq 1/T$
4. Average Type = Voltage
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement


6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.8.2. Test Setup



6.8.3. Test Result


Refer to Appendix A.8.

Appendix A – Test Result

A.1 Duty Cycle Test Result


Test Site	WZ-TR3	Test Engineer	Lynn Yang
Test Date	2023-05-23		

Test Mode	Duty Cycle
802.11b	62.42%
802.11g	96.30%
802.11n-HT20	86.81%
802.11n-HT40	86.95%
802.11ax-HE20	95.03%
802.11ax-HE40	94.53%




Duty Cycle (T = Transmission Duration)

802.11ax-HE20 (T = 5.445ms)



802.11ax-HE40 (T = 5.445ms)




A.2 6dB Bandwidth Test Result

Test Site	WZ-TR3	Test Engineer	Lynn Yang
Test Date	2023-05-23		


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	8.070	≥ 0.5
11b	1Mbps	06	2437	8.062	≥ 0.5
11b	1Mbps	11	2462	8.069	≥ 0.5
11g	6Mbps	01	2412	16.33	≥ 0.5
11g	6Mbps	06	2437	16.32	≥ 0.5
11g	6Mbps	11	2462	16.35	≥ 0.5
11n-HT20	MCS0	01	2412	17.56	≥ 0.5
11n-HT20	MCS0	06	2437	17.57	≥ 0.5
11n-HT20	MCS0	11	2462	17.59	≥ 0.5
11n-HT40	MCS0	03	2422	35.91	≥ 0.5
11n-HT40	MCS0	06	2437	35.48	≥ 0.5
11n-HT40	MCS0	09	2452	36.28	≥ 0.5
11ax-HE20	MCS0	01	2412	18.90	≥ 0.5
11ax-HE20	MCS0	06	2437	18.87	≥ 0.5
11ax-HE20	MCS0	11	2462	18.98	≥ 0.5
11ax-HE40	MCS0	03	2422	37.81	≥ 0.5
11ax-HE40	MCS0	06	2437	37.26	≥ 0.5
11ax-HE40	MCS0	09	2452	37.95	≥ 0.5

802.11b 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11ax-HE20 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11ax-HE40 6dB Bandwidth


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



A.3 Output Power Test Result

Test Site	WZ-TR3	Test Engineer	Lynn Yang
Test Date	2023-05-24	Antenna No.	1#

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)				Total AV Power (dBm)	Limit (dBm)
				Ant 0	Ant 1	Ant 2	Ant 3		
11b	1Mbps	01	2412	22.88	23.20	22.73	22.75	28.91	≤ 30.00
11b	1Mbps	06	2437	22.47	23.02	22.41	22.59	28.65	≤ 30.00
11b	1Mbps	09	2452	22.38	22.93	22.66	22.79	28.72	≤ 30.00
11b	1Mbps	10	2457	18.79	19.39	18.98	19.25	25.13	≤ 30.00
11b	1Mbps	11	2462	18.78	19.50	19.16	19.41	25.24	≤ 30.00
11g	6Mbps	01	2412	19.69	20.21	19.52	19.50	25.76	≤ 30.00
11g	6Mbps	06	2437	22.55	22.91	22.51	22.46	28.63	≤ 30.00
11g	6Mbps	09	2452	20.70	21.09	20.59	20.68	26.79	≤ 30.00
11g	6Mbps	10	2457	17.26	17.42	17.01	17.28	23.27	≤ 30.00
11g	6Mbps	11	2462	14.39	15.02	14.62	14.83	20.74	≤ 30.00
11n-HT20	MCS0	01	2412	20.06	20.13	19.42	19.35	25.78	≤ 30.00
11n-HT20	MCS0	02	2417	20.95	21.03	20.20	20.26	26.65	≤ 30.00
11n-HT20	MCS0	06	2437	23.15	23.26	22.83	22.75	29.02	≤ 30.00
11n-HT20	MCS0	08	2447	21.11	21.38	21.02	21.06	27.17	≤ 30.00
11n-HT20	MCS0	09	2452	19.10	19.42	19.01	19.09	25.18	≤ 30.00
11n-HT20	MCS0	10	2457	19.11	19.55	19.02	19.05	25.21	≤ 30.00
11n-HT20	MCS0	11	2462	15.10	15.34	14.56	15.16	21.07	≤ 30.00
11n-HT40	MCS0	03	2422	18.41	18.72	18.10	18.02	24.34	≤ 30.00
11n-HT40	MCS0	06	2437	16.15	16.19	16.21	15.98	22.15	≤ 30.00
11n-HT40	MCS0	07	2442	13.15	13.50	12.68	12.82	19.07	≤ 30.00
11n-HT40	MCS0	08	2447	12.08	12.26	11.85	11.90	18.05	≤ 30.00
11n-HT40	MCS0	09	2452	10.78	11.23	11.05	10.66	16.96	≤ 30.00
11ax-HE20	MCS0	01	2412	18.43	19.03	18.25	18.17	24.50	≤ 30.00
11ax-HE20	MCS0	02	2417	19.98	20.37	19.66	19.72	25.96	≤ 30.00
11ax-HE20	MCS0	06	2437	22.66	23.15	22.51	22.78	28.80	≤ 30.00
11ax-HE20	MCS0	08	2447	20.08	20.70	20.21	20.33	26.36	≤ 30.00
11ax-HE20	MCS0	09	2452	18.26	18.41	18.15	18.26	24.29	≤ 30.00
11ax-HE20	MCS0	10	2457	18.25	18.65	18.18	18.40	24.39	≤ 30.00
11ax-HE20	MCS0	11	2462	14.15	14.78	14.12	14.53	20.42	≤ 30.00
11ax-HE40	MCS0	03	2422	16.96	17.38	16.65	16.61	22.93	≤ 30.00
11ax-HE40	MCS0	06	2437	14.86	14.81	14.96	14.56	20.82	≤ 30.00

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)				Total AV Power (dBm)	Limit (dBm)
				Ant 0	Ant 1	Ant 2	Ant 3		
11ax-HE40	MCS0	09	2452	11.80	12.11	11.66	11.81	17.87	≤ 30.00

Note: Total AV Power (dBm) = $10 \cdot \log \{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$.

Test Site	WZ-TR3	Test Engineer	Lynn Yang
Test Date	2023-05-25 ~ 2023-08-28	Antenna No.	2#

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)				Total AV Power (dBm)	Limit (dBm)
				Ant 0	Ant 1	Ant 2	Ant 3		
11b	1Mbps	01	2412	16.15	16.46	15.86	15.72	22.08	≤ 22.50
11b	1Mbps	06	2437	15.51	16.21	15.62	15.87	21.83	≤ 22.50
11b	1Mbps	11	2462	15.91	16.61	16.15	16.45	22.31	≤ 22.50
11g	6Mbps	01	2412	14.80	15.20	14.45	14.57	20.79	≤ 22.50
11g	6Mbps	06	2437	14.96	15.41	14.79	14.97	21.06	≤ 22.50
11g	6Mbps	10	2457	14.16	14.63	14.03	14.20	20.28	≤ 22.50
11g	6Mbps	11	2462	11.13	11.56	10.70	10.90	17.11	≤ 22.50
11n-HT20	MCS0	01	2412	13.46	13.63	13.01	12.96	19.30	≤ 22.50
11n-HT20	MCS0	06	2437	14.61	14.79	14.09	14.42	20.51	≤ 22.50
11n-HT20	MCS0	11	2462	11.73	11.73	11.14	11.58	17.57	≤ 22.50
11n-HT40	MCS0	03	2422	12.42	12.62	12.17	12.26	18.39	≤ 22.50
11n-HT40	MCS0	06	2437	9.72	10.12	9.49	9.57	15.75	≤ 22.50
11n-HT40	MCS0	09	2452	7.68	7.93	7.46	7.55	13.68	≤ 22.50
11ax-HE20	MCS0	01	2412	13.47	13.89	13.26	13.23	19.49	≤ 22.50
11ax-HE20	MCS0	06	2437	14.13	14.62	13.95	14.24	20.26	≤ 22.50
11ax-HE20	MCS0	10	2457	13.72	14.35	13.33	13.89	19.86	≤ 22.50
11ax-HE20	MCS0	11	2462	9.10	9.55	9.01	9.27	15.26	≤ 22.50
11ax-HE40	MCS0	03	2422	12.01	12.43	11.83	11.93	18.08	≤ 22.50
11ax-HE40	MCS0	06	2437	8.85	9.16	8.65	8.75	14.88	≤ 22.50
11ax-HE40	MCS0	09	2452	7.28	7.55	7.03	7.23	13.30	≤ 22.50

Note 1: Total AV Power (dBm) = $10 \cdot \log \{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$.

Note 2: Limit (dBm) = 30 dBm – (Directional Gain for Power (dBi) – 6 dBi)

A.4 Power Spectral Density Test Result

Antenna 1#:

Test Site	WZ-TR3	Test Engineer	Lynn Yang
Test Date	2023-05-24~2023-06-11		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	PSD (dBm/10kHz)				Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Result
				Ant 0	Ant 1	Ant 2	Ant 3			
11b	1Mbps	01	2412	-6.11	-5.22	-5.64	-6.83	2.16	≤ 3.48	Pass
11b	1Mbps	06	2437	-6.32	-6.29	-5.80	-6.52	1.85	≤ 3.48	Pass
11b	1Mbps	11	2462	-10.67	-10.68	-10.79	-10.74	-2.65	≤ 3.48	Pass
11g	6Mbps	01	2412	-9.25	-8.91	-9.17	-9.32	-2.98	≤ 3.48	Pass
11g	6Mbps	06	2437	-5.55	-5.00	-5.41	-5.69	0.78	≤ 3.48	Pass
11g	6Mbps	11	2462	-14.68	-13.65	-14.09	-14.33	-7.99	≤ 3.48	Pass
11n-HT20	MCS0	01	2412	-9.59	-9.67	-10.08	-10.04	-3.21	≤ 3.48	Pass
11n-HT20	MCS0	06	2437	-6.64	-6.75	-6.65	-6.91	-0.10	≤ 3.48	Pass
11n-HT20	MCS0	11	2462	-14.39	-14.07	-14.77	-14.24	-7.73	≤ 3.48	Pass
11n-HT40	MCS0	03	2422	-14.34	-14.24	-14.71	-14.52	-7.82	≤ 3.48	Pass
11n-HT40	MCS0	06	2437	-16.90	-16.66	-16.70	-16.85	-10.15	≤ 3.48	Pass
11n-HT40	MCS0	09	2452	-21.74	-21.85	-22.65	-21.96	-15.41	≤ 3.48	Pass
11ax-HE20	MCS0	01	2412	-12.49	-11.86	-12.56	-12.19	-6.02	≤ 3.48	Pass
11ax-HE20	MCS0	06	2437	-8.02	-7.20	-7.90	-7.29	-1.34	≤ 3.48	Pass
11ax-HE20	MCS0	11	2462	-16.59	-16.10	-16.48	-16.41	-10.15	≤ 3.48	Pass
11ax-HE40	MCS0	03	2422	-16.68	-16.37	-17.26	-16.78	-10.50	≤ 3.48	Pass
11ax-HE40	MCS0	06	2437	-18.47	-19.00	-18.62	-19.06	-12.51	≤ 3.48	Pass
11ax-HE40	MCS0	09	2452	-21.56	-21.70	-22.22	-21.80	-15.55	≤ 3.48	Pass

Note 1: When EUT duty cycle < 98%, the total PSD (dBm/10kHz) = $10 \cdot \log \{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)} + 10^{(\text{Ant 2 PSD}/10)} + 10^{(\text{Ant 3 PSD}/10)}\} + 10 \cdot \log (1/\text{Duty cycle})$.

When EUT duty cycle ≥ 98%, the total PSD (dBm/10kHz) = $10 \cdot \log \{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)} + 10^{(\text{Ant 2 PSD}/10)} + 10^{(\text{Ant 3 PSD}/10)}\}$.

Note 2: Limit (dBm/3kHz) = 8 dBm/3kHz – (Directional Gain for PSD (dBi) – 6 dBi)

802.11b - PSD – Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g - PSD – Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 - PSD – Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 - PSD – Ant 0


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)



802.11ax-HE20 - PSD – Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)



802.11ax-HE40 - PSD – Ant 0

Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)



802.11b - PSD – Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g - PSD – Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)

