

Test Report

Report No. : FCC2024-00018

Company : ZEROWELL Inc.

Representative : SangJin Kim

Address : 102ho, 106ho, 17-31, Cheondamwagi-ro 280beon-gil, Buk-gu, Gwangju, South Korea

1. Product Name : Humidified air purifier
- Type and Model : ZWAH-800WIU
2. Use of Report : Evaluation of EMC test
3. Date of Receipt : 2024-07-17
4. Date of test : 2024-07-17 ~ 2024-08-02
5. Testing Method : FCC 47 CFR Part 15 Subpart B
ANSI C 63.4-2014
6. Test Results : as stated in the annexed paper

Tested by : Jin Sung, Kim

Approved by : Sung Ryul, Kim

Jin - Sung, Kim

Sung Ryul Kim

1. This result of the above report are unrelated to KS Q ISO/IEC 17025 and KOLAS recognition and the result of testing with samples and sample names suggested by the client does not guarantee the quality of entire products
2. This report should not be used for advertising, lawsuit, etc. without any official permission of KTC. It is only used for the purpose of the quality test.
3. The authenticity of the report is available on the website (www.ktc.re.kr).

2024-10-24



Korea Testing Certification institute

www.ktc.re.kr [15809] 22 Heungan-daero27beon-gil, Gunpo-si, Gyeonggi-Do, Korea
TEL : +82-1899-7654, FAX : +82-31-428-2926

Test Result

Report No. : FCC2024-00018

TABLE OF CONTENTS

1. TESTING PROGRAM DETAILS	3
1.1 Applicant Information	5
1.2 Supporting Equipment Used During Test	5
1.3 Input / Output Ports	5
1.4 Power Interface.....	5
1.5 EUT Operation Modes.....	6
1.6 EUT Configuration Modes	6
1.7 Test System Layout.....	7
1.8 Applicable Standards for Testing	7
1.9 Summary of Test Results	7
1.10 Series Models.....	8
1.11 Measurement uncertainty.....	8
2. CONDUCTED EMISSION	9
2.1 Limits of conducted emission measurement.....	9
2.2 Environment Conditions.....	9
2.3 Test Site.....	9
2.4 Test Equipment List.....	9
2.5 Test Results.....	10
3. RADIATED EMISSION	12
3.1 Limits of radiated emission measurement	12
3.2 Environment Conditions.....	12
3.3 Test Site.....	13
3.4 Test Equipment List.....	13
3.5 Test Results.....	15

Test Result

Report No. : FCC2024-00018

1. Testing Program Details

Testing procedure and testing location	
Testing Laboratory	KTC (Korea Testing Certification Institute)
Testing location / address	[15809] 22 Heungan-daero27beon-gil, Gunpo-si, Gyeonggi-Do, Republic of Korea
Tested by (name)	Jin Sung, Kim
Approved by (name)	Sung Ryul, Kim
Test item description	Humidified air purifier
Applicant	ZEROWELL Inc.
Applicant Address	102ho, 106ho, 17-31, Cheondamwagi-ro 280beon-gil, Buk-gu, Gwangju, South Korea
Manufacturer	ZEROWELL Inc.
Manufacturer Address	102ho, 106ho, 17-31, Cheondamwagi-ro 280beon-gil, Buk-gu, Gwangju, South Korea
Factory	ZEROWELL Inc.
Factory Address	102ho, 106ho, 17-31, Cheondamwagi-ro 280beon-gil, Buk-gu, Gwangju, South Korea
FCC ID	2BC63-ZWAH-800WIU
Model / Type reference	ZWAH-800WIU / ZWAH-820WIU
Input Power Range	24 Vdc
Clock frequencies	8 MHz
Hardware version	- Main PCB : ZWAH-U800W Main Ver 0.3A - Power PCB : 800WIS-Power-V0.6A - Sub PCB : ZWAH-800AWI PWR RX V0.2 & ZWAH-800AWI PWR TX V0.2 - Snesor PCB : HD-2020W SENSOR V0.31
Firmware version	- ZWAH-800WIU_V1.01 - ZWH-820WIU_V1.01
Test site MRA or registration number	KR0006

Test Result

Report No. : FCC2024-00018

Possible test case verdicts	
- test case does not apply to test object	N/A
- test object does meet requirement	P (Pass)
- test object does not meet requirement	F (Fail)
Testing	
Date of receipt of test item	2024-07-17
Date(s) of performance of tests	2024-07-17 ~ 2024-08-02

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Test Result

Report No. : FCC2024-00018

1.1 Applicant Information

Name	ZEROWELL Inc.
Address	102ho, 106ho, 17-31, Cheondamwagi-ro 280beon-gil, Buk-gu, Gwangju, South Korea
FCC ID	2BC63-ZWAH-800WIU

1.2 Supporting Equipment Used During Test

Use	Product Type	Manufacturer	Model	Comments
EUT	Humidified air purifier	ZEROWELL Inc.	ZWAH-800WIU	-
EUT	I.T.E. POWER SUPPLY	W&T ELECTRONICS CO.,LTD.	W&T-AD1824B240100U	24V DC Power Supply

Supplementary information: EUT = Equipment Under Test, AE = Auxiliary / Associated Equipment, SIM = Simulator (Not Subjected to Test).

1.3 Input / Output Ports

Port No.	Name	Type	Cable Max. > 3 m	Cable Shielded	Comments
1	DC 24 V	DC	1.5	N	24V DC Power Supply output

Supplementary information: AC = AC Power Port, DC = DC Power Port, N/E = Non-Electrical, TP = Telecommunication Ports, I/O = Signal Input or Output Port (Not Involved in Process Control).

1.4 Power Interface

Mode No.	Voltage (V)	Current (A)	Power (W)	Frequency (Hz)	Phases (No.)	Comments
1	120	-	-	60	1	24V DC Power Supply Input

Supplementary information : -

Test Result

Report No. : FCC2024-00018

1.5 EUT Operation Modes

Mode No.	Description
1	Humidification Mode
2	Air purification Mode


1.6 EUT Configuration Modes

Mode No.	Description
1	The EUT was supplied with 12 V power and tested with the settings as follows. Humidification Mode, Wind speed : Turbo Mood : ON Timer : 6 H
2	The EUT was supplied with 12 V power and tested with the settings as follows. Air purification Mode Wind speed : Turbo Mood : ON Timer : 6 H

Test Result

Report No. : FCC2024-00018

1.7 Test System Layout



1.8 Applicable Standards for Testing

Standards	Status	Deviation
FCC 47 CFR Part 15 Subpart B ANSI C 63.4-2014	Applicable	No Deviation

1.9 Summary of Test Results

Requirement - Test	Result	Remark
Conducted Emission	P	-
Radiated Emissions(Below 1GHz)	P	-
Radiated Emissions(Above 1GHz)	P	-

Test Result

Report No. : FCC2024-00018

1.10 Series Models

Except for the following, the circuit and component layout are identical between the basic model and the variant model.

	Paricle Sensor	Air Filter
ZWAH-800WIU(Basic Model)	Used	Used
ZWH-820WIU(Variant Model)	Not Used	Not Used

1.11 Measurement uncertainty

Measurement	Uncertainty	
Conducted Emission	± 2.60 dB	
Radiated Emissions(30 MHz - 1 GHz)	H	± 3.38 dB
	V	± 3.96 dB
Radiated Emissions(1 GHz - 6 GHz)	H	± 6.66 dB
	V	± 6.04 dB
-This uncertainty represents an expanded uncertainty expressed at approximately 95% confidence level using a coverage factor of k=2.		

Test Result

Report No. : FCC2024-00018

2. Conducted Emission

The initial preliminary exploratory scans were performed over the measuring frequency range(0.15 MHz to 30 MHz) using a max hold mode incorporating a Peak detector and Average detector and using the software of EP5/CE (Version 5.4.12 from TOYO). The final test data was measured using a Quasi-Peak detector and Average detector.

2.1 Limits of conducted emission measurement

Frequency of emission (MHz)	Conducted limit (dB μ V)		Class
	Quasi-peak	Average	
0.15 - 0.5	66 to 56	56 to 46	B
0.5 - 5	56	46	
5 - 30	60	50	

2.2 Environment Conditions

Temperature	(22 \pm 2) °C
Humidity	(43 \pm 5) % R.H.
Atmospheric Pressure	(101.5 \pm 0.5) kPa

2.3 Test Site

Conducted Test Room in KTC Laboratory


2.4 Test Equipment List

Equipment	Model	Manufacturer	Series No.	Cal. Date	Cal. Due
EMI Test Receiver	N9038A	Agilent	MY53290038	2023-12-27	2024-12-27
LISN	ENV216	Rohde & Schwarz	101550	2023-12-26	2024-12-26

Test Result


Report No. : FCC2024-00018

2.5 Test Results



Test Result

Report No. : FCC2024-00018



Test Result

Report No. : FCC2024-00018

3. Radiated Emission

The initial preliminary exploratory scans were performed over the measuring frequency range(30 MHz to 6 GHz) using a max hold mode incorporating a Peak detector and using the software of Radiated Emission Measurement Software EP5/RE(Version 6.0.10 from TOYO). The final test data was measured using a Quasi-Peak detector below 1 GHz and a Peak and Average detector above 1 GHz. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m and the EUT was rotated 360° to find the maximum emitting point for each frequency.

3.1 Limits of radiated emission measurement

- Below 1 GHz

Frequency of emission (MHz)	Limits ($\mu\text{V}/\text{m}$)	Measuring Distance (m)	Class
	Quasi-peak		
30 - 88	100	3	B
88 - 216	150		
216 - 960	200		
960 - 1 000	500		

- Above 1 GHz

Frequency of emission (GHz)	Detector type	Limits ($\text{dB}(\mu\text{V}/\text{m})$)	Measuring Distance (m)	Class
1 ~ 6	Average	54	3	B
1 ~ 6	Peak	74		

3.2 Environment Conditions

- Below 1 GHz

Temperature	$(22 \pm 2) ^\circ\text{C}$
Humidity	$(43 \pm 5) \% \text{ R.H.}$
Atmospheric Pressure	$(101.5 \pm 0.5) \text{ kPa}$

Test Result

Report No. : FCC2024-00018

- Above 1 GHz

Temperature	(22 ± 2) °C
Humidity	(43 ± 5) % R.H.
Atmospheric Pressure	(101.5 ± 0.5) kPa

3.3 Test Site

10 m Semi-Anechoic Chamber in KTC Laboratory

3.4 Test Equipment List

- Below 1GHz

Equipment	Model	Manufacturer	Series No.	Cal. Date	Cal. Due
EMI Test Receiver	ESR 7	Rohde & Schwarz	101368	2024-07-08	2025-07-08
EMI Test Receiver	ESR 7	Rohde & Schwarz	102656	2024-07-08	2025-07-08
Bilog Antenna	VULB9168	Schwarzbeck	1043	2023-08-21	2025-08-21
Bilog Antenna	VULB9168	Schwarzbeck	1044	2023-09-05	2025-09-05
Pre Amplifier	310N	SONOMA	340214	2023-12-26	2024-12-26
Pre Amplifier	310N	SONOMA	340215	2023-12-26	2024-12-26
Antenna Master	innco systems	MA 4640-XP-ET-0800	7150519	-	-
Antenna Master	innco systems	MA 4640-XP-ET-0800	7160519	-	-
Turn Table	innco systems	DT3000-3t	-	-	-

Test Result

Report No. : FCC2024-00018

- Above 1 GHz


Equipment	Model	Manufacturer	Series No.	Cal. Date	Cal. Due
EMI Test Receiver	ESR 7	Rohde & Schwarz	101368	2024-07-08	2025-07-08
RF Amplifier	SCU-18	Rohde & Schwarz	10142	2024-07-08	2025-07-08
Horn Antenna	BBHA9120D	Schwarzbeck	918	2023-12-28	2024-12-28
Antenna Master	AM2.0	Maturo GmbH	-	-	-
Turn Table	DT3000-3t	innco systems	-	-	-

Test Result

Report No. : FCC2024-00018

3.5 Test Results


- Below 1GHz



Test Result

Report No. : FCC2024-00018

Test Date	2024-07-30		
Test Rating	120V~, 60Hz	EUT Operation Modes	2




Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	32.773	V	40.9	-13.2	27.7	40.0	12.3	102.4	47.3
2	128.948	H	37.4	-12.8	24.6	43.5	18.9	256.8	108.4
3	135.557	V	40.6	-12.0	28.6	43.5	14.9	102.6	175.3
4	404.828	H	30.6	-6.8	23.8	46.0	22.2	129.4	345.3

Test Result


Report No. : FCC2024-00018

- Above 1GHz



Test Result

Report No. : FCC2024-00018



- End of the Test Report -