

TEST REPORT

Report No.: BCTC2408541397-2E

Applicant: SHENZHEN SNAPPER TECHNOLOGY CO., LTD

Product Name: Travel Power Bank

Test Model: PS-B009WALR

Tested Date: 2024-08-09 to 2024-08-29

Issued Date: 2024-08-29

Shenzhen BCTC Testing Co., Ltd.



FCC ID: 2BC8J-PS-B009WALR

Product Name: Travel Power Bank
Trademark: N/A
Model/Type Reference: PS-B009WALR
PS-B009WA, PS-B009WAL, QM10005AC, FO 008, APBCH10SQBKB,
APBCH10SQWHB, A 0319A, DLP4349C
Prepared For: SHENZHEN SNAPPER TECHNOLOGY CO., LTD
Address: F4, BldgE, Fenghuang third Industrial area Tengfeng Road, Fuyong, Baoan,
Shenzhen, 518000, China
Manufacturer: SHENZHEN SNAPPER TECHNOLOGY CO., LTD
Address: F4, BldgE, Fenghuang third Industrial area Tengfeng Road, Fuyong, Baoan,
Shenzhen, 518000, China
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road,
Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China.
Sample Received Date: 2024-08-09
Sample Tested Date: 2024-08-09 to 2024-08-29
Issue Date: 2024-08-29
Report No.: BCTC2408541397-2E
Test Standards: FCC CFR 47 part1, 1.1307(b), 1.1310
Test Results: PASS

Tested by:
Shanshan Zhang

Shanshan. Zhang / Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.




Table Of Content

| Test Report Declaration | Page |
|---|------|
| 1. Version | 4 |
| 2. Product Information | 5 |
| 2.1 Product Information | 5 |
| 2.2 Support Equipment | 5 |
| 2.3 Test Mode | 6 |
| 3. Test Facility And Test Instrument Used | 7 |
| 3.1 Test Facility | 7 |
| 3.2 Test Instrument Used | 7 |
| 4. Method Of Measurement | 8 |
| 4.1 Applicable Standard | 8 |
| 4.2 Block Diagram Of Test Setup | 8 |
| 4.3 Limit | 9 |
| 4.4 Test procedure | 9 |
| 4.5 Equipment Approval Considerations | 10 |
| 4.6 E and H field Strength | 11 |
| 5. Photographs Of Test Set-Up | 18 |

(Note: N/A Means Not Applicable)


BCTC
 BCTC
 PPR
 Report



1. Version

| Report No. | Issue Date | Description | Approved |
|-------------------|------------|-------------|----------|
| BCTC2408541397-2E | 2024-08-29 | Original | Valid |
| | | | |

TEC
TC
OVB
t See



2. Product Information

2.1 Product Information

| | |
|-----------------------|---|
| Model/Type Reference: | PS-B009WALR PS-B009WA, PS-B009WAL, QM10005AC, FO 008, APBCH10SQBKB, APBCH10SQWHB, A 0319A, DLP4349C |
| Model Differences: | All the model are the same circuit and RF module, except model names and appearance of the color. |
| Hardware Version: | N/A |
| Software Version: | N/A |
| Modulation: | ASK |
| Operation Frequency: | 115kHz-205kHz, 320-350kHz |
| Antenna installation: | loop coil antenna |
| Ratings: | Battery: 10000mAh @3.7V 37Wh AC Input: 100-240V AC, 50Hz/60Hz, 0.3A(Max) Type-C Input: DC 5V=3A, 9V=2A, 12V=1.5A Type-C Output: DC 5V=3A, 9V=2.22A, 12V=1.67A Type-C Wire Output: DC 5V=3A, 9V=2.22A, 12V=1.67A Lightning adaptor output: DC 5V=2.4A, 9V=2.0A USB-A Output: DC 5V=3A, 9V=2A, 12V=1.5A, 18W Max Wireless Output: 5W/7.5W/10W/15W Watch Wireless Output: 5V=2.5W (Max) Adaptor mode output: 5V=2A Total Sharing Output: 5V=3A |

2.2 Support Equipment

| No. | Device Type | Brand | Model | Series No. | Note |
|-----|-------------------|--------|-------------|------------|-----------|
| E-1 | Travel Power Bank | N/A | PS-B009WALR | N/A | EUT |
| E-2 | ADAPTER | UGREEN | CD122 | N/A | Auxiliary |
| E-3 | Dummy load | N/A | DL01 | N/A | Auxiliary |

Notes:

- All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


2.3 Test Mode

| | | |
|---------|--------|--|
| AC Mode | Mode 1 | AC Plug in + Wireless 5W(115-205kHz) |
| | Mode 2 | AC Plug in + Wireless 2.5W(320-350kHz) |
| | Mode 3 | Type-C in +Wireless 5W(115-205kHz) |
| | Mode 4 | Type-C in + Wireless 2.5W(320-350kHz) |
| DC Mode | Mode 5 | Wireless 5W(115-205kHz) |
| | Mode 6 | Wireless 7.5W(115-205kHz) |
| | Mode 7 | Wireless 10W(115-205kHz) |
| | Mode 8 | Wireless 15W(115-205kHz) |
| | Mode 9 | Wireless 2.5W(320-350kHz) |

Note:

All test mode were tested and passed, only shows the worst case mode which were recorded in this report.

BCTC CO., LTD



3. Test Facility And Test Instrument Used

3.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850


A2LA certificate registration number is: CN1212

ISED Registered No.: 23583

ISED CAB identifier: CN0017

3.2 Test Instrument Used

| EMF Test | | | | | |
|--|--------------|---------|----------------|--------------|--------------|
| Equipment | Manufacturer | Model# | Serial# | Last Cal. | Next Cal. |
| Electromagnet -ic radiation tester | Wavecontrol | SMP160 | 19SN0980 | May 25, 2024 | May 24, 2025 |
| Electromagnet -ic field probe | Wavecontrol | WP400-3 | 20WP120082 | May 16, 2024 | May 15, 2025 |
| Software | Frad | EZ-EMC | EMC-CON 3A1 | \ | \ |




4. Method Of Measurement

4.1 Applicable Standard


According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1093 RF exposure is calculated. According KDB680106 D01v04: RF Exposure Wireless Charging v04.

4.2 Block Diagram Of Test Setup

A:



B:



4.3 Limit

| Limits for Occupational / Controlled Exposure | | | | |
|---|-----------------------------------|-----------------------------------|--|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

| Limits for General Population / Uncontrolled Exposure | | | | |
|---|-----------------------------------|-----------------------------------|--|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180 / f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1 | 30 |

4.4 Test procedure

- a) The RF exposure test was performed in anechoic chamber.
- b) The measurement probe was placed at 0 cm surrounding the device for test setup A; and the measurement Probe was placed at 20/22/24 cm for the test setup B.
- c) The highest emission level was recorded and compared with limit as soon as measurement of each
- d) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- d) The EUT was measured according to the dictates of KDB680106 D01v04.
- f) Remark: The EUT's test position A, B, C, D, E and F is valid for the E and H field measurements.

4.5 Equipment Approval Considerations

The EUT does comply with item 5(b) of KDB 680106 D01v04

1) Power transfer frequency is less than 1MHz

Yes, the device operate in the frequency range from 115kHz-205kHz, 320-350kHz.

2) Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of the primary coil is 15W.

3) A client device providing the maximum permitted load is placed in physical contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter.

4) Only § 2.1091-Mobile exposure conditions apply

No, the EUT is portable condition assessment

5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.

Yes, Conform to

6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time.

Yes, confirm.

4.6 E and H field Strength

We measured the H-Field Strength of 20cm, 22cm and 24cm, and recorded the test data of the worst 20cm Mobile: Test Mode 3 (the worst mode)

H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

| Frequency Range (MHz) | Test Position A(uT) | Test Position B(uT) | Test Position C(uT) | Test Position D(uT) | Test Position E(uT) | Test Position Top(uT) |
|-----------------------|---------------------|---------------------|---------------------|---------------------|---------------------|-----------------------|
| 0.115-0.205 | 0.0156 | 0.0071 | 0.0062 | 0.0124 | 0.0061 | 0.0058 |

| Frequency Range (MHz) | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position Top(A/m) | 50% Limits Test (A/m) | Limits Test (A/m) |
|-----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------------------|-----------------------|-------------------|
| 0.115-0.205 | 0.0125 | 0.0057 | 0.0047 | 0.0091 | 0.0046 | 0.0043 | 0.815 | 1.63 |

Note: $A/m = uT \div 1.25$

Mobile: Test Mode 4 (the worst mode)

H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

| Frequency Range (MHz) | Test Position A(uT) | Test Position B(uT) | Test Position C(uT) | Test Position D(uT) | Test Position E(uT) | Test Position Top(uT) |
|-----------------------|---------------------|---------------------|---------------------|---------------------|---------------------|-----------------------|
| 0.320-0.350 | 0.0179 | 0.0098 | 0.0094 | 0.0137 | 0.0072 | 0.0089 |

| Frequency Range (MHz) | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position Top(A/m) | 50% Limits Test (A/m) | Limits Test (A/m) |
|-----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------------------|-----------------------|-------------------|
| 0.320-0.350 | 0.0143 | 0.0078 | 0.0075 | 0.0110 | 0.0058 | 0.0071 | 0.815 | 1.63 |

Note: $A/m = uT \div 1.25$



Portable: Test Mode 8 (the worst mode)
 Transmitter Battery level: 100% battery

H-Filed Strength at (distance from 2cm to 20cm at 2cm iteration) surrounding the EUT (A/m)

| Test distance (cm) | Test Position A(uT) | Test Position B(uT) | Test Position C(uT) | Test Position D(uT) | Test Position E(uT) | Test Position F(uT) |
|--------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| 2 | 0.1385 | 0.1045 | 0.0920 | 0.1165 | 0.0568 | 0.0575 |
| 4 | 0.0540 | 0.0326 | 0.0324 | 0.0378 | 0.0223 | 0.0214 |
| 6 | 0.0241 | 0.0141 | 0.0140 | 0.0195 | 0.0125 | 0.0111 |
| 8 | 0.0190 | 0.0089 | 0.0083 | 0.0140 | 0.0080 | 0.0079 |
| 10 | 0.0192 | 0.0078 | 0.0079 | 0.0136 | 0.0068 | 0.0077 |
| 12 | 0.0185 | 0.0087 | 0.0084 | 0.0139 | 0.0074 | 0.0067 |
| 14 | 0.0192 | 0.0083 | 0.0075 | 0.0141 | 0.0076 | 0.0066 |
| 16 | 0.0181 | 0.0091 | 0.0070 | 0.0129 | 0.0068 | 0.0072 |
| 18 | 0.0181 | 0.0090 | 0.0077 | 0.0138 | 0.0072 | 0.0078 |
| 20 | 0.0182 | 0.0089 | 0.0074 | 0.0142 | 0.0072 | 0.0067 |

| Test distance (cm) | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|--------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 2 | 0.1108 | 0.0836 | 0.0736 | 0.0932 | 0.0454 | 0.0460 | 1.63 |
| 4 | 0.0432 | 0.0261 | 0.0259 | 0.0302 | 0.0178 | 0.0171 | 1.63 |
| 6 | 0.0193 | 0.0113 | 0.0112 | 0.0156 | 0.0100 | 0.0089 | 1.63 |
| 8 | 0.0152 | 0.0071 | 0.0066 | 0.0112 | 0.0064 | 0.0063 | 1.63 |
| 10 | 0.0154 | 0.0062 | 0.0063 | 0.0109 | 0.0054 | 0.0062 | 1.63 |
| 12 | 0.0148 | 0.0070 | 0.0067 | 0.0111 | 0.0059 | 0.0054 | 1.63 |
| 14 | 0.0154 | 0.0066 | 0.0060 | 0.0113 | 0.0061 | 0.0053 | 1.63 |
| 16 | 0.0145 | 0.0073 | 0.0056 | 0.0103 | 0.0054 | 0.0058 | 1.63 |
| 18 | 0.0145 | 0.0072 | 0.0062 | 0.0110 | 0.0058 | 0.0062 | 1.63 |
| 20 | 0.0146 | 0.0071 | 0.0059 | 0.0114 | 0.0058 | 0.0054 | 1.63 |

Note: $A/m = uT/1.25$

Using Biot-Savart Law, the value of 2cm can be estimated through the test results of 4cm:
Distance: 2cm

| Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 0.1440 | 0.0869 | 0.0864 | 0.1008 | 0.0541 | 0.0519 | 1.63 |

Agreement Ratio
Distance: 2cm

| Transmitter Battery level: 100% battery | | | | | | |
|---|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Test Position | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) |
| Measure Value (A/m) | 0.1108 | 0.0836 | 0.0736 | 0.0932 | 0.0454 | 0.0460 |
| Valuation(A/m) | 0.1440 | 0.0869 | 0.0864 | 0.1008 | 0.0541 | 0.0519 |
| Agreement ratio | 26.06 | 3.87 | 16.00 | 7.84 | 17.40 | 12.05 |
| Limit | 30% | 30% | 30% | 30% | 30% | 30% |
| Test result | Pass | Pass | Pass | Pass | Pass | Pass |

Using Biot-Savart Law, the value of 4cm can be estimated through the test results of 6cm:
Distance: 4cm

| Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 0.0455 | 0.0266 | 0.0264 | 0.0367 | 0.0232 | 0.0206 | 1.63 |


Agreement Ratio
Distance: 4cm

| Transmitter Battery level: 100% battery | | | | | | |
|---|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Test Position | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) |
| Measure Value (A/m) | 0.0432 | 0.0261 | 0.0259 | 0.0302 | 0.0178 | 0.0171 |
| Valuation(A/m) | 0.0455 | 0.0266 | 0.0264 | 0.0367 | 0.0232 | 0.0206 |
| Agreement ratio | 5.19 | 1.97 | 1.83 | 19.30 | 26.12 | 18.45 |
| Limit | 30% | 30% | 30% | 30% | 30% | 30% |
| Test result | Pass | Pass | Pass | Pass | Pass | Pass |

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

Using Biot-Savart Law, the value of 0cm can be estimated through the test results of 2cm:
Distance: 0cm

| Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 0.8544 | 0.6446 | 0.5675 | 0.7187 | 0.1850 | 0.1873 | 1.63 |
| Test result: Pass | | | | | | |



Portable: Test Mode 9 (the worst mode)
 Transmitter Battery level: 100% battery

H-Filed Strength at (distance from 2cm to 20cm at 2cm iteration) surrounding the EUT (A/m)

| Test distance (cm) | Test Position A(uT) | Test Position B(uT) | Test Position C(uT) | Test Position D(uT) | Test Position E(uT) | Test Position F(uT) |
|--------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| 2 | 0.1385 | 0.1046 | 0.0919 | 0.1163 | 0.0571 | 0.0578 |
| 4 | 0.0536 | 0.0325 | 0.0329 | 0.0381 | 0.0236 | 0.0224 |
| 6 | 0.0249 | 0.0150 | 0.0149 | 0.0200 | 0.0133 | 0.0126 |
| 8 | 0.0194 | 0.0100 | 0.0096 | 0.0141 | 0.0086 | 0.0096 |
| 10 | 0.0185 | 0.0088 | 0.0085 | 0.0133 | 0.0083 | 0.0089 |
| 12 | 0.0188 | 0.0093 | 0.0096 | 0.0139 | 0.0086 | 0.0085 |
| 14 | 0.0184 | 0.0097 | 0.0091 | 0.0140 | 0.0077 | 0.0091 |
| 16 | 0.0183 | 0.0100 | 0.0092 | 0.0139 | 0.0084 | 0.0089 |
| 18 | 0.0190 | 0.0089 | 0.0085 | 0.0137 | 0.0088 | 0.0094 |
| 20 | 0.0187 | 0.0100 | 0.0096 | 0.0141 | 0.0078 | 0.0097 |

| Test distance (cm) | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|--------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 2 | 0.1108 | 0.0837 | 0.0735 | 0.0930 | 0.0457 | 0.0462 | 1.63 |
| 4 | 0.0429 | 0.0260 | 0.0263 | 0.0305 | 0.0189 | 0.0179 | 1.63 |
| 6 | 0.0199 | 0.0120 | 0.0119 | 0.0160 | 0.0106 | 0.0101 | 1.63 |
| 8 | 0.0155 | 0.0080 | 0.0077 | 0.0113 | 0.0069 | 0.0077 | 1.63 |
| 10 | 0.0148 | 0.0070 | 0.0068 | 0.0106 | 0.0066 | 0.0071 | 1.63 |
| 12 | 0.0150 | 0.0074 | 0.0077 | 0.0111 | 0.0069 | 0.0068 | 1.63 |
| 14 | 0.0147 | 0.0078 | 0.0073 | 0.0112 | 0.0062 | 0.0073 | 1.63 |
| 16 | 0.0146 | 0.0080 | 0.0074 | 0.0111 | 0.0067 | 0.0071 | 1.63 |
| 18 | 0.0152 | 0.0071 | 0.0068 | 0.0110 | 0.0070 | 0.0075 | 1.63 |
| 20 | 0.0150 | 0.0080 | 0.0077 | 0.0113 | 0.0062 | 0.0078 | 1.63 |

Note: $A/m = uT/1.25$

BCTC
 B
 AP
 Re

Using Biot-Savart Law, the value of 2cm can be estimated through the test results of 4cm:

Distance: 2cm

| Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 0.1430 | 0.0867 | 0.0877 | 0.1017 | 0.0573 | 0.0542 | 1.63 |

Agreement Ratio

Distance: 2cm

| Transmitter Battery level: 100% battery | | | | | | |
|---|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Test Position | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) |
| Measure Value (A/m) | 0.1108 | 0.0837 | 0.0735 | 0.0930 | 0.0457 | 0.0462 |
| Valuation(A/m) | 0.1430 | 0.0867 | 0.0877 | 0.1017 | 0.0573 | 0.0542 |
| Agreement ratio | 25.37 | 3.52 | 17.62 | 8.94 | 22.52 | 15.94 |
| Limit | 30% | 30% | 30% | 30% | 30% | 30% |
| Test result | Pass | Pass | Pass | Pass | Pass | Pass |

Using Biot-Savart Law, the value of 4cm can be estimated through the test results of 6cm:

Distance: 4cm

| Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 0.0469 | 0.0283 | 0.0280 | 0.0377 | 0.0225 | 0.0235 | 1.63 |

Agreement Ratio


Distance: 4cm

| Transmitter Battery level: 100% battery | | | | | | |
|---|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Test Position | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) |
| Measure Value (A/m) | 0.0429 | 0.0260 | 0.0263 | 0.0305 | 0.0189 | 0.0179 |
| Valuation(A/m) | 0.0469 | 0.0283 | 0.0280 | 0.0377 | 0.0225 | 0.0235 |
| Agreement ratio | 8.91 | 8.47 | 6.26 | 21.11 | 17.39 | 27.05 |
| Limit | 30% | 30% | 30% | 30% | 30% | 30% |
| Test result | Pass | Pass | Pass | Pass | Pass | Pass |

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

Using Biot-Savart Law, the value of 0cm can be estimated through the test results of 2cm:
Distance: 0cm


| Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 0.8544 | 0.6454 | 0.5667 | 0.7171 | 0.1861 | 0.1881 | 1.63 |
| Test result: Pass | | | | | | |



TE
T
OV
t Se

5. Photographs Of Test Set-Up

Mobile:



EST
C
ED
sal

Portable:



STATEMENT

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****

2017