




# TEST REPORT

<p><b>Eurofins KCTL Co.,Ltd.</b>                  65, Sinwon-ro, Yeongtong-gu,                  Suwon-si, Gyeonggi-do, 16677, Korea                  TEL: 82-70-5008-1021 FAX: 82-505-299-8311  <a href="http://www.kctl.co.kr">www.kctl.co.kr</a></p>	<p>Report No.:                  KR24-SRF0089                  Page (1) of (7)</p>	 <b>KCTL</b>
--	---	---

**1. Client**

- Name : ITOFROM
- Address : 5F DS Building 8, Dogok-ro 7-gil Gangnam-gu, Seoul,06255, Korea
- Date of Receipt : 2024-04-08

**2. Use of Report** : Certification

**3. Name of Product / Model** : Smart Mold Sensor / NHS24

**4. Manufacturer / Country of Origin** : ITOFROM / Korea

**5. FCC ID** : 2BC8U-I2F-NHS24

**6. Date of Test** : 2024-05-03 to 2024-05-10

**7. Location of Test** :  Permanent Testing Lab  On Site Testing  
 (Address:65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)

**8. Test method used** : Part 1.1310

**9. Test Result** : Refer to the test result in the test report

Affirmation	Tested by	Technical Manager
	Name : Sehwan Park (Signature)	Name : Harim Lee (Signature)

2024-05-20

**Eurofins KCTL Co.,Ltd.**

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.

**REPORT REVISION HISTORY**

Date	Revision	Page No
2024-05-20	Originally issued	-

*This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

**General remarks for test reports**

**Statement concerning the uncertainty of the measurement systems used for the tests**

(may be required by the product standard or client)

**Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:**

**Procedure number, issue date and title:**


Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

**Statement not required by the standard or client used for type testing**

# CONTENTS

- 1. General information .....4
- 2. Device information .....4
  - 2.1. Frequency/channel operations.....5
- 3. RF Exposure.....6
  - 3.1. Test results.....7



<p><b>Eurofins KCTL Co.,Ltd.</b>  65, Sinwon-ro, Yeongtong-gu,  Suwon-si, Gyeonggi-do, 16677, Korea  TEL: 82-70-5008-1021 FAX: 82-505-299-8311  <a href="http://www.kctl.co.kr">www.kctl.co.kr</a></p>	<p>Report No.:  KR24-SRF0089  Page (4) of (7)</p>	
--	---	---

## 1. General information

Client : ITOFROM  
Address : 5F DS Building 8, Dogok-ro 7-gil Gangnam-gu, Seoul,06255, Korea  
Manufacturer : ITOFROM  
Address : 5F DS Building 8, Dogok-ro 7-gil Gangnam-gu, Seoul,06255, Korea  
Laboratory : Eurofins KCTL Co.,Ltd.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
CAB Identifier: KR0040  
ISED Number: 8035A  
KOLAS No.: KT231

## 2. Device information

Equipment under test : Smart Mold Sensor  
Model : NHS24  
Modulation technique : GFSK  
Number of channels : 40 ch  
Power source : DC 3.6 V  
Antenna type : Chip antenna  
Antenna gain : 1.71 dBi  
Frequency range : 2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy)  
Software version : V1.0.0  
Hardware version : V1.0.0  
Operation temperature : -25 °C ~ 85 °C  
Test device serial No. : Conducted: CCM2349J12011  
Radiated: CCM2410J12034

## 2.1. Frequency/channel operations

This device contains the following capabilities:

Bluetooth Low Energy

Ch.	Frequency (MHz)
00	2 402
⋮	⋮
19	2 440
⋮	⋮
39	2 480

Table 2.2.1. Bluetooth Low Energy



### 3. RF Exposure

#### Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, \*= plane-wave equivalent power density

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100 kHz

#### MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad (\Rightarrow R = \sqrt{PG / 4\pi S})$$

S = power density [mW/cm<sup>2</sup>]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

### 3.1. Test results

#### Calculation Result of RF exposure

Maximum tune-up tolerance

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Max Tune-up Power [mW]	Ant Gain [dBi]	Power density at 20 cm [mW/cm <sup>2</sup> ]	Limit [mW/cm <sup>2</sup> ]
BLE	2 402 ~ 2 480	4.00	2.51	1.71	0.000 74	1.00

**Note.**

- The power density  $P_d$  at a distance of 20 cm calculated from the friis transmission Formula is far below the limit of 1 mW/cm<sup>2</sup>.

**End of test report**