

# STRAX Americas, Inc.

# TEST REPORT

**SCOPE OF WORK**

SAR Assessment– CW14

**REPORT NUMBER**

230703055SZN-002

**ISSUE DATE**

19 July 2023

**[REVISED DATE]**

[-----]

**PAGES**

10

**DOCUMENT CONTROL NUMBER**

RF Exposure

© 2017 INTERTEK



## Test Report

Applicant : STRAX Americas, Inc.  
2606 NW 97th Ave. Doral, FL 33172, USA

Sample Description

Product : Wireless Charging Car Mount  
Model No. : CW14  
FCC ID : 2BCBM-CW14  
Brand Name : JEWEL  
Electrical Rating : Input: DC 9V 2A via USB port

Date Received : 03 July 2023  
Date Test Conducted : 03 July 2023 to 14 July 2023

Test Requested : Test for compliance with CFR 47 part 1  
Test Method : Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

Test Result : Pass  
Conclusion : When determining of test conclusion, measurement uncertainty of tests have been considered.

\*\*\*\*\* End of Page \*\*\*\*\*

Prepared and Checked By:

Approved By:

\_\_\_\_\_  
**Bruce Zheng**  
Project Engineer

\_\_\_\_\_  
**Peter Kang**  
Sr. Technical Supervisor  
Date: 19 July 2023

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Services Shenzhen Ltd. Longhua Branch**


101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288

Fax: (86 755) 8601 6751

## Test Report

### Test Setup Configuration



#### Note

- The RF exposure test is performed in the shield room.
- The test distance is between the edge of the charger and the geometric centre of probe.

### Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ186-04	Electric and Magnetic Field Analyzer	Narda	EHP-50F	510WY90119	2022-08-01	2023-08-01

### Support Equipment List

Description	Manufacturer	Detail
Mobile Phone (Provided by Intertek)	Samsung	S7
USB cable (Provided by Applicant)	Merchsource, LLC	Unshielded, without ferrite,100cm
Car Charger (Provided by Applicant)	Merchsource, LLC	Input DC 12/24V Output 3.6-6.5V/3A, 6.5-9V/2A, 9-12V/1.5A
Car Charger Adapter with DC undetachable cable (Provided by Intertek)	/	Unshield, 70cm
VALVE REGULATED LEAD-ACID BATTERY (Provided by Intertek)	OCEAN	12V7Ah (20HR)

**Reference Limit:**

**Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	(100) *	30

Note: \* = Plane wave equivalent power density

**Test Result: Pass**

**H-Field Strength at 0 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Probe Position Bottom (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.1335	0.1335	0.1302	0.1326	0.1338	0.1397	1.63
0.110-0.205	50% Battery Level	0.1333	0.1334	0.1249	0.1311	0.1323	0.1342	1.63
0.110-0.205	99% Battery Level	0.1125	0.1250	0.1178	0.1141	0.1139	0.1312	1.63
0.110-0.205	Stand-by	0.1101	0.1249	0.1119	0.1104	0.1098	0.1307	1.63

**E-Field Strength at 0 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Probe Position Bottom (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	6.6922	6.4622	6.4805	6.2908	7.0044	6.6204	614
0.110-0.205	50% Battery Level	6.5833	6.4339	6.4582	6.1324	6.9936	6.5796	614
0.110-0.205	99% Battery Level	6.1431	6.0970	6.4306	6.1218	6.0991	6.4434	614
0.110-0.205	Stand-by	6.0767	6.0670	6.2381	6.0349	5.8151	6.2019	614

**H-Field Strength at 2 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Probe Position Bottom (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.2446	0.2387	0.2313	0.2328	0.2309	0.2351	1.63
0.110-0.205	50% Battery Level	0.2338	0.2367	0.2275	0.2311	0.2293	0.2349	1.63
0.110-0.205	99% Battery Level	0.2331	0.2354	0.2263	0.2269	0.2277	0.2328	1.63
0.110-0.205	Stand-by	0.2246	0.2300	0.2201	0.2153	0.1992	0.2301	1.63

**E-Field Strength at 2 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Probe Position Bottom (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	4.2119	4.6216	4.0451	4.6668	4.0770	4.3007	614
0.110-0.205	50% Battery Level	4.1799	4.3084	4.0426	4.6625	4.0348	4.2425	614
0.110-0.205	99% Battery Level	4.0563	4.2838	4.0283	4.0689	4.0056	4.1883	614
0.110-0.205	Stand-by	3.9721	4.1734	3.9534	4.0466	3.8386	4.1497	614

**H-Field Strength at 4 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Probe Position Bottom (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.2276	0.2272	0.2289	0.2278	0.2275	0.2266	1.63
0.110-0.205	50% Battery Level	0.2270	0.2259	0.2274	0.2270	0.2253	0.2262	1.63
0.110-0.205	99% Battery Level	0.2254	0.2239	0.2270	0.2249	0.2252	0.2253	1.63
0.110-0.205	Stand-by	0.2215	0.2199	0.2266	0.2190	0.2218	0.1926	1.63

**E-Field Strength at 4 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Probe Position Bottom (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	4.3255	4.5805	4.6635	4.4878	4.4118	4.3841	614
0.110-0.205	50% Battery Level	4.2135	4.5226	4.6215	4.4572	4.4070	4.2619	614
0.110-0.205	99% Battery Level	4.0698	4.0778	4.2267	4.1208	4.3743	4.1883	614
0.110-0.205	Stand-by	3.9486	4.0394	4.1311	4.0645	4.1861	4.1772	614

**H-Field Strength at 6 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Probe Position Bottom (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.2245	0.2256	0.2240	0.2233	0.2222	0.2231	1.63
0.110-0.205	50% Battery Level	0.2220	0.2251	0.2237	0.2231	0.2210	0.2290	1.63
0.110-0.205	99% Battery Level	0.1916	0.2212	0.2224	0.2233	0.2206	0.2273	1.63
0.110-0.205	Stand-by	0.1878	0.2116	0.1910	0.2219	0.1913	0.2150	1.63

**E-Field Strength at 6 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Probe Position Bottom (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	4.5612	4.4115	4.1095	4.5281	4.4110	4.1416	614
0.110-0.205	50% Battery Level	4.5609	4.4083	4.0874	4.4586	4.4062	4.1347	614
0.110-0.205	99% Battery Level	4.3684	4.2287	4.0540	4.3525	4.3183	4.0950	614
0.110-0.205	Stand-by	4.0076	4.1438	3.7699	4.2013	4.3147	3.8484	614

**H-Field Strength at 8 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Probe Position Bottom (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.0355	0.0352	0.0345	0.0355	0.0354	0.0352	1.63
0.110-0.205	50% Battery Level	0.0343	0.0334	0.0337	0.0331	0.0340	0.0340	1.63
0.110-0.205	99% Battery Level	0.0305	0.0333	0.0293	0.0318	0.0336	0.0334	1.63
0.110-0.205	Stand-by	0.0280	0.0187	0.0286	0.0273	0.0284	0.0293	1.63

**E-Field Strength at 8 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Probe Position Bottom (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	1.5803	1.6314	1.4872	1.5118	1.5144	1.5047	614
0.110-0.205	50% Battery Level	1.5747	1.4497	1.4639	1.3617	1.5118	1.5043	614
0.110-0.205	99% Battery Level	1.3276	1.4301	1.2610	1.3430	1.3211	1.3722	614
0.110-0.205	Stand-by	1.1567	1.4201	1.0661	1.3393	1.2615	1.1755	614

**H-Field Strength at 10 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Probe Position Bottom (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.0357	0.0377	0.0365	0.0367	0.0370	0.0366	1.63
0.110-0.205	50% Battery Level	0.0349	0.0359	0.0354	0.0358	0.0351	0.0342	1.63
0.110-0.205	99% Battery Level	0.0304	0.0343	0.0338	0.0343	0.0337	0.0339	1.63
0.110-0.205	Stand-by	0.0261	0.0333	0.0294	0.0302	0.0284	0.0280	1.63

**E-Field Strength at 10 cm surrounding the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Probe Position Bottom (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	1.2925	1.4878	1.3885	1.3192	1.4447	1.5067	614
0.110-0.205	50% Battery Level	1.2878	1.3888	1.3241	1.2869	1.4057	1.3804	614
0.110-0.205	99% Battery Level	1.1933	1.2879	1.3169	1.2791	1.3100	1.3777	614
0.110-0.205	Stand-by	1.1488	1.1134	1.2031	1.2591	1.2613	1.0963	614

**H-Field Strength at 15 cm surrounding the EUT and 20cm above the top surface of the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Limits (A/m)
0.110-0.205	1% Battery Level	0.0236	0.0216	0.0216	0.0220	0.0222	1.63
0.110-0.205	50% Battery Level	0.0219	0.0214	0.0210	0.0215	0.0204	1.63
0.110-0.205	99% Battery Level	0.0203	0.0204	0.0191	0.0211	0.0198	1.63
0.110-0.205	Stand-by	0.0190	0.0178	0.0188	0.0185	0.0164	1.63


**E-Field Strength at 15 cm surrounding the EUT and 20cm above the top surface of the EUT**

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Limits (V/m)
0.110-0.205	1% Battery Level	1.0831	1.0842	1.1071	0.9805	1.0265	614
0.110-0.205	50% Battery Level	1.0788	1.0775	1.1024	0.9779	1.0233	614
0.110-0.205	99% Battery Level	1.0507	0.9315	0.9655	0.9590	0.9096	614
0.110-0.205	Stand-by	0.9564	0.9091	0.8369	0.7901	0.8353	614



Configuration photo of the test:


H-Field & E-Field Strength test photos




Front 0cm



Rear 0cm



Left 0cm



Right 0cm



Top 0cm



Bottom 0cm

\*\*\*\*\* End of Report\*\*\*\*\*