

FCC ID:2BCCC-Y25

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.3	2.69	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	5.199	3.31	5±1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	4.609	2.89	4±1	5.00	3.16	<5	0.99599	3.00	YES
π /4DQPSK	2.402	4.667	2.93	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	5.556	3.59	5±1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	4.845	3.05	4±1	5.00	3.16	<5	0.99599	3.00	YES

BLE:1M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.327	2.71	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.44	5.245	3.35	5±1	6.00	3.98	<5	1.24373	3.00	YES
	2.480	4.493	2.81	4±1	5.00	3.16	<5	0.99599	3.00	YES

BLE:2M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.089	2.56	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.44	5.144	3.27	5±1	6.00	3.98	<5	1.24373	3.00	YES
	2.480	4.578	2.87	4±1	5.00	3.16	<5	0.99599	3.00	YES

Conclusion:

For the max result : $1.24398 \leq$ FCC Limit 3.0 for 1g SAR.