



FCC TEST REPORT

FCC ID: 2BCDQ-MSF101

Product : Mousse Smart Pet Feeder
Model Name : MSF101, MSF102, MSF103, MSF104, MSF105
Brand : meoof
Report No. : NCT23030212XE

Prepared for

Guangzhou Miao Culture Technology Co., Ltd.

Room 225, 2nd Floor, Building 2, No.188 Kaitai Avenue, Huangpu District, Guangzhou

Prepared by

Shenzhen NCT Testing Technology Co., Ltd.

**A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District,
Shenzhen, People's Republic of China**

TEL: 400-8868-419

FAX: 86-755-27790922

1 TEST RESULT CERTIFICATION

Applicant's name : Guangzhou Miao Culture Technology Co., Ltd.
Address : Room 225, 2nd Floor, Building 2, No.188 Kaitai Avenue,
: Huangpu District, Guangzhou
Manufacture's name : Guangzhou Miao Culture Technology Co., Ltd.
Address : Room 225, 2nd Floor, Building 2, No.188 Kaitai Avenue,
: Huangpu District, Guangzhou
Product name : Mousse Smart Pet Feeder
Model name : MSF101, MSF102, MSF103, MSF104, MSF105
Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : ANSI C63.10:2013
Date of test : Jul. 25, 2023-Aug. 3, 2023
Date of Issue : Aug.03, 2019

This device described above has been tested by NCT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NCT, this document may be altered or revised by NCT, personal only, and shall be noted in the revision of the document.

Test Engineer:



Keven Wu / Engineer

Technical Manager:



Henry Wang / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF E.U.T.	6
3.2 CHANNEL LIST	7
3.3 TEST SITE	11
4 EQUIPMENT DURING TEST	12
4.1 EQUIPMENTS LIST	12
4.2 MEASUREMENT UNCERTAINTY	14
4.3 DESCRIPTION OF SUPPORT UNITS	14
5 CONDUCTED EMISSION	15
5.1 E.U.T. OPERATION	15
5.2 EUT SETUP	15
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	16
5.4 MEASUREMENT PROCEDURE	16
5.5 CONDUCTED EMISSION LIMIT	16
5.6 MEASUREMENT DESCRIPTION	16
5.7 CONDUCTED EMISSION TEST RESULT	16
6 RADIATED SPURIOUS EMISSIONS	19
6.1 EUT OPERATION	19
6.2 TEST SETUP	20
6.3 SPECTRUM ANALYZER SETUP	21
6.4 TEST PROCEDURE	22
6.5 SUMMARY OF TEST RESULTS	23
7 CONDUCTED SPURIOUS EMISSION	32
7.1 TEST PROCEDURE	32
7.2 TEST RESULT	32

8 BAND EDGE MEASUREMENT	45
8.1 TEST PROCEDURE	45
8.2 TEST RESULT	46
9 6DB BANDWIDTH MEASUREMENT	50
9.1 TEST PROCEDURE	50
9.2 TEST RESULT	50
10 MAXIMUM PEAK OUTPUT POWER	57
10.1 TEST PROCEDURE	57
10.2 TEST RESULT	57
11 POWER SPECTRAL DENSITY	58
11.1 TEST PROCEDURE	58
11.2 TEST RESULT	58
12 ANTENNA APPLICATION	65
12.1 ANTENNA REQUIREMENT	65
12.2 RESULT	65
13 TEST SETUP	66
14 EUT PHOTOS	68

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS
Remark: N/A: Not Applicable		

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Mousse Smart Pet Feeder
Model Name	:	MSF101
Sample ID	:	23030212A-00
Sample(s) Status:	:	Engineer sample
Series Model	:	MSF102, MSF103, MSF104, MSF105
Model Different.:	:	All the same except the model number.
Specification	:	802.11b/g/n HT20
Operation Frequency	:	2412-2462MHz for 802.11b/g/n20; 2422-2452MHz for 802.11n40;
Number of Channel	:	11 channels for 802.11b/g/n20; 7 channels for 802.11n40;
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	FPCB Antenna
Antenna Gain	:	2 dBi
Power supply	:	DC 5V From adapter input AC 120V/60Hz or DC 3.7V from Battery
Hardware Version	:	V1.0.24
Software Version	:	U56_WIFI01_RTL_MAIN_BOM_V2_2
<p>Remark : the Antenna gain is provided by customer from Antenna spec. and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.</p>		

3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0; were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20)/n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		


Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
3	2422	6	2437	9	2452


The maximum duty cycle as following table:

Test Plots:


802.11b




802.11g



802.11n(HT20)



802.11n(HT40)



3.3 Test Site

Site Description

- EMC Lab. : Accredited by CNAS, 2022-09-27
- The certificate is valid until 2028.01.07
- The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)
- The Certificate Registration Number is L8251
- Designation Number: CN1347
- Test Firm Registration Number: 894804
- Accredited by A2LA, June 14, 2023
- The Certificate Registration Number is 6837.01
- Accredited by Industry Canada, November 09, 2018
- The Conformity Assessment Body Identifier is CN0150
- Company Number: 30806
- Name of Firm : Shenzhen NCT Testing Technology Co., Ltd.
- Site Location : A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

4 Equipment During Test

4.1 Equipments List

Conducted emission Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	944 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESPI	101604	Rohde & Schwarz	2023/6/21	2024/6/20
LISN	ENV 216	102796	Rohde & Schwarz	2023/6/21	2024/6/20
LISN	VN1-13S	004023	CRANAGE	2023/6/21	2024/6/20
Cable	RG223-1500MM	NA	RG	2023/6/21	2024/6/20

Radiated emission & Radio Frequency Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESCI	101178	Rohde & Schwarz	2023/6/21	2024/6/20
Spectrum Analyze (10Hz-26.5GHz)	N9020A	MY50510202	Agilent	2023/6/21	2024/6/20
Amplifi (30MHz-1GHz)	BBV 9743 B	00374	SCHNARZBECK	2023/6/21	2024/6/20
Bilog Antenna (30MHz-1GHz)	VULB9162	00473	SCHNARZBECK	2023/3/19	2025/3/18
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHNARZBECK	2023/3/19	2025/3/18
Pream plifier (1GHz-18GHz)	BBV 9718D	0024	SCHNARZBECK	2023/6/21	2024/6/20
Spectrum Analyze (1GHz-40GHz)	FSV 40	100952	Rohde & Schwarz	2023/6/21	2024/6/20
Pream plifier (15GHz-40GHz)	BBV 9718D	0024	SCHNARZBECK	2023/6/21	2024/6/20
Broadband Antenna (15GHz-40GHz)	SAS-574	588	A.H.System	2023/3/19	2025/3/18
Loop Antenna (9KHz-30MHz)	FMZB1519B	014	SCHNARZBECK	2023/6/21	2024/6/20

Amplifier (9KHz-30MHz)	CVP 9222 C	00109	SCHNARZBECK	2023/6/21	2024/6/20
MXG Signal Analyzer	N9020A	101178	RS	2023/6/21	2024/6/20
MXG Vector Signal Generator	N5182A	MY50510202	Agilent	2023/6/21	2024/6/20
MXG Analog Signal Generator	N5181A	00374	SCHWARZBECK	2023/6/21	2024/6/20
Power Sensor	TR1029-2	00473	SCHNARZBECK	2023/6/21	2024/6/20
RF Swith	TR1029-1	02622	SCHNARZBECK	2023/6/21	2024/6/20
Cable	DA800- 4000MM	NA	DA	2023/6/21	2024/6/20
Cable	DA800- 11000MM	NA	DA	2023/6/21	2024/6/20

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	AUDIX	e3	6.120718
2	EMC radiation test system	AUDIX	e3	6.120718
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB

4.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Mousse Smart Pet Feeder	meoof	MSF101	N/A	EUT
E-2	ADAPTER	N/A	TPA-46B050100UU	N/A	Auxiliary
E-3	USB Line	N/A	N/A	N/A	Auxiliary

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207
Test Method : ANSI C63.10: 2013
Test Result : PASS
Frequency Range : 150kHz to 30MHz
Class/Severity : Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature : 24.5 °C
Humidity : 51.3 % RH
Atmospheric Pressure : 101.11kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

Pass.

Please refer to the following pages.


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		



No.	Freq MHz	Cable Loss dB	LISN Factor dB/m	Receiver Reading dBuV	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	0.170	0.00	9.54	28.51	38.05	54.94	-16.89	Average
2.	0.170	0.00	9.54	47.37	56.91	64.94	-8.03	QP
3.	0.226	0.01	9.55	23.67	33.23	52.61	-19.38	Average
4.	0.226	0.01	9.55	40.71	50.27	62.61	-12.34	QP
5.	0.294	0.01	9.56	19.34	28.91	50.41	-21.50	Average
6.	0.294	0.01	9.56	34.42	43.99	60.41	-16.42	QP
7.	0.352	0.01	9.56	20.80	30.37	48.91	-18.54	Average
8.	0.352	0.01	9.56	35.47	45.04	58.91	-13.87	QP
9.	0.406	0.01	9.57	19.99	29.57	47.73	-18.16	Average
10.	0.406	0.01	9.57	33.87	43.45	57.73	-14.28	QP
11.	0.527	0.01	9.57	24.72	34.30	46.00	-11.70	Average
12.	0.527	0.01	9.57	33.64	43.22	56.00	-12.78	QP

Notes: 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
 3.Measurement Level = Reading level + Correct Factor

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Freq MHz	Cable Loss dB	LISN Factor dB/m	Receiver Reading dBUV	Emission Level dBUV/m	Limit dBUV/m	Over Limit dB	Remark
1.	0.170	0.00	9.54	27.51	37.05	54.94	-17.89	Average
2.	0.170	0.00	9.54	45.14	54.68	64.94	-10.26	QP
3.	0.230	0.01	9.55	20.61	30.17	52.44	-22.27	Average
4.	0.230	0.01	9.55	41.12	50.68	62.44	-11.76	QP
5.	0.294	0.01	9.56	16.29	25.86	50.41	-24.55	Average
6.	0.294	0.01	9.56	34.82	44.39	60.41	-16.02	QP
7.	0.358	0.01	9.57	15.62	25.20	48.78	-23.58	Average
8.	0.358	0.01	9.57	31.24	40.82	58.78	-17.96	QP
9.	0.474	0.01	9.58	19.28	28.87	46.45	-17.58	Average
10.	0.474	0.01	9.58	29.87	39.46	56.45	-16.99	QP
11.	0.527	0.01	9.58	19.93	29.52	46.00	-16.48	Average
12.	0.527	0.01	9.58	26.42	36.01	56.00	-19.99	QP

Notes: 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
 3.Measurement Level = Reading level + Correct Factor

6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method : ANSI C63.10:2013
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log ^{(2400/F(kHz))} + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log ^{(24000/F(kHz))} + 40
1.705 ~ 30	30	30	100 * 30	20log ⁽³⁰⁾ + 40
30 ~ 88	100	3	100	20log ⁽¹⁰⁰⁾
88 ~ 216	150	3	150	20log ⁽¹⁵⁰⁾
216 ~ 960	200	3	200	20log ⁽²⁰⁰⁾
Above 960	500	3	500	20log ⁽⁵⁰⁰⁾

6.1 EUT Operation


Operating Environment :

Temperature: : 24.5°C
 Humidity: : 52 % RH
 Atmospheric Pressure: : 101.11kPa
 Test Voltage : AC 120V 60Hz


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz

6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room

6.5 Summary of Test Results**Test Frequency: 9KHz-30MHz**

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);
Limit line = Specific limits (dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBμV	Emission Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
1	48.163	0.42	12.67	14.25	27.34	40.00	-12.66	QP
2	81.783	0.61	9.74	15.29	25.64	40.00	-14.36	QP
3	205.675	1.08	11.60	17.84	30.52	43.50	-12.98	QP
4	225.308	1.12	12.25	21.21	34.58	46.00	-11.42	QP
5	278.067	1.24	13.76	23.99	38.99	46.00	-7.01	QP
6	319.937	1.31	14.64	26.42	42.37	46.00	-3.63	QP

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dB μ V	Emission Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
1	31.843	0.26	10.20	19.10	29.56	40.00	-10.44	QP
2	36.001	0.31	11.44	20.00	31.75	40.00	-8.25	QP
3	160.346	0.94	8.82	19.36	29.12	43.50	-14.38	QP
4	269.428	1.22	13.53	21.31	36.06	46.00	-9.94	QP
5	321.061	1.31	14.65	26.06	42.02	46.00	-3.98	QP
6	338.400	1.34	14.93	20.15	36.42	46.00	-9.58	QP

Test Frequency: From 1GHz to 18GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Low Channel:2412MHz									
V	4824.00	50.50	30.55	5.77	24.66	50.38	74.00	-23.62	PK
V	4824.00	39.85	30.55	5.77	24.66	39.73	54.00	-14.27	AV
V	7236.00	48.19	30.33	6.32	24.55	48.73	74.00	-25.27	PK
V	7236.00	41.43	30.33	6.32	24.55	41.97	54.00	-12.03	AV
V	9648.00	48.72	30.85	7.45	24.69	50.01	74.00	-23.99	PK
V	9648.00	40.71	30.85	7.45	24.69	42.00	54.00	-12.00	AV
V	12060.00	48.12	31.02	8.99	25.57	51.66	74.00	-22.34	PK
V	12060.00	38.47	31.02	8.99	25.57	42.01	54.00	-11.99	AV
H	4824.00	51.68	30.55	5.77	24.66	51.56	74.00	-22.44	PK
H	4824.00	40.59	30.55	5.77	24.66	40.47	54.00	-13.53	AV
H	7236.00	49.47	30.33	6.32	24.55	50.01	74.00	-23.99	PK
H	7236.00	41.33	30.33	6.32	24.55	41.87	54.00	-12.13	AV
H	9648.00	49.76	30.85	7.45	24.69	51.05	74.00	-22.95	PK
H	9648.00	40.29	30.85	7.45	24.69	41.58	54.00	-12.42	AV
H	12060.00	50.18	31.02	8.99	25.57	53.72	74.00	-20.28	PK
H	12060.00	39.67	31.02	8.99	25.57	43.21	54.00	-10.79	AV

Radiated Band Emission Measurement:

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Middle Channel:2437MHz									
V	4874.00	48.65	30.55	5.77	24.66	48.53	74.00	-25.47	PK
V	4874.00	39.13	30.55	5.77	24.66	39.01	54.00	-14.99	AV
V	7311.00	47.54	30.33	6.32	24.55	48.08	74.00	-25.92	PK
V	7311.00	40.12	30.33	6.32	24.55	40.66	54.00	-13.34	AV
V	9748.00	46.82	30.85	7.45	24.69	48.11	74.00	-25.89	PK
V	9748.00	38.79	30.85	7.45	24.69	40.08	54.00	-13.92	AV
V	12185.00	47.39	31.02	8.99	25.57	50.93	74.00	-23.07	PK
V	12185.00	38.33	31.02	8.99	25.57	41.87	54.00	-12.13	AV
H	4874.00	49.31	30.55	5.77	24.66	49.19	74.00	-24.81	PK
H	4874.00	40.45	30.55	5.77	24.66	40.33	54.00	-13.67	AV
H	7311.00	48.76	30.33	6.32	24.55	49.30	74.00	-24.70	PK
H	7311.00	39.24	30.33	6.32	24.55	39.78	54.00	-14.22	AV
H	9748.00	49.42	30.85	7.45	24.69	50.71	74.00	-23.29	PK
H	9748.00	39.79	30.85	7.45	24.69	41.08	54.00	-12.92	AV
H	12185.00	49.26	31.02	8.99	25.57	52.80	74.00	-21.20	PK
H	12185.00	37.83	31.02	8.99	25.57	41.37	54.00	-12.63	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2462MHz									
V	4924.00	49.50	30.55	5.77	24.66	49.38	74.00	-24.62	PK
V	4924.00	38.79	30.55	5.77	24.66	38.67	54.00	-15.33	AV
V	7386.00	46.30	30.33	6.32	24.55	46.84	74.00	-27.16	PK
V	7386.00	40.82	30.33	6.32	24.55	41.36	54.00	-12.64	AV
V	9848.00	47.50	30.85	7.45	24.69	48.79	74.00	-25.21	PK
V	9848.00	39.91	30.85	7.45	24.69	41.20	54.00	-12.80	AV
V	12310.00	46.32	31.02	8.99	25.57	49.86	74.00	-24.14	PK
V	12310.00	38.05	31.02	8.99	25.57	41.59	54.00	-12.41	AV
H	4924.00	50.26	30.55	5.77	24.66	50.14	74.00	-23.86	PK
H	4924.00	40.62	30.55	5.77	24.66	40.50	54.00	-13.50	AV
H	7386.00	48.14	30.33	6.32	24.55	48.68	74.00	-25.32	PK
H	7386.00	40.00	30.33	6.32	24.55	40.54	54.00	-13.46	AV
H	9848.00	48.54	30.85	7.45	24.69	49.83	74.00	-24.17	PK
H	9848.00	40.69	30.85	7.45	24.69	41.98	54.00	-12.02	AV
H	12310.00	48.94	31.02	8.99	25.57	52.48	74.00	-21.52	PK
H	12310.00	37.46	31.02	8.99	25.57	41.00	54.00	-13.00	AV

Note:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. We test all the mode and recorded the worst mode in the report.

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	53.38	30.22	4.85	23.98	51.99	74.00	PK	PASS
	H	2390.00	46.18	30.22	4.85	23.98	44.79	54.00	AV	PASS
	H	2400.00	55.32	30.22	4.85	23.98	53.93	74.00	PK	PASS
	H	2400.00	47.46	30.22	4.85	23.98	46.07	54.00	AV	PASS
	V	2390.00	54.51	30.22	4.85	23.98	53.12	74.00	PK	PASS
	V	2390.00	46.70	30.22	4.85	23.98	45.31	54.00	AV	PASS
	V	2400.00	55.35	30.22	4.85	23.98	53.96	74.00	PK	PASS
	V	2400.00	48.13	30.22	4.85	23.98	46.74	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	56.11	30.22	4.85	23.98	54.72	74.00	PK	PASS
	H	2483.50	45.16	30.22	4.85	23.98	43.77	54.00	AV	PASS
	H	2500.00	56.70	30.22	4.85	23.98	55.31	74.00	PK	PASS
	H	2500.00	48.80	30.22	4.85	23.98	47.41	54.00	AV	PASS
	V	2483.50	57.77	30.22	4.85	23.98	56.38	74.00	PK	PASS
	V	2483.50	46.16	30.22	4.85	23.98	44.77	54.00	AV	PASS
	V	2500.00	56.69	30.22	4.85	23.98	55.30	74.00	PK	PASS
	V	2500.00	45.94	30.22	4.85	23.98	44.55	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	55.49	30.22	4.85	23.98	54.10	74.00	PK	PASS
	H	2390.00	47.79	30.22	4.85	23.98	46.40	54.00	AV	PASS
	H	2400.00	57.19	30.22	4.85	23.98	55.80	74.00	PK	PASS

	H	2400.00	44.62	30.22	4.85	23.98	43.23	54.00	AV	PASS	
	V	2390.00	56.65	30.22	4.85	23.98	55.26	74.00	PK	PASS	
	V	2390.00	47.13	30.22	4.85	23.98	45.74	54.00	AV	PASS	
	V	2400.00	55.51	30.22	4.85	23.98	54.12	74.00	PK	PASS	
	V	2400.00	45.92	30.22	4.85	23.98	44.53	54.00	AV	PASS	
	High Channel 2462MHz										
	H	2483.50	51.92	30.22	4.85	23.98	50.53	74.00	PK	PASS	
	H	2483.50	43.58	30.22	4.85	23.98	42.19	54.00	AV	PASS	
	H	2500.00	57.42	30.22	4.85	23.98	56.03	74.00	PK	PASS	
	H	2500.00	44.09	30.22	4.85	23.98	42.70	54.00	AV	PASS	
	V	2483.50	54.35	30.22	4.85	23.98	52.96	74.00	PK	PASS	
	V	2483.50	47.61	30.22	4.85	23.98	46.22	54.00	AV	PASS	
	V	2500.00	52.89	30.22	4.85	23.98	51.50	74.00	PK	PASS	
	V	2500.00	46.48	30.22	4.85	23.98	45.09	54.00	AV	PASS	
802.11 n20	Low Channel 2412MHz										
	H	2390.00	54.19	30.22	4.85	23.98	52.80	74.00	PK	PASS	
	H	2390.00	47.11	30.22	4.85	23.98	45.72	54.00	AV	PASS	
	H	2400.00	57.28	30.22	4.85	23.98	55.89	74.00	PK	PASS	
	H	2400.00	44.81	30.22	4.85	23.98	43.42	54.00	AV	PASS	
	V	2390.00	55.16	30.22	4.85	23.98	53.77	74.00	PK	PASS	
	V	2390.00	48.46	30.22	4.85	23.98	47.07	54.00	AV	PASS	
	V	2400.00	58.54	30.22	4.85	23.98	57.15	74.00	PK	PASS	
	V	2400.00	48.16	30.22	4.85	23.98	46.77	54.00	AV	PASS	
		High Channel 2462MHz									
		H	2483.50	54.50	30.22	4.85	23.98	53.11	74.00	PK	PASS
		H	2483.50	46.91	30.22	4.85	23.98	45.52	54.00	AV	PASS

	H	2500.00	57.72	30.22	4.85	23.98	56.33	74.00	PK	PASS
	H	2500.00	44.72	30.22	4.85	23.98	43.33	54.00	AV	PASS
	V	2483.50	55.18	30.22	4.85	23.98	53.79	74.00	PK	PASS
	V	2483.50	48.63	30.22	4.85	23.98	47.24	54.00	AV	PASS
	V	2500.00	58.66	30.22	4.85	23.98	57.27	74.00	PK	PASS
	V	2500.00	47.65	30.22	4.85	23.98	46.26	54.00	AV	PASS
802.11 n40	Low Channel 2422MHz									
	H	2390.00	54.56	30.22	4.85	23.98	53.17	74.00	PK	PASS
	H	2390.00	47.06	30.22	4.85	23.98	45.67	54.00	AV	PASS
	H	2400.00	57.05	30.22	4.85	23.98	55.66	74.00	PK	PASS
	H	2400.00	45.26	30.22	4.85	23.98	43.87	54.00	AV	PASS
	V	2390.00	54.90	30.22	4.85	23.98	53.51	74.00	PK	PASS
	V	2390.00	48.81	30.22	4.85	23.98	47.42	54.00	AV	PASS
	V	2400.00	58.93	30.22	4.85	23.98	57.54	74.00	PK	PASS
	V	2400.00	48.20	30.22	4.85	23.98	46.81	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	54.22	30.22	4.85	23.98	52.83	74.00	PK	PASS
	H	2483.50	47.14	30.22	4.85	23.98	45.75	54.00	AV	PASS
	H	2500.00	57.57	30.22	4.85	23.98	56.18	74.00	PK	PASS
	H	2500.00	44.80	30.22	4.85	23.98	43.41	54.00	AV	PASS
	V	2483.50	55.03	30.22	4.85	23.98	53.64	74.00	PK	PASS
	V	2483.50	48.75	30.22	4.85	23.98	47.36	54.00	AV	PASS
	V	2500.00	58.65	30.22	4.85	23.98	57.26	74.00	PK	PASS
	V	2500.00	48.35	30.22	4.85	23.98	46.96	52.36	AV	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

7 Conducted Spurious Emission



Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Result



802.11 b
Low Channel





Middle Channel





High Channel





802.11g
Low Channel





Middle Channel




High Channel





802.11n-HT20
Low Channel




Middle Channel





High Channel





802.11n-HT40
Low Channel



Middle Channel



High Channel



8 Band Edge Measurement


Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

8.2 Test Result

802.11b



802.11g

