

Test Report

Report No.: MTi230805003-01E3

Date of issue: 2023-08-19

Applicant: Beijing Cozyla Technology Ltd.

Product: Cozyla Frame

Model(s): Cozyla CD-3X341F

FCC ID: 2BCES-CD3X341F

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.



Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Environmental Conditions	7
1.4	Description of support units	7
1.5	Measurement uncertainty	7
2	Summary of Test Result	8
3	Test Facilities and accreditations	9
3.1	Test laboratory	9
4	List of test equipment.....	10
5	Evaluation Results (Evaluation).....	11
5.1	Antenna requirement	11
6	Radio Spectrum Matter Test Results (RF)	11
6.1	Conducted Emission at AC power line	11
6.2	Occupied Bandwidth	16
6.3	Maximum Conducted Output Power.....	17
6.4	Power Spectral Density	18
6.5	Unwanted emission(Conducted)	19
6.6	Band edge emissions (Radiated)	20
6.7	Radiated emissions (below 1GHz)	29
6.8	Radiated emissions (above 1GHz).....	33
	Photographs of the test setup	37
	Photographs of the EUT.....	38
	Appendix A: DTS Bandwidth	40
	Appendix B: Maximum conducted output power.....	45
	Appendix C: Maximum power spectral density.....	46
	Appendix D: Band edge measurements	51
	Appendix E: Conducted Spurious Emission	54
	Appendix F: Duty Cycle	66

Test Result Certification	
Applicant:	Beijing Cozyla Technology Ltd.
Address:	Room A419 Building1, No. 12 Shangdi Information Road, Haidian District, Beijing PRC 100080
Manufacturer:	Beijing Cozyla Technology Ltd.
Address:	Room A419 Building1, No. 12 Shangdi Information Road, Haidian District, Beijing PRC 100080
Product description	
Product name:	Cozyla Frame
Trademark:	Cozyla
Model name:	Cozyla CD-3X341F
Series Model:	N/A
Standards:	47 CFR Part 15.247
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02
Date of Test	
Date of test:	2023-08-14 to 2023-08-19
Test result:	Pass

Test Engineer	:	<i>David. Lee</i>
		(David Lee)
Reviewed By	:	<i>Leon Chen</i>
		(Leon Chen)
Approved By	:	<i>Tom Xue</i>
		(Tom Xue)

1 General Description

1.1 Description of the EUT

Product name:	Cozyla Frame
Model name:	Cozyla CD-3X341F
Series Model:	N/A
Model difference:	N/A
Electrical rating:	Input: DC5V 2A
Accessories:	AC/DC ADAPTER MODEL: KA12C-0502000USS INPUT: 100-240V~ 50/60Hz 0.35A Max OUTPUT: DC5V 2A Adapter manufacturer: SHENZHEN KEYU POWER SUPPLY TECHNOLOGY CO., LTD.
Hardware version:	JHA33-U-C-DDR3*4 V1.0
Software version:	08170923
Test sample(s) number:	MTi230805003-01S1001
RF specification	
Operating frequency range:	802.11b/g/n20:2412~2462 MHz 802.11n40:2422~2452 MHz
Modulation type:	IEEE 802.11b : DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna(s) type:	FPC ANT
Antenna(s) gain:	2.93dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX-802.11b
Mode2	TX-802.11g
Mode3	TX-802.11N(HT20)
Mode4	TX-802.11N(HT40)

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software:

For power setting, refer to below table.

Software:		CMD	
Mode	2412MHz	2437MHz	2462MHz
802.11b	DEF	DEF	DEF
802.11g	DEF	DEF	DEF
802.11n(HT20)	DEF	DEF	DEF
Mode	2422MHz	2437MHz	2452MHz
802.11n(HT40)	DEF	DEF	DEF

Note: The EUT is connected to the computer via USB, the computer use CMD and enters the command to adjust the EUT operating frequency and power setting.

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
/	/	/	/
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.1dB
Occupied channel bandwidth	±3 %
RF output power, conducted	±1 dB
Power Spectral Density, conducted	±1 dB
Unwanted Emissions, conducted	±1 dB
Radiated spurious emissions (1GHz~26GHz)	5.3dB
Radiated spurious emissions (9kHz~30MHz)	4.3dB
Radiated spurious emissions (30MHz~1GHz)	4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
3	Occupied Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
4	Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
5	Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
6	Unwanted emission(Conducted)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
7	Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
8	Radiated emissions (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
9	Radiated emissions (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2023-04-26	2024-04-25
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2023-05-05	2024-05-04
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2023-06-03	2024-06-02
Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2023-04-26	2024-04-25
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2023-04-25	2024-04-24
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2023-04-25	2024-04-24
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2023-04-25	2024-04-24
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2023-04-26	2024-04-25
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2023-04-26	2024-04-25
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2023-05-05	2024-05-04
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2023-04-25	2024-04-24
9	DC Power Supply	Agilent	E3632A	MY40027695	2023-05-05	2024-05-04
Emissions in frequency bands (above 1GHz) Band edge emissions (Radiated)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2023-05-26	2024-05-25
3	Amplifier	Agilent	8449B	3008A01120	2023-06-26	2024-06-25
4	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
5	MXA signal analyzer	Agilent	N9020A	MY54440859	2023-05-05	2024-05-04
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Amplifier	Hewlett-Packard	8447F	3113A06184	2023-06-26	2024-06-25
4	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
5	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2023-06-11	2025-06-10

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Description of the antenna of EUT:	The antenna of the EUT is permanently attached.
Conclusion:	The EUT complies with the requirement of FCC PART 15.203.

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2013 section 6.2		
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	17.2 °C	Humidity:	59.2 %	Atmospheric Pressure:	98 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1				

6.1.2 Test Setup Diagram:




6.1.3 Test Data:

Mode1(AC120V/60Hz) / Line: Line




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1500	32.43	10.19	42.62	66.00	-23.38	QP	
2	0.1740	15.77	10.18	25.95	54.77	-28.82	AVG	
3 *	0.4860	34.10	10.24	44.34	56.24	-11.90	QP	
4	0.4900	23.10	10.24	33.34	46.17	-12.83	AVG	
5	0.9620	24.47	10.11	34.58	56.00	-21.42	QP	
6	1.0500	8.88	10.11	18.99	46.00	-27.01	AVG	
7	2.0020	20.15	10.31	30.46	56.00	-25.54	QP	
8	2.0260	6.43	10.31	16.74	46.00	-29.26	AVG	
9	3.9260	4.08	10.52	14.60	46.00	-31.40	AVG	
10	4.1220	18.95	10.54	29.49	56.00	-26.51	QP	
11	23.0660	24.92	10.65	35.57	60.00	-24.43	QP	
12	23.3620	8.68	10.66	19.34	50.00	-30.66	AVG	

Mode1(AC120V/60Hz) / Line: Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	31.41	10.14	41.55	65.79	-24.24	QP	
2		0.1539	17.49	10.14	27.63	55.79	-28.16	AVG	
3	*	0.4860	24.59	10.05	34.64	46.24	-11.60	AVG	
4		0.4900	31.66	10.05	41.71	56.17	-14.46	QP	
5		0.8900	16.89	10.09	26.98	46.00	-19.02	AVG	
6		1.0980	24.24	10.09	34.33	56.00	-21.67	QP	
7		1.8060	12.21	10.31	22.52	46.00	-23.48	AVG	
8		1.9980	21.07	10.36	31.43	56.00	-24.57	QP	
9		5.0180	8.50	10.59	19.09	50.00	-30.91	AVG	
10		5.7700	16.93	10.62	27.55	60.00	-32.45	QP	
11		23.3100	20.41	10.64	31.05	60.00	-28.95	QP	
12		23.3100	7.05	10.64	17.69	50.00	-32.31	AVG	

Mode1(AC240V/60Hz) / Line: Line



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.1500	30.45	10.19	40.64	66.00	-25.36	QP	
2		0.1660	14.49	10.18	24.67	55.16	-30.49	AVG	
3	*	0.4900	35.28	10.24	45.52	56.17	-10.65	QP	
4		0.4900	24.56	10.24	34.80	46.17	-11.37	AVG	
5		0.7460	15.09	10.15	25.24	46.00	-20.76	AVG	
6		0.7940	27.46	10.14	37.60	56.00	-18.40	QP	
7		1.0660	24.76	10.12	34.88	56.00	-21.12	QP	
8		1.1140	13.14	10.12	23.26	46.00	-22.74	AVG	
9		2.0620	23.12	10.31	33.43	56.00	-22.57	QP	
10		3.0140	10.72	10.41	21.13	46.00	-24.87	AVG	
11		22.4580	20.06	10.63	30.69	60.00	-29.31	QP	
12		23.1299	6.13	10.64	16.77	50.00	-33.23	AVG	

Mode1(AC240V/60Hz) / Line: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1660	18.11	10.12	28.23	55.16	-26.93	AVG	
2		0.1700	31.34	10.12	41.46	64.96	-23.50	QP	
3		0.4900	31.85	10.05	41.90	56.17	-14.27	QP	
4	*	0.4940	26.32	10.05	36.37	46.10	-9.73	AVG	
5		0.6300	20.05	10.10	30.15	46.00	-15.85	AVG	
6		0.8059	26.48	10.11	36.59	56.00	-19.41	QP	
7		1.1420	18.74	10.10	28.84	46.00	-17.16	AVG	
8		1.1900	25.38	10.12	35.50	56.00	-20.50	QP	
9		1.9660	24.32	10.35	34.67	56.00	-21.33	QP	
10		2.0140	18.84	10.37	29.21	46.00	-16.79	AVG	
11		3.9980	21.35	10.50	31.85	56.00	-24.15	QP	
12		3.9980	14.94	10.50	25.44	46.00	-20.56	AVG	


6.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C		Humidity:	58 %	
Atmospheric Pressure:			101 kPa		
Test mode:		Mode1, Mode2, Mode3, Mode4			

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.


6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.


6.5 Unwanted emission(Conducted)

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.


6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.		
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

6.6.1 E.U.T. Operation:

Operating Environment:						
Temperature:	26 °C		Humidity:	54 %	Atmospheric Pressure:	98 kPa
Test mode:		Mode1, Mode2, Mode3, Mode4				
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.						

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	46.63	-2.66	43.97	74.00	-30.03	peak
2		2310.000	36.85	-2.66	34.19	54.00	-19.81	AVG
3		2390.000	55.22	-2.03	53.19	74.00	-20.81	peak
4	*	2390.000	45.53	-2.03	43.50	54.00	-10.50	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	43.11	-2.66	40.45	74.00	-33.55	peak
2		2310.000	33.14	-2.66	30.48	54.00	-23.52	AVG
3		2390.000	53.96	-2.03	51.93	74.00	-22.07	peak
4	*	2390.000	37.61	-2.03	35.58	54.00	-18.42	AVG

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	51.82	-1.91	49.91	74.00	-24.09	peak
2	*	2483.500	42.94	-1.91	41.03	54.00	-12.97	AVG
3		2500.000	50.53	-1.80	48.73	74.00	-25.27	peak
4		2500.000	40.99	-1.80	39.19	54.00	-14.81	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	47.61	-1.91	45.70	74.00	-28.30	peak
2	*	2483.500	38.49	-1.91	36.58	54.00	-17.42	AVG
3		2500.000	47.81	-1.80	46.01	74.00	-27.99	peak
4		2500.000	37.82	-1.80	36.02	54.00	-17.98	AVG

Mode2 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	43.69	-2.66	41.03	74.00	-32.97	peak
2		2310.000	34.85	-2.66	32.19	54.00	-21.81	AVG
3		2390.000	55.03	-2.03	53.00	74.00	-21.00	peak
4	*	2390.000	43.83	-2.03	41.80	54.00	-12.20	AVG

Mode2 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	42.61	-2.66	39.95	74.00	-34.05	peak
2		2310.000	33.05	-2.66	30.39	54.00	-23.61	AVG
3		2390.000	55.26	-2.03	53.23	74.00	-20.77	peak
4	*	2390.000	36.85	-2.03	34.82	54.00	-19.18	AVG

Mode2 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	51.12	-1.91	49.21	74.00	-24.79	peak
2	*	2483.500	41.92	-1.91	40.01	54.00	-13.99	AVG
3		2500.000	49.60	-1.80	47.80	74.00	-26.20	peak
4		2500.000	40.33	-1.80	38.53	54.00	-15.47	AVG

Mode2 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	46.89	-1.91	44.98	74.00	-29.02	peak
2	*	2483.500	38.04	-1.91	36.13	54.00	-17.87	AVG
3		2500.000	48.14	-1.80	46.34	74.00	-27.66	peak
4		2500.000	37.88	-1.80	36.08	54.00	-17.92	AVG

Mode3 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	43.93	-2.66	41.27	74.00	-32.73	peak
2		2310.000	33.83	-2.66	31.17	54.00	-22.83	AVG
3	*	2390.000	63.56	-2.03	61.53	74.00	-12.47	peak
4		2390.000	43.16	-2.03	41.13	54.00	-12.87	AVG

Mode3 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	43.38	-2.66	40.72	74.00	-33.28	peak
2		2310.000	32.99	-2.66	30.33	54.00	-23.67	AVG
3		2390.000	53.85	-2.03	51.82	74.00	-22.18	peak
4	*	2390.000	37.38	-2.03	35.35	54.00	-18.65	AVG

Mode3 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	59.22	-1.91	57.31	74.00	-16.69	peak
2	*	2483.500	42.49	-1.91	40.58	54.00	-13.42	AVG
3		2500.000	48.70	-1.80	46.90	74.00	-27.10	peak
4		2500.000	38.89	-1.80	37.09	54.00	-16.91	AVG

Mode3 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	47.07	-1.91	45.16	74.00	-28.84	peak
2	*	2483.500	37.94	-1.91	36.03	54.00	-17.97	AVG
3		2500.000	46.89	-1.80	45.09	74.00	-28.91	peak
4		2500.000	37.59	-1.80	35.79	54.00	-18.21	AVG

Mode4 / Polarization: Horizontal / Band: 2.4G / BW: 40 / CH: 03

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	42.95	-2.66	40.29	74.00	-33.71	peak
2		2310.000	33.70	-2.66	31.04	54.00	-22.96	AVG
3		2390.000	59.86	-2.03	57.83	74.00	-16.17	peak
4	*	2390.000	46.85	-2.03	44.82	54.00	-9.18	AVG

Mode4 / Polarization: Vertical / Band: 2.4G / BW: 40 / CH: 03

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	42.19	-2.66	39.53	74.00	-34.47	peak
2		2310.000	32.91	-2.66	30.25	54.00	-23.75	AVG
3		2390.000	53.68	-2.03	51.65	74.00	-22.35	peak
4	*	2390.000	37.88	-2.03	35.85	54.00	-18.15	AVG

Mode4 / Polarization: Horizontal / Band: 2.4G / BW: 40 / CH: 09

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	58.84	-1.91	56.93	74.00	-17.07	peak
2	*	2483.500	45.21	-1.91	43.30	54.00	-10.70	AVG
3		2500.000	49.25	-1.80	47.45	74.00	-26.55	peak
4		2500.000	39.41	-1.80	37.61	54.00	-16.39	AVG

Mode4 / Polarization: Vertical / Band: 2.4G / BW: 40 / CH: 09

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	49.08	-1.91	47.17	74.00	-26.83	peak
2	*	2483.500	38.56	-1.91	36.65	54.00	-17.35	AVG
3		2500.000	47.80	-1.80	46.00	74.00	-28.00	peak
4		2500.000	38.03	-1.80	36.23	54.00	-17.77	AVG


6.7 Radiated emissions (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	26 °C	Humidity:	54 %	Atmospheric Pressure:	98 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1				
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.					


6.7.2 Test Setup Diagram:






6.7.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		51.8430	29.99	-7.44	22.55	40.00	-17.45	QP	
2		106.3850	38.02	-7.06	30.96	43.50	-12.54	QP	
3		150.0108	42.44	-10.99	31.45	43.50	-12.05	QP	
4	*	230.9068	43.93	-7.29	36.64	46.00	-9.36	QP	
5		374.6225	35.92	-4.60	31.32	46.00	-14.68	QP	
6		478.8456	33.65	-3.87	29.78	46.00	-16.22	QP	

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		35.4993	39.94	-9.93	30.01	40.00	-9.99	QP	
2	*	52.0251	38.69	-7.49	31.20	40.00	-8.80	QP	
3		105.6415	37.69	-7.18	30.51	43.50	-12.99	QP	
4		159.2251	43.17	-10.60	32.57	43.50	-10.93	QP	
5		377.2591	31.24	-4.67	26.57	46.00	-19.43	QP	
6		550.9480	31.83	-2.53	29.30	46.00	-16.70	QP	


6.8 Radiated emissions (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	26 °C	Humidity:	54 %	Atmospheric Pressure:	98 kPa
Test mode:	Mode1, Mode2, Mode3, mode4				
Final test mode:	Mode1				
Note: Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported.					

6.8.2 Test Setup Diagram:



6.8.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	40.09	2.81	42.90	74.00	-31.10	peak
2		4824.000	33.60	2.81	36.41	54.00	-17.59	AVG
3		7236.000	41.43	9.10	50.53	74.00	-23.47	peak
4		7236.000	35.28	9.10	44.38	54.00	-9.62	AVG
5		9648.000	41.51	10.98	52.49	74.00	-21.51	peak
6	*	9648.000	35.33	10.98	46.31	54.00	-7.69	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 01

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	40.30	2.81	43.11	74.00	-30.89	peak
2		4824.000	33.27	2.81	36.08	54.00	-17.92	AVG
3		7236.000	44.22	9.10	53.32	74.00	-20.68	peak
4	*	7236.000	38.57	9.10	47.67	54.00	-6.33	AVG
5		9648.000	41.39	10.98	52.37	74.00	-21.63	peak
6		9648.000	35.76	10.98	46.74	54.00	-7.26	AVG

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 06

No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	4874.000	41.06	3.02	44.08	74.00	-29.92	peak
2	4874.000	35.39	3.02	38.41	54.00	-15.59	AVG
3	7311.000	43.25	8.97	52.22	74.00	-21.78	peak
4 *	7311.000	37.85	8.97	46.82	54.00	-7.18	AVG
5	9748.000	40.96	11.95	52.91	74.00	-21.09	peak
6	9748.000	34.42	11.95	46.37	54.00	-7.63	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 06

No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	4874.000	41.53	3.02	44.55	74.00	-29.45	peak
2	4874.000	35.23	3.02	38.25	54.00	-15.75	AVG
3	7311.000	47.66	8.97	56.63	74.00	-17.37	peak
4 *	7311.000	43.69	8.97	52.66	54.00	-1.34	AVG
5	9748.000	40.76	11.95	52.71	74.00	-21.29	peak
6	9748.000	34.34	11.95	46.29	54.00	-7.71	AVG

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	41.07	3.27	44.34	74.00	-29.66	peak
2		4924.000	34.95	3.27	38.22	54.00	-15.78	AVG
3		7386.000	43.07	9.16	52.23	74.00	-21.77	peak
4		7386.000	37.07	9.16	46.23	54.00	-7.77	AVG
5		9848.000	41.35	11.50	52.85	74.00	-21.15	peak
6	*	9848.000	35.24	11.50	46.74	54.00	-7.26	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	40.56	3.27	43.83	74.00	-30.17	peak
2		4924.000	33.14	3.27	36.41	54.00	-17.59	AVG
3		7386.000	48.32	9.16	57.48	74.00	-16.52	peak
4	*	7386.000	43.86	9.16	53.02	54.00	-0.98	AVG
5		9848.000	39.86	11.50	51.36	74.00	-22.64	peak
6		9848.000	33.73	11.50	45.23	54.00	-8.77	AVG

Photographs of the test setup

Refer to Appendix - Test Setup Photos.

Photographs of the EUT

Refer to Appendix - EUT Photos

Appendix

Appendix A: DTS Bandwidth


Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	10.000	0.5	PASS
		2437	8.600	0.5	PASS
		2462	9.600	0.5	PASS
11G	Ant1	2412	16.440	0.5	PASS
		2437	16.280	0.5	PASS
		2462	16.360	0.5	PASS
11N20SISO	Ant1	2412	17.520	0.5	PASS
		2437	17.560	0.5	PASS
		2462	17.560	0.5	PASS
11N40SISO	Ant1	2422	35.280	0.5	PASS
		2437	35.120	0.5	PASS
		2452	34.960	0.5	PASS


Test Graphs



11G Ant1 2412




11G Ant1 2437




11G Ant1 2462



11N20SISO Ant1 2412




11N20SISO Ant1 2437




11N20SISO Ant1 2462




11N40SISO Ant1 2422



11N40SISO Ant1 2437



11N40SISO Ant1 2452



Appendix B: Maximum conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Peak Power [dBm]	Conducted Limit [dBm]	Verdict
11B	Ant1	2412	17.57	≤30.00	PASS
		2437	17.79	≤30.00	PASS
		2462	17.66	≤30.00	PASS
11G	Ant1	2412	15.75	≤30.00	PASS
		2437	16.21	≤30.00	PASS
		2462	15.95	≤30.00	PASS
11N20SISO	Ant1	2412	14.70	≤30.00	PASS
		2437	15.14	≤30.00	PASS
		2462	14.71	≤30.00	PASS
11N40SISO	Ant1	2422	14.78	≤30.00	PASS
		2437	15.25	≤30.00	PASS
		2452	15.07	≤30.00	PASS

Appendix C: Maximum power spectral density


Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-7.69	≤8.00	PASS
		2437	-7.39	≤8.00	PASS
		2462	-7.99	≤8.00	PASS
11G	Ant1	2412	-16.68	≤8.00	PASS
		2437	-16.13	≤8.00	PASS
		2462	-16.64	≤8.00	PASS
11N20SISO	Ant1	2412	-17.41	≤8.00	PASS
		2437	-17.33	≤8.00	PASS
		2462	-16.93	≤8.00	PASS
11N40SISO	Ant1	2422	-20.64	≤8.00	PASS
		2437	-20.72	≤8.00	PASS
		2452	-19.89	≤8.00	PASS


Test Graphs




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452

