

RF TEST REPORT

FCC ID: 2BCFY-HT580

Test Report No.....: RF240130006-01-002
 Product(s) Name.....: XGSPON Gateway
 Model(s).....: HT-580AXT, HT-580AET
 Trade Mark.....: HEIGHTS
 Applicant.....: Heights Telecom T LTD
 Address.....: Ha-Sakhlav 6, Irus, 7680900, Israel
 Receipt Date.....: 2024.02.01
 Test Date.....: 2024.02.02~2024.03.21
 Issued Date.....: 2024.03.22
 Standards.....: 47 CFR FCC Part 15, Subpart E(Section 15.407);
 ANSI C63.10:2013
 Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.


Prepared By:	Checked By:	Approved By:	
Black Ding	Tim Zhang	Misue Su	
<i>Black Ding</i>	<i>Tim.zhang</i>	<i>Misue Su</i>	

Table of Contents

History of this test report.....	4
1. General Information	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Basic Description of Equipment Under Test.....	5
1.4 Transmit Operating Mode.....	6
2. Summary of Test Results	7
2.1 Summary of Test Items	7
2.2 Application of Standard	7
2.3 Test Instruments.....	8
2.4 Operation Mode.....	9
2.5 Test Condition	9
2.6 Duty Cycle of Test Signal	10
2.7 Measurement Uncertainty	17
2.8 Test Location	17
2.9 SUPPORT UNITS	17
3. Test Procedure And Results	18
3.1 AC Power Line Conducted Emission.....	18
3.1.1 Limit	18
3.1.2 Test Procedure	18
3.1.3 Test Setup.....	18
3.1.4 Test Result.....	19
3.2 Radiated Emission.....	23
3.2.1 Limit	23
3.2.2 Test Procedure	24
3.2.3 Test Setup.....	25
3.2.4 Test Result.....	26
3.3 Spectrum Bandwidth	165
3.3.1 Limit	165
3.3.2 Test Procedure	165

3.3.3	Test Setup.....	166
3.3.4	Test Result.....	167
3.4	Conducted Output Power	583
3.4.1	Limit	583
3.4.2	Test Procedure	583
3.4.3	Test Setup.....	583
3.4.4	Table of Parameters of Text Software Setting	584
3.4.5	The Result.....	588
3.5	Power Spectral Density	621
3.5.1	Limit	621
3.5.2	Test Procedure	621
3.5.3	Test Setup.....	622
3.5.4	The Result.....	623

History of this test report

Original Report Issue Date: 2024.03.22

- No additional attachment
- Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. General Information

1.1 Applicant

Heights Telecom T LTD

Ha-Sakhlav 6, Irus, 7680900, Israel

1.2 Manufacturer

Heights Telecom T LTD

Ha-Sakhlav 6, Irus, 7680900, Israel

1.3 Basic Description of Equipment Under Test

Product No.	POC240130006-S001, POC240130006-S002	
Equipment Name	XGSPON Gateway	
Model Name	HT-580AXT, HT-580AET	
Model differences	Only WAN port and optical fiber port part of the circuit is different	
Trade Mark	HEIGHTS	
Power Supply	DC 12V from adapter	
Adapter Information	Model: SOY-1200350US-056 Input: 100-240V~ 50/60Hz 1.2A Max Output: 12V=== 3.5A	
Operating Temperature	0°C-45°C	
EUT Stage	○ Product Unit	● Final-Sample
Operating Band & Max Conducted Output Power	5150MHz ~5250MHz	802.11ax40: 28.86dBm(0.769W)
	5250MHz ~5350MHz	802.11ac40: 22.83dBm(0.192W)
	5470MHz ~5725MHz	802.11ax80: 23.84dBm(0.242W)
	5725MHz ~5850MHz	802.11ax40: 29.00dBm(0.794W)
Product Type	IEEE 802.11a/n/ac/ax: WLAN (MIMO)	
Nominal Bandwidth	20MHz / 40MHz / 80MHz / 160MHz	
Modulation	OFDM, OFDMA	
Antenna gain	Ant1: 4.30dBi, Ant2: 4.10dBi, Ant3: 4.10dBi, Ant4: 4.30dBi	
Directional gain	2.11dBi(from the antenna report)	
Antenna type	PCB Antenna	
Data Rate (Mbps)	IEEE 11a mode : 6/9/12/18/24/36/48/54 IEEE 11n mode : up to 600 IEEE 11ac mode : up to 3464 IEEE 11ax mode : up to 4803.9	
Type of Device	Master device (Indoor AP for 5150MHz~5250MHz)	
DFS Function (Master devices)	●	5250MHz ~5350MHz
	●	5470MHz ~5725MHz

Channel Information			
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
5150-5250	802.11a /n /ac /ax (20MHz)	5180-5240	36-48
5250-5350		5260-5320	52-64
5470-5725		5500-5700	100-140
5725-5850		5745-5825	149-165
5150-5250	802.11n /ac /ax (40MHz)	5190-5230	38-46
5250-5350		5270-5310	54-62
5470-5725		5510-5670	102-134
5725-5850		5755-5795	151-159
5150-5250	802.11ac /ax (80MHz)	5210	42
5250-5350		5290	58
5470-5725		5530-5610	106-122
5725-5850		5775	155
5150-5350	802.11 ac /ax (160MHz)	5250	50
5470-5725		5570	114

Note: For 802.11ax mode only support full RU mode.

1.4 Transmit Operating Mode

Transmit Operating Mode				Transmit Multiple Antennas			
<input type="radio"/>	Operating mode 1 (single antenna)			<input type="radio"/>	1TX		
<input type="radio"/>	Operating mode 2 (multiple antenna, no beam forming)			<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	Operating mode 3 (multiple antenna, with beam forming)			<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	802.11a	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11n(20MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11n(40MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ac(20MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ac(40MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ac(80MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ac(160MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ax(20MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ax(40MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ax(80MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/>	802.11ax(160MHz)	Operating mode	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>

Beamforming gain: 1.5dB

2. Summary of Test Results

2.1 Summary of Test Items

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Test item	Standard	Results	Remarks
AC Power Conducted Emission	15.207 15.407(b)	Pass	Meet the requirement of the limit
Radiated Emission	15.205(a) 15.209(a) 15.407(b)	Pass	Meet the requirement of the limit
Antenna Requirements	15.203	Compliance	Note
Spectrum Bandwidth	15.407(a) 15.407(e)	Pass	Meet the requirement of the limit
Conducted Output Power	15.407(a)	Pass	Meet the requirement of the limit
Power Spectral Density	15.407(a)	Pass	Meet the requirement of the limit
Dynamic Frequency Selection (DFS)	15.407(h)	Pass	See the report RF240130006-01-003 for details
Note: The EUT has 4 PCB antennas arrangement which was permanently attached.			

2.2 Application of Standard

47 CFR FCC Part 15, Subpart E

KDB 662911 D01 Multiple Transmitter Output v02r01

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

ANSI C63.10:2013

2.3 Test Instruments

Radiated Emissions						
No.	Equipment	Manufacturer	Type No.	Serial No.	Cal. date (yyyy/mm/dd)	Cal. Due date (yyyy/mm/dd)
1	Test receiver	Rohde&Schwarz	ESU	100184	2023/5/3	2024/5/2
2	MXA Signal Analyzer	Keysight	N9010A	MY51440158	2023/4/22	2024/4/21
3	Log periodic antenna	Schwarzbeck	VULB 9168	1151	2023/5/4	2024/5/3
4	Low frequency amplifier	/	LNA 0920N	2014	2023/5/3	2024/5/2
5	High frequency amplifier	Schwarzbeck	BBV 9718	284	2023/5/3	2024/5/2
6	Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1273	2023/5/4	2024/5/3
7	Temp&Humidity Recorder	Meideshi	JR900	/	2023/5/3	2024/5/2
8	Horn Antenna	SCHWARZBECK	BBHA 9170	9170#685	2023/7/16	2024/7/15
9	Loop Antenna	SCHWARZBECK	FMZB1519 B	00029	2023/7/16	2024/7/15
10	Broadband preamplifier	Schwarzbeck	BBV9721	9721-019	2023/5/3	2024/5/2
13	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2			
Conducted Emission						
1	LISN	Rohde&Schwarz	ENV216	100075	2023/5/3	2024/5/2
2	ISN	Schwarzbeck	CATE 5 8158	#171	2023/5/3	2024/5/2
3	ISN	Schwarzbeck	CAT 3 8158	00187	2023/4/1	2024/3/31
4	Test receiver	Rohde&Schwarz	ESCI	100718	2023/5/3	2024/5/2
5	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	2023/5/3	2024/5/2
6	Temp&Humidity Recorder	Meideshi	JR900	/	2023/5/3	2024/5/2
7	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2			
RF Conducted Emission						
1	MXA Signal Analyzer	Keysight	N9021B	MY60080169	2023/4/23	2024/4/22
2	RF Control Unit	dsusoft	JS0806-2	21G8060449	2023/4/23	2024/4/22
3	power supply unit	dsusoft	JS0806-4ADC	N/A	2023/4/23	2024/4/22
4	VXG Signal Generator	Keysight	M9384B	MY61270787	2023/4/23	2024/4/22
5	EXG Analog Signal Generator	Keysight	N5173B	MY59101282	2023/4/23	2024/4/22
6	Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	1201.0002 K50-116064-Dt	2023/4/23	2024/4/22
7	Test software	dsusoft	JS1120-3 Ver.3.2.22.0			

2.4 Operation Mode

The EUT was supplied by and it was run in TX mode that was controlled by Master provided RF testing program. The worst case test result was showed in the report.

2.5 Test Condition

Test Item	Environmental conditions	Input Power	Tested by
AC Power Conducted Emission	23.7°C, 49% RH	AC 120V/60Hz	Albert Fan
Radiated Emission	23.3°C, 52% RH	AC 120V/60Hz	Albert Fan
Spectrum Bandwidth	23.5°C, 50% RH	DC 12V	Henry Huang
Conducted Power	23.5°C, 50% RH	DC 12V	Henry Huang
Power Spectral Density	23.5°C, 50% RH	DC 12V	Henry Huang

Note: Adapter supply voltage AC 120V/60Hz.

The applicant declare the operating environment of EUT as below:

Normal conditions: 12V DC, 0~45°C

2.6 Duty Cycle of Test Signal


If duty cycle is $\geq 98\%$, duty factor is not required.

If duty cycle is $< 98\%$, duty factor shall be considered.


All the duty factor of other test mode have been considered.

Test Mode	Freq(MHz)	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Limit	Verdict
11A-CDD	5180	0.12	0.23	52.17	---	---
11N20MIMO	5180	0.15	0.24	62.50	---	---
11N40MIMO	5190	0.12	0.22	54.55	---	---
11AC20MIMO	5180	0.15	0.18	83.33	---	---
11AC40MIMO	5190	0.13	0.15	86.67	---	---
11AC80MIMO	5210	0.12	0.15	80.00	---	---
11AC160MIMO	5250	0.12	0.14	85.71	---	---
11AX20MIMO	5180	0.33	0.35	94.29	---	---
11AX40MIMO	5190	0.31	0.34	91.18	---	---
11AX80MIMO	5210	0.30	0.33	90.91	---	---
11AX160MIMO	5250	0.45	0.49	91.84	---	---


Test Graphs




11N20MIMO_Ant1_5180




11N20MIMO_Ant2_5180




11N40MIMO_Ant1_5190




11AC20MIMO_Ant1_5180




11AC40MIMO_Ant1_5190




11AC80MIMO_Ant1_5210




11AC160MIMO_Ant1_5250




11AX20MIMO_Ant1_5180




11AX40MIMO_Ant1_5190



11AX80MIMO_Ant1_5210



11AX160MIMO_Ant1_5250



2.7 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 143.88\text{kHz}$
Power Spectral Density	$\pm 0.743\text{dB}$
Conducted Spurious Emission	$\pm 1.328\text{dB}$
RF power conducted	$\pm 0.384\text{dB}$
Conducted emission(9kHz~30MHz) AC main	$\pm 2.72\text{dB}$
Radiated emission(9kHz~30MHz)	$\pm 2.66\text{dB}$
Radiated emission (30MHz~1GHz)	$\pm 4.62\text{dB}$
Radiated emission (1GHz~18GHz)	$\pm 4.86\text{dB}$
Radiated emission (18GHz~40GHz)	$\pm 3.80\text{dB}$

2.8 Test Location

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier:	CN0145
A2LA Certificate Number:	6823.01
Telephone:	0755-26024411

2.9 SUPPORT UNITS

None

3. Test Procedure And Results

3.1 AC Power Line Conducted Emission

3.1.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.


2. The lower limit shall apply at the transition frequencies.

3.1.2 Test Procedure

Test Method	
<input checked="" type="radio"/> Conducted Measurement	<input type="radio"/> Radiated Measurement
Test Channels	
<input type="radio"/> Lowest, Middle and Highest Channel	<input type="radio"/> Lowest and Highest Channel
Environmental conditions	
<input checked="" type="radio"/> Normal	<input type="radio"/> Normal and Extreme
Note: <input checked="" type="radio"/> : Test <input type="radio"/> : No Test	

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

3.1.3 Test Setup



3.1.4 Test Result


Note:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Measurement = Reading + Correct Factor.
3. Over = Measurement – Limit
4. The TX AX40MIMO Mode Channel 151 is found to be the worst case and recorded.

HT-580AXT:

150kHz~30MHz	TX AX40MIMO Channel 151
--------------	-------------------------

Line




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1620	34.54	20.09	54.63	65.36	-10.73	QP	
2		0.1620	17.50	20.09	37.59	55.36	-17.77	AVG	
3		0.1940	29.06	20.02	49.08	63.86	-14.78	QP	
4		0.1940	13.46	20.02	33.48	53.86	-20.38	AVG	
5		0.2780	21.19	20.06	41.25	60.88	-19.63	QP	
6		0.2780	8.20	20.06	28.26	50.88	-22.62	AVG	
7		0.4500	18.32	20.29	38.61	56.88	-18.27	QP	
8		0.4500	9.73	20.29	30.02	46.88	-16.86	AVG	
9		0.8100	7.29	20.28	27.57	56.00	-28.43	QP	
10		0.8100	-0.60	20.28	19.68	46.00	-26.32	AVG	
11		1.8300	8.54	20.11	28.65	56.00	-27.35	QP	
12		1.8300	1.98	20.11	22.09	46.00	-23.91	AVG	

150kHz~30MHz

TX AX40MIMO Channel 151

Neutral

Conducted Emission Measurement




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	37.84	20.30	58.14	66.00	-7.86	QP	
2		0.1500	20.81	20.30	41.11	56.00	-14.89	AVG	
3		0.1945	29.37	20.33	49.70	63.84	-14.14	QP	
4		0.1945	12.50	20.33	32.83	53.84	-21.01	AVG	
5		0.2820	20.52	20.08	40.60	60.76	-20.16	QP	
6		0.2820	4.02	20.08	24.10	50.76	-26.66	AVG	
7		0.4140	17.25	20.21	37.46	57.57	-20.11	QP	
8		0.4140	5.68	20.21	25.89	47.57	-21.68	AVG	
9		0.4460	17.26	20.14	37.40	56.95	-19.55	QP	
10		0.4460	9.46	20.14	29.60	46.95	-17.35	AVG	
11		0.5540	14.24	20.15	34.39	56.00	-21.61	QP	
12		0.5540	4.12	20.15	24.27	46.00	-21.73	AVG	

HT-580AET:


150kHz~30MHz	TX AX40MIMO Channel 151
--------------	-------------------------

Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1580	35.14	20.07	55.21	65.57	-10.36	QP	
2		0.1580	18.16	20.07	38.23	55.57	-17.34	AVG	
3		0.2100	26.41	19.99	46.40	63.21	-16.81	QP	
4		0.2100	7.07	19.99	27.06	53.21	-26.15	AVG	
5		0.3340	16.32	20.04	36.36	59.35	-22.99	QP	
6		0.3340	1.73	20.04	21.77	49.35	-27.58	AVG	
7		0.3940	16.09	20.33	36.42	57.98	-21.56	QP	
8		0.3940	6.43	20.33	26.76	47.98	-21.22	AVG	
9		0.4820	11.54	20.23	31.77	56.30	-24.53	QP	
10		0.4820	-0.36	20.23	19.87	46.30	-26.43	AVG	
11		1.8180	9.37	20.11	29.48	56.00	-26.52	QP	
12		1.8180	1.93	20.11	22.04	46.00	-23.96	AVG	

Conducted Emission Measurement



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1620	34.96	20.26	55.22	65.36	-10.14	QP	
2		0.1620	20.42	20.26	40.68	55.36	-14.68	AVG	
3		0.2060	26.89	20.31	47.20	63.37	-16.17	QP	
4		0.2060	9.59	20.31	29.90	53.37	-23.47	AVG	
5		0.2780	20.98	20.08	41.06	60.88	-19.82	QP	
6		0.2780	8.16	20.08	28.24	50.88	-22.64	AVG	
7		0.3700	19.15	20.02	39.17	58.50	-19.33	QP	
8		0.3700	9.96	20.02	29.98	48.50	-18.52	AVG	
9		0.4460	17.41	20.14	37.55	56.95	-19.40	QP	
10		0.4460	7.00	20.14	27.14	46.95	-19.81	AVG	
11		1.8340	11.83	20.34	32.17	56.00	-23.83	QP	
12		1.8340	3.91	20.34	24.25	46.00	-21.75	AVG	

3.2 Radiated Emission

3.2.1 Limit

1) Limit of radiated emission measurement:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Distance Meters(m)	Field Strength Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 – 0.49	300	2400/F(kHz)	-
0.490 – 1.705	30	24000/F(kHz)	-
1.705 – 30	30	30	-
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

2) Limit of unwanted emission out of the restricted bands:

Frequency(MHz)	EIRP Limit(dBm/MHz)	Equivalent Field Strength at 3m($\text{dB}\mu\text{V}/\text{m}$)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 NOTE (2)	68.2
	10 NOTE (2)	105.2
	15.6 NOTE (2)	110.8
	27 NOTE (2)	122.2

Note: (1) The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength: $E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] + 95.2$, for $d=3\text{m}$

(2) According to 15.407(b)(4)(i), all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


3.2.2 Test Procedure

Test Method	
○Conducted Measurement	●Radiated Measurement
Test Channels	
●Lowest, Middle and Highest Channel	○ Lowest and Highest Channel
Environmental conditions	
●Normal	○Normal and Extreme
Note:●:Test ○:No Test	


- a) The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b) The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c) The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e) The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f) The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g) All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h) All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i) For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.2.3 Test Setup


(A) Radiated Emission Test Set-Up Frequency Below 30 MHz



(B) Radiated Emission Test Set-Up Frequency 30 MHz-1000 MHz



(C) Radiated Emission Test Set-Up Frequency Above 1 GHz



3.2.4 Test Result

1) Radiated emission: 9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

2) Radiated emission: 30MHz-1G

Note:


1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit
3. The TX AX40MIMO Mode Channel 151 is found to be the worst case and recorded.

HT-580AXT:


Below 1G (30MHz~1GHz)

TX AX40MIMO Channel 151

VERTICAL



HORIZONTAL




HT-580AET:


Below 1G (30MHz~1GHz)

TX AX40MIMO Channel 151

VERTICAL



HORIZONTAL




3) Radiated emission: Above 1G

Note:


1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit

Above 1G (1GHz~18GHz)	Test mode:11A-CDD	Test Channel:36
-----------------------	-------------------	-----------------

VERTICAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10360.000	57.61	7.05	64.66	68.20	-3.54	peak	



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4500.000	41.45	3.85	45.30	68.20	-22.90	peak	
2		5150.000	58.07	5.62	63.69	68.20	-4.51	peak	
3	*	5150.000	48.07	5.62	53.69	54.00	-0.31	AVG	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10360.000	55.47	7.05	62.52	68.20	-5.68	peak		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4500.000	40.89	3.85	44.74	68.20	-23.46	peak		
2		5150.000	53.25	5.62	58.87	68.20	-9.33	peak		
3	*	5150.000	42.95	5.62	48.57	54.00	-5.43	AVG		

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:40

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10400.000	57.77	6.55	64.32	68.20	-3.88	peak		

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10400.000	55.85	6.55	62.40	68.20	-5.80	peak		

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:48

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10480.000	58.38	6.47	64.85	68.20	-3.35	peak		

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10480.000	56.11	6.47	62.58	68.20	-5.62	peak		

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:52

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10520.000	58.07	6.30	64.37	68.20	-3.83	peak	

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10520.000	56.78	6.30	63.08	68.20	-5.12	peak	


Above 1G (1GHz~18GHz)

Test mode: 11A-CDD

Test Channel:56

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10560.000	58.16	5.98	64.14	68.20	-4.06	peak		

HORIZONTAL

Radiated Emission





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10560.000	56.25	5.98	62.23	68.20	-5.97	peak		

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:64

VERTICAL




HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		10640.000	56.12	6.47	62.59	74.00	-11.41			peak
2 *		10640.000	45.13	6.47	51.60	54.00	-2.40			AVG

Radiated Emission





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		5350.000	54.29	4.44	58.73	68.20	-9.47			peak
2 *		5350.000	41.81	4.44	46.25	54.00	-7.75			AVG
3		5460.000	40.52	4.51	45.03	68.20	-23.17			peak

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:100

VERTICAL




HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11000.000	58.93	3.44	62.37	74.00	-11.63	peak		
2 *		11000.000	47.83	3.44	51.27	54.00	-2.73	AVG		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	39.59	4.44	44.03	68.20	-24.17	peak		
2 *		5460.000	48.63	4.51	53.14	68.20	-15.06	peak		

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:116

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11160.000	15.78	48.77	64.55	74.00	-9.45	peak		
2	*	11160.000	4.60	48.77	53.37	54.00	-0.63	AVG		

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11160.000	13.20	48.77	61.97	74.00	-12.03	peak		
2	*	11160.000	2.62	48.77	51.39	54.00	-2.61	AVG		

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:140

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11400.000	15.70	49.06	64.76	74.00	-9.24	peak	
2	*	11400.000	3.98	49.06	53.04	54.00	-0.96	AVG	

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11400.000	13.16	49.06	62.22	74.00	-11.78	peak	
2	*	11400.000	2.02	49.06	51.08	54.00	-2.92	AVG	

Above 1G (1GHz~18GHz)


Test mode: 11A-CDD

Test Channel:149

VERTICAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11490.000	15.69	49.26	64.95	74.00	-9.05	peak	
2 *		11490.000	4.39	49.26	53.65	54.00	-0.35	AVG	



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1 *		5650.000	40.95	15.12	56.07	68.20	-12.13	peak	
2		5700.000	40.89	15.46	56.35	105.20	-48.85	peak	
3		5720.000	63.55	15.33	78.88	110.80	-31.92	peak	
4		5725.000	69.68	15.30	84.98	122.20	-37.22	peak	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11490.000	13.28	49.26	62.54	74.00	-11.46			peak
2 *		11490.000	1.84	49.26	51.10	54.00	-2.90			AVG

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1 *		5650.000	40.53	15.12	55.65	68.20	-12.55			peak
2		5700.000	40.07	15.46	55.53	105.20	-49.67			peak
3		5720.000	58.05	15.33	73.38	110.80	-37.42			peak
4		5725.000	63.98	15.30	79.28	122.20	-42.92			peak

Above 1G (1GHz~18GHz)

Test mode: 11A-CDD

Test Channel:157

VERTICAL



HORIZONTAL





Above 1G (1GHz~18GHz)

Test mode: 11A-CDD


Test Channel:165

VERTICAL




HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11650.000	14.15	48.62	62.77	74.00	-11.23			peak
2 *		11650.000	2.64	48.62	51.26	54.00	-2.74			AVG

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5850.000	55.13	15.18	70.31	122.20	-51.89			peak
2		5855.000	43.09	15.25	58.34	110.80	-52.46			peak
3		5875.000	39.92	15.51	55.43	105.20	-49.77			peak
4 *		5925.000	39.10	16.28	55.38	68.20	-12.82			peak


Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:36


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10360.000	57.48	7.05	64.53	68.20	-3.67	peak	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4500.000	40.96	3.85	44.81	68.20	-23.39	peak	
2		5150.000	53.43	5.62	59.05	68.20	-9.15	peak	
3	*	5150.000	47.69	5.62	53.31	54.00	-0.69	AVG	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10360.000	55.68	7.05	62.73	68.20	-5.47	peak	

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4500.000	41.30	3.85	45.15	68.20	-23.05	peak	
2	*	5150.000	46.97	5.62	52.59	68.20	-15.61	peak	

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:40

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10400.000	58.23	6.55	64.78	68.20	-3.42	peak	

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10400.000	55.82	6.55	62.37	68.20	-5.83	peak	

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:48

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10480.000	57.94	6.47	64.41	68.20	-3.79	peak	

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10480.000	55.83	6.47	62.30	68.20	-5.90	peak	

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:52

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10520.000	58.08	6.30	64.38	68.20	-3.82	peak		

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10520.000	56.51	6.30	62.81	68.20	-5.39	peak		

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:56

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10560.000	58.17	5.98	64.15	68.20	-4.05	peak	

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10560.000	56.08	5.98	62.06	68.20	-6.14	peak	


Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:64


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		10640.000	57.86	6.47	64.33	74.00	-9.67	peak		
2 *		10640.000	47.38	6.47	53.85	54.00	-0.15	AVG		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	57.58	4.44	62.02	68.20	-6.18	peak		
2 *		5350.000	49.35	4.44	53.79	54.00	-0.21	AVG		
3		5460.000	40.26	4.51	44.77	68.20	-23.43	peak		


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		10640.000	54.82	6.47	61.29	74.00	-12.71	peak		
2	*	10640.000	45.20	6.47	51.67	54.00	-2.33	AVG		

Radiated Emission





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	54.09	4.44	58.53	68.20	-9.67	peak		
2	*	5350.000	45.19	4.44	49.63	54.00	-4.37	AVG		
3		5460.000	40.95	4.51	45.46	68.20	-22.74	peak		

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:100

VERTICAL




HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11000.000	59.34	3.44	62.78	74.00	-11.22			peak
2 *		11000.000	48.51	3.44	51.95	54.00	-2.05			AVG

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		5350.000	40.73	4.44	45.17	68.20	-23.03			peak
2		5460.000	54.59	4.51	59.10	68.20	-9.10			peak
3 *		5460.000	43.04	4.51	47.55	54.00	-6.45			AVG

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:116

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11160.000	16.01	48.77	64.78	74.00	-9.22	peak		
2	*	11160.000	4.92	48.77	53.69	54.00	-0.31	AVG		

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11160.000	13.17	48.77	61.94	74.00	-12.06	peak		
2	*	11160.000	1.79	48.77	50.56	54.00	-3.44	AVG		


Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:140

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11400.000	15.20	49.06	64.26	74.00	-9.74	peak		
2	*	11400.000	3.98	49.06	53.04	54.00	-0.96	AVG		

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11400.000	13.76	49.06	62.82	74.00	-11.18	peak		
2	*	11400.000	2.48	49.06	51.54	54.00	-2.46	AVG		


Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:149


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11490.000	15.19	49.26	64.45	74.00	-9.55	peak	
2 *		11490.000	4.48	49.26	53.74	54.00	-0.26	AVG	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1 *		5650.000	39.95	15.12	55.07	68.20	-13.13	peak	
2		5700.000	40.63	15.46	56.09	105.20	-49.11	peak	
3		5720.000	64.83	15.33	80.16	110.80	-30.64	peak	
4		5725.000	71.11	15.30	86.41	122.20	-35.79	peak	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Table
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11490.000	13.09	49.26	62.35	74.00	-11.65	peak		
2 *		11490.000	2.41	49.26	51.67	54.00	-2.33	AVG		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Table
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1 *		5650.000	40.08	15.12	55.20	68.20	-13.00	peak		
2		5700.000	40.06	15.46	55.52	105.20	-49.68	peak		
3		5720.000	60.19	15.33	75.52	110.80	-35.28	peak		
4		5725.000	65.73	15.30	81.03	122.20	-41.17	peak		

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:157

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11570.000	15.57	48.95	64.52	74.00	-9.48	peak		
2	*	11570.000	4.40	48.95	53.35	54.00	-0.65	AVG		

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11570.000	13.24	48.95	62.19	74.00	-11.81	peak		
2	*	11570.000	2.85	48.95	51.80	54.00	-2.20	AVG		


Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:165


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11650.000	15.94	48.62	64.56	74.00	-9.44	peak	
2 *		11650.000	4.75	48.62	53.37	54.00	-0.63	AVG	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		5850.000	60.33	15.18	75.51	122.20	-46.69	peak	
2		5855.000	52.19	15.25	67.44	110.80	-43.36	peak	
3		5875.000	38.88	15.51	54.39	105.20	-50.81	peak	
4 *		5925.000	39.54	16.28	55.82	68.20	-12.38	peak	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11650.000	13.49	48.62	62.11	74.00	-11.89	peak		
2 *		11650.000	2.41	48.62	51.03	54.00	-2.97	AVG		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		5850.000	56.32	15.18	71.50	122.20	-50.70	peak		
2		5855.000	46.67	15.25	61.92	110.80	-48.88	peak		
3		5875.000	39.99	15.51	55.50	105.20	-49.70	peak		
4 *		5925.000	40.37	16.28	56.65	68.20	-11.55	peak		


Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:38


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	10380.000	57.17	6.80	63.97	68.20	-4.23	peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4500.000	41.26	3.85	45.11	68.20	-23.09	peak		
2		5150.000	61.30	5.62	66.92	68.20	-1.28	peak		
3	*	5150.000	47.92	5.62	53.54	54.00	-0.46	AVG		


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	10380.000	55.53	6.80	62.33	68.20	-5.87	peak			

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4500.000	41.15	3.85	45.00	68.20	-23.20	peak			
2		5150.000	51.29	5.62	56.91	68.20	-11.29	peak			
3	*	5150.000	39.86	5.62	45.48	54.00	-8.52	AVG			

Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO


Test Channel:46

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10460.000	58.19	6.49	64.68	68.20	-3.52	peak	

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10460.000	55.73	6.49	62.22	68.20	-5.98	peak	

Above 1G (1GHz~18GHz)


Test mode: 11N40MIMO

Test Channel:54

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:62


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		10620.000	58.18	6.07	64.25	74.00	-9.75	peak	
2 *		10620.000	47.25	6.07	53.32	54.00	-0.68	AVG	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		5350.000	62.17	4.44	66.61	68.20	-1.59	peak	
2 *		5350.000	48.85	4.44	53.29	54.00	-0.71	AVG	
3		5460.000	40.90	4.51	45.41	68.20	-22.79	peak	


HORIZONTALA

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		10620.000	56.52	6.07	62.59	74.00	-11.41			peak
2 *		10620.000	45.39	6.07	51.46	54.00	-2.54			AVG

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	57.25	4.44	61.69	68.20	-6.51			peak
2 *		5350.000	44.27	4.44	48.71	54.00	-5.29			AVG
3		5460.000	40.40	4.51	44.91	68.20	-23.29			peak

VERTICAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11020.000	60.57	3.66	64.23	74.00	-9.77			peak
2 *		11020.000	49.93	3.66	53.59	54.00	-0.41			AVG



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		5350.000	41.08	4.44	45.52	68.20	-22.68			peak
2 *		5460.000	61.97	4.51	66.48	68.20	-1.72			peak
3		5460.000	47.76	4.51	52.27	54.00	-1.73			AVG


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11020.000	58.16	3.66	61.82	74.00	-12.18	peak		
2 *		11020.000	47.33	3.66	50.99	54.00	-3.01	AVG		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	40.10	4.44	44.54	68.20	-23.66	peak		
2		5460.000	53.74	4.51	58.25	68.20	-9.95	peak		
3 *		5460.000	41.98	4.51	46.49	54.00	-7.51	AVG		

Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO


Test Channel:118

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11180.000	15.50	48.77	64.27	74.00	-9.73	peak		
2	*	11180.000	4.29	48.77	53.06	54.00	-0.94	AVG		

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11180.000	13.57	48.77	62.34	74.00	-11.66	peak		
2	*	11180.000	3.14	48.77	51.91	54.00	-2.09	AVG		

Above 1G (1GHz~18GHz)


Test mode: 11N40MIMO

Test Channel:134

VERTICAL



HORIZONTAL





Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO


Test Channel:151

VERTICAL




HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11510.000	12.84	49.24	62.08	74.00	-11.92	peak		
2 *		11510.000	2.00	49.24	51.24	54.00	-2.76	AVG		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1 *		5650.000	39.76	15.12	54.88	68.20	-13.32	peak		
2		5700.000	58.01	15.46	73.47	105.20	-31.73	peak		
3		5720.000	75.04	15.33	90.37	110.80	-20.43	peak		
4		5725.000	76.61	15.30	91.91	122.20	-30.29	peak		


Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:159


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11590.000	15.70	48.86	64.56	74.00	-9.44	peak	
2 *		11590.000	4.29	48.86	53.15	54.00	-0.85	AVG	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		5850.000	73.63	15.18	88.81	122.20	-33.39	peak	
2		5855.000	69.95	15.25	85.20	110.80	-25.60	peak	
3		5875.000	55.87	15.51	71.38	105.20	-33.82	peak	
4 *		5925.000	39.06	16.28	55.34	68.20	-12.86	peak	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11590.000	13.80	48.86	62.66	74.00	-11.34			peak
2 *		11590.000	2.56	48.86	51.42	54.00	-2.58			AVG

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		5850.000	72.69	15.18	87.87	122.20	-34.33			peak
2		5855.000	69.53	15.25	84.78	110.80	-26.02			peak
3		5875.000	57.15	15.51	72.66	105.20	-32.54			peak
4 *		5925.000	39.11	16.28	55.39	68.20	-12.81			peak


Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO

Test Channel:36


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10360.000	57.52	7.05	64.57	68.20	-3.63	peak	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4500.000	41.07	3.85	44.92	68.20	-23.28	peak	
2	*	5150.000	62.40	5.62	68.02	68.20	-0.18	peak	
3		5150.000	46.61	5.62	52.23	54.00	-1.77	AVG	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	10360.000	55.71	7.05	62.76	68.20	-5.44	peak			

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4500.000	42.32	3.85	46.17	68.20	-22.03	peak			
2	*	5150.000	56.14	5.62	61.76	68.20	-6.44	peak			
3		5150.000	41.82	5.62	47.44	54.00	-6.56	AVG			


Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO

Test Channel:40

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10400.000	57.52	6.55	64.07	68.20	-4.13	peak	

HORIZONTAL

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10400.000	56.40	6.55	62.95	68.20	-5.25	peak	

Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO


Test Channel:48

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10480.000	58.52	6.47	64.99	68.20	-3.21	peak	

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10480.000	56.32	6.47	62.79	68.20	-5.41	peak	


Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO

Test Channel:52

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10520.000	57.89	6.30	64.19	68.20	-4.01	peak	

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10520.000	56.29	6.30	62.59	68.20	-5.61	peak	


Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO

Test Channel:56

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10560.000	58.95	5.98	64.93	68.20	-3.27	peak	

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10560.000	56.77	5.98	62.75	68.20	-5.45	peak	


Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO

Test Channel:64


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		10640.000	57.84	6.47	64.31	74.00	-9.69	peak		
2 *		10640.000	46.65	6.47	53.12	54.00	-0.88	AVG		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1 *		5350.000	63.54	4.44	67.98	68.20	-0.22	peak		
2		5350.000	48.66	4.44	53.10	54.00	-0.90	AVG		
3		5460.000	40.55	4.51	45.06	68.20	-23.14	peak		


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		10640.000	55.76	6.47	62.23	74.00	-11.77	peak	
2 *		10640.000	44.87	6.47	51.34	54.00	-2.66	AVG	

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1 *		5350.000	61.33	4.44	65.77	68.20	-2.43	peak	
2		5350.000	46.73	4.44	51.17	54.00	-2.83	AVG	
3		5460.000	41.00	4.51	45.51	68.20	-22.69	peak	

Above 1G (1GHz~18GHz)


Test mode: 11AC20MIMO

Test Channel:100

VERTICAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11000.000	61.07	3.44	64.51	74.00	-9.49	peak		
2 *		11000.000	50.16	3.44	53.60	54.00	-0.40	AVG		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	40.99	4.44	45.43	68.20	-22.77	peak		
2		5460.000	60.65	4.51	65.16	68.20	-3.04	peak		
3 *		5460.000	48.52	4.51	53.03	54.00	-0.97	AVG		


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		11000.000	58.15	3.44	61.59	74.00	-12.41	peak			
2 *		11000.000	47.49	3.44	50.93	54.00	-3.07	AVG			

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		5350.000	41.49	4.44	45.93	68.20	-22.27	peak			
2		5460.000	52.92	4.51	57.43	68.20	-10.77	peak			
3 *		5460.000	41.71	4.51	46.22	54.00	-7.78	AVG			

Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO


Test Channel:116

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11160.000	15.49	48.77	64.26	74.00	-9.74	peak		
2 *		11160.000	4.88	48.77	53.65	54.00	-0.35	AVG		

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11160.000	12.77	48.77	61.54	74.00	-12.46	peak		
2 *		11160.000	2.17	48.77	50.94	54.00	-3.06	AVG		

Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO


Test Channel:140

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11400.000	15.21	49.06	64.27	74.00	-9.73	peak	
2 *		11400.000	4.13	49.06	53.19	54.00	-0.81	AVG	

HORIZONTAL





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		11400.000	13.37	49.06	62.43	74.00	-11.57	peak	
2 *		11400.000	2.23	49.06	51.29	54.00	-2.71	AVG	

Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO


Test Channel:149

VERTICAL




HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	
1		11490.000	13.14	49.26	62.40	74.00	-11.60			peak
2	*	11490.000	2.33	49.26	51.59	54.00	-2.41			AVG

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	5650.000	39.14	15.12	54.26	68.20	-13.94			peak
2		5700.000	39.46	15.46	54.92	105.20	-50.28			peak
3		5720.000	59.84	15.33	75.17	110.80	-35.63			peak
4		5725.000	70.77	15.30	86.07	122.20	-36.13			peak

Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO


Test Channel:157

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11570.000	15.34	48.95	64.29	74.00	-9.71	peak		
2	*	11570.000	4.21	48.95	53.16	54.00	-0.84	AVG		

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11570.000	13.38	48.95	62.33	74.00	-11.67	peak		
2	*	11570.000	2.62	48.95	51.57	54.00	-2.43	AVG		


Above 1G (1GHz~18GHz)

Test mode: 11AC20MIMO

Test Channel:165


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11650.000	15.63	48.62	64.25	74.00	-9.75	peak		
2 *		11650.000	5.01	48.62	53.63	54.00	-0.37	AVG		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5850.000	69.59	15.18	84.77	122.20	-37.43	peak		
2		5855.000	53.75	15.25	69.00	110.80	-41.80	peak		
3		5875.000	38.87	15.51	54.38	105.20	-50.82	peak		
4 *		5925.000	39.71	16.28	55.99	68.20	-12.21	peak		


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11650.000	13.87	48.62	62.49	74.00	-11.51			peak
2 *		11650.000	2.69	48.62	51.31	54.00	-2.69			AVG

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5850.000	69.99	15.18	85.17	122.20	-37.03			peak
2		5855.000	55.82	15.25	71.07	110.80	-39.73			peak
3		5875.000	39.55	15.51	55.06	105.20	-50.14			peak
4 *		5925.000	38.91	16.28	55.19	68.20	-13.01			peak


Above 1G (1GHz~18GHz)

Test mode: 11AC40MIMO

Test Channel:38


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10380.000	57.49	6.80	64.29	68.20	-3.91	peak	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4500.000	41.81	3.85	45.66	68.20	-22.54	peak	
2	*	5150.000	61.88	5.62	67.50	68.20	-0.70	peak	
3		5150.000	46.66	5.62	52.28	54.00	-1.72	AVG	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10380.000	55.57	6.80	62.37	68.20	-5.83	peak	

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4500.000	40.94	3.85	44.79	68.20	-23.41	peak	
2		5150.000	53.54	5.62	59.16	68.20	-9.04	peak	
3	*	5150.000	41.20	5.62	46.82	54.00	-7.18	AVG	

Above 1G (1GHz~18GHz)

Test mode: 11AC40MIMO


Test Channel:46

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10460.000	58.00	6.49	64.49	68.20	-3.71	peak	

HORIZONTAL




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10460.000	55.53	6.49	62.02	68.20	-6.18	peak	

Above 1G (1GHz~18GHz)

Test mode: 11AC40MIMO


Test Channel:54

VERTICAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10540.000	58.15	6.14	64.29	68.20	-3.91	peak	

HORIZONTAL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	10540.000	56.05	6.14	62.19	68.20	-6.01	peak	


Above 1G (1GHz~18GHz)

Test mode: 11AC40MIMO

Test Channel:62


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		10620.000	58.48	6.07	64.55	74.00	-9.45	peak	
2 *		10620.000	47.60	6.07	53.67	54.00	-0.33	AVG	


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		5350.000	62.32	4.44	66.76	68.20	-1.44	peak	
2 *		5350.000	48.36	4.44	52.80	54.00	-1.20	AVG	
3		5460.000	41.19	4.51	45.70	68.20	-22.50	peak	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		10620.000	56.48	6.07	62.55	74.00	-11.45	peak		
2 *		10620.000	45.14	6.07	51.21	54.00	-2.79	AVG		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.000	58.37	4.44	62.81	68.20	-5.39	peak		
2 *		5350.000	45.12	4.44	49.56	54.00	-4.44	AVG		
3		5460.000	40.48	4.51	44.99	68.20	-23.21	peak		