



FCC TEST REPORT

FCC ID: 2BCGU-P07

Product	:	Finder
Model Name	:	P07
Serial Model	:	P071, P072, P073, P074, P075, P076, P077, P078, P079, P08, P081, P082, P083, P084, P085, P086, P087, P088, P089, P09, P10, P11, P12, P113, P14
Brand	:	N/A
Report No.	:	PTC23080303702E-FC01
Prepared for		
Trangjan Technology Group(Dongguan)Co.,Ltd 3&4 F, No.3-2 Times Thinking, 159 Sanlian Rd., Luwu, Changping, Dongguan, Cuangdong, China 523570		
Prepared by		
Precise Testing & Certification (Guangdong) Co., Ltd. Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China. TEL: +86-769-3880 8222 FAX: +86-769-3882 6111		



1 TEST RESULT CERTIFICATION

Applicant's name : Trangjan Technology Group(Dongguan)Co.,Ltd
Address : 3&4 F, No.3-2 Times Thinking, 159 Sanlian Rd., Luwu, Changping, Dongguan, Cuangdong, China 523570
Manufacture's name : Trangjan Technology Group(Dongguan)Co.,Ltd
Address : 3&4 F, No.3-2 Times Thinking, 159 Sanlian Rd., Luwu, Changping, Dongguan, Cuangdong, China 523570
Product name : Finder
Model name : P07, P071, P072, P073, P074, P075, P076, P077, P078, P079, P08, P081, P082, P083, P084, P085, P086, P087, P088, P089, P09, P10, P11, P12, P113, P14
Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : ANSI C63.10:2013
Test Date : Aug. 19, 2023 to Aug. 22, 2023
Date of Issue : Sep. 01, 2023
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu/ Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
2.1 TEST SITE.....	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF E.U.T.	7
3.2 CHANNEL LIST	8
4 EQUIPMENT DURING TEST	9
4.1 EQUIPMENTS LIST	9
4.2 MEASUREMENT UNCERTAINTY	11
4.3 DESCRIPTION OF SUPPORT UNITS	12
5 CONDUCTED EMISSION	13
5.1 E.U.T. OPERATION	13
5.2 EUT SETUP	13
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
5.4 MEASUREMENT PROCEDURE	14
5.5 CONDUCTED EMISSION LIMIT	14
5.6 MEASUREMENT DESCRIPTION	14
5.7 CONDUCTED EMISSION TEST RESULT	14
6 RADIATED SPURIOUS EMISSIONS	15
6.1 EUT OPERATION	15
6.2 TEST SETUP	16
6.3 SPECTRUM ANALYZER SETUP	17
6.4 TEST PROCEDURE	18
6.5 SUMMARY OF TEST RESULTS	20
7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT	31
7.1 TEST PROCEDURE	31
7.2 TEST SETUP	31
7.3 TEST RESULT	32
8 6DB BANDWIDTH MEASUREMENT	45



TEST PROCEDURE	45
TEST SETUP	45
TEST RESULT	45
9 MAXIMUM PEAK OUTPUT POWER	49
9.1 TEST PROCEDURE	49
9.2 TEST SETUP	49
9.3 TEST RESULT	49
10 POWER SPECTRAL DENSITY	53
10.1 TEST PROCEDURE	53
10.2 TEST SETUP	53
10.3 TEST RESULT	53
11 ANTENNA APPLICATION	57
11.1 ANTENNA REQUIREMENT	57
11.2 RESULT	57
12 APPENDIX I -- TEST SETUP PHOTO	58
13 APPENDIX II -- EUT EXTERNAL PHOTO	59
14 APPENDIX III -- EUT INTERNAL PHOTO	62



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	N/A
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS



Report No.: PTC23070308102E-FC02

2.1 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Finder
Model Name/HVIN	:	P07
Additional model	:	P071, P072, P073, P074, P075, P076, P077, P078, P079, P08, P081, P082, P083, P084, P085, P086, P087, P088, P089, P09, P10, P11, P12, P113, P14
Model difference	:	The difference between different models is the shell shape, shell color and packaging.
Operating frequency	:	2402-2480MHz for BLE
Number of Channels	:	40 channels For DTS
Type of Modulation	:	GFSK for BLE 1Mbps/ 2Mbps
Antenna installation	:	PCB Antenna
Antenna Gain	:	2.2 dBi
Power supply	:	Input: DC 3V/0.02A
Hardware Version/HMN	:	1.0.0
Software Version/FVIN	:	1.0.1
Test Sample No.	:	PTC23080303702E-1/2, PTC23080303702E-2/2



3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.



4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due	Calibration period
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-30GHz	Aug. 20, 2024	1 year
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug. 20, 2024	1 year
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug. 20, 2024	1 year
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug. 20, 2024	1 year
Test S/W	Tonscend	JS1120-3	/	/	/	/

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due	Calibration period
EMI Receiver Test	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug. 20, 2024	1 year
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Aug. 20, 2024	1 year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Aug. 20, 2024	1 year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Aug. 20, 2024	1 year
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Aug. 20, 2024	1 year
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Aug. 20, 2024	1 year
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Aug. 20, 2024	1 year
Power Amplifier	LUNAR EM	LNA1G18-40	J1010000008 1	1GHz-26.5GHz	Aug. 20, 2024	1 year



Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	14GHz-40GHz z	Aug. 20, 2024	1 year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz z	Aug. 20, 2024	1 year
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz z	Aug. 20, 2024	1 year
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug. 20, 2024	1 year
Test S/W	Tonscend	TS+	/	/	/	/

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due	Calibration period
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug. 20, 2024	1 year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Aug. 20, 2024	1 year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Aug. 20, 2024	1 year
Test S/W	Tonscend	JS32-CE	/	/	/	/



4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9kHz~30MHz)	±3.15dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	



4.3 Description of Support Units

Equipment	Model No.	Series No.
N/A	N/A	N/A

5 Conducted Emission

Test Requirement	:	FCC CFR 47 Part 15 Section 15.207
Test Method	:	ANSI C63.10: 2013
Test Result	:	PASS
Frequency Range	:	150kHz to 30MHz
Class/Severity	:	Class B


5.1 E.U.T. Operation

Operating Environment :

Temperature	:	25.5 °C
Humidity	:	51 % RH
Atmospheric Pressure	:	101.2kPa


5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013:





5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

N/A

Note: The EUT only powered by battery, so the Conducted Emission test is not applicable.



6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method : ANSI C63.10:2013
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation


Operating Environment :

Temperature : 23.5 °C
 Humidity : 51.1 % RH
 Atmospheric Pressure : 101.2kPa


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value



6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



For Average Measurement:

$VBW=10\text{Hz}$, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μs)	1/T(KHz)	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (GFSK (CH00: 2402MHz)).



Antenna Polarization: Vertical GFSK(CH00: 2402MHz)




Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	36.79	37.05	-17.06	19.99	40.00	20.01	Vertical	PASS
2	55.22	37.62	-23.73	13.89	40.00	26.11	Vertical	PASS
3	99.84	35.03	-19.59	15.44	43.50	28.06	Vertical	PASS
4	148.34	41.06	-18.77	22.29	43.50	21.21	Vertical	PASS
5	168.71	37.24	-19.33	17.91	43.50	25.59	Vertical	PASS
6	583.87	33.42	-9.60	23.82	46.00	22.18	Vertical	PASS

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Antenna Polarization: Horizontal GFSK(CH00: 2402MHz)



Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Polarity	Verdict
1	34.85	33.03	-16.12	16.91	40.00	23.09	Horizontal	PASS
2	87.23	31.92	-21.83	10.09	40.00	29.91	Horizontal	PASS
3	127.97	33.25	-17.77	15.48	43.50	28.02	Horizontal	PASS
4	250.19	33.29	-19.28	14.01	46.00	31.99	Horizontal	PASS
5	397.63	32.69	-13.18	19.51	46.00	26.49	Horizontal	PASS
6	558.65	34.58	-10.02	24.56	46.00	21.44	Horizontal	PASS

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Test Frequency 1GHz-25GHz:

Test Mode: CH00 GFSK					Test channel:Low Channel (2402MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	45.39	30.16	6.58	34.09	48.04	74	-25.96	V
7206	43.11	37.11	7.73	34.50	53.45	74	-20.55	V
9608	38.47	39.31	9.23	34.79	52.22	74	-21.78	V
4804	46.44	34.04	6.58	34.09	52.97	74	-21.03	H
7206	36.31	37.11	7.73	34.50	46.65	74	-27.35	H
9608	40.00	39.31	9.23	34.79	53.75	74	-20.25	H
Average Value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	32.93	34.38	6.69	34.09	39.91	54	-14.09	V
7206	27.27	37.22	7.78	34.53	37.74	54	-16.26	V
9608	24.04	39.46	9.35	34.8	38.05	54	-15.95	V
4804	33.73	34.38	6.69	34.09	40.71	54	-13.29	H
7206	29.21	37.22	7.78	34.53	39.68	54	-14.32	H
9608	24.98	39.46	9.35	34.8	38.99	54	-15.01	H



Test Mode: CH19 GFSK					Test channel: Middle Channel (2440MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	49.05	30.16	6.58	34.09	51.70	74	-22.30	V
7320	41.15	37.11	7.73	34.50	51.49	74	-22.51	V
9760	40.12	39.31	9.23	34.79	53.87	74	-20.13	V
4880	47.26	34.04	6.58	34.09	53.79	74	-20.21	H
7320	44.43	37.11	7.73	34.50	54.77	74	-19.23	H
9760	38.86	39.31	9.23	34.79	52.61	74	-21.39	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	32.97	34.38	6.69	34.09	39.95	54	-14.05	V
7320	26.28	37.22	7.78	34.53	36.75	54	-17.25	V
9760	25.04	39.46	9.35	34.80	39.05	54	-14.95	V
4880	32.73	34.38	6.69	34.09	39.71	54	-14.29	H
7320	30.21	37.22	7.78	34.53	40.68	54	-13.32	H
9760	25.98	39.46	9.35	34.80	39.99	54	-14.01	H



Test Mode: CH39 GFSK					Test channel:High Channel (2480MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960	46.39	30.16	6.58	34.09	49.04	74	-24.96	V
7440	41.11	37.11	7.73	34.50	51.45	74	-22.55	V
9920	39.47	39.31	9.23	34.79	53.22	74	-20.78	V
4960	46.22	34.04	6.58	34.09	52.75	74	-21.25	H
7440	36.46	37.11	7.73	34.50	46.80	74	-27.20	H
9920	40.04	39.31	9.23	34.79	53.79	74	-20.21	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960	30.79	34.38	6.69	34.09	37.77	54	-16.23	V
7440	27.28	37.22	7.78	34.53	37.75	54	-16.25	V
9920	26.04	39.46	9.35	34.80	40.05	54	-13.95	V
4960	30.73	34.38	6.69	34.09	37.71	54	-16.29	H
7440	26.21	37.22	7.78	34.53	36.68	54	-17.32	H
9920	25.93	39.46	9.35	34.80	39.94	54	-14.06	H

Note: 1. The testing has been conformed to 10*2480MHz=24800MHz.

- 2. All other emissions more than 30dB below the limit.
- 3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
 Emission Level = Reading + Factor
 Margin=Emission Level-Limit




Spurious Emission in Restricted Bands


Test Mode	Antenna	ChName	Frequency [MHz]	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE_1M	Ant1	Low	2402	Peak	2390.000	-46.68	≤-21.20	48.52	≤74	PASS
BLE_1M	Ant1	Low	2402	Peak	2310.000	-48	≤-21.20	47.20	≤74	PASS
BLE_1M	Ant1	Low	2402	Peak	2334.125	-43.67	≤-21.20	51.53	≤74	PASS
BLE_1M	Ant1	Low	2402	AV	2390.000	-53.12	≤-41.20	42.08	≤54	PASS
BLE_1M	Ant1	Low	2402	AV	2310.000	-53.38	≤-41.20	41.82	≤54	PASS
BLE_1M	Ant1	Low	2402	AV	2389.565	-53.11	≤-41.20	42.09	≤54	PASS
BLE_1M	Ant1	High	2480	Peak	2483.500	-47.34	≤-21.20	47.86	≤74	PASS
BLE_1M	Ant1	High	2480	Peak	2500.000	-47.94	≤-21.20	47.26	≤74	PASS
BLE_1M	Ant1	High	2480	Peak	2499.600	-44.15	≤-21.20	51.05	≤74	PASS
BLE_1M	Ant1	High	2480	AV	2483.500	-48.63	≤-41.20	46.57	≤54	PASS
BLE_1M	Ant1	High	2480	AV	2500.000	-53.07	≤-41.20	42.13	≤54	PASS
BLE_1M	Ant1	High	2480	AV	2483.520	-48.63	≤-41.20	46.57	≤54	PASS
BLE_2M	Ant1	Low	2402	Peak	2390.000	-49.02	≤-21.20	46.18	≤74	PASS
BLE_2M	Ant1	Low	2402	Peak	2310.000	-49.24	≤-21.20	45.96	≤74	PASS
BLE_2M	Ant1	Low	2402	Peak	2376.755	-43.92	≤-21.20	51.28	≤74	PASS
BLE_2M	Ant1	Low	2402	AV	2390.000	-53.13	≤-41.20	42.07	≤54	PASS
BLE_2M	Ant1	Low	2402	AV	2310.000	-53.38	≤-41.20	41.82	≤54	PASS
BLE_2M	Ant1	Low	2402	AV	2389.880	-53.1	≤-41.20	42.10	≤54	PASS
BLE_2M	Ant1	High	2480	Peak	2483.500	-43.49	≤-21.20	51.71	≤74	PASS
BLE_2M	Ant1	High	2480	Peak	2500.000	-48.51	≤-21.20	46.69	≤74	PASS
BLE_2M	Ant1	High	2480	Peak	2483.520	-43.49	≤-21.20	51.71	≤74	PASS
BLE_2M	Ant1	High	2480	AV	2483.500	-41.6	≤-41.20	53.60	≤54	PASS
BLE_2M	Ant1	High	2480	AV	2500.000	-53.08	≤-41.20	42.12	≤54	PASS
BLE_2M	Ant1	High	2480	AV	2483.520	-41.6	≤-41.20	53.60	≤54	PASS

Note:


1. The Antenna Gain is compensated in the graph.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.




BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2480-PASS




BLE_1M-Ant1-2480-PASS




BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2480-PASS



BLE_2M-Ant1-2480-PASS




7 Conduct Band Edge And Spurious Emissions Measurement

- Test Requirement : Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
- Test Method : ANSI C63.10:2013
- Test Limit : Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Setup





7.3 Test Result


Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	0~Reference	3.74	3.74	---	PASS
BLE_1M	Ant1	2402	30~1000	3.74	-57.92	≤-16.26	PASS
BLE_1M	Ant1	2402	1000~26500	3.74	-41.4	≤-16.26	PASS
BLE_1M	Ant1	2440	1000~26500	3.80	-42.25	≤-16.2	PASS
BLE_1M	Ant1	2440	0~Reference	3.80	3.80	---	PASS
BLE_1M	Ant1	2440	30~1000	3.80	-58.28	≤-16.2	PASS
BLE_1M	Ant1	2480	0~Reference	3.25	3.25	---	PASS
BLE_1M	Ant1	2480	30~1000	3.25	-58.06	≤-16.75	PASS
BLE_1M	Ant1	2480	1000~26500	3.25	-41.89	≤-16.75	PASS
BLE_2M	Ant1	2402	0~Reference	3.20	3.20	---	PASS
BLE_2M	Ant1	2402	30~1000	3.20	-58.25	≤-16.8	PASS
BLE_2M	Ant1	2402	1000~26500	3.20	-41.83	≤-16.8	PASS
BLE_2M	Ant1	2440	0~Reference	3.04	3.04	---	PASS
BLE_2M	Ant1	2440	30~1000	3.04	-58.15	≤-16.96	PASS
BLE_2M	Ant1	2440	1000~26500	3.04	-41.42	≤-16.96	PASS
BLE_2M	Ant1	2480	0~Reference	1.67	1.67	---	PASS
BLE_2M	Ant1	2480	30~1000	1.67	-58.23	≤-18.33	PASS
BLE_2M	Ant1	2480	1000~26500	1.67	-41.87	≤-18.33	PASS




Test Graphs:




BLE_1M-Ant1-2402-0~Reference-PASS



BLE_1M-Ant1-2402-30~1000-PASS




BLE_1M-Ant1-2402-1000~26500-PASS



BLE_1M-Ant1-2440-1000~26500-PASS




BLE_1M-Ant1-2440-0~Reference-PASS




BLE_1M-Ant1-2440-30~1000-PASS



BLE_1M-Ant1-2480-0~Reference-PASS




BLE_1M-Ant1-2480-30~1000-PASS




BLE_1M-Ant1-2480-1000~26500-PASS



BLE_2M-Ant1-2402-0~Reference-PASS




BLE_2M-Ant1-2402-30~1000-PASS




BLE_2M-Ant1-2402-1000~26500-PASS



BLE_2M-Ant1-2440-0~Reference-PASS




BLE_2M-Ant1-2440-30~1000-PASS




BLE_2M-Ant1-2440-1000~26500-PASS



BLE_2M-Ant1-2480-0~Reference-PASS



BLE_2M-Ant1-2480-30~1000-PASS




BLE_2M-Ant1-2480-1000~26500-PASS




Band edge:


Test Mode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	4.59	-47.06	≤-15.41	PASS
BLE_1M	Ant1	High	2480	4.37	-46.58	≤-15.63	PASS
BLE_2M	Ant1	Low	2402	3.53	-32.4	≤-16.47	PASS
BLE_2M	Ant1	High	2480	3.25	-46.59	≤-16.75	PASS



BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS