

RF MEASUREMENT REPORT

FCC ID : 2BCGWBE65V2
Applicant : TP-LINK CORPORATION PTE. LTD.
Application Type : Certification
Product : BE11000 Whole Home Mesh Wi-Fi 7 System
Model No. : Deco BE65, Deco BE63, Deco BE11000, HB610,
Hexagon PB60, Deco BE65 Pro
Brand Name : tp-link
FCC Classification : Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s) : Part15 Subpart E (Section 15.407)
Received Date : November 13, 2023
Test Date : November 17, 2023 ~ January 10, 2024

Test By : Owen Tsai
(Owen Tsai)
Reviewed By : Paddy Chen
(Paddy Chen)
Approved By : Chenz Ker
(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v02r01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2311TW0113-U3	1.0	Original Report	2024-01-18	Invalid
2311TW0113-U3	2.0	Add a new model name	2024-01-26	Valid

CONTENTS

Description	Page
General Information	6
1. INTRODUCTION	7
1.1. Scope	7
1.2. MRT Test Location	7
2. PRODUCT INFORMATION	8
2.1. Equipment Description.....	8
2.2. Product Specification Subjective to this Report.....	9
2.3. Working Frequencies for this report	10
2.4. Description of Available Antennas.....	11
2.5. Test Mode	12
2.6. Configuration of Test System.....	13
2.7. Test System Details.....	14
2.8. Description of Test Software	14
2.9. Applied Standards	14
2.10. Duty Cycle	15
2.11. Test Configuration	17
2.12. EMI Suppression Device(s)/Modifications.....	17
2.13. Labeling Requirements.....	17
3. DESCRIPTION OF TEST	18
3.1. Evaluation Procedure	18
3.2. AC Line Conducted Emissions	18
3.3. Radiated Emissions	19
4. ANTENNA REQUIREMENTS	20
5. TEST EQUIPMENT CALIBRATION DATE	21
6. MEASUREMENT UNCERTAINTY	22
7. TEST RESULT	23
7.1. Summary	23
7.2. 26dB Bandwidth Measurement.....	24
7.2.1. Test Limit	24
7.2.2. Test Procedure used.....	24
7.2.3. Test Setting.....	24
7.2.4. Test Setup	24
7.2.5. Test Result.....	25

7.3.	6dB Bandwidth Measurement.....	47
7.3.1.	Test Limit	47
7.3.2.	Test Procedure used.....	47
7.3.3.	Test Setting.....	47
7.3.4.	Test Setup	47
7.3.5.	Test Result.....	48
7.4.	Output Power Measurement	55
7.4.1.	Test Limit	55
7.4.2.	Test Procedure Used	55
7.4.3.	Test Setting.....	55
7.4.4.	Test Setup	55
7.4.5.	Test Result.....	56
7.5.	Transmit Power Control	60
7.5.1.	Test Limit	60
7.5.2.	Test Procedure Used	60
7.5.3.	Test Setting.....	60
7.5.4.	Test Setup	60
7.5.5.	Test Result.....	60
7.6.	Power Spectral Density Measurement.....	61
7.6.1.	Test Limit	61
7.6.2.	Test Procedure Used	61
7.6.3.	Test Setting.....	61
7.6.4.	Test Setup	62
7.6.5.	Test Result.....	63
7.7.	Frequency Stability Measurement.....	103
7.7.1.	Test Limit	103
7.7.2.	Test Limit	103
7.7.3.	Test Setup	104
7.7.4.	Test Result.....	104
7.8.	Radiated Spurious Emission Measurement	105
7.8.1.	Test Limit	105
7.8.2.	Test Procedure Used	105
7.8.3.	Test Setting.....	105
7.8.4.	Test Setup	107
7.8.5.	Test Result.....	108
7.9.	Radiated Restricted Band Edge Measurement	326
7.9.1.	Test Limit	326
7.9.2.	Test Procedure Used	327
7.9.3.	Test Setting.....	327

7.9.4. Test Setup	328
7.9.5. Test Result.....	329
7.10. AC Conducted Emissions Measurement.....	525
7.10.1. Test Limit	525
7.10.2. Test Setup	525
7.10.3. Test Result.....	526
8. CONCLUSION.....	530
Appendix A : Test Setup Photograph	531
Appendix B : EUT Photograph.....	531
Appendix C : Internal Photograph	531

General Information

Applicant	TP-LINK CORPORATION PTE. LTD.
Applicant Address	7 Temasek Boulevard #29-03 Suntec Tower One, Singapore 038987
Manufacturer	TP-LINK CORPORATION PTE. LTD.
Manufacturer Address	7 Temasek Boulevard #29-03 Suntec Tower One, Singapore 038987
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.407

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Canada, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	BE11000 Whole Home Mesh Wi-Fi 7 System
Model No.:	Deco BE65, Deco BE63, Deco BE11000, HB610, Hexagon PB60, Deco BE65 Pro
Brand Name:	tp-link
Wi-Fi Specification:	802.11a/b/g/n/ac/ax/be
EUT Identification No.:	#1-1 (Conducted) #1-2 (Radiated)
Accessory	
Power Adapter	BRAND: tp-link MODEL: T120250-2B4 INPUT: 100 - 240V ~ 50/60Hz 0.8A. OUTPUT: DC 12.0V 2.5A Cable Out: Non-shielding, 1.5m

Note 1: Models Difference:

- a) The Deco BE63 and Deco BE11000 are exactly the same as the Deco BE65 except for the model.
- b) The HB610 is exactly the same as the Deco BE65 except for the model, the silkscreen on enclose.
- c) Hexagon PB60 remove the USB port and related circuits based on HB610. Other software and hardware designs are consistent with HB610.
- d) The Deco BE65 Pro has the different USB port, PHY/Switch solutions and the power for FEM from the Deco BE65, but the RF curcirt (including the schematic, layout, antenna, antenna position and RF parameters) is exactly the same as the Deco BE65.

Note 2: Some validation tests are evaluated in the EMC report as per the differences as above, only Deco BE65 was evaluated in this report.

2.2. Product Specification Subjective to this Report

Frequency Range:	For 802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20: 5180~5240MHz, 5260~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40: 5190~5230MHz, 5270~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80/be-EHT80: 5210MHz, 5290MHz, 5530MHz, 5610 MHz, 5690MHz, 5775MHz For 802.11ac-VHT160/ax-HE160/be-EHT160: 5250MHz, 5570MHz For 802.11be-EHT240: 5650MHz
Type of Modulation:	802.11a/n/ac: OFDM 802.11ax/be: OFDMA
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 1733.3Mbps 802.11ax: up to 2402Mbps 802.11be: up to 4323Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80/be-EHT80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

802.11ac-VHT160/ax-HE160/be-EHT160

Channel	Frequency	Channel	Frequency	Channel	Frequency
50	5250MHz	114	5570 MHz	--	--

802.11be-EHT240

Channel	Frequency	Channel	Frequency	Channel	Frequency
130	5650 MHz	--	--	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	Tx Paths	Number of spatial streams	Antenna Gain (dBi)		Beamforming Directional Gain (dBi)	CDD Directional Gain (dBi)	
				Ant 0	Ant 1		For Power	For PSD
Dipole	2400 ~ 2483.5	2	1	1.98	1.85	4.37	1.98	4.37
Dipole	5150 ~ 5350	2	1	3.00	3.00	5.51	3.00	5.51
	5470 ~ 5850		1	3.00	3.00	5.78	3.00	5.78
Franklin	5925 ~ 6425	2	1	3.00	3.00	5.45	3.00	5.45
			2	3.00	3.00	--	3.00	3.00
	6425 ~ 7125	2	1	3.00	3.00	5.51	3.00	5.51
			2	3.00	3.00	--	3.00	3.00

1. The device supports CDD Mode and Beamforming mode, details refer to the table as below.

2. CDD signals are correlated, the directional gain as follows,

When $N_{SS}=1$, for power measurements: Array Gain = 0 dB for $N_{ANT} \leq 4$, the directional gain = max antenna gain + array gain

For power spectral density (PSD) measurements: the max directional gain (each angle) = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$

When $N_{SS}=4$, the Directional Gain = $G_{ANT\ MAX} + 10 \log(N_{ANT}/N_{SS})$ dB

3. Beamforming signals are correlated, the directional gain as follows,

the max directional gain (each angle) = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$

4. The information as above is from the antenna report.

Test Mode	Tx Paths	CDD Mode	Beamforming Mode
802.11b/g (DTS)	2	√	X
802.11nax/be (DTS)	2	√	√
802.11a (NII)	2	√	X
802.11n/ac/ax/be (NII)	2	√	√
802.11ax/be (6ID & 6PP)	2	√	√

2.5. Test Mode


CDD Mode
Mode 1: Transmit by 802.11a_Nss=1 (6Mbps) (CDD mode)
Mode 2: Transmit by 802.11ac-VHT20_Nss=1 (MCS0) (CDD mode)
Mode 3: Transmit by 802.11ac-VHT40_Nss=1 (MCS0) (CDD mode)
Mode 4: Transmit by 802.11ac-VHT80_Nss=1 (MCS0) (CDD mode)
Mode 5: Transmit by 802.11ac-VHT160_Nss=1 (MCS0) (CDD mode)
Mode 6: Transmit by 802.11ax-HE20_Nss=1 (MCS0) (CDD mode)
Mode 7: Transmit by 802.11ax-HE40_Nss=1 (MCS0) (CDD mode)
Mode 8: Transmit by 802.11ax-HE80_Nss=1 (MCS0) (CDD mode)
Mode 9: Transmit by 802.11ax-HE160_Nss=1 (MCS0) (CDD mode)
Mode 10: Transmit by 802.11be-EHT20_Nss=1 (MCS0) (CDD mode)
Mode 11: Transmit by 802.11be-EHT40_Nss=1 (MCS0) (CDD mode)
Mode 12: Transmit by 802.11be-EHT80_Nss=1 (MCS0) (CDD mode)
Mode 13: Transmit by 802.11be-EHT160_Nss=1 (MCS0) (CDD mode)
Mode 14: Transmit by 802.11be-EHT240_Nss=1 (MCS0) (CDD mode)
Beamforming Mode
Mode 15: Transmit by 802.11ac-VHT20_Nss=1 (MCS0) (Beamforming Mode)
Mode 16: Transmit by 802.11ac-VHT40_Nss=1 (MCS0) (Beamforming Mode)
Mode 17: Transmit by 802.11ac-VHT80_Nss=1 (MCS0) (Beamforming Mode)
Mode 18: Transmit by 802.11ac-VHT160_Nss=1 (MCS0) (Beamforming Mode)
Mode 19: Transmit by 802.11ax-HE20_Nss=1 (MCS0) (Beamforming Mode)
Mode 20: Transmit by 802.11ax-HE40_Nss=1 (MCS0) (Beamforming Mode)
Mode 21: Transmit by 802.11ax-HE80_Nss=1 (MCS0) (Beamforming Mode)
Mode 22: Transmit by 802.11ax-HE160_Nss=1 (MCS0) (Beamforming Mode)
Mode 23: Transmit by 802.11be-EHT20_Nss=1 (MCS0) (Beamforming Mode)
Mode 24: Transmit by 802.11be-EHT40_Nss=1 (MCS0) (Beamforming Mode)
Mode 25: Transmit by 802.11be-EHT80_Nss=1 (MCS0) (Beamforming Mode)
Mode 26: Transmit by 802.11be-EHT160_Nss=1 (MCS0) (Beamforming Mode)
Mode 27: Transmit by 802.11be-EHT240_Nss=1 (MCS0) (Beamforming Mode)
Remark:
1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.
2. This device supports 2 N _{ss} and power level of 2 N _{ss} is less than or equal to the power of 1 N _{ss} . The worst case is N _{ss} =1.
3. Due to CDD mode was the worst mode, so all test items were evaluated in this report. The beamforming mode only evaluated the RF output power.

4. EUT supports one configuration only in 802.11ax/be full RU mode.
5. 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report.
6. As Designated by manufacturer, the lowest data rate was the worst condition, so all the tests were done with lowest data rate.

2.6. Configuration of Test System

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram



Signal Cable Type	Signal Cable Description
A	LAN Cable

2.7. Test System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Notebook PC	Lenovo	20Y7-006KTW	N/A	Non-shielded, 0.8m

2.8. Description of Test Software

The test utility software used during testing was “QSPR”, the version is ver5.0-00202.

Note: Final power setting please refer to operational description.

2.9. Applied Standards


According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:


- FCC Part 15.247
- KDB 789033 D02v02r01,
- KDB 662911 D01v02r01
- ANSI C63.10-2013


2.10. Duty Cycle

5GHz (NII) operation is possible in 20MHz, 40MHz, 80MHz, 160MHz and 240MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
802.11a	99.10%
802.11ac-VHT20	98.35%
802.11ac-VHT40	97.06%
802.11ac-VHT80	96.89%
802.11ac-VHT160	97.11%
802.11ax-HE20	97.15%
802.11ax-HE40	96.68%
802.11ax-HE80	98.15%
802.11ax-HE160	97.54%
802.11be-EHT20	98.66%
802.11be-EHT 40	98.14%
802.11be-EHT 80	97.26%
802.11be-EHT 160	97.38%
802.11be-EHT 240	96.40%







2.11. Test Configuration

The device was tested per the guidance of KDB 789033 D02v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.12. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.13. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlets supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 789033 D02v02r01 were used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that those cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2024/3/7
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2024/4/17
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2024/5/10
DIVA PLUS Funk-Wetterstation	TFA	35.1083	MRTTWA00050	1 year	2024/6/15

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Acitive Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2024/5/22
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2024/10/31
Broadband Hornantenna	RFSPIN	DRH18-E	MRTTWA00087	1 year	2024/5/17
Broadband Preamplifier	EMC Instruments corporation	EMC118A45SE	MRTTWA00088	1 year	2024/5/17
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2024/3/20
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2024/3/27
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2024/3/8
Signal Analyzer	R&S	FSVA3044	MRTTWA00092	1 year	2024/6/29
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00034	1 year	2024/6/26
Cable	HUBERSUHNER	EMC105-NM-NM-3000	MRTTWE00035	1 year	2024/6/26
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00032	1 year	2024/6/4

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2024/4/19
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2024/10/17
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2024/7/19
Attenuator	WTI	218FS-20	MRTTWE00026	1 year	2024/11/1
Attenuator	WTI	218FS-10	MRTTWE00027	1 year	2024/6/14
Temperature & Humidity Chamber	TEN BILLION	TTH-B3UP	MRTTWA00036	1 year	2024/6/11
DIVA PLUS Funk-Wetterstation	TFA	35.1083	MRTTWA00050	1 year	2024/6/15

Software	Version	Function
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 150kHz~30MHz: $\pm 2.53\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 9kHz ~ 1GHz: $\pm 4.25\text{dB}$ 1GHz ~ 40GHz: $\pm 4.45\text{dB}$
Conducted Power (Carrier Power / Power Density)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.82^\circ\text{C} / \pm 3\%$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 78.4\text{Hz}$

7. TEST RESULT

7.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section 7.2
15.407(e)	6dB Bandwidth	$\geq 500\text{kHz}$		Pass	Section 7.3
15.407(a)(1)(ii), (2), (3)	Maximum Conducted Output Power	Refer to section 7.4		Pass	Section 7.4
15.407(h)(1)	Transmit Power Control	$\leq 24 \text{ dBm}$		Pass	Section 7.5
15.407(a)(1)(ii), (2), (3), (12)	Peak Power Spectral Density	Refer to section 7.6		Pass	Section 7.6
15.407(g)	Frequency Stability	N/A		Pass	Section 7.7
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Refer to Section 7.8		Pass	Section 7.8 & 7.9
15.205, 15.209 15.407(b)(8), (9), (10)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.10

Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

7.2. 26dB Bandwidth Measurement

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

KDB 789033 D02v02r01- Section C.1

7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW \geq 3 \times RBW.
4. Detector = Peak.
5. Trace mode = max hold.

7.2.4. Test Setup



7.2.5. Test Result

Product	BE11000 Whole Home Mesh Wi-Fi 7 System	Test Engineer	Xuan
Test Site	SR6	Test Date	2023/11/23~2024/1/10

Test Mode	Data Rate/MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11a	6Mbps	36	5180	22.360	16.686
802.11a	6Mbps	44	5220	34.150	18.459
802.11a	6Mbps	48	5240	37.250	18.430
802.11a	6Mbps	52	5260	21.500	16.718
802.11a	6Mbps	60	5300	21.960	16.715
802.11a	6Mbps	64	5320	22.420	16.770
802.11a	6Mbps	100	5500	22.180	16.708
802.11a	6Mbps	116	5580	22.290	16.741
802.11a	6Mbps	140	5700	21.510	16.710
802.11a	6Mbps	144	5720	21.730	16.702
802.11a	6Mbps	149	5745	37.280	20.956
802.11a	6Mbps	157	5785	39.910	29.303
802.11a	6Mbps	165	5825	40.000	32.900
802.11ac-VHT20	MCS0	36	5180	22.180	17.825
802.11ac-VHT20	MCS0	44	5220	37.810	18.723
802.11ac-VHT20	MCS0	48	5240	35.410	18.954
802.11ac-VHT20	MCS0	52	5260	22.140	17.807
802.11ac-VHT20	MCS0	60	5300	22.220	17.840
802.11ac-VHT20	MCS0	64	5320	22.320	17.850
802.11ac-VHT20	MCS0	100	5500	22.460	17.847
802.11ac-VHT20	MCS0	116	5580	21.780	17.849
802.11ac-VHT20	MCS0	140	5700	22.050	17.804
802.11ac-VHT20	MCS0	144	5720	22.310	17.817
802.11ac-VHT20	MCS0	149	5745	39.940	23.054
802.11ac-VHT20	MCS0	157	5785	40.000	30.006
802.11ac-VHT20	MCS0	165	5825	40.000	33.811

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11ac-VHT40	MCS0	38	5190	42.850	36.459
802.11ac-VHT40	MCS0	46	5230	79.110	39.251
802.11ac-VHT40	MCS0	54	5270	43.750	36.406
802.11ac-VHT40	MCS0	62	5310	43.870	36.485
802.11ac-VHT40	MCS0	102	5510	43.770	36.438
802.11ac-VHT40	MCS0	110	5550	44.350	36.433
802.11ac-VHT40	MCS0	134	5670	43.350	36.411
802.11ac-VHT40	MCS0	142	5710	43.940	36.429
802.11ac-VHT40	MCS0	151	5755	80.000	53.047
802.11ac-VHT40	MCS0	159	5795	80.000	59.601
802.11ac-VHT80	MCS0	42	5210	89.640	76.194
802.11ac-VHT80	MCS0	58	5290	88.390	76.020
802.11ac-VHT80	MCS0	106	5530	91.970	76.115
802.11ac-VHT80	MCS0	122	5610	92.520	76.082
802.11ac-VHT80	MCS0	138	5690	90.900	75.950
802.11ac-VHT80	MCS0	155	5775	90.850	76.156
802.11ac-VHT160	MCS0	50	5250	168.800	155.370
802.11ac-VHT160	MCS0	114	5570	171.800	155.420
802.11ax-HE20	MCS0	36	5180	21.770	19.066
802.11ax-HE20	MCS0	44	5220	38.730	19.314
802.11ax-HE20	MCS0	48	5240	36.710	19.284
802.11ax-HE20	MCS0	52	5260	22.440	19.007
802.11ax-HE20	MCS0	60	5300	22.180	19.029
802.11ax-HE20	MCS0	64	5320	21.750	18.973
802.11ax-HE20	MCS0	100	5500	21.890	19.027
802.11ax-HE20	MCS0	116	5580	22.270	19.028
802.11ax-HE20	MCS0	140	5700	22.490	19.016
802.11ax-HE20	MCS0	144	5720	22.360	19.040
802.11ax-HE20	MCS0	149	5745	39.840	20.428
802.11ax-HE20	MCS0	157	5785	40.000	28.885
802.11ax-HE20	MCS0	165	5825	40.000	33.398

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11ax-HE40	MCS0	38	5190	42.790	37.899
802.11ax-HE40	MCS0	46	5230	75.630	38.467
802.11ax-HE40	MCS0	54	5270	42.680	37.887
802.11ax-HE40	MCS0	62	5310	42.820	37.874
802.11ax-HE40	MCS0	102	5510	42.940	37.884
802.11ax-HE40	MCS0	110	5550	42.870	37.962
802.11ax-HE40	MCS0	134	5670	43.060	37.927
802.11ax-HE40	MCS0	142	5710	43.010	37.887
802.11ax-HE40	MCS0	151	5755	80.000	51.646
802.11ax-HE40	MCS0	159	5795	80.000	57.811
802.11ax-HE80	MCS0	42	5210	86.500	77.652
802.11ax-HE80	MCS0	58	5290	85.380	77.692
802.11ax-HE80	MCS0	106	5530	86.400	77.656
802.11ax-HE80	MCS0	122	5610	85.320	77.645
802.11ax-HE80	MCS0	138	5690	86.160	77.663
802.11ax-HE80	MCS0	155	5775	85.780	77.701
802.11ax-HE160	MCS0	50	5250	167.700	156.890
802.11ax-HE160	MCS0	114	5570	165.100	156.990
802.11be-EHT20	MCS0	36	5180	23.170	19.001
802.11be-EHT20	MCS0	44	5220	39.710	19.440
802.11be-EHT20	MCS0	48	5240	39.900	19.448
802.11be-EHT20	MCS0	52	5260	22.310	19.012
802.11be-EHT20	MCS0	60	5300	22.300	19.010
802.11be-EHT20	MCS0	64	5320	21.990	19.035
802.11be-EHT20	MCS0	100	5500	23.130	19.019
802.11be-EHT20	MCS0	116	5580	21.790	19.016
802.11be-EHT20	MCS0	140	5700	22.910	19.038
802.11be-EHT20	MCS0	144	5720	21.820	19.019
802.11be-EHT20	MCS0	149	5745	39.820	21.164
802.11be-EHT20	MCS0	157	5785	40.000	29.281
802.11be-EHT20	MCS0	165	5825	40.000	33.278

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11be-EHT40	MCS0	38	5190	42.600	37.976
802.11be-EHT40	MCS0	46	5230	78.500	38.526
802.11be-EHT40	MCS0	54	5270	43.510	37.966
802.11be-EHT40	MCS0	62	5310	43.670	37.974
802.11be-EHT40	MCS0	102	5510	43.240	37.926
802.11be-EHT40	MCS0	110	5550	42.590	37.907
802.11be-EHT40	MCS0	134	5670	43.010	37.926
802.11be-EHT40	MCS0	142	5710	42.810	37.877
802.11be-EHT40	MCS0	151	5755	76.440	39.140
802.11be-EHT40	MCS0	159	5795	80.000	57.757
802.11be-EHT80	MCS0	42	5210	86.140	77.547
802.11be-EHT80	MCS0	58	5290	84.270	77.789
802.11be-EHT80	MCS0	106	5530	85.830	77.661
802.11be-EHT80	MCS0	122	5610	86.610	77.854
802.11be-EHT80	MCS0	138	5690	84.970	77.735
802.11be-EHT80	MCS0	155	5775	85.960	77.625
802.11be-EHT160	MCS0	50	5250	170.100	156.810
802.11be-EHT160	MCS0	114	5570	166.400	157.470
802.11be-EHT240	MCS0	130	5650	282.700	236.780

