

1 2 3 4 5 6 7 8 9

A

A

357mm

11.89±0.5mm

4.68±0.3mm

2.53±0.3mm

3.64±0.3mm

63.3mm

B

B

C

C



D

D

E

E

1 2 3 4 5 6 7 8 9


Kasa Smart Wi-Fi Power Strip, 6-Outlet
 Model: HS300
 Rating: 125V~ 60Hz 15A 1875W max
 VPR: 600V(L-N) 600V(L-G) 600V(N-G)
 Type 3 SPD
 USB: 5V  2.4A Each & Total
 CONFORMS TO UL STD.
 1363&1449&62368- 1&60730- 1
 FCC ID: 2BCGWHS300V2





Intertek 5010780



CAUTION:
 To Reduce the Risk of Electric Shock – Use Only Indoors.
 Risk of Electric Shock. Do not plug into another relocatable power tap
 or an extension cord.
USE ONLY IN DRY LOCATIONS.

WARNING:
 Timer could turn-on unexpectedly without the user being present.
 To Reduce the Hazardous Condition – Unplug the appliance from
 the receptacle before servicing.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference. 2) This device must accept any interference received, including interference that may cause undesired operation.


Kasa Smart Wi-Fi Power Strip, 6-Outlet
 Model: HS300
 Rating: 125V~ 60Hz 15A 1875W max
 VPR: 600V(L-N) 600V(L-G) 600V(N-G)
 Type 3 SPD
 USB: 5V  2.4A Each & Total
 CONFORMS TO UL STD.
 1363&1449&62368- 1&60730- 1
 FCC ID: 2BCGWHS300V2



Intertek 5010780



CAUTION:
 To Reduce the Risk of Electric Shock – Use Only Indoors.
 Risk of Electric Shock. Do not plug into another relocatable power tap
 or an extension cord.
USE ONLY IN DRY LOCATIONS.

WARNING:
 Timer could turn-on unexpectedly without the user being present.
 To Reduce the Hazardous Condition – Unplug the appliance from
 the receptacle before servicing.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference. 2) This device must accept any interference received, including interference that may cause undesired operation.