



FCC Radio Test Report

FCC ID: 2BCGWRE605XV2

This report concerns: Class II permissive Change

Project No. : 2405G090
Equipment : AX1800 Wi-Fi 6 Range Extender
Brand Name : tp-link
Test Model : RE605X
Series Model : N/A
Applicant : TP-LINK CORPORATION PTE. LTD.
Address : 7 Temasek Boulevard #29-03 Suntec Tower One, Singapore 038987
Manufacturer : TP-LINK CORPORATION PTE. LTD.
Address : 7 Temasek Boulevard #29-03 Suntec Tower One, Singapore 038987
Date of Receipt : May 23, 2024
Date of Test : May 23, 2024 ~ May 29, 2024
Issued Date : May 30, 2024
Report Version : R00
Test Sample : Engineering Sample No.: SSL20240523110
Standard(s) : FCC CFR Title 47, Part 15, Subpart E

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Grani Zhou
Grani Zhou

Approved by : Chay Cai
Chay Cai

Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong,
People's Republic of China

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by **BTL**.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the ISO/IEC 17025: 2017 requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

| Table of Contents | Page |
|--|-------------|
| REPORT ISSUED HISTORY | 4 |
| 1 . APPLICABLE STANDARDS | 5 |
| 2 . SUMMARY OF TEST RESULTS | 5 |
| 2.1 TEST FACILITY | 6 |
| 2.2 MEASUREMENT UNCERTAINTY | 6 |
| 2.3 TEST ENVIRONMENT CONDITIONS | 6 |
| 3 . GENERAL INFORMATION | 7 |
| 3.1 GENERAL DESCRIPTION OF EUT | 7 |
| 3.2 DESCRIPTION OF TEST MODES | 10 |
| 3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 11 |
| 3.4 SUPPORT UNITS | 11 |
| 3.5 CUSTOMER INFORMATION DESCRIPTION | 11 |
| 4 . RADIATED EMISSIONS | 12 |
| 4.1 LIMIT | 12 |
| 4.2 TEST PROCEDURE | 12 |
| 4.3 DEVIATION FROM TEST STANDARD | 13 |
| 4.4 TEST SETUP | 13 |
| 4.5 EUT OPERATING CONDITIONS | 14 |
| 4.6 TEST RESULTS - 30 MHZ TO 1000 MHZ | 14 |
| 4.7 TEST RESULTS - ABOVE 1000 MHZ | 14 |
| 5 . MEASUREMENT INSTRUMENTS LIST | 15 |
| 6 . EUT TEST PHOTO | 16 |
| APPENDIX A - RADIATED EMISSION - 30 MHZ TO 1000 MHZ | 18 |
| APPENDIX B - RADIATED EMISSION- ABOVE 1000 MHZ | 21 |

REPORT ISSUED HISTORY

| Report No. | Version | Description | Issued Date | Note |
|---------------------|---------|------------------|--------------|-------|
| BTL-FCCP-2-2405G090 | R00 | Original Report. | May 30, 2024 | Valid |

1. APPLICABLE STANDARDS

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

ANSI C63.10-2013

The following reference test guidance is not within the scope of accreditation of A2LA:

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| FCC CFR Title 47, Part 15, Subpart E | | | | |
|--------------------------------------|-------------------|--------------------------|----------|--------|
| Standard(s) Section | Test Item | Test Result | Judgment | Remark |
| 15.407(b) 15.205(a) 15.209(a) | Radiated Emission | APPENDIX A APPENDIX B | PASS | ----- |

Note:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The worst cases of radiated emissions except 9kHz to 30 MHz have been re-evaluated by sample of FCC ID: 2BCGWRE605XV2, model name: RE605X. It is found that the new data are the worse, so the test data are reissue from the FCC ID: 2BCGWRE605XV2, model name: RE605X. Model difference(s): (1) Model RE605X changed the signal transformer of the network port. (2) The heat sink on the back of the PCB has been removed and a graphite heat sink is pasted on the upper cover housing instead.
- (3) The other test records and results please refer to the test report number: FR3N1401B, issued date is 2024-03-20, and issued by:
Test Laboratory: Sporton International Inc.(ShenZhen)
Address: 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China

Which was accredited by A2LA, FCC registration number is 421272, with the scopes of cited standards in this test report.

This report is only valid conjunction with the above referenced test report.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Dalang, Dongguan City, Guangdong People's Republic of China.

BTL's Registration Number for FCC: 747969

BTL's Designation Number for FCC: CN1377

2.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95.45% confidence level (based on a coverage factor (k=2))

The BTL measurement uncertainty as below table:

A. Radiated emissions test:

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U,(dB) |
|-----------------|--------|-----------------------------|------------|--------|
| DG-CB03 (3m) | CISPR | 30MHz ~ 200MHz | V | 4.40 |
| | | 30MHz ~ 200MHz | H | 3.62 |
| | | 200MHz ~ 1,000MHz | V | 4.58 |
| | | 200MHz ~ 1,000MHz | H | 3.98 |

| Test Site | Method | Measurement Frequency Range | U,(dB) |
|-----------------|--------|-----------------------------|--------|
| DG-CB03 (3m) | CISPR | 1GHz ~ 6GHz | 4.08 |
| | | 6GHz ~ 18GHz | 4.62 |

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

2.3 TEST ENVIRONMENT CONDITIONS

| Test Item | Temperature | Humidity | Test Voltage | Tested By | Test Date |
|---|-------------|----------|--------------|-------------|--------------|
| Radiated Emissions -30MHz to 1000MHz | 23°C | 53% | AC 120V/60Hz | Jensen Zhou | May 23, 2024 |
| Radiated Emissions -Above 1000MHz | 24°C | 56% | AC 120V/60Hz | Jensen Zhou | May 29, 2024 |

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | |
|-----------------------------|--|
| Equipment | AX1800 Wi-Fi 6 Range Extender |
| Brand Name | tp-link |
| Test Model | RE605X |
| Series Model | N/A |
| Model Difference(s) | N/A |
| Power Source | AC Mains. |
| Power Rating | 100-240V~ |
| Operation Frequency Band(s) | UNII-1: 5150 MHz ~ 5250 MHz UNII-2A: 5250 MHz ~ 5350 MHz UNII-2C: 5470 MHz ~ 5725 MHz UNII-3: 5725 MHz ~ 5850 MHz |
| Modulation Type | IEEE 802.11a/n/ac: OFDM IEEE 802.11ax: OFDMA |
| Bit Rate of Transmitter | IEEE 802.11a: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 300 Mbps IEEE 802.11ac: up to 1733.3 Mbps IEEE 802.11ax: up to 2402 Mbps |

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- Channel List:

| IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20) | | IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40) | | IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80) | |
|---|-----------------|---|-----------------|---|-----------------|
| UNII-1 | | UNII-1 | | UNII-1 | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 36 | 5180 | 38 | 5190 | 42 | 5210 |
| 40 | 5200 | 46 | 5230 | | |
| 44 | 5220 | | | | |
| 48 | 5240 | | | | |

| IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20) | | IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40) | | IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80) | |
|---|-----------------|---|-----------------|---|-----------------|
| UNII-2A | | UNII-2A | | UNII-2A | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 52 | 5260 | 54 | 5270 | 58 | 5290 |
| 56 | 5280 | 62 | 5310 | | |
| 60 | 5300 | | | | |
| 64 | 5320 | | | | |

| IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20) | | IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40) | | IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80) | |
|---|-----------------|---|-----------------|---|-----------------|
| UNII-2C | | UNII-2C | | UNII-2C | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 100 | 5500 | 102 | 5510 | 106 | 5530 |
| 104 | 5520 | 110 | 5550 | 122 | 5610 |
| 108 | 5540 | 118 | 5590 | 138 | 5690 |
| 112 | 5560 | 126 | 5630 | | |
| 116 | 5580 | 134 | 5670 | | |
| 120 | 5600 | 137 | 5710 | | |
| 124 | 5620 | | | | |
| 128 | 5640 | | | | |
| 132 | 5660 | | | | |
| 136 | 5680 | | | | |
| 140 | 5700 | | | | |
| 144 | 5720 | | | | |

| IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20) | | IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40) | | IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80) | |
|---|-----------------|---|-----------------|---|-----------------|
| UNII-3 | | UNII-3 | | UNII-3 | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 149 | 5745 | 151 | 5755 | 155 | 5775 |
| 153 | 5765 | 159 | 5795 | | |
| 157 | 5785 | | | | |
| 161 | 5805 | | | | |
| 165 | 5825 | | | | |

3. Table for Filed Antenna:

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(\text{NANT}/\text{NSS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $\text{NANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode for 802.11a/n/ac/ax modes.

For power, the directional gain GANT is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

| | | | DG for Power (dBi) | DG for PSD (dBi) | Power Limit Reduction (dB) | PSD Limit Reduction (dB) |
|---------|-----------------|-----------------|-----------------------------|---------------------------|-------------------------------------|-----------------------------------|
| | Ant. 1 (dBi) | Ant. 2 (dBi) | | | | |
| UNII-1 | 3.00 | 3.00 | 3.00 | 6.01 | 0.00 | 0.01 |
| UNII-2A | 3.00 | 3.00 | 3.00 | 6.01 | 0.00 | 0.01 |
| UNII-2C | 3.00 | 3.00 | 3.00 | 6.01 | 0.00 | 0.01 |
| UNII-3 | 3.00 | 3.00 | 3.00 | 6.01 | 0.00 | 0.01 |

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)

3.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

| Pretest Mode | Description |
|--------------|-----------------------------|
| Mode 1 | TX AX(HE20) Mode Channel 48 |

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.


| Radiated emissions test – Above 1GHz | |
|---|-----------------------------|
| Final Test Mode | Description |
| Mode 1 | TX AX(HE20) Mode Channel 48 |

| Radiated emissions test - Below 1GHz | |
|---|-----------------------------|
| Final Test Mode | Description |
| Mode 1 | TX AX(HE20) Mode Channel 48 |

Note:

- (1) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz and 26.5GHz~40GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.

3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.4 SUPPORT UNITS

| Item | Equipment | Brand | Model No. | Series No. |
|------|-----------|-------|-------------|------------|
| A | Notebook | Honor | 14SER5 3500 | N/A |

| Item | Cable Type | Shielded Type | Ferrite Core | Length |
|------|------------|---------------|--------------|--------|
| 1 | AC Cable | NO | NO | 1.2m |
| 2 | RJ45 Cable | NO | NO | 10m |

3.5 CUSTOMER INFORMATION DESCRIPTION

- 1) The antenna gain and beamforming gains are provided by the manufacturer.

4. RADIATED EMISSIONS

4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSIONS MEASUREMENT (30 MHz to 1000 MHz)

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS (Above 1000 MHz)

| Frequency (MHz) | EIRP Limit (dBm/MHz) | Equivalent Field Strength at 3m (dBμV/m) |
|-----------------------|----------------------|--|
| 5150-5250 | -27 | 68.2 |
| 5250-5350 | -27 | 68.2 |
| 5470-5725 | -27 | 68.2 |
| 5725-5850 NOTE (2) | -27 | 68.2 |
| | 10 | 105.2 |
| | 15.6 | 110.8 |
| | 27 | 122.2 |

NOTE:

(1) The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

(2) According to 15.407(b)(4)(i), all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

4.2 TEST PROCEDURE

- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
(below 1 GHz)
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

| Spectrum Parameters | Setting |
|------------------------|---------------------------------|
| Start ~ Stop Frequency | 30 MHz~1000 MHz for RBW 100 kHz |


| Spectrum Parameters | Setting |
|--|--|
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic or 40 GHz, whichever is lower |
| RBW / VBW (Emission in restricted band) | 1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value |


| Receiver Parameters | Setting |
|------------------------|----------------------------------|
| Start ~ Stop Frequency | 30 MHz~1000 MHz for QP detector |
| Start ~ Stop Frequency | 1 GHz~40 GHz for PK/AVG detector |

4.3 DEVIATION FROM TEST STANDARD

No deviation.

4.4 TEST SETUP





4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULTS - 30 MHZ TO 1000 MHZ

Please refer to the APPENDIX A.

4.7 TEST RESULTS - ABOVE 1000 MHZ

Please refer to the APPENDIX B.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.



5. MEASUREMENT INSTRUMENTS LIST

| Radiated Emissions - 30 MHz to 1 GHz | | | | | |
|--------------------------------------|--------------------------|----------------|--------------------------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Trilog-Broadband Antenna | Schwarzbeck | VULB 9168 | 1462 | Dec. 13, 2024 |
| 2 | Attenuator | EMC INSTRUMENT | EMCI-N-6-06 | AT-06009 | Dec. 13, 2024 |
| 3 | Preamplifier | EMC INSTRUMENT | EMC001330 | 980863 | Apr. 07, 2025 |
| 4 | Cable | RegalWay | LMR400-NMNM-12.5m | N/A | Jul. 04, 2024 |
| 5 | Cable | RegalWay | LMR400-NMNM-3m | N/A | Jul. 04, 2024 |
| 6 | Cable | RegalWay | LMR400-NMNM-0.5m | N/A | Jul. 04, 2024 |
| 7 | Receiver | Agilent | N9038A | MY52130039 | Dec. 22, 2024 |
| 8 | Positioning Controller | MF | MF-7802 | N/A | N/A |
| 9 | Measurement Software | Farad | EZ-EMC Ver.NB-03A1-01 | N/A | N/A |
| 10 | 966 Chamber room | CM | 9*6*6 | N/A | May 16, 2025 |



| Radiated Emissions - Above 1 GHz | | | | | |
|----------------------------------|-----------------------------|------------------|-------------------------------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Receiver | Agilent | N9038A | MY52130039 | Dec. 22, 2024 |
| 2 | Preamplifier | EMC INSTRUMENT | EMC118A45SE | 980888 | Nov. 17, 2024 |
| 3 | EXA Spectrum Analyzer | Keysight | N9010A | MY55150209 | Jun. 16, 2024 |
| 4 | Double Ridged Guide Antenna | ETS | 3115 | 75789 | May 31, 2024 |
| 5 | Cable | RegalWay | RWLP50-4.0A-SMSM-1 2.5M | N/A | Feb. 19, 2025 |
| 6 | Cable | RegalWay | RWLP50-4.0A-NMRAS M-2.5M | N/A | Aug. 08, 2024 |
| 7 | Cable | RegalWay | RWLP50-4.0A-NMRAS MRA-0.8M | N/A | Aug. 08, 2024 |
| 8 | 966 Chamber room | CM | 9*6*6 | N/A | May 19, 2025 |
| 9 | Attenuator | Talent Microwave | TA10A2-S-18 | N/A | N/A |
| 10 | Filter | STI | STI15-9969 | N/A | Jun. 16, 2024 |
| 11 | Positioning Controller | MF | MF-7802 | N/A | N/A |
| 12 | Measurement Software | Farad | EZ-EMC Ver.NB-03A1-01 | N/A | N/A |

Remark "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.


6. EUT TEST PHOTO**Radiated Emissions Test Photos****30 MHz to 1 GHz**

Radiated Emissions Test Photos
Above 1 GHz



APPENDIX A - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

| | | | |
|-----------|-----------------------------|--------------|----------|
| Test Mode | TX AX(HE20) Mode Channel 48 | Polarization | Vertical |
|-----------|-----------------------------|--------------|----------|




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 44.065 | 37.23 | -11.45 | 25.78 | 40.00 | -14.22 | peak | |
| 2 | | 150.280 | 35.57 | -11.15 | 24.42 | 43.50 | -19.08 | peak | |
| 3 | | 432.550 | 37.86 | -7.14 | 30.72 | 46.00 | -15.28 | peak | |
| 4 | | 589.205 | 39.23 | -3.88 | 35.35 | 46.00 | -10.65 | peak | |
| 5 | | 747.315 | 37.43 | -1.17 | 36.26 | 46.00 | -9.74 | peak | |
| 6 | * | 912.700 | 38.01 | 0.25 | 38.26 | 46.00 | -7.74 | peak | |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

| | | | |
|-----------|-----------------------------|--------------|------------|
| Test Mode | TX AX(HE20) Mode Channel 48 | Polarization | Horizontal |
|-----------|-----------------------------|--------------|------------|




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 47.460 | 35.34 | -11.34 | 24.00 | 40.00 | -16.00 | peak | |
| 2 | | 163.375 | 35.90 | -10.97 | 24.93 | 43.50 | -18.57 | peak | |
| 3 | | 372.410 | 38.50 | -8.85 | 29.65 | 46.00 | -16.35 | peak | |
| 4 | | 482.990 | 38.07 | -6.19 | 31.88 | 46.00 | -14.12 | peak | |
| 5 | | 602.300 | 38.26 | -3.56 | 34.70 | 46.00 | -11.30 | peak | |
| 6 | * | 834.130 | 38.40 | -0.75 | 37.65 | 46.00 | -8.35 | peak | |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value

APPENDIX B - RADIATED EMISSION- ABOVE 1000 MHZ

| | | | |
|-----------|-----------------------------|--------------|----------|
| Test Mode | TX AX(HE20) Mode Channel 48 | Polarization | Vertical |
|-----------|-----------------------------|--------------|----------|




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 5150.000 | 42.79 | 11.54 | 54.33 | 74.00 | -19.67 | peak | |
| 2 | | 5150.000 | 34.47 | 11.54 | 46.01 | 54.00 | -7.99 | AVG | |
| 3 | * | 5242.300 | 103.13 | 11.72 | 114.85 | 68.20 | 46.65 | peak | No Limit |
| 4 | X | 5242.700 | 95.53 | 11.72 | 107.25 | 68.20 | 39.05 | AVG | No Limit |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

| | | | |
|-----------|-----------------------------|--------------|------------|
| Test Mode | TX AX(HE20) Mode Channel 48 | Polarization | Horizontal |
|-----------|-----------------------------|--------------|------------|




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 5150.000 | 36.99 | 11.54 | 48.53 | 74.00 | -25.47 | peak | |
| 2 | | 5150.000 | 28.16 | 11.54 | 39.70 | 54.00 | -14.30 | AVG | |
| 3 | X | 5239.100 | 86.68 | 11.73 | 98.41 | 68.20 | 30.21 | AVG | No Limit |
| 4 | * | 5239.300 | 95.01 | 11.73 | 106.74 | 68.20 | 38.54 | peak | No Limit |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value

| | | | |
|-----------|-----------------------------|--------------|----------|
| Test Mode | TX AX(HE20) Mode Channel 48 | Polarization | Vertical |
|-----------|-----------------------------|--------------|----------|




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | * | 10480.675 | 46.63 | 7.64 | 54.27 | 68.20 | -13.93 | peak | |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

| | | | |
|-----------|-----------------------------|--------------|------------|
| Test Mode | TX AX(HE20) Mode Channel 48 | Polarization | Horizontal |
|-----------|-----------------------------|--------------|------------|



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | * | 10478.200 | 40.98 | 7.64 | 48.62 | 68.20 | -19.58 | peak | |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value

End of Test Report