Shenzhen Global Test Service Co..Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation

GTS20230619008-1-4 Report Reference No.:: FCC ID.:: 2BCHCAIC8660-9001

Compiled by

(position+printed name+signature): File administrators Peter Xiao

Supervised by

(position+printed name+signature): Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) .: Manager Jason Hu

Date of issue: Aug.08, 2023

Shenzhen Global Test Service Co.,Ltd. **Representative Laboratory Name**

*

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Address::

Community, Pinghu Street, Longgang District, Shenzhen,

Guanadona

Applicant's name.....: **Aerospace Intelligent Control (Beijing) Monitoring**

Technology Co., Ltd.

F6, Building 9, No. 55 Zique Road, Haidian District, Beijing, China Address::

Test specification:

47CFR §1.1310 Basis and purpose

Standard....:: 47CFR §2.1091 Radiofrequency radiation exposure evaluation:

mobile devices

TRF Originator:: Shenzhen Global Test Service Co., Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description:: Multi-condition Full-information Intelligent Data Processor /

Wireless Intelligent Gateway

Trade Mark: N/A

Manufacturer: Aerospace Intelligent Control (Beijing) Monitoring Technology

Co., Ltd.

Model/Type reference: AIC8660-9001

Listed Models: AIC8640-02

Hardware Version:: N/A

Software Version: N/A

Rating.....: DC 12.0V/1.5A

Result: PASS

Report No.: GTS20230619008-1-4 Page 2 of 11

TEST REPORT

Test Report No. :	GTS20230619008-1-4	Aug.08, 2023
	G1G2G2GG01GGGG 1 4	Date of issue

Equipment under Test : Multi-condition Full-information Intelligent Data Processor /

Wireless Intelligent Gateway

Model /Type : AIC8660-9001

Listed model : AIC8640-02

Applicant : Aerospace Intelligent Control (Beijing) Monitoring Technology

Co., Ltd.

Address : F6, Building 9, No. 55 Zique Road, Haidian District, Beijing, China

Manufacturer : Aerospace Intelligent Control (Beijing) Monitoring Technology

Co., Ltd.

:

Address F6, Building 9, No. 55 Zique Road, Haidian District, Beijing, China

Test Result: PASS	
-------------------	--

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY	4
1.1 EUT CONFIGURATION	
2. TEST ENVIRONMENT	
2.1 Address of the test laboratory	
2.2 TEST FACILITY	
2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY	
3. METHOD OF MEASUREMENT	6
3.1 Applicable Standard	
3.3 LIMIT	
3.4 MPE CALCULATION METHOD	
4. CONDUCTED POWER RESULTS	8
5. MANUFACTURING TOLERANCE	9
6. MEASUREMENT RESULTS	10
6.1 Standalone MPE Evaluation	10
7. CONCLUSION	11

Report No.: GTS20230619008-1-4 Page 4 of 11

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

supplied by the manufacturer

 \circ - supplied by the lab

1	Length (m):	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name:	Multi-condition Full-information Intelligent Data Processor / Wireless Intelligent Gateway	
Trade Mark:	N/A	
Model/Type reference:	AIC8660-9001	
List Model:	AIC8640-02	
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different, So no additional models were tested.	
Power supply:	DC 12.0V/1.5A	
Hardware Version	N/A	
Software Version	N/A	
Sample ID	GTS20230619008-1-S0001-1#>S20230619008-1-S0001-2#	
ZigBee		
Frequency Range	2405MHz ~ 2480MHz	
Channel Number	16 channels	
Channel Spacing 5MHz		
Modulation Type	OQPSK	
Antenna Description	External antenna, 2.00 dBi(Max.) for 2.4G Band	

Report No.: GTS20230619008-1-4 Page 5 of 11

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Report No.: GTS20230619008-1-4 Page 6 of 11

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field planewave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time		
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm²)	(minute)		
	Limits for Occupational/Controlled Exposure					
0.3 - 3.0	614	1.63	(100) *	6		
3.0 - 30	1842/f	4.89/f	(900/f ²)*	6		
30 – 300	61.4	0.163	1.0	6		
300 – 1500	/	/	f/300	6		
1500 – 100,000	/	/	5	6		

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Elimite for Maximum 1 emillioniste Expedite (MLE)/effective a Expedite					
Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time	
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm²)	(minute)	
Limits for Occupational/Controlled Exposure					
0.3 - 3.0	614	1.63	(100) *	30	
3.0 - 30	824/f	2.19/f	$(180/f^2)^*$	30	
30 - 300	27.5	0.073	0.2	30	
300 – 1500	/	/	f/1500	30	
1500 – 100,000	/	/	1.0	30	

F=frequency in MHz

^{*=}Plane-wave equivalent power density

Report No.: GTS20230619008-1-4 Page 7 of 11

3.4 MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR²

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum soure-baed Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, r =20cm, as well as the gain of the used antenna is 2.00dBi for ZigBee, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

AIC8660-9001 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	ZigBee ANT0	External antenna	2.4 – 2.5 GHz	2.00dBi(Max.) for 2.4G band

Report No.: GTS20230619008-1-4 Page 8 of 11

4. Conducted Power Results

ZigBee

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
	0	2405	0.57
OQPSK	07	2440	1.88
	15	2480	1.45

Report No.: GTS20230619008-1-4 Page 9 of 11

5. Manufacturing Tolerance

ZigBee

OQPSK (Peak)					
Channel Channel 0 Channel 7 Channel 15					
Target (dBm) 0		1.0	1.0		
Tolerance ±(dB)	1.0	1.0	1.0		

Report No.: GTS20230619008-1-4 Page 10 of 11

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, r =20cm, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

ZigBee

Modulation Type	Output power		Antenna	Antenna	MPE	MPE
	dBm	mW	Gain	Gain (mW/cm²)	Limits	
			(dBi)	(linear)	(IIIVV/CIII)	(mW/cm²)
OQPSK	2.00	1.5849	2.00	1.5849	0.0005	1.0000

Remark:

- 1. Output power including tune-up tolerance;
- 2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

Report No.: GTS20230619008-1-4 Page 11 of 11

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.
End of Report