

TEST REPORT

Applicant Name: Fanvil Link Technology Co.,LTD
Address: A03, A08, 3rd Floor, Building 2, Daqian Industrial Plant, Zone 67, Xingdong Community, Xin'an Street, Bao'an District, Shenzhen ,China
Report Number: 2401U79863E-RFC
FCC ID: 2BCUQ-V62W
IC: 32680-V62W

Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2;
RSS-247 ISSUE 3, AUGUST 2023

Sample Description

Product Type: IP Phone
Model No.: V62W
Multiple Model(s) No.: V61W
Trade Mark: **Fanvil**
Date Received: 2024/06/11
Issue Date: 2024/08/05

| | |
|--------------|-------------------|
| Test Result: | Pass [▲] |
|--------------|-------------------|

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Jojo Guo

Jojo Guo
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY4

GENERAL INFORMATION.....5

PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....5

OBJECTIVE5

TEST METHODOLOGY5

MEASUREMENT UNCERTAINTY6

TEST FACILITY6

SYSTEM TEST CONFIGURATION.....7

DESCRIPTION OF TEST CONFIGURATION7

EUT EXERCISE SOFTWARE7

SPECIAL ACCESSORIES.....7

EQUIPMENT MODIFICATIONS7

SUPPORT EQUIPMENT LIST AND DETAILS8

EXTERNAL I/O CABLE.....8

BLOCK DIAGRAM OF TEST SETUP9

SUMMARY OF TEST RESULTS11

TEST EQUIPMENT LIST12

FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- RF EXPOSURE13

APPLICABLE STANDARD13

RESULT14

RSS-102 ISSUE 5 § 2.5.2 - EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION.....15

APPLICABLE STANDARD15

RESULT15

FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT16

APPLICABLE STANDARD16

ANTENNA CONNECTOR CONSTRUCTION16

FCC §15.207 (A) & RSS-GEN § 8.8 - AC LINE CONDUCTED EMISSIONS.....17

APPLICABLE STANDARD17

EUT SETUP17

EMI TEST RECEIVER SETUP.....17

TEST PROCEDURE17

FACTOR & OVER LIMIT CALCULATION.....18

TEST DATA18

FCC §15.209, §15.205 & §15.247(D) & RSS-247§ 5.5 - SPURIOUS EMISSIONS29

APPLICABLE STANDARD29

EUT SETUP29

EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP30

TEST PROCEDURE31

FACTOR & OVER LIMIT/MARGIN CALCULATION31

TEST DATA31

FCC §15.247(A) (1) & RSS-247 § 5.1 (B) - CHANNEL SEPARATION TEST50
 APPLICABLE STANDARD50
 TEST PROCEDURE50
 TEST DATA51

FCC §15.247(A) (1) & RSS-247 § 5.1 (A), RSS-GEN § 6.7 - 20 DB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH52
 APPLICABLE STANDARD52
 TEST PROCEDURE52
 TEST DATA53

FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - QUANTITY OF HOPPING CHANNEL TEST.....54
 APPLICABLE STANDARD54
 TEST PROCEDURE54
 TEST DATA55

FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME)56
 APPLICABLE STANDARD56
 TEST PROCEDURE56
 TEST DATA57

FCC §15.247(B) (1) & RSS-247§ 5.1(B) &§ 5.4(B) - PEAK OUTPUT POWER MEASUREMENT58
 APPLICABLE STANDARD58
 TEST PROCEDURE58
 TEST DATA59

FCC §15.247(D) & RSS-247 § 5.5 - BAND EDGES TESTING60
 APPLICABLE STANDARD60
 TEST PROCEDURE60
 TEST DATA61

EUT PHOTOGRAPHS62

TEST SETUP PHOTOGRAPHS63

APPENDIX64
 APPENDIX A: 20DB EMISSION BANDWIDTH.....64
 APPENDIX B: OCCUPIED CHANNEL BANDWIDTH70
 APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....76
 APPENDIX D: CARRIER FREQUENCY SEPARATION81
 APPENDIX E: TIME OF OCCUPANCY84
 APPENDIX F: NUMBER OF HOPPING CHANNELS94
 APPENDIX G: BAND EDGE MEASUREMENTS97

DOCUMENT REVISION HISTORY

| Revision Number | Report Number | Description of Revision | Date of Revision |
|-----------------|-----------------|-------------------------|------------------|
| 0 | 2401U79863E-RFC | Original Report | 2024/08/05 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|---|--|
| HVIN | V62W, V61W |
| FVIN | Test_rf_telnet |
| Product | IP Phone |
| Tested Model | V62W |
| Multiple Model(s) | V61W |
| Frequency Range | Bluetooth: 2402-2480MHz |
| Transmit Power | 6.32dBm |
| Modulation Technique | Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Antenna Specification [#] | 5.1dBi (provided by the applicant) |
| Voltage Range | DC 5V from adapter or DC 48V from POE |
| Sample serial number | For Model: V62W: 2MMX-3 for Conducted and Radiated Emissions 2MMX-1 for RF Conducted Test For Model: V61W: 2MMX-8 for Conducted and Radiated Emissions (Assigned by BAACL, Shenzhen) |
| Sample/EUT Status | Good condition |
| Adapter Information | Adapter 1 Model: F05L5-050100SPAU Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5.0V, 1.0A, 5.0W Adapter 2 Model: DCT06W050100US-D0 Input: AC 100-240V, 50/60Hz, 200mA Output: DC 5.0V, 1.0A |
| Note: The Multiple models are electrically identical with the test model except for model name, button, button PCB and sales channels. Please refer to the declaration letter [#] for more detail, which was provided by manufacturer. | |

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021Amendment 2 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021Amendment 2 of the Innovation, Science and Economic Development Canada rules.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

| Parameter | | Uncertainty |
|------------------------------------|--------------------------------------|---------------------------------------|
| Occupied Channel Bandwidth | | ±5% |
| RF output power, conducted | | 0.72 dB(k=2, 95% level of confidence) |
| AC Power Lines Conducted Emissions | 9kHz-150kHz | 3.94dB(k=2, 95% level of confidence) |
| | 150kHz-30MHz | 3.84dB(k=2, 95% level of confidence) |
| Radiated Emissions | 9kHz - 30MHz | 3.30dB(k=2, 95% level of confidence) |
| | 30MHz~200MHz (Horizontal) | 4.48dB(k=2, 95% level of confidence) |
| | 30MHz~200MHz (Vertical) | 4.55dB(k=2, 95% level of confidence) |
| | 200MHz~1000MHz (Horizontal) | 4.85dB(k=2, 95% level of confidence) |
| | 200MHz~1000MHz (Vertical) | 5.05dB(k=2, 95% level of confidence) |
| | 1GHz - 6GHz | 5.35dB(k=2, 95% level of confidence) |
| | 6GHz - 18GHz | 5.44dB(k=2, 95% level of confidence) |
| 18GHz - 40GHz | 5.16dB(k=2, 95% level of confidence) | |
| Temperature | | ±1°C |
| Humidity | | ±1% |
| Supply voltages | | ±0.4% |

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0 | 2402 | 40 | 2442 |
| 1 | 2403 | 41 | 2443 |
| 2 | 2404 | 42 | 2444 |
| ... | ... | ... | ... |
| ... | ... | ... | ... |
| 36 | 2438 | 75 | 2477 |
| 37 | 2439 | 76 | 2478 |
| 38 | 2440 | 77 | 2479 |
| 39 | 2441 | 78 | 2480 |

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

“Moba Xterm #” exercise software was used and the power level is default #. The power level was provided by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|--------------------|---------------|
| BULL | Receptacle | GN-415K | 5503290068073 |
| Grandstream | IP Phone | GXV3480 | T11223323B898 |
| N/A | Earphone1 | N/A | N/A |
| N/A | Earphone2 | N/A | N/A |
| HIKVISION | Router | DS-3WR03 | 10021642429 |
| Lenovo | PC | TIANYI510Pro-18ICB | R3NO28B21001 |


External I/O Cable

| Cable Description | Length (m) | From Port | To |
|------------------------------------|------------|------------|------------|
| Un-shielded un-detachable AC cable | 1.2 | Receptacle | LISN/Mains |
| Un-shielded un-detachable DC cable | 1.5 | Adapter | EUT |
| Un-shielded detachable RJ45 cable | 8.0 | Router | EUT |
| Un-shielded detachable RJ45 cable | 8.0 | PC | EUT |
| Un-shielded detachable RJ45 cable | 1.0 | Router | IP Phone |


Block Diagram of Test Setup

For conducted emission:


For adapter:




For POE:



For radiated emission below 1GHz:



For radiated emission above 1GHz:



SUMMARY OF TEST RESULTS

| FCC Rules | RSS Rules | Description of Test | Result |
|--|---------------------------------|--|---------------|
| §15.247 (i), §1.1307 (b) (3) & §2.1091 | RSS-102 Issue 5 § 2.5.2 | RF Exposure & Exemption Limits for Routine Evaluation – RF Exposure Evaluation | Compliant |
| FCC §15.203 | RSS-Gen §6.8 | Antenna Requirement | Compliant |
| FCC §15.207(a) | RSS-Gen §8.8 | AC Line Conducted Emissions | Compliant |
| FCC §15.205, §15.209, §15.247(d) | RSS-247 § 5.5, RSS-GEN § 8.10 | Radiated Emissions | Compliant |
| FCC §15.247(a)(1) | RSS-247 § 5.1(a), RSS-GEN § 6.7 | 20 dB Emission Bandwidth & 99% Occupied Bandwidth | Compliant |
| FCC §15.247(a)(1) | RSS-247 § 5.1 (b) | Channel Separation Test | Compliant |
| FCC §15.247(a)(1)(iii) | RSS-247 § 5.1 (d) | Time of Occupancy (Dwell Time) | Compliant |
| FCC §15.247(a)(1)(iii) | RSS-247 § 5.1 (d) | Quantity of hopping channel Test | Compliant |
| FCC §15.247(b)(1) | RSS-247 § 5.1(b) & § 5.4(b) | Peak Output Power Measurement | Compliant |
| FCC §15.247(d) | RSS-247 § 5.5 | Band edges | Compliant |

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------------|-------------------------|-------------------------|------------------------|------------------|----------------------|
| Conducted Emission Test | | | | | |
| Unknown | CE Cable | Unknown | UF A210B-1-0720-504504 | 2024/05/21 | 2025/05/20 |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 101120 | 2024/01/16 | 2025/01/15 |
| Rohde & Schwarz | LISN | ENV216 | 101613 | 2024/01/16 | 2025/01/15 |
| Rohde & Schwarz | Transient Limiter | ESH3Z2 | DE25985 | 2024/05/21 | 2025/05/20 |
| Audix | EMI Test software | E3 | 191218(V9) | NCR | NCR |
| Radiated Emission Test | | | | | |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-1 | 2023/07/20 | 2026/07/19 |
| Rohde & Schwarz | EMI Test Receiver | ESR3 | 102455 | 2024/01/16 | 2025/01/15 |
| Sonoma instrument | Pre-amplifier | 310N | 186238 | 2024/05/21 | 2025/05/20 |
| BACL | Active Loop Antenna | 1313-1A | 4031911 | 2024/05/14 | 2027/05/13 |
| Unknown | Cable | Chamber Cable 1 | F-03-EM236 | 2024/05/21 | 2025/05/20 |
| Unknown | Cable | XH500C | J-10M-A | 2024/05/21 | 2025/05/20 |
| A.H.System | Pre-amplifier | PAM-1840VH | 190 | 2023/08/02 | 2024/08/01 |
| Electro-Mechanics Co | Horn Antenna | 3116 | 9510-2270 | 2023/09/18 | 2026/09/17 |
| SNSD | 2.4G Band Reject filter | BSF2402-2480MN-0898-001 | 2.4G filter | 2023/08/03 | 2024/08/02 |
| Unknown | RF Cable | KMSE | 0735 | 2023/10/08 | 2024/10/07 |
| Unknown | RF Cable | XH750A-N | J-10M | 2024/06/18 | 2025/06/17 |
| Unknown | RF Cable | UFA147 | 219661 | 2023/10/08 | 2024/10/07 |
| Schwarzbeck | Horn Antenna | BBHA9120D(1201) | 1143 | 2023/07/26 | 2026/07/25 |
| COM-POWER | Pre-amplifier | PA-122 | 181919 | 2024/06/18 | 2025/06/17 |
| Rohde&Schwarz | Spectrum Analyzer | FSV40 | 101605 | 2024/03/27 | 2025/03/26 |
| Audix | EMI Test software | E3 | 19821b(V9) | NCR | NCR |
| RF Conducted Test | | | | | |
| Rohde & Schwarz | Spectrum Analyzer | FSV40 | 101473 | 2024/01/16 | 2025/01/15 |
| Tonscend | RF control Unit | JS0806-2 | 19D8060154 | 2023/09/06 | 2024/09/05 |
| MARCONI | 10dB Attenuator | 6534/3 | 2942 | 2024/06/27 | 2025/06/26 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- RF EXPOSURE

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34 | $1,920 R^2$. |
| 1.34-30 | $3,450 R^2/f^2$. |
| 30-300 | $3.83 R^2$. |
| 300-1,500 | $0.0128 R^2f$. |
| 1,500-100,000 | $19.2R^2$. |

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

For worst case:

| Mode | Frequency (MHz) | Tune up conducted power [#] | Antenna Gain [#] | | ERP | | Evaluation Distance (m) | ERP Limit (mW) |
|------|-----------------|--------------------------------------|---------------------------|-------|-------|------|-------------------------|----------------|
| | | (dBm) | (dBi) | (dBd) | (dBm) | (mW) | | |
| BT | 2402-2480 | 6.5 | 5.1 | 2.95 | 9.45 | 8.81 | 0.2 | 768 |

Note 1: The tune-up power and antenna gain was declared by the applicant.

Note 2: 0dBd=2.15dBi.

Note 3: The BT and wifi cannot transmit at same time.

To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

RSS-102 Issue 5 § 2.5.2 - EXEMPTION LIMITS FOR ROUTINE EVALUATION- RF EXPOSURE EVALUATION

Applicable Standard

According to RSS-102 Issue 5 § (2.5.2):

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance). In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Result

Calculated Data:

The max tune-up conducted output power is 6.5 dBm, antenna gain is 5.1dBi.

Time-averaged maximum e.i.r.p. of the device is $6.5\text{dBm} + 5.1\text{dBi} = 11.6\text{dBm} = 0.014\text{ W}$

The worst case is $f = 2402\text{ MHz}$:

The limit is $1.31 \times 10^{-2} f^{0.6834}\text{ W} = 2.68\text{ W}$

$0.014\text{ W} < 2.68\text{ W}$

Note: The BT and wifi cannot transmit at same time.

So the RF Exposure evaluation can be exempted.

FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to FCC § 15.203, the applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device’s antenna shall be stated, based on a measurement or on data from the antenna’s manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device’s ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangement which was permanently attached for Bluetooth and the maximum antenna gain[#] is 5.1dBi, fulfill the requirement of this section. Please refer to the EUT photos.

| Antenna Type | Antenna Gain [#] | Impedance | Frequency Range |
|--------------|---------------------------|-----------|-----------------|
| Integral | 5.1dBi | 50Ω | 2.4~2.5GHz |


Result: Compliant

FCC §15.207 (a) & RSS-GEN § 8.8 - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), RSS-GEN § 8.8

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207 & RSS-Gen.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data


Environmental Conditions

| | |
|---------------------------|---------|
| Temperature: | 25°C |
| Relative Humidity: | 75 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Macy Shi from 2024-07-19 to 2024-08-01.

EUT operation mode: Transmitting (maximum output power mode 8DPSK, Low Channel)

For Model: V62W
 For Adapter 1
 AC 120V/60 Hz, Line




Date: 2024-07-19

Condition: Line
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.16 | 15.17 | 36.15 | 10.87 | 10.11 | 55.30 | -19.15 | Average |
| 2 | 0.16 | 23.41 | 44.39 | 10.87 | 10.11 | 65.30 | -20.91 | QP |
| 3 | 0.20 | 11.57 | 32.45 | 10.79 | 10.09 | 53.45 | -21.00 | Average |
| 4 | 0.20 | 19.55 | 40.43 | 10.79 | 10.09 | 63.45 | -23.02 | QP |
| 5 | 0.48 | 17.99 | 38.63 | 10.51 | 10.13 | 46.32 | -7.69 | Average |
| 6 | 0.48 | 26.40 | 47.04 | 10.51 | 10.13 | 56.32 | -9.28 | QP |
| 7 | 0.51 | 16.11 | 36.75 | 10.50 | 10.14 | 46.00 | -9.25 | Average |
| 8 | 0.51 | 25.12 | 45.76 | 10.50 | 10.14 | 56.00 | -10.24 | QP |
| 9 | 2.65 | 6.00 | 26.65 | 10.48 | 10.17 | 46.00 | -19.35 | Average |
| 10 | 2.65 | 16.16 | 36.81 | 10.48 | 10.17 | 56.00 | -19.19 | QP |
| 11 | 11.20 | 17.52 | 38.33 | 10.60 | 10.21 | 50.00 | -11.67 | Average |
| 12 | 11.20 | 25.62 | 46.43 | 10.60 | 10.21 | 60.00 | -13.57 | QP |

AC 120V/60 Hz, Neutral




Date: 2024-07-19

Condition: Neutral
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.17 | 13.50 | 34.14 | 10.53 | 10.11 | 55.21 | -21.07 | Average |
| 2 | 0.17 | 22.51 | 43.15 | 10.53 | 10.11 | 65.21 | -22.06 | QP |
| 3 | 0.21 | 9.98 | 30.48 | 10.41 | 10.09 | 53.27 | -22.79 | Average |
| 4 | 0.21 | 18.43 | 38.93 | 10.41 | 10.09 | 63.27 | -24.34 | QP |
| 5 | 0.49 | 11.45 | 32.28 | 10.69 | 10.14 | 46.14 | -13.86 | Average |
| 6 | 0.49 | 21.31 | 42.14 | 10.69 | 10.14 | 56.14 | -14.00 | QP |
| 7 | 0.51 | 11.35 | 32.19 | 10.70 | 10.14 | 46.00 | -13.81 | Average |
| 8 | 0.51 | 22.08 | 42.92 | 10.70 | 10.14 | 56.00 | -13.08 | QP |
| 9 | 2.14 | 8.66 | 29.24 | 10.40 | 10.18 | 46.00 | -16.76 | Average |
| 10 | 2.14 | 15.11 | 35.69 | 10.40 | 10.18 | 56.00 | -20.31 | QP |
| 11 | 21.83 | 7.62 | 28.46 | 10.66 | 10.18 | 50.00 | -21.54 | Average |
| 12 | 21.83 | 14.72 | 35.56 | 10.66 | 10.18 | 60.00 | -24.44 | QP |

For Adapter 2
AC 120V/60 Hz, Line


Date: 2024-07-19



Condition: Line
Project : 2401U79863E-RF
tester : Macy.shi
Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.19 | 12.06 | 32.97 | 10.82 | 10.09 | 53.98 | -21.01 | Average |
| 2 | 0.19 | 16.94 | 37.85 | 10.82 | 10.09 | 63.98 | -26.13 | QP |
| 3 | 0.23 | 5.74 | 26.57 | 10.75 | 10.08 | 52.39 | -25.82 | Average |
| 4 | 0.23 | 15.12 | 35.95 | 10.75 | 10.08 | 62.39 | -26.44 | QP |
| 5 | 0.33 | 24.93 | 45.69 | 10.64 | 10.12 | 49.49 | -3.80 | Average |
| 6 | 0.33 | 27.92 | 48.68 | 10.64 | 10.12 | 59.49 | -10.81 | QP |
| 7 | 0.50 | 18.90 | 39.54 | 10.50 | 10.14 | 46.00 | -6.46 | Average |
| 8 | 0.50 | 26.51 | 47.15 | 10.50 | 10.14 | 56.00 | -8.85 | QP |
| 9 | 2.03 | 8.35 | 29.13 | 10.59 | 10.19 | 46.00 | -16.87 | Average |
| 10 | 2.03 | 12.09 | 32.87 | 10.59 | 10.19 | 56.00 | -23.13 | QP |
| 11 | 11.44 | 8.63 | 29.44 | 10.60 | 10.21 | 50.00 | -20.56 | Average |
| 12 | 11.44 | 19.34 | 40.15 | 10.60 | 10.21 | 60.00 | -19.85 | QP |

AC 120V/60 Hz, Neutral




Condition: Neutral
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.15 | 10.41 | 31.13 | 10.59 | 10.13 | 55.82 | -24.69 | Average |
| 2 | 0.15 | 19.67 | 40.39 | 10.59 | 10.13 | 65.82 | -25.43 | QP |
| 3 | 0.27 | 4.22 | 24.81 | 10.50 | 10.09 | 50.98 | -26.17 | Average |
| 4 | 0.27 | 13.70 | 34.29 | 10.50 | 10.09 | 60.98 | -26.69 | QP |
| 5 | 0.50 | 16.68 | 37.52 | 10.70 | 10.14 | 46.00 | -8.48 | Average |
| 6 | 0.50 | 25.19 | 46.03 | 10.70 | 10.14 | 56.00 | -9.97 | QP |
| 7 | 0.68 | 10.30 | 31.14 | 10.70 | 10.14 | 46.00 | -14.86 | Average |
| 8 | 0.68 | 18.80 | 39.64 | 10.70 | 10.14 | 56.00 | -16.36 | QP |
| 9 | 2.14 | 2.90 | 23.48 | 10.40 | 10.18 | 46.00 | -22.52 | Average |
| 10 | 2.14 | 10.32 | 30.90 | 10.40 | 10.18 | 56.00 | -25.10 | QP |
| 11 | 11.44 | 4.02 | 25.03 | 10.80 | 10.21 | 50.00 | -24.97 | Average |
| 12 | 11.44 | 13.45 | 34.46 | 10.80 | 10.21 | 60.00 | -25.54 | QP |

For POE
AC 120V/60 Hz, Line


Date: 2024-08-01



Condition: Line
Project : 2401U79863E-RF
tester : Macy.shi
Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.15 | 10.01 | 31.03 | 10.89 | 10.13 | 55.82 | -24.79 | Average |
| 2 | 0.15 | 14.77 | 35.79 | 10.89 | 10.13 | 65.82 | -30.03 | QP |
| 3 | 0.23 | 2.88 | 23.71 | 10.75 | 10.08 | 52.30 | -28.59 | Average |
| 4 | 0.23 | 16.57 | 37.40 | 10.75 | 10.08 | 62.30 | -24.90 | QP |
| 5 | 0.44 | 1.95 | 22.60 | 10.54 | 10.11 | 47.11 | -24.51 | Average |
| 6 | 0.44 | 11.06 | 31.71 | 10.54 | 10.11 | 57.11 | -25.40 | QP |
| 7 | 0.58 | 2.68 | 23.30 | 10.50 | 10.12 | 46.00 | -22.70 | Average |
| 8 | 0.58 | 13.53 | 34.15 | 10.50 | 10.12 | 56.00 | -21.85 | QP |
| 9 | 2.26 | 0.35 | 21.08 | 10.55 | 10.18 | 46.00 | -24.92 | Average |
| 10 | 2.26 | 8.19 | 28.92 | 10.55 | 10.18 | 56.00 | -27.08 | QP |
| 11 | 24.53 | 4.92 | 25.81 | 10.70 | 10.19 | 50.00 | -24.19 | Average |
| 12 | 24.53 | 14.34 | 35.23 | 10.70 | 10.19 | 60.00 | -24.77 | QP |

AC 120V/60 Hz, Neutral



Date: 2024-08-01


Condition: Neutral
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.15 | 7.62 | 28.32 | 10.58 | 10.12 | 55.74 | -27.42 | Average |
| 2 | 0.15 | 12.45 | 33.15 | 10.58 | 10.12 | 65.74 | -32.59 | QP |
| 3 | 0.20 | 3.81 | 24.30 | 10.40 | 10.09 | 53.54 | -29.24 | Average |
| 4 | 0.20 | 7.58 | 28.07 | 10.40 | 10.09 | 63.54 | -35.47 | QP |
| 5 | 0.46 | 3.20 | 23.99 | 10.67 | 10.12 | 46.76 | -22.77 | Average |
| 6 | 0.46 | 10.24 | 31.03 | 10.67 | 10.12 | 56.76 | -25.73 | QP |
| 7 | 12.19 | 18.08 | 39.09 | 10.80 | 10.21 | 50.00 | -10.91 | Average |
| 8 | 12.19 | 26.56 | 47.57 | 10.80 | 10.21 | 60.00 | -12.43 | QP |
| 9 | 18.82 | 12.10 | 33.00 | 10.72 | 10.18 | 50.00 | -17.00 | Average |
| 10 | 18.82 | 17.60 | 38.50 | 10.72 | 10.18 | 60.00 | -21.50 | QP |
| 11 | 24.53 | 10.10 | 30.89 | 10.60 | 10.19 | 50.00 | -19.11 | Average |
| 12 | 24.53 | 16.90 | 37.69 | 10.60 | 10.19 | 60.00 | -22.31 | QP |

For Model: V61W

For Adapter 2(according to the test result of model V62W, adapter 2 was worst, so for model V61W, adapter 2 was select to test.)

AC 120V/60 Hz, Line




Date: 2024-07-19

Condition: Line
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.15 | 12.59 | 33.60 | 10.89 | 10.12 | 55.74 | -22.14 | Average |
| 2 | 0.15 | 20.65 | 41.66 | 10.89 | 10.12 | 65.74 | -24.08 | QP |
| 3 | 0.21 | 9.46 | 30.33 | 10.78 | 10.09 | 53.10 | -22.77 | Average |
| 4 | 0.21 | 16.62 | 37.49 | 10.78 | 10.09 | 63.10 | -25.61 | QP |
| 5 | 0.33 | 24.38 | 45.14 | 10.64 | 10.12 | 49.49 | -4.35 | Average |
| 6 | 0.33 | 27.54 | 48.30 | 10.64 | 10.12 | 59.49 | -11.19 | QP |
| 7 | 0.50 | 12.90 | 33.54 | 10.50 | 10.14 | 46.00 | -12.46 | Average |
| 8 | 0.50 | 21.34 | 41.98 | 10.50 | 10.14 | 56.00 | -14.02 | QP |
| 9 | 2.01 | 8.06 | 28.85 | 10.60 | 10.19 | 46.00 | -17.15 | Average |
| 10 | 2.01 | 14.32 | 35.11 | 10.60 | 10.19 | 56.00 | -20.89 | QP |
| 11 | 13.41 | 7.34 | 28.16 | 10.60 | 10.22 | 50.00 | -21.84 | Average |
| 12 | 13.41 | 17.82 | 38.64 | 10.60 | 10.22 | 60.00 | -21.36 | QP |

AC 120V/60 Hz, Neutral

Date: 2024-07-19




Condition: Neutral
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.15 | 9.67 | 30.37 | 10.58 | 10.12 | 55.74 | -25.37 | Average |
| 2 | 0.15 | 19.91 | 40.61 | 10.58 | 10.12 | 65.74 | -25.13 | QP |
| 3 | 0.25 | 3.43 | 23.99 | 10.48 | 10.08 | 51.69 | -27.70 | Average |
| 4 | 0.25 | 14.29 | 34.85 | 10.48 | 10.08 | 61.69 | -26.84 | QP |
| 5 | 0.33 | 15.65 | 36.33 | 10.56 | 10.12 | 49.49 | -13.16 | Average |
| 6 | 0.33 | 22.19 | 42.87 | 10.56 | 10.12 | 59.49 | -16.62 | QP |
| 7 | 0.50 | 8.60 | 29.44 | 10.70 | 10.14 | 46.00 | -16.56 | Average |
| 8 | 0.50 | 18.63 | 39.47 | 10.70 | 10.14 | 56.00 | -16.53 | QP |
| 9 | 2.01 | 2.47 | 23.06 | 10.40 | 10.19 | 46.00 | -22.94 | Average |
| 10 | 2.01 | 9.25 | 29.84 | 10.40 | 10.19 | 56.00 | -26.16 | QP |
| 11 | 7.89 | 4.00 | 24.93 | 10.73 | 10.20 | 50.00 | -25.07 | Average |
| 12 | 7.89 | 12.37 | 33.30 | 10.73 | 10.20 | 60.00 | -26.70 | QP |

For POE
AC 120V/60 Hz, Line

Date: 2024-08-01




Condition: Line
Project : 2401U79863E-RF
tester : Macy.shi
Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.16 | 5.81 | 26.82 | 10.89 | 10.12 | 55.65 | -28.83 | Average |
| 2 | 0.16 | 9.86 | 30.87 | 10.89 | 10.12 | 65.65 | -34.78 | QP |
| 3 | 0.19 | 8.61 | 29.52 | 10.82 | 10.09 | 54.15 | -24.63 | Average |
| 4 | 0.19 | 13.61 | 34.52 | 10.82 | 10.09 | 64.15 | -29.63 | QP |
| 5 | 0.34 | 3.17 | 23.92 | 10.63 | 10.12 | 49.31 | -25.39 | Average |
| 6 | 0.34 | 8.49 | 29.24 | 10.63 | 10.12 | 59.31 | -30.07 | QP |
| 7 | 12.06 | 8.60 | 29.41 | 10.60 | 10.21 | 50.00 | -20.59 | Average |
| 8 | 12.06 | 14.80 | 35.61 | 10.60 | 10.21 | 60.00 | -24.39 | QP |
| 9 | 19.02 | 15.40 | 36.43 | 10.85 | 10.18 | 50.00 | -13.57 | Average |
| 10 | 19.02 | 18.80 | 39.83 | 10.85 | 10.18 | 60.00 | -20.17 | QP |
| 11 | 24.02 | 10.04 | 30.95 | 10.72 | 10.19 | 50.00 | -19.05 | Average |
| 12 | 24.02 | 18.57 | 39.48 | 10.72 | 10.19 | 60.00 | -20.52 | QP |

AC 120V/60 Hz, Neutral

Date: 2024-08-01



Condition: Neutral
 Project : 2401U79863E-RF
 tester : Macy.shi
 Note : BT

| | Read Freq | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|----|-----------|------------|------------|-------------|------------|------------|------------|---------|
| | MHz | dBuV | dBuV | dB | dB | dBuV | dB | |
| 1 | 0.15 | 9.26 | 29.98 | 10.59 | 10.13 | 55.82 | -25.84 | Average |
| 2 | 0.15 | 13.60 | 34.32 | 10.59 | 10.13 | 65.82 | -31.50 | QP |
| 3 | 0.39 | 3.56 | 24.28 | 10.61 | 10.11 | 48.17 | -23.89 | Average |
| 4 | 0.39 | 12.17 | 32.89 | 10.61 | 10.11 | 58.17 | -25.28 | QP |
| 5 | 4.95 | 2.10 | 22.79 | 10.51 | 10.18 | 46.00 | -23.21 | Average |
| 6 | 4.95 | 10.41 | 31.10 | 10.51 | 10.18 | 56.00 | -24.90 | QP |
| 7 | 12.06 | 9.80 | 30.81 | 10.80 | 10.21 | 50.00 | -19.19 | Average |
| 8 | 12.06 | 16.90 | 37.91 | 10.80 | 10.21 | 60.00 | -22.09 | QP |
| 9 | 19.85 | 13.20 | 34.07 | 10.70 | 10.17 | 50.00 | -15.93 | Average |
| 10 | 19.85 | 17.30 | 38.17 | 10.70 | 10.17 | 60.00 | -21.83 | QP |
| 11 | 24.02 | 11.56 | 32.36 | 10.61 | 10.19 | 50.00 | -17.64 | Average |
| 12 | 24.02 | 17.42 | 38.22 | 10.61 | 10.19 | 60.00 | -21.78 | QP |


FCC §15.209, §15.205 & §15.247(D) & RSS-247§ 5.5 - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d); RSS-247§ 5.5; RSS-GEN § 8.10

EUT Setup


9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247, RSS-247, RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Measurement |
|-------------------|---|-----------|---------|-------------|
| 9 kHz – 150 kHz | / | / | 200 Hz | QP |
| | 300 Hz | 1 kHz | / | PK |
| 150 kHz – 30 MHz | / | / | 9 kHz | QP |
| | 10 kHz | 30 kHz | / | PK |
| 30 MHz – 1000 MHz | / | / | 120 kHz | QP |
| | 100 kHz | 300 kHz | / | PK |
| Above 1 GHz | Harmonics & Band Edge | | | |
| | 1MHz | 3 MHz | / | PK |
| | Average Emission Level=Peak Emission Level+20*log(Duty cycle) | | | |
| | Other Emissions | | | |
| | 1MHz | 3 MHz | / | PK |
| | 1MHz | 10 Hz | / | Average |

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 22~25.6°C |
| Relative Humidity: | 50~54 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Anson Su on 2024-07-19 for below 1GHz and Sadow Tan on 2024-07-15 for above 1GHz.

EUT operation mode: Transmitting

Note: for below 1GHz range, the POE power mode was evaluated under the worst case mode(5G wifi) according to the result of adapter, it was verified POE power mode compliance with requirement, so the POE mode not performed in this report.

Note: After pre-scan in the X, Y and Z axes of orientation, the worst case as below:

9 kHz-30MHz: *(maximum output power mode 8DPSK, Low Channel)*


The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.

30MHz-1GHz: (maximum output power mode 8DPSK, Low Channel)

For Model: V62W

For Adapter 1


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number: 2401U79863E-RF
 Test Mode : BT
 Tester : Anson Su

| | Freq | Factor | Read Level | Level | Limit | Over | Remark |
|---|--------|--------|------------|--------|--------|--------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 40.03 | -11.54 | 23.99 | 12.45 | 40.00 | -27.55 | QP |
| 2 | 197.98 | -13.73 | 46.76 | 33.03 | 43.50 | -10.47 | QP |
| 3 | 233.96 | -14.20 | 49.68 | 35.48 | 46.00 | -10.52 | QP |
| 4 | 306.08 | -12.67 | 45.29 | 32.62 | 46.00 | -13.38 | QP |
| 5 | 341.98 | -12.11 | 44.29 | 32.18 | 46.00 | -13.82 | QP |
| 6 | 850.29 | -4.82 | 40.20 | 35.38 | 46.00 | -10.62 | QP |

Vertical




Site : Chamber A
 Condition : 3m Vertical
 Project Number: 2401U79863E-RF
 Test Mode : BT
 Tester : Anson Su

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 43.79 | -15.16 | 38.28 | 23.12 | 40.00 | -16.88 | QP |
| 2 | 58.72 | -18.82 | 39.66 | 20.84 | 40.00 | -19.16 | QP |
| 3 | 197.98 | -14.81 | 49.30 | 34.49 | 43.50 | -9.01 | QP |
| 4 | 233.96 | -14.86 | 42.66 | 27.80 | 46.00 | -18.20 | QP |
| 5 | 549.98 | -8.26 | 35.53 | 27.27 | 46.00 | -18.73 | QP |
| 6 | 850.29 | -5.12 | 34.09 | 28.97 | 46.00 | -17.03 | QP |

For Adapter 2


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number: 2401U79863E-RF
 Test Mode : BT
 Tester : Anson Su

| | Freq | Factor | Read Level | Level | Limit | Over | Remark |
|---|--------|--------|------------|--------|--------|--------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 40.29 | -11.70 | 23.41 | 11.71 | 40.00 | -28.29 | QP |
| 2 | 98.44 | -15.85 | 29.51 | 13.66 | 43.50 | -29.84 | QP |
| 3 | 197.98 | -13.73 | 47.10 | 33.37 | 43.50 | -10.13 | QP |
| 4 | 234.07 | -14.20 | 49.33 | 35.13 | 46.00 | -10.87 | QP |
| 5 | 650.23 | -6.73 | 31.21 | 24.48 | 46.00 | -21.52 | QP |
| 6 | 850.29 | -4.82 | 39.60 | 34.78 | 46.00 | -11.22 | QP |

Vertical




Site : Chamber A
 Condition : 3m Vertical
 Project Number: 2401U79863E-RF
 Test Mode : BT
 Tester : Anson Su

| | Freq | Factor | Read Level | Limit Level | Over Limit | Remark |
|---|--------|--------|------------|-------------|------------|-----------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB |
| 1 | 43.79 | -15.16 | 35.76 | 20.60 | 40.00 | -19.40 QP |
| 2 | 62.76 | -18.80 | 38.99 | 20.19 | 40.00 | -19.81 QP |
| 3 | 197.98 | -14.81 | 43.08 | 28.27 | 43.50 | -15.23 QP |
| 4 | 233.96 | -14.86 | 41.52 | 26.66 | 46.00 | -19.34 QP |
| 5 | 594.09 | -8.24 | 38.40 | 30.16 | 46.00 | -15.84 QP |
| 6 | 850.29 | -5.12 | 34.37 | 29.25 | 46.00 | -16.75 QP |

For Model: V61W

For Adapter 1 (according to the test result of model V62W, adapter 1 was worst, so for model V61W, adapter 1 was select to test)


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number: 2401U79863E-RF
 Test Mode : BT
 Tester : Anson Su

| | Freq | Factor | Read Level | Level | Limit | Over | Remark |
|---|--------|--------|------------|--------|--------|--------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 41.46 | -12.45 | 25.31 | 12.86 | 40.00 | -27.14 | QP |
| 2 | 108.84 | -13.35 | 32.37 | 19.02 | 43.50 | -24.48 | QP |
| 3 | 150.01 | -13.57 | 37.94 | 24.37 | 43.50 | -19.13 | QP |
| 4 | 249.97 | -14.53 | 46.50 | 31.97 | 46.00 | -14.03 | QP |
| 5 | 750.11 | -5.54 | 36.90 | 31.36 | 46.00 | -14.64 | QP |
| 6 | 850.29 | -4.82 | 39.98 | 35.16 | 46.00 | -10.84 | QP |

Vertical



Site : Chamber A
 Condition : 3m Vertical
 Project Number: 2401U79863E-RF
 Test Mode : BT
 Tester : Anson Su

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 43.77 | -15.15 | 37.96 | 22.81 | 40.00 | -17.19 | QP |
| 2 | 62.95 | -18.80 | 38.08 | 19.28 | 40.00 | -20.72 | QP |
| 3 | 197.98 | -14.81 | 43.94 | 29.13 | 43.50 | -14.37 | QP |
| 4 | 249.97 | -14.93 | 42.09 | 27.16 | 46.00 | -18.84 | QP |
| 5 | 550.22 | -8.26 | 35.58 | 27.32 | 46.00 | -18.68 | QP |
| 6 | 850.29 | -5.12 | 33.24 | 28.12 | 46.00 | -17.88 | QP |

Above 1GHz: (model V62W was tested)

| Frequency (MHz) | Receiver | | Polar (H/V) | Factor (dB/m) | Corrected Amplitude (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
|--------------------------|----------------|--------|-------------|---------------|------------------------------|----------------|-------------|
| | Reading (dBµV) | PK/Ave | | | | | |
| 8DPSK(worst case) | | | | | | | |
| Low Channel 2402MHz | | | | | | | |
| 2374.08 | 54.49 | PK | H | -3.20 | 51.29 | 74 | -22.71 |
| 2360.19 | 54.20 | PK | V | -3.18 | 51.02 | 74 | -22.98 |
| 4804.00 | 58.86 | PK | H | 1.69 | 60.55 | 74 | -13.45 |
| 4804.00 | 55.84 | PK | V | 1.69 | 57.53 | 74 | -16.47 |
| Middle Channel 2441MHz | | | | | | | |
| 4882.00 | 54.94 | PK | H | 1.69 | 56.63 | 74 | -17.37 |
| 4882.00 | 52.17 | PK | V | 1.69 | 53.86 | 74 | -20.14 |
| High Channel 2480MHz | | | | | | | |
| 2499.59 | 54.15 | PK | H | -3.20 | 50.95 | 74 | -23.05 |
| 2489.21 | 54.46 | PK | V | -3.18 | 51.28 | 74 | -22.72 |
| 4960.00 | 50.99 | PK | H | 2.77 | 53.76 | 74 | -20.24 |
| 4960.00 | 48.59 | PK | V | 2.77 | 51.36 | 74 | -22.64 |

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

| Field Strength of Average | | | | | | | |
|---------------------------|-------------------------------|-------------|----------------------------------|------------------------|----------------|-------------|----------|
| Frequency (MHz) | Peak Measurement @3m (dBµV/m) | Polar (H/V) | Duty Cycle Corrected Factor (dB) | Average Level (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Comment |
| Low Channel 2402MHz | | | | | | | |
| 2374.08 | 51.29 | H | -24.73 | 26.56 | 54 | -27.44 | Bandedge |
| 2360.19 | 51.02 | V | -24.73 | 26.29 | 54 | -27.71 | Bandedge |
| 4804.00 | 60.55 | H | -24.73 | 35.82 | 54 | -18.18 | Harmonic |
| 4804.00 | 57.53 | V | -24.73 | 32.80 | 54 | -21.20 | Harmonic |
| Middle Channel 2441MHz | | | | | | | |
| 4882.00 | 56.63 | H | -24.73 | 31.90 | 54 | -22.10 | Harmonic |
| 4882.00 | 53.86 | V | -24.73 | 29.13 | 54 | -24.87 | Harmonic |
| High Channel 2480MHz | | | | | | | |
| 2499.59 | 50.95 | H | -24.73 | 26.22 | 54 | -27.78 | Bandedge |
| 2489.21 | 51.28 | V | -24.73 | 26.55 | 54 | -27.45 | Bandedge |
| 4960.00 | 53.76 | H | -24.73 | 29.03 | 54 | -24.97 | Harmonic |
| 4960.00 | 51.36 | V | -24.73 | 26.63 | 54 | -27.37 | Harmonic |


Note: Average level= Peak level+ Duty Cycle Corrected Factor

Worst case duty cycle:

Duty cycle = Ton/100ms = 2.90*2/100=0.058


Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.058 = -24.73

**Duty Cycle
(100ms)**



ProjectNo.:2401U79863E-RF Tester:Sadow Tan
Date: 15.JUL.2024 15:46:48


**Duty Cycle
(1s)**



ProjectNo.:2401U79863E-RF Tester:Sadow Tan
Date: 15.JUL.2024 15:44:01

Test plots for Band Edge Measurements (Radiated):


| 8DPSK | | | |
|---------------|---------|---------------|------------|
| Test Channel: | 2480MHz | Ant. Polar. : | Horizontal |



Condition : Horizontal
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480

| 1 | Freq Factor | | Read Level | | Limit | Over | Remark |
|---|-------------|-------|------------|--------|-------|--------|--------|
| | MHz | dB/m | dBuV | dBuV/m | Line | Limit | |
| | 2499.594 | -3.20 | 54.15 | 50.95 | 74.00 | -23.05 | peak |


| 8DPSK | | | |
|---------------|---------|---------------|----------|
| Test Channel: | 2480MHz | Ant. Polar. : | Vertical |



Condition : Vertical
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480


| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|----------|--------|------------|--------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 2489.206 | -3.18 | 54.46 | 51.28 | 74.00 | -22.72 | peak |

Harmonic Measurements:



Vertical


1-4GHz



Condition : Vertical
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|----------|--------|------------|--------|------------|------------|---------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 3907.375 | -0.48 | 33.79 | 33.31 | 54.00 | -20.69 | Average |
| 2 | 3907.375 | -0.48 | 48.53 | 48.05 | 74.00 | -25.95 | Peak |

Horizontal




4-18GHz

Condition : Horizontal
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|-----------|--------|------------|--------|------------|------------|---------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 4960.000 | 2.77 | 50.99 | 53.76 | 74.00 | -20.24 | Peak |
| 2 | 17917.750 | 24.04 | 22.66 | 46.70 | 54.00 | -7.30 | Average |
| 3 | 17917.750 | 24.04 | 37.91 | 61.95 | 74.00 | -12.05 | Peak |

Vertical




4-18GHz

Condition : Vertical
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|-----------|--------|------------|--------|------------|------------|---------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 4960.000 | 2.77 | 48.59 | 51.36 | 74.00 | -22.64 | Peak |
| 2 | 14860.500 | 16.71 | 30.27 | 46.98 | 54.00 | -7.02 | Average |
| 3 | 14860.500 | 16.71 | 45.27 | 61.98 | 74.00 | -12.02 | Peak |

Horizontal

18-25GHz




Condition : Horizontal
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|-----------|--------|------------|--------|------------|------------|---------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 23473.130 | 17.43 | 26.42 | 43.85 | 54.00 | -10.15 | Average |
| 2 | 23473.130 | 17.43 | 41.62 | 59.05 | 74.00 | -14.95 | peak |

Vertical

18-25GHz



Condition : Vertical
 Project No.: 2401U79863E-RF
 Tester : Sadow Tan
 Note : BT_2480

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|-----------|--------|------------|--------|------------|------------|---------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 24359.500 | 18.66 | 25.74 | 44.40 | 54.00 | -9.60 | Average |
| 2 | 24359.500 | 18.66 | 40.79 | 59.45 | 74.00 | -14.55 | peak |

FCC §15.247(a) (1) & RSS-247 § 5.1 (b) - CHANNEL SEPARATION TEST

Applicable Standard

According to FCC §15.247(a) (1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


According to RSS-247 § 5.1 (b):

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.2

1. Set the EUT in transmitting mode, max hold the channel.
2. Set the adjacent channel of the EUT and max hold another trace.
3. Measure the channel separation.



Test Data**Environmental Conditions**

| | |
|---------------------------|---------|
| Temperature: | 24 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Navilite Cai on 2024-07-12.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) & RSS-247 § 5.1 (a), RSS-GEN § 6.7 - 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

Applicable Standard

According to FCC §15.247(a) (1):

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to RSS-247 § 5.1 (a), RSS-GEN § 6.7:

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “20 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

Test Procedure


Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data

Environmental Conditions

| | |
|---------------------------|---------|
| Temperature: | 24 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Navilite Cai on 2024-07-12.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


According to RSS-247 § 5.1 (d):

Frequency hopping systems (FHSS) operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.3

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.



Test Data**Environmental Conditions**

| | |
|---------------------------|---------|
| Temperature: | 24 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Navilite Cai on 2024-07-12.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


According to RSS-247 § 5.1 (d):

Frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses



Note 1: A period time= $0.4 \times 79 = 31.6(S)$, Result=BurstWidth*Totalhops

Note 2: Totalhops=Hopping Number in $3.16s \times 10$

Note 3: Hopping Number in $3.16s =$ Total of highest signals in $3.16s$ (Second high signals were other channel)

Test Data**Environmental Conditions**

| | |
|---------------------------|---------|
| Temperature: | 24 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Navilite Cai on 2024-07-12.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (1) & RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to FCC §15.247(b) (1):

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

According to RSS-247§ 5.1(b) &§ 5.4(b):


For frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.5

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data**Environmental Conditions**

| | |
|---------------------------|---------|
| Temperature: | 24 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Navilite Cai on 2024-07-12.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(d) & RSS-247 § 5.5 - BAND EDGES TESTING

Applicable Standard

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


According to RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(e), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data**Environmental Conditions**

| | |
|---------------------------|---------|
| Temperature: | 24 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Navilite Cai on 2024-07-12.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

EUT PHOTOGRAPHS

Please refer to the attachment 2401U79863E-RF External photo and 2401U79863E-RF Internal photo.


TEST SETUP PHOTOGRAPHS



Please refer to the attachment 2401U79863E-RFC Test Setup photo.



APPENDIX**Appendix A: 20dB Emission Bandwidth****Test Result**



| Test Mode | Antenna | Frequency[MHz] | 20db EBW[MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|---------------|---------|---------|------------|---------|
| DH1 | Ant1 | 2402 | 0.94 | 2401.53 | 2402.47 | --- | --- |
| | | 2441 | 0.94 | 2440.53 | 2441.48 | --- | --- |
| | | 2480 | 0.95 | 2479.53 | 2480.48 | --- | --- |
| 2DH1 | Ant1 | 2402 | 1.31 | 2401.33 | 2402.65 | --- | --- |
| | | 2441 | 1.31 | 2440.33 | 2441.65 | --- | --- |
| | | 2480 | 1.31 | 2479.33 | 2480.65 | --- | --- |
| 3DH1 | Ant1 | 2402 | 1.28 | 2401.36 | 2402.64 | --- | --- |
| | | 2441 | 1.28 | 2440.36 | 2441.64 | --- | --- |
| | | 2480 | 1.28 | 2479.36 | 2480.64 | --- | --- |


Test Graphs
















Appendix B: Occupied Channel Bandwidth**Test Result**



| Test Mode | Antenna | Frequency[MHz] | OCB [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|-----------|-----------|-----------|------------|---------|
| DH1 | Ant1 | 2402 | 0.839 | 2401.5774 | 2402.4166 | --- | --- |
| | | 2441 | 0.836 | 2440.5804 | 2441.4166 | --- | --- |
| | | 2480 | 0.833 | 2479.5804 | 2480.4136 | --- | --- |
| 2DH1 | Ant1 | 2402 | 1.193 | 2401.4036 | 2402.5964 | --- | --- |
| | | 2441 | 1.187 | 2440.4036 | 2441.5904 | --- | --- |
| | | 2480 | 1.181 | 2479.4036 | 2480.5844 | --- | --- |
| 3DH1 | Ant1 | 2402 | 1.172 | 2401.4246 | 2402.5964 | --- | --- |
| | | 2441 | 1.169 | 2440.4246 | 2441.5934 | --- | --- |
| | | 2480 | 1.166 | 2479.4276 | 2480.5934 | --- | --- |


Test Graphs














Appendix C: Maximum Conducted Output Power



Test Result Peak



| Test Mode | Antenna | Frequency [MHz] | Conducted Peak Power [dBm] | Conducted Limit[dBm] | EIRP[dBm] | EIRP Limit[dBm] | Verdict |
|-----------|---------|-----------------|----------------------------|----------------------|-----------|-----------------|---------|
| DH1 | Ant1 | 2402 | 3.42 | ≤20.97 | 8.52 | ≤36.00 | PASS |
| | | 2441 | 1.48 | ≤20.97 | 6.58 | ≤36.00 | PASS |
| | | 2480 | 0.42 | ≤20.97 | 5.52 | ≤36.00 | PASS |
| 2DH1 | Ant1 | 2402 | 5.82 | ≤20.97 | 10.92 | ≤36.00 | PASS |
| | | 2441 | 4.13 | ≤20.97 | 9.23 | ≤36.00 | PASS |
| | | 2480 | 2.80 | ≤20.97 | 7.90 | ≤36.00 | PASS |
| 3DH1 | Ant1 | 2402 | 6.32 | ≤20.97 | 11.42 | ≤36.00 | PASS |
| | | 2441 | 4.50 | ≤20.97 | 9.60 | ≤36.00 | PASS |
| | | 2480 | 3.22 | ≤20.97 | 8.32 | ≤36.00 | PASS |


Test Graphs














Appendix D: Carrier Frequency Separation**Test Result**

| Test Mode | Antenna | Frequency[MHz] | Result[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|-------------|--------------|---------|
| DH1 | Ant1 | Hop | 1.003 | ≥ 0.627 | PASS |
| 2DH1 | Ant1 | Hop | 1 | ≥ 0.873 | PASS |
| 3DH1 | Ant1 | Hop | 1.003 | ≥ 0.853 | PASS |

Test Graphs





Appendix E: Time of occupancy**Test Result**


| Test Mode | Antenna | Frequency[MHz] | Burst Width [ms] | Total Hops [Num] | Result[s] | Limit[s] | Verdict |
|-----------|---------|----------------|------------------|------------------|-----------|----------|---------|
| DH1 | Ant1 | Hop | 0.365 | 320 | 0.117 | ≤0.4 | PASS |
| DH3 | Ant1 | Hop | 1.611 | 170 | 0.274 | ≤0.4 | PASS |
| DH5 | Ant1 | Hop | 2.853 | 130 | 0.371 | ≤0.4 | PASS |
| 2DH1 | Ant1 | Hop | 0.374 | 320 | 0.120 | ≤0.4 | PASS |
| 2DH3 | Ant1 | Hop | 1.619 | 170 | 0.275 | ≤0.4 | PASS |
| 2DH5 | Ant1 | Hop | 2.858 | 120 | 0.343 | ≤0.4 | PASS |
| 3DH1 | Ant1 | Hop | 0.375 | 330 | 0.124 | ≤0.4 | PASS |
| 3DH3 | Ant1 | Hop | 1.618 | 180 | 0.291 | ≤0.4 | PASS |
| 3DH5 | Ant1 | Hop | 2.860 | 130 | 0.372 | ≤0.4 | PASS |



Note 1: A period time= $0.4 \times 79 = 31.6$ (S), Result=BurstWidth*Totalhops



Note 2: Totalhops=Hopping Number in $3.16s \times 10$



Note 3: Hopping Number in $3.16s =$ Total of highest signals in $3.16s$ (Second high signals were other channel)



Test Graphs






























Appendix F: Number Of Hopping Channels**Test Result**

| Test Mode | Antenna | Frequency[MHz] | Result[Num] | Limit[Num] | Verdict |
|-----------|---------|----------------|-------------|------------|---------|
| DH1 | Ant1 | Hop | 79 | ≥ 15 | PASS |
| 2DH1 | Ant1 | Hop | 79 | ≥ 15 | PASS |
| 3DH1 | Ant1 | Hop | 79 | ≥ 15 | PASS |



Test Graphs








Appendix G: Band Edge Measurements

Test Graphs






2DH1_Ant1_Low_2402







ProjectNo.: 2401U79863E-RF Tester: Navilite.Cai
 Date: 12.JUL.2024 11:52:24



2DH1_Ant1_High_2480



ProjectNo.: 2401U79863E-RF Tester: Navilite.Cai
 Date: 12.JUL.2024 11:59:30







***** END OF REPORT *****