

Part Acknowledgment Letter

Part acknowledgement

Full name of supplier: Donguan Ierice Technology Co., Ltd.

Address of supplier: 96 Long Wu Road, Tai Ling Shan, Dongguan (3F, building L, Kam Hung Tat Science and Technology Park)

Name of material: Watch coil

Material specifications: Soft magnetic 25 * 2.6MM 0.08 * 24P 7.7UH-8.0UH single stranded double layer tape Soft magnetic 25 * 2.6MM 0.08 * 24P 7.7UH-8.0UH single stranded double layer tape

Type and model: W406

Customer name: Luoxin Electronics

Customer data: E28-00021

Sample delivery time: 2023-7-20

Notes: ☐ New materials: ☐ Alternative:

Acknowledge the results	☐ Qualified ☐ Disqualified
	Reasons for non-conformance:
	Acceptance of non-conformance and sample handling: ☐ Return purchase ☐ Disposal



Signature of supplier		
Applicant	Quality	Approved
Lu Lin	Liang Meixiang	Lu Rusheng
Recognition Stamp		
Date: 2023.7.20		

Recognize the signature				
Applicant	Tester	Project	Quality	Approved
Recognition Stamp				
Date:				



一、Table of contents

1. Cover	Page 1-1
2. Table of contents	Page 2-2
3. Product drawings	Page 3-3
4. Size Map	Page 4-4
5. Product parameters	Page 5-5
6. Technical requirements	Page 5-5
7. Electrical parameters	Page 5-5
8. Packaging	Page 6-6
9. Bill of materials	Page 7-7

二、Product drawing:



三、 A plan: unit:MM



A	7.65±0.05
B	2.5±0.05
C	2±1
D	14±0.2
E	20.7±0.3
F	21±0.2
G	7.7±0.5
H	13.5±0.2
I	23.5±0.2
J	25±0.3
K	2.5±0.1
L	2.25±0.1
M	40±1

四、Product parameters:

Feet	Diameter of the line	Number of turns	Notes
1 - 2	0.08*24P	14	Hot Air Strand

五、Technical requirements:

1. Fix the head and tail of thread to prevent loose and broken thread
2. According to customer's requirements, the length of wire shears, Tinning, tinning depth of $2 \pm 1\text{MM}$
3. In the magnetic point on the appropriate white glue, paste the coil, the process to ensure that the product surface clean and tidy
4. The soft disk used is with round hole, no damage
5. Install 7.65x2.5 mm magnet in the middle hole of the finished product and paste 14mm diameter round double-sid adhesive on the back of the finished product

六、Electrical parameters:

1. Inductance value, Q value:

$$\text{PIN PIN } 1 - 2 = 7.7 \sim 8.0\text{UH}$$

The above inductance values are based on chuanhua 1062A instrument, using 10KHZ/0.3 vrms as the standard or equivalent instrument. The Q value is based on chuanhua 1062A instrument and 100KHZ/0.3 vrms or equivalent instrument

七、Packaging:




Figure 1: Single-layer foam tray, 1 box packing 240 pcs



Figure 2: Uniform Direction Line head up neatly into the disk



Figure 3: put into the packing box, each box put 10 layers



Figure 4: sealing the box with transparent glue

江西络鑫科技有限公司			
进料标签			客户: JX
供应商	LX1265		ROHS
订单号	J3301-2307000834		
料号	E28-00021		
规格	G2*25-3400GS-7.8UH-7MM		
数量	2400	单位	PCS
生产周期	2333		
生产批次	20230720001		
交货日期	2023/7/20		

Figure 5: Packaging label



Figure 6: materials stacked, neat, labels to facilitate the search for materials

八、 Bill of materials:

NO	Name	Material	Suppliers	Notes
1	Hot Air Line	0.08*24P	Uyghur or equivalent	
2	Disk	G25 soft substrate	TX or equivalent	
3	Tin	Hightemperature environmental protection	Thond Island or equivalent	
4	White glue	BY882	Treasure month or equivalent	
5	Double-sided glue	513-14mm	Hung Fai or equivalent	
6	Strong magnetism	7.65*2.5(s t r e n g t h 3400± 200GS)	Win-win or equal	