



Maximum Permissible Exposure Report

1. Product Information

EUT	: Home Automation Controller
Test Model	: OliverIQ Home Automation Controller (Gen 1)
Power Supply	: Input: 5V $\overline{\text{---}}$ 3.0A For AC Adapter Input: 100-240V~, 50/60Hz, 0.7A Max Adapter Output: 5V $\overline{\text{---}}$ 3A
Hardware Version	: RKH230509
Software Version	: FW20240124
Bluetooth:	
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V4.0(DSS) 40 channels for Bluetooth V4.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V4.0 (DSS) 2MHz for Bluetooth V4.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.0(DSS) GFSK for Bluetooth V4.0 (DTS)
Bluetooth Version	: V4.0
Antenna Description	: Ant1: FPC Antenna, 2.36dBi(Max.)
WIFI(2.4G Band):	
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: FPC Antenna, 2.36dBi(Max.) Ant2: FPC Antenna, 2.36dBi(Max.)
WIFI(5.2G Band):	
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: FPC Antenna, 2.59dBi(Max.) Ant2: FPC Antenna, 2.59dBi(Max.)
WIFI(5.3G Band):	
Frequency Range	: 5260MHz~5320MHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Channel Number	: 4 Channels for 20MHz bandwidth(5260MHz~5320MHz) 2 channels for 40MHz bandwidth(5270MHz~5310MHz) 1 channels for 80MHz bandwidth(5290MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: FPC Antenna, 2.59dBi(Max.) Ant2: FPC Antenna, 2.59dBi(Max.)
WIFI(5.5G Band):	
Frequency Range	: 5500MHz~5700MHz
Channel Number	: 11 Channels for 20MHz bandwidth(5500MHz~5700MHz) 5 Channels for 40MHz bandwidth(5510MHz~5670MHz) 2 Channels for 80MHz bandwidth(5530MHz, 5610MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: FPC Antenna, 2.59dBi(Max.) Ant2: FPC Antenna, 2.59dBi(Max.)
WIFI(5.8G Band)	
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: FPC Antenna, 2.59dBi(Max.) Ant2: FPC Antenna, 2.59dBi(Max.)
Zigbee	
Frequency Range	: 2405MHz-2480MHz
Channel Spacing	: 5MHz
Channel Number	: 16 Channels
Modulation Type	: O-QPSK
Antenna Description	: FPC Antenna, 2.0dBi(Max.)
Z-Wave	
Frequency Range	: 908.42MHz
Channel Number	: 1
Modulation Type	: GFSK
Antenna Description	: Metal Antenna, 0.78dBi(Max)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density
P=power input to antenna
G=power gain of the antenna in the direction of interest relative to an isotropic radiator
R=distance to the center of radiation of the antenna

5. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-0.94
	39	2441	-0.48
	78	2480	-0.45
$\pi/4$ DQPSK	0	2402	0.37
	39	2441	0.65
	78	2480	0.76
8DPSK	0	2402	0.3
	39	2441	0.74
	78	2480	0.85

[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE_1M	0	2402	0.39
	19	2440	0.84
	39	2480	0.99

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Peak Conducted Output Power (dBm)	Ant 2 Peak Conducted Output Power (dBm)
11B	1	2412	15.29	14.01
	6	2437	15.7	14.16
	11	2462	15.3	14.1
11G	1	2412	14.67	13.23
	6	2437	14.12	13.6
	11	2462	14.9	13.57
11N20 SISO	1	2412	13.07	12.71
	6	2437	13.36	12.82
	11	2462	13.17	12.8





11N40 SISO	3	2412	12.77	11.02
	6	2437	12.62	11.86
	9	2462	12.47	11.64

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
11N20 MIMO	1	2412	15.90
	6	2437	16.11
	11	2462	16.00
11N40 MIMO	3	2412	14.99
	6	2437	15.27
	9	2462	15.09

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	36	5180	12.34	11.44
	40	5200	12.42	12.15
	48	5240	13	12.11
11N20 SISO	36	5180	11.9	10.82
	40	5200	11.6	10.7
	48	5240	11.58	10.64
11N40 SISO	38	5190	10.57	9.47
	46	5230	10.63	9.87
11AC20 SISO	36	5180	11.86	10.88
	40	5200	11.59	10.61
	48	5240	11.57	10.6
11AC40 SISO	38	5190	10.59	9.55
	46	5230	10.75	9.94
11AC80 SISO	42	5210	9.8	8.42

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	36	5180	14.40
	40	5200	14.18
	48	5240	14.15
11N40 MIMO	38	5190	13.07
	46	5230	13.28
11AC20 MIMO	36	5180	14.41
	40	5200	14.14



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



	48	5240	14.12
11AC40 MIMO	38	5190	13.11
	46	5230	13.37
11AC80 MIMO	42	5210	12.17

[5.3G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
IEEE 802.11a	52	5260	13.19	11.28
	60	5280	13.09	11.28
	64	5320	12.71	11.74
IEEE 802.11n HT20	52	5260	11.78	10.99
	60	5280	11.49	10.54
	64	5320	12.1	11.19
IEEE 802.11n HT40	54	5270	10.89	10.23
	62	5310	10.83	10.19
IEEE 802.11ac VHT20	52	5260	11.71	10.87
	60	5280	11.49	10.52
	64	5320	12.04	11.06
IEEE 802.11ac VHT40	54	5270	10.37	9.61
	62	5310	11.23	10.16
IEEE 802.11ac VHT80	58	5290	9.42	8.7

[5.3G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	52	5260	14.41
	60	5280	14.05
	64	5320	14.68
11N40 MIMO	54	5270	13.58
	62	5310	13.53
11AC20 MIMO	52	5260	14.32
	60	5280	14.04
	64	5320	14.59
11AC40 MIMO	54	5270	13.02
	62	5310	13.74
11AC80 MIMO	58	5290	12.09

[5.5G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
------	---------	-----------------	--------------------------------------	--------------------------------------



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



11A	100	5500	12.51	11.54
	116	5580	12.48	11.43
	140	5700	12.48	11.41
11N20 SISO	100	5500	11.74	10.76
	116	5580	11.89	10.83
	140	5700	11.93	10.92
11N40 SISO	102	5510	10.96	10.1
	110	5550	11.01	9.34
	134	5670	11.21	9.53
11AC20 SISO	100	5500	11.79	10.89
	116	5580	11.65	10.94
	140	5700	11.76	10.95
11AC40 SISO	102	5510	11.2	9.51
	110	5550	11.04	9.31
	134	5670	10.51	9.56
11AC80 SISO	106	5530	10.11	9.14
	122	5610	10.23	8.5

[5.5G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	100	5500	14.29
	116	5580	14.40
	140	5700	14.46
11N40 MIMO	102	5510	13.56
	110	5550	13.27
	134	5670	13.46
11AC20 MIMO	100	5500	14.37
	116	5580	14.32
	140	5700	14.38
11AC40 MIMO	102	5510	13.45
	110	5550	13.27
	134	5670	13.07
11AC80 MIMO	106	5530	12.66
	122	5610	12.46

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	149	5745	12.53	11.96
	157	5785	12.57	11.58
	165	5825	12.74	11.88



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



11N20 SISO	149	5745	11.85	11.03
	157	5785	11.95	11.01
	165	5825	12.14	10.42
11N40 SISO	151	5755	10.64	9.24
	159	5795	10.28	9.96
11AC20 SISO	149	5745	11.83	10.55
	157	5785	11.85	10.59
	165	5825	12.17	10.45
11AC40 SISO	151	5755	10.54	9.33
	159	5795	10.34	9.46
11AC80 SISO	155	5775	9.35	8.27

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	149	5745	14.47
	157	5785	14.52
	165	5825	14.37
11N40 MIMO	151	5755	13.01
	159	5795	13.13
11AC20 MIMO	149	5745	14.25
	157	5785	14.28
	165	5825	14.40
11AC40 MIMO	151	5755	12.99
	159	5795	12.93
11AC80 MIMO	155	5775	11.85

< Zigbee Max Conducted Power >< Ant1>

Mode	Channel	Frequency (MHz)	Max Conducted Power (dBm)
O-QPSK	0	2405	-0.18
	7	2440	0.03
	15	2480	0.02

Z-wave(GFSK): 908.42MHz

TX frequency (the Worst):908.42MHz

Max. Field Strength: 87.18dBuV/m @3m

EIRP=E-104.7+20logD=87.18-104.7+20log3=-7.98dBm

Maximum Conducted Output Power: -7.98dBm

Turn-up: -7±1



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**6. Manufacturing Tolerance**

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance \pm (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance \pm (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance \pm (dB)	1.0	1.0	1.0

[BLE]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance \pm (dB)	1.0	1.0	1.0

[2.4G WIFI]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N20 MIMO(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N40 MIMO(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	14.0	15.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20 MIMO(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40 MIMO(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	13.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC20 MIMO(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40 MIMO(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	13.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC80 MIMO(Average)			
Channel	Channel 42		
Target (dBm)	12.0		
Tolerance ±(dB)	1.0		

[5.3G WIFI]

11A (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	13.0	13.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT20 MIMO(Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT40 MIMO(Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	13.0	13.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT20 MIMO(Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT40 MIMO(Average)			



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Channel	Channel 54	Channel 62
Target (dBm)	13.0	13.0
Tolerance ± (dB)	1.0	1.0
11AC VHT80 MIMO(Average)		
Channel	Channel 58	
Target (dBm)	12.0	
Tolerance ± (dB)	1.0	

[5.5G WIFI]

11A (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT20 MIMO(Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT40 MIMO(Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	13.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT20 MIMO(Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC HT40 MIMO(Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	13.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT80 MIMO(Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	12.0	12.0	
Tolerance ± (dB)	1.0	1.0	

[5.8G WIFI]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	12.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20 MIMO(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40 MIMO(Average)			



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Channel	Channel 151		Channel 159	
Target (dBm)	13.0		13.0	
Tolerance \pm (dB)	1.0		1.0	
11AC20 MIMO(Average)				
Channel	Channel 149	Channel 157	Channel 165	
Target (dBm)	14.0	14.0	14.0	
Tolerance \pm (dB)	1.0	1.0	1.0	
11AC40 MIMO(Average)				
Channel	Channel 151		Channel 159	
Target (dBm)	12.0		12.0	
Tolerance \pm (dB)	1.0		1.0	
11AC80 MIMO(Average)				
Channel	Channel 155			
Target (dBm)	11.0			
Tolerance \pm (dB)	1.0			

<Zigbee>

O-QPSK (Peak)			
Channel	Channel 0	Channel 7	Channel 15
Target (dBm)	0	0	0
Tolerance \pm (dB)	1.0	1.0	1.0

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	1.0	1.2589	2.36	1.7219	0.0004	1.0000
$\pi/4$ -DQPSK	1.0	1.2589	2.36	1.7219	0.0004	1.0000
8-DPSK	1.0	1.2589	2.36	1.7219	0.0004	1.0000

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT LE	1.0	1.2589	2.36	1.7219	0.0004	1.0000

[2.4G WIFI]

Modulation Type	Output power	Antenna	Antenna	MPE	MPE
-----------------	--------------	---------	---------	-----	-----



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



	dBm	mW	Gain (dBi)	Gain (linear)	(mW/cm ²)	Limits (mW/cm ²)
IEEE 802.11b	16.0	39.8107	2.36	1.7219	0.0136	1.0000
IEEE 802.11g	15.0	31.6228	2.36	1.7219	0.0108	1.0000
IEEE 802.11n HT20 MIMO	17.0	50.1187	5.37	3.4435	0.0344	1.0000
IEEE 802.11n HT40 MIMO	16.0	39.8107	5.37	3.4435	0.0273	1.0000

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	2.59	1.8155	0.0091	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11n HT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11ac VHT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT80 MIMO	13.0	19.9526	5.60	3.6308	0.0144	1.0000

[5.3G WIFI]

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	2.59	1.8155	0.0091	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11n HT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11ac VHT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT80 MIMO	13.0	19.9526	5.60	3.6308	0.0144	1.0000

[5.5G WIFI]

Band/Mode	RF output power		Antenna Gain	Antenna Gain	MPE (mW/cm ²)	MPE Limits
	dBm	mW				





			(dBi)	(linear)		(mW/cm ²)
IEEE 802.11a	13.0	19.9526	2.59	1.8155	0.0072	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11n HT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11ac VHT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT80 MIMO	13.0	19.9526	5.60	3.6308	0.0144	1.0000

[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	2.59	1.8155	0.0072	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11n HT40 MIMO	14.0	25.1189	5.60	3.6308	0.0182	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	5.60	3.6308	0.0229	1.0000
IEEE 802.11ac VHT40 MIMO	13.0	19.9526	5.60	3.6308	0.0144	1.0000
IEEE 802.11ac VHT80 MIMO	12.0	15.8489	5.60	3.6308	0.0115	1.0000

<Zigbee>

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
O-QPSK	1.0	1.2589	2.0	1.5849	0.0004	1.0000

< Z-wave >

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	-6.0	0.2512	0.78	1.1967	0.0001	0.6056

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



8.2 Simultaneous Transmission MPE Evaluation

The EUT equipped with one BT/2.4GWIFI/5G WIFI antenna, one 2.4GWIFI/5G WIFI antenna, one Zigbee antenna and one Z-Wave antenna. So, need consider simultaneous transmission;
 According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 $\Sigma\Sigma$ of MPE ratios ≤ 1.0

Mode	WLAN MIMO MPE (mW/cm ²)	Zigbee MPE (mW/cm ²)	Z-Wave MPE (mW/cm ²)	Σ MPE ratios	Limit	Results
Ant1+ Ant2+ Ant3+ Ant4	0.0344	0.0004	0.0001	0.0349	1.0	PASS

Remark:

1. Output power including turn-up tolerance;
2. BT/BLE/2.4G WIFI output power is burst peak power;
3. 5G WIFI output power is burst average power;
4. MPE evaluate distance is 20cm from user manual provide by manufacturer;
5. MPE values = $PG/4\pi R^2$

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

