

# TEST REPORT

Report No.: BCTC2408779616-2E

---

Applicant: CMS Electracom

---

Product Name: Echo Qi2 Wireless Charger

---

Test Model: ECW3

---


Tested Date: 2024-08-21 to 2024-08-30

---

Issued Date: 2024-10-15

---


**Shenzhen BCTC Testing Co., Ltd.**



# FCC ID: 2BD57-ECW3

Product Name: Echo Qi2 Wireless Charger  
Trademark: CMS Electracom  
Model/Type reference: ECW3  
Prepared For: CMS Electracom  
Address: 24 Binney Rd kings Park New South Wales 2148 Australia  
Manufacturer: Shenzhen Xiaodi Network Technology Co., Ltd  
Address: 3-4/F, building D, De Mei Industiral center, Donghuan Second Road, Longhua New District, Shenzhen, China  
Prepared By: Shenzhen BCTC Testing Co., Ltd.  
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China  
Sample Received Date: 2024-08-21  
Sample tested Date: 2024-08-21 to 2024-08-30  
Report No.: BCTC2408779616-2E  
Test Standards: FCC CFR 47 part1, 1.1307(b), 1.1310  
KDB 680106 D01 Wireless Power Transfer v04  
Test Results: PASS

Tested by:



Brave Zeng/ Project Handler

Approved by:



Zero Zhou/Reviewer


The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.



## Table Of Content

Test Report Declaration	Page
1. Version .....	4
2. Product Information .....	5
2.1 Product Information .....	5
2.2 Support Equipment .....	5
2.3 Test Mode .....	5
3. Test Facility And Test Instrument Used .....	6
3.1 Test Facility .....	6
3.2 Test Instrument Used .....	6
4. Method Of Measurement .....	7
4.1 Applicable Standard .....	7
4.2 Block Diagram Of Test Setup .....	7
4.3 Limit .....	8
4.4 Test procedure .....	8
4.5 Equipment Approval Considerations .....	9
4.6 E and H field Strength .....	10
5. Photographs Of Test Set-Up .....	13

(Note: N/A Means Not Applicable)




BCTC  
 BCTC  
 PPR  
 Report

**1. Version**

Report No.	Issue Date	Description	Approved
BCTC2408779616-2E	2024-10-15	Original	Valid

TEC  
TC  
OVB  
t See



## 2. Product Information

### 2.1 Product Information

Model/Type reference:	ECW3
Model differences:	N/A
Operation Frequency:	112kHz-205kHz
Type of Modulation:	ASK
Antenna installation:	loop coil antenna
Ratings:	Input: AC 100-240V,50-60HZ Output: 15W
Hardware Version:	N/A
Software Version:	N/A

### 2.2 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Echo Qi2 Wireless Charger	N/A	ECW3	N/A	EUT
E-2	Dummy load	N/A	N/A	N/A	Auxiliary

#### Notes:

- All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### 2.3 Test Mode

Test Mode 1	Wireless charger 15W (Phone)
-------------	------------------------------

### 3. Test Facility And Test Instrument Used


#### 3.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850  
 A2LA certificate registration number is: CN1212  
 ISED Registered No.: 23583  
 ISED CAB identifier: CN0017

#### 3.2 Test Instrument Used

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Electromagnet-ic radiation tester	Wavecontrol	SMP160	19SN0980	May 14, 2024	May 15, 2025
Electromagne-tic field probe	Wavecontrol	WP400-3	20WP120082	Sept. 08, 2023	Sept. 07, 2024
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\





## 4. Method Of Measurement

### 4.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1093 RF exposure is calculated. According KDB 680106 D01 v04:

### 4.2 Block Diagram Of Test Setup



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 20/22/24 cm measured from the center of the probe(s) to the edge of the device

### 4.3 Limit

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

### 4.4 Test procedure

- a) The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- b) The measurement probe was placed at test distance (20/22/24cm) which is between the edge of the charger and the geometric centre of probe.
- c) The turn table was rotated 360d degree to search of highest strength.
- d) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- e) The EUT were measured according to the dictates of KDB 680106 D01 v04.



#### 4.5 Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01 v04

1) The power transfer frequency is below 1 MHz.

Yes, the device operate in the frequency range from 112-205KHz .

2) The output power from each transmitting element is less than or equal to 15 watts.

Yes, the maximum output power of the primary coil is 15W.

3) A client device providing the maximum permitted load is placed in physical contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter.

4) Only § 2.1091-Mobile exposure conditions apply

Yes, EUT is a fixed state assessment

5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.

Yes, Conform to

6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time.

Yes, Conform to



#### 4.6 E and H field Strength

E-Field test results the electric field strength at 20cm around the EUT.

Battery level	Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position Top	50% Limits Test (V/m)	Limits Test (V/m)
1%	0.112-0.205	0.063	0.077	0.062	0.076	0.078	0.062	307	614
50%	0.112-0.205	0.066	0.065	0.071	0.066	0.074	0.077	307	614
99%	0.112-0.205	0.060	0.071	0.066	0.074	0.074	0.066	307	614

H-Field test results the electric field strength at 20cm around the EUT.

Battery level	Frequency Range (MHz)	Test Position A(uT)	Test Position B(uT)	Test Position C(uT)	Test Position D(uT)	Test Position E(uT)	Test Position Top(uT)	50% Limits Test (uT)	Limits Test (uT)
1%	0.112-0.205	0.077	0.065	0.073	0.076	0.067	0.080	1.019	2.038
50%	0.112-0.205	0.076	0.063	0.076	0.066	0.066	0.620	1.019	2.038
99%	0.112-0.205	0.065	0.064	0.077	0.073	0.076	0.078	1.019	2.038

Battery level	Frequency Range (MHz)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position Top(A/m)	50% Limits Test (A/m)	Limits Test (A/m)
1%	0.112-0.205	0.061	0.052	0.058	0.061	0.053	0.064	0.815	1.63
50%	0.112-0.205	0.060	0.050	0.061	0.053	0.053	0.496	0.815	1.63
99%	0.112-0.205	0.052	0.051	0.062	0.058	0.061	0.063	0.815	1.63

Note: A/m = uT ÷ 1.25

E-Field test results the electric field strength at 22cm around the EUT.

Battery level	Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position Top	50% Limits Test (V/m)	Limits Test (V/m)
1%	0.112-0.205	0.069	0.065	0.060	0.063	0.075	0.076	307	614
50%	0.112-0.205	0.064	0.068	0.060	0.069	0.079	0.076	307	614
99%	0.112-0.205	0.077	0.070	0.062	0.071	0.064	0.071	307	614

H-Field test results the electric field strength at 22cm around the EUT.

Battery level	Frequency Range (MHz)	Test Position A(uT)	Test Position B(uT)	Test Position C(uT)	Test Position D(uT)	Test Position E(uT)	Test Position Top(uT)	50% Limits Test (uT)	Limits Test (uT)
1%	0.112-0.205	0.063	0.073	0.067	0.071	0.073	0.134	1.019	2.038
50%	0.112-0.205	0.074	0.061	0.060	0.073	0.067	0.605	1.019	2.038
99%	0.112-0.205	0.079	0.073	0.071	0.062	0.073	0.071	1.019	2.038

Battery level	Frequency Range (MHz)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position Top(A/m)	50% Limits Test (A/m)	Limits Test (A/m)
1%	0.112-0.205	0.051	0.059	0.053	0.057	0.058	0.107	0.815	1.63
50%	0.112-0.205	0.059	0.049	0.048	0.058	0.054	0.484	0.815	1.63
99%	0.112-0.205	0.063	0.058	0.057	0.049	0.058	0.057	0.815	1.63

Note: A/m = uT ÷ 1.25

E-Field test results the electric field strength at 24cm around the EUT.

Battery level	Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position Top	50% Limits Test (V/m)	Limits Test (V/m)
1%	0.112-0.205	0.072	0.078	0.075	0.078	0.072	0.065	307	614
50%	0.112-0.205	0.065	0.072	0.064	0.073	0.063	0.066	307	614
99%	0.112-0.205	0.068	0.070	0.067	0.063	0.064	0.064	307	614

H-Field test results the electric field strength at 24cm around the EUT.



Battery level	Frequency Range (MHz)	Test Position A(uT)	Test Position B(uT)	Test Position C(uT)	Test Position D(uT)	Test Position E(uT)	Test Position Top(uT)	50% Limits Test (uT)	Limits Test (uT)
1%	0.112-0.205	0.063	0.066	0.061	0.072	0.074	0.119	1.019	2.038
50%	0.112-0.205	0.062	0.079	0.063	0.064	0.070	0.609	1.019	2.038
99%	0.112-0.205	0.071	0.078	0.066	0.073	0.066	0.069	1.019	2.038

Battery level	Frequency Range (MHz)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position Top(A/m)	50% Limits Test (A/m)	Limits Test (A/m)
1%	0.112-0.205	0.050	0.052	0.049	0.058	0.059	0.095	0.815	1.63
50%	0.112-0.205	0.050	0.063	0.050	0.051	0.056	0.487	0.815	1.63
99%	0.112-0.205	0.057	0.062	0.053	0.058	0.053	0.055	0.815	1.63

Note: A/m = uT ÷ 1.25

ST  
C  
ED  
sal

### 5. Photographs Of Test Set-Up



**STATEMENT**

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

## Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>Consultation E-mail: [bctc@bctc-lab.com.cn](mailto:bctc@bctc-lab.com.cn)Complaint/Advice E-mail: [advice@bctc-lab.com.cn](mailto:advice@bctc-lab.com.cn)**\*\*\*\*\* END \*\*\*\*\***

2017