



TEST REPORT

Application No.: BTEK230923004AE
Applicant: Camojojo, INC.
Address of Applicant: 3311 S RAINBOW STE 105, Las Vegas, NV, 89146, USA
Manufacturer: Camojojo, INC.
Address of Manufacturer: 3311 S RAINBOW STE 105, Las Vegas, NV, 89146, USA
Factory: SY Electronic Technical Co.,Ltd.
Address of Factory: 5th floor, 4th Bldg, Antongda Industrial Park, 1 Liuxian 3rd Rd, Baoan Dist., Shenzhen, China

Equipment Under Test (EUT):

EUT Name: Bird Feeder Camera

Model No.: hibird

Trade Mark:



Standard(s) : 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2023-10-31

Date of Test: 2023-10-31 to 2023-12-18

Date of Issue: 2023-12-18

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Damon Su
EMC Laboratory Manager





Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-12-18		Original

Authorized for issue by:				
		<i>Elma Yang</i>		
		Elma Yang/ Project Engineer		
		<i>Carl Yang</i>		
		Carl Yang /Reviewer		



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Deviation from Standards	7
4.6 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data	12
7.2 Conducted Average Output Power	错误!未定义书签。
7.2.1 E.U.T. Operation	15
7.2.2 Test Mode Description	15
7.2.3 Test Setup Diagram	16
7.2.4 Measurement Procedure and Data	16
7.3 Minimum 6dB Bandwidth	17
7.3.1 E.U.T. Operation	17
7.3.2 Test Mode Description	17
7.3.3 Test Setup Diagram	17
7.3.4 Measurement Procedure and Data	17
7.4 Power Spectrum Density	18
7.4.1 E.U.T. Operation	18
7.4.2 Test Mode Description	18
7.4.3 Test Setup Diagram	18
7.4.4 Measurement Procedure and Data	18
7.5 Conducted Band Edges Measurement	19
7.5.1 E.U.T. Operation	19
7.5.2 Test Mode Description	19
7.5.3 Test Setup Diagram	20
7.5.4 Measurement Procedure and Data	20
7.6 Conducted Spurious Emissions	21
7.6.1 E.U.T. Operation	21
7.6.2 Test Mode Description	21
7.6.3 Test Setup Diagram	22
7.6.4 Measurement Procedure and Data	22
7.7 Radiated Emissions which fall in the restricted bands	23
7.7.1 E.U.T. Operation	23



7.7.2 Test Mode Description	23
7.7.3 Test Setup Diagram.....	24
7.7.4 Measurement Procedure and Data.....	24
7.8 Radiated Spurious Emissions (Below 1GHz).....	28
7.8.1 E.U.T. Operation	28
7.8.2 Test Mode Description	28
7.8.3 Test Setup Diagram.....	29
7.8.4 Measurement Procedure and Data.....	29
7.9 Radiated Spurious Emissions (Above 1GHz).....	32
7.9.1 E.U.T. Operation	32
7.9.2 Test Mode Description	32
7.9.3 Test Setup Diagram.....	33
7.9.4 Measurement Procedure and Data.....	33
8 Test Setup Photo	39
9 EUT Constructional Details (EUT Photos)	39
10 Appendix	40



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 5V 2A from adapter; DC 3.7V(10000mAh) from Battery
Cable(s):	N/A
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n(HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Channel Numbers:	802.11b/g, 802.11n HT20: 11 Channels
Channel Spacing:	5MHz
Antenna Type:	External Antenna
Antenna Gain:	5 dBi
Hardware Version:	NA
Software and Firmware Version:	NA
Remark: The information in this section is provided by the applicant or manufacturer, BANTEK is not liable to the accuracy, suitability, reliability or/and integrity of the information.	
Sample No.:	BTEK230923005AE-01

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	FUSHIGANG	AS1201A0502000USU	--

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.12\text{dB}$
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.06\text{dB}$ (3m); $\pm 4.46\text{dB}$ (10m)
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)



4.4 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.,

A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518103

Tel:0755-2334 4200 Fax: 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Shielding Room	YIHENG ENECTRONIC	9*5*3.3	YH-BT-220304-04	2022-03-03	2025-03-02
EMI Test Receiver	Rohde&Schwarz	ESCI	101021	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	N/A	N/A
LISN	Rohde&Schwarz	ENV216	101472	2023-06-12	2024-06-11
LISN	Schwarzbeck	NSLK 8128	05127	2023-06-12	2024-06-11

RF Conducted					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Shielding Room	YIHENG ENECTRONIC	5.5*3.1*3	YH-BT-220304-03	2022-03-03	2025-03-02
EXA Signal Analyzer	KEYSIGHT	N9020A	MY54230486	2023-06-12	2024-06-11
DC Power Supply	E3632A	E3642A	KR75304416	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-6dB	N/A	2023-06-12	2024-06-11
Attenuator	RswTech	SMA-JK-3dB	N/A	2023-06-12	2024-06-11
RF Control Unit	Techy	TR1029-1	N/A	2023-06-12	2024-06-11
RF Sensor Unit	Techy	TR1029-2	N/A	2023-06-12	2024-06-11
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	141258	2023-06-12	2024-06-11
MXG Vector Signal Generator	Agilent	N5182A	US46240522	2023-06-12	2024-06-11
Programmable Temperature&Humidity Chamber	GRT	GR-HWX1000	GR22051001	2023-06-12	2024-06-11
Measurement Software	TACHOY	RF TestSoft	N/A	N/A	N/A

RSE					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	YIHENG ENECTRONIC	966	YH-BT-220304-01	2022-05-06	2025-05-05
EMI Test Receiver	Rohde&Schwarz	ESCI	100694	2023-06-12	2024-06-11
TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	01324	2022-06-15	2025-06-14
Pre-Amplifier	Schwarzbeck	BBV 9745	#180	2023-06-12	2024-06-11
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	2023-06-12	2024-06-11
EXA Signal Analyzer	Keysight	N9020A	MY54440290	2023-06-12	2024-06-11
Horn Antenna	Schwarzbeck	BBHA 9120D	02695	2022-06-15	2025-06-14
Pre-Amplifier	Tonscend	TAP0118045	AP20K806109	2023-06-12	2024-06-11
Horn Antenna	SCHWARZBECK	BBHA9170	1157	2022-06-15	2025-06-14
Low Noise Pre-amplifier	SKET	LNPA-1840G-	SK2022032902	2023-06-12	2024-06-11





		50			
Signal analyzer	ROHDE&SCHWARZ	FSQ40	100010	2023-06-12	2024-06-11
Loop Antenna	ETS	6502	00201177	2022-06-15	2025-06-14

General used equipment					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Humidity/Temperature/Barometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11
Humidity/Temperature/Barometric Pressure Indicator	KUMAR	F132	N/A	2023-06-12	2024-06-11



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.


15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is A External Antenna. The best case gain of the antenna is 5dBi.

Please refer to photos.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.2 °C

Humidity: 60.5 % RH


Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 50\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.




Test Mode: 01; Line: Live line; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3165	21.66	19.82	41.48	59.80	-18.32	QP	P	
2	0.3165	13.72	19.82	33.54	49.80	-16.26	AVG	P	
3	0.5010	19.77	19.84	39.61	56.00	-16.39	QP	P	
4	0.5010	10.29	19.84	30.13	46.00	-15.87	AVG	P	
5 *	1.1805	24.13	20.02	44.15	56.00	-11.85	QP	P	
6	1.1805	8.97	20.02	28.99	46.00	-17.01	AVG	P	
7	5.2575	19.58	20.29	39.87	60.00	-20.13	QP	P	
8	5.2575	6.85	20.29	27.14	50.00	-22.86	AVG	P	
9	10.6530	19.40	20.90	40.30	60.00	-19.70	QP	P	
10	10.6530	6.96	20.90	27.86	50.00	-22.14	AVG	P	
11	26.4344	20.05	22.77	42.82	60.00	-17.18	QP	P	
12	26.4344	7.48	22.77	30.25	50.00	-19.75	AVG	P	



Test Mode: 01; Line: Neutral Line; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	31.45	19.76	51.21	66.00	-14.79	QP	P	
2	0.1500	12.84	19.76	32.60	56.00	-23.40	AVG	P	
3	0.3165	22.92	19.83	42.75	59.80	-17.05	QP	P	
4	0.3165	14.65	19.83	34.48	49.80	-15.32	AVG	P	
5	0.5594	21.23	19.87	41.10	56.00	-14.90	QP	P	
6	0.5594	9.92	19.87	29.79	46.00	-16.21	AVG	P	
7 *	1.1984	22.92	20.03	42.95	56.00	-13.05	QP	P	
8	1.1984	8.23	20.03	28.26	46.00	-17.74	AVG	P	
9	4.3484	19.61	20.19	39.80	56.00	-16.20	QP	P	
10	4.3484	7.03	20.19	27.22	46.00	-18.78	AVG	P	
11	29.2560	20.42	23.12	43.54	60.00	-16.46	QP	P	
12	29.2560	7.46	23.12	30.58	50.00	-19.42	AVG	P	

Note:

- 1) Pre-scan all modes and recorded the worst case results in this report(Low Channel).
- 2) Level= Reading+ Factor; Margin=Level-limit.



7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 20.5 °C Humidity: 50.0 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.3 Minimum 6dB Bandwidth

Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥ 500 kHz

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 20.5 °C Humidity: 50.0 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 20.5 °C Humidity: 50.0 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation


Operating Environment:
Temperature: 20.5 °C Humidity: 50.0 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.205(c).

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20.5 °C

Humidity: 50.0 % RH


Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C

Humidity: 54.3 % RH


Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.36	-30.59	37.77	74.00	-36.23	peak	P
2	2390.000	70.29	-30.49	39.80	74.00	-34.20	peak	P
3	2400.000	79.23	-30.48	48.75	74.00	-25.25	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	67.16	-30.59	36.57	74.00	-37.43	peak	P
2	2390.000	70.78	-30.49	40.29	74.00	-33.71	peak	P
3	2400.000	77.54	-30.48	47.06	74.00	-26.94	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.59	-30.39	49.20	74.00	-24.80	peak	P
2	2500.000	71.51	-30.37	41.14	74.00	-32.86	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.70	-30.39	49.31	74.00	-24.69	peak	P
2	2500.000	70.85	-30.37	40.48	74.00	-33.52	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	67.13	-30.59	36.54	74.00	-37.46	peak	P
2	2390.000	69.42	-30.49	38.93	74.00	-35.07	peak	P
3	2400.000	78.49	-30.48	48.01	74.00	-25.99	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.67	-30.59	38.08	74.00	-35.92	peak	P
2	2390.000	69.79	-30.49	39.30	74.00	-34.70	peak	P
3	2400.000	78.13	-30.48	47.65	74.00	-26.35	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.25	-30.39	48.86	74.00	-25.14	peak	P
2	2500.000	71.48	-30.37	41.11	74.00	-32.89	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	80.75	-30.39	50.36	74.00	-23.64	peak	P
2	2500.000	70.58	-30.37	40.21	74.00	-33.79	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	67.32	-30.59	36.73	74.00	-37.27	peak	P
2	2390.000	69.63	-30.49	39.14	74.00	-34.86	peak	P
3	2400.000	78.59	-30.48	48.11	74.00	-25.89	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.000	68.56	-30.59	37.97	74.00	-36.03	peak	P
2	2390.000	69.32	-30.49	38.83	74.00	-35.17	peak	P
3	2400.000	78.29	-30.48	47.81	74.00	-26.19	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.71	-30.39	49.32	74.00	-24.68	peak	P
2	2500.000	70.12	-30.37	39.75	74.00	-34.25	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.500	79.37	-30.39	48.98	74.00	-25.02	peak	P
2	2500.000	70.63	-30.37	40.26	74.00	-33.74	peak	P

Note: Level = Reading level + Factor

Factor= Antenna Factor+ Cable Loss-Preamplifier Factor



7.8 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C

Humidity: 68.6 % RH


Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.




Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	38.4810	40.55	-17.05	23.50	40.00	-16.50	QP	100	196	P	
2	50.4090	40.37	-17.57	22.80	40.00	-17.20	QP	100	159	P	
3	239.9873	56.78	-19.11	37.67	46.00	-8.33	QP	100	12	P	
4	287.9904	48.44	-18.06	30.38	46.00	-15.62	QP	200	336	P	
5	721.7258	47.08	-9.13	37.95	46.00	-8.05	QP	100	12	P	
6 *	912.8620	47.58	-7.77	39.81	46.00	-6.19	QP	100	336	P	



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	37.9450	40.11	-17.11	23.00	40.00	-17.00	QP	100	221	P	
2	152.6640	40.83	-16.92	23.91	43.50	-19.59	QP	200	300	P	
3 *	239.9873	58.17	-19.11	39.06	46.00	-6.94	QP	100	156	P	
4	287.9904	48.33	-18.06	30.27	46.00	-15.73	QP	200	221	P	
5	721.7258	46.86	-9.13	37.73	46.00	-8.27	QP	100	209	P	
6	912.8620	46.67	-7.77	38.90	46.00	-7.10	QP	100	257	P	

Note:

- 1) Pre-scan all modes and recorded the worst case results in this report (Low Channel).
- 2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3) Level= Reading+ Factor, Margin= Level- Limit, Factor= Antenna Factor Cable Loss-Preamp Factor



7.9 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C

Humidity: 54.3 % RH


Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.
Final test	01	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2915.341	68.97	-30.41	38.56	74.00	-35.44	peak	P
2	4277.720	68.51	-29.17	39.34	74.00	-34.66	peak	P
3	6085.368	64.50	-26.33	38.17	74.00	-35.83	peak	P
4	8644.900	69.18	-25.12	44.06	74.00	-29.94	peak	P
5	11047.001	68.36	-23.82	44.54	74.00	-29.46	peak	P
6	14218.069	70.66	-20.51	50.16	74.00	-23.84	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2972.319	66.86	-30.56	36.31	74.00	-37.69	peak	P
2	4313.683	68.37	-29.51	38.86	74.00	-35.14	peak	P
3	6354.104	67.44	-25.56	41.88	74.00	-32.12	peak	P
4	8576.808	69.87	-24.28	45.59	74.00	-28.41	peak	P
5	11286.898	68.26	-23.75	44.51	74.00	-29.49	peak	P
6	14955.720	71.28	-20.07	51.21	74.00	-22.79	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2914.318	69.28	-29.44	39.84	74.00	-34.16	peak	P
2	4276.519	67.92	-29.74	38.17	74.00	-35.83	peak	P
3	6085.911	64.65	-24.64	40.01	74.00	-33.99	peak	P
4	8645.861	69.88	-25.48	44.40	74.00	-29.60	peak	P
5	11046.338	67.26	-24.11	43.15	74.00	-30.85	peak	P
6	14218.599	71.26	-20.76	50.50	74.00	-23.50	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2973.031	67.94	-28.73	39.21	74.00	-34.79	peak	P
2	4313.620	67.83	-28.41	39.43	74.00	-34.57	peak	P
3	6353.145	67.93	-25.49	42.45	74.00	-31.55	peak	P
4	8575.601	69.00	-25.04	43.97	74.00	-30.03	peak	P
5	11286.271	68.69	-24.03	44.67	74.00	-29.33	peak	P
6	14956.694	71.79	-21.04	50.75	74.00	-23.25	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2914.872	69.68	-29.71	39.97	74.00	-34.03	peak	P
2	4277.843	68.12	-28.45	39.67	74.00	-34.33	peak	P
3	6084.924	65.39	-24.51	40.88	74.00	-33.12	peak	P
4	8646.397	70.63	-25.92	44.71	74.00	-29.29	peak	P
5	11047.581	67.61	-22.65	44.96	74.00	-29.04	peak	P
6	14217.319	70.30	-20.58	49.71	74.00	-24.29	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2972.545	67.85	-29.68	38.17	74.00	-35.83	peak	P
2	4313.149	69.57	-29.39	40.18	74.00	-33.82	peak	P
3	6353.750	67.27	-25.82	41.45	74.00	-32.55	peak	P
4	8576.842	70.19	-25.84	44.35	74.00	-29.65	peak	P
5	11285.535	68.83	-22.43	46.40	74.00	-27.60	peak	P
6	14955.760	71.17	-20.91	50.26	74.00	-23.74	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2913.946	69.13	-28.86	40.27	74.00	-33.73	peak	P
2	4276.760	68.87	-29.77	39.10	74.00	-34.90	peak	P
3	6085.375	64.90	-24.87	40.03	74.00	-33.97	peak	P
4	8646.208	68.99	-24.27	44.72	74.00	-29.28	peak	P
5	11046.588	67.06	-23.67	43.39	74.00	-30.61	peak	P
6	14217.191	71.11	-21.48	49.63	74.00	-24.37	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2973.010	66.13	-30.21	35.93	74.00	-38.07	peak	P
2	4313.864	69.31	-28.68	40.63	74.00	-33.37	peak	P
3	6353.549	67.68	-24.86	42.82	74.00	-31.18	peak	P
4	8575.386	69.07	-24.48	44.59	74.00	-29.41	peak	P
5	11285.663	68.68	-23.29	45.38	74.00	-28.62	peak	P
6	14956.400	71.13	-20.60	50.53	74.00	-23.47	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2915.416	70.19	-29.90	40.29	74.00	-33.71	peak	P
2	4276.363	67.22	-29.75	37.47	74.00	-36.53	peak	P
3	6086.151	65.49	-25.25	40.25	74.00	-33.75	peak	P
4	8646.452	69.90	-25.68	44.22	74.00	-29.78	peak	P
5	11046.456	67.68	-22.80	44.88	74.00	-29.12	peak	P
6	14218.287	70.45	-21.36	49.10	74.00	-24.90	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2973.046	66.53	-28.74	37.79	74.00	-36.21	peak	P
2	4313.854	69.09	-28.43	40.66	74.00	-33.34	peak	P
3	6354.120	67.64	-24.49	43.15	74.00	-30.85	peak	P
4	8575.876	69.35	-25.23	44.12	74.00	-29.88	peak	P
5	11285.990	68.17	-22.65	45.52	74.00	-28.48	peak	P
6	14956.005	70.03	-19.33	50.69	74.00	-23.31	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2915.292	70.25	-29.39	40.86	74.00	-33.14	peak	P
2	4277.638	67.28	-29.17	38.11	74.00	-35.89	peak	P
3	6085.667	65.08	-24.97	40.11	74.00	-33.89	peak	P
4	8645.635	69.14	-25.58	43.55	74.00	-30.45	peak	P
5	11048.133	67.13	-23.79	43.33	74.00	-30.67	peak	P
6	14219.062	70.28	-21.07	49.21	74.00	-24.79	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2972.954	66.91	-28.91	38.01	74.00	-35.99	peak	P
2	4313.662	69.77	-29.04	40.73	74.00	-33.27	peak	P
3	6352.519	67.29	-24.61	42.68	74.00	-31.32	peak	P
4	8575.208	70.26	-24.40	45.86	74.00	-28.14	peak	P
5	11286.555	68.43	-23.07	45.36	74.00	-28.64	peak	P
6	14955.783	70.90	-21.12	49.78	74.00	-24.22	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2914.894	69.39	-29.28	40.11	74.00	-33.89	peak	P
2	4276.827	68.03	-29.77	38.26	74.00	-35.74	peak	P
3	6084.886	64.77	-25.57	39.20	74.00	-34.80	peak	P
4	8645.866	70.41	-25.28	45.14	74.00	-28.86	peak	P
5	11047.672	67.60	-23.34	44.26	74.00	-29.74	peak	P
6	14218.409	70.92	-21.21	49.72	74.00	-24.28	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2973.670	67.13	-28.77	38.36	74.00	-35.64	peak	P
2	4313.811	69.04	-27.91	41.13	74.00	-32.87	peak	P
3	6353.525	66.73	-25.01	41.72	74.00	-32.28	peak	P
4	8575.841	68.82	-26.14	42.68	74.00	-31.32	peak	P
5	11286.397	68.89	-23.43	45.45	74.00	-28.55	peak	P
6	14956.786	70.91	-20.56	50.35	74.00	-23.65	peak	P

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2915.413	69.49	-28.94	40.55	74.00	-33.45	peak	P
2	4278.053	67.86	-28.75	39.12	74.00	-34.88	peak	P
3	6085.432	64.79	-25.51	39.28	74.00	-34.72	peak	P
4	8645.250	69.66	-25.61	44.05	74.00	-29.95	peak	P
5	11046.532	67.70	-22.90	44.80	74.00	-29.20	peak	P
6	14217.624	69.90	-21.53	48.36	74.00	-25.64	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2973.782	66.93	-30.00	36.93	74.00	-37.07	peak	P
2	4312.427	68.49	-28.54	39.95	74.00	-34.05	peak	P
3	6353.286	67.65	-25.55	42.10	74.00	-31.90	peak	P
4	8576.524	69.05	-25.62	43.43	74.00	-30.57	peak	P
5	11286.459	67.02	-23.25	43.77	74.00	-30.23	peak	P
6	14955.198	70.60	-19.74	50.85	74.00	-23.15	peak	P



Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2915.335	70.32	-29.58	40.74	74.00	-33.26	peak	P
2	4276.826	67.51	-28.63	38.87	74.00	-35.13	peak	P
3	6084.906	64.98	-25.96	39.01	74.00	-34.99	peak	P
4	8645.026	70.13	-24.10	46.02	74.00	-27.98	peak	P
5	11046.860	67.51	-22.63	44.88	74.00	-29.12	peak	P
6	14218.054	69.97	-20.95	49.02	74.00	-24.98	peak	P

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin (dB)	Detector	P/F
1	2972.395	66.07	-30.09	35.97	74.00	-38.03	peak	P
2	4313.887	69.44	-28.50	40.94	74.00	-33.06	peak	P
3	6352.302	67.16	-26.03	41.12	74.00	-32.88	peak	P
4	8575.708	69.86	-25.14	44.72	74.00	-29.28	peak	P
5	11286.299	67.91	-24.26	43.65	74.00	-30.35	peak	P
6	14956.650	71.26	-19.62	51.64	74.00	-22.36	peak	P



8 Test Setup Photo

Please Refer to appendix – Test Setup Photos for BTEK230923004AE

9 EUT Constructional Details (EUT Photos)


Please Refer to appendix - External and Internal Photos for BTEK230923004AE







10 Appendix



1. -6dB Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	8.49	500	Pass
NVNT	ANT1	802.11b	2437.00	8.66	500	Pass
NVNT	ANT1	802.11b	2462.00	8.90	500	Pass
NVNT	ANT1	802.11g	2412.00	16.42	500	Pass
NVNT	ANT1	802.11g	2437.00	16.42	500	Pass
NVNT	ANT1	802.11g	2462.00	16.41	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	17.74	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.76	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.77	500	Pass


















2. 99% Occupied Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	802.11b	2412.00	11.615
NVNT	ANT1	802.11b	2437.00	11.588
NVNT	ANT1	802.11b	2462.00	11.622
NVNT	ANT1	802.11g	2412.00	16.970
NVNT	ANT1	802.11g	2437.00	16.970
NVNT	ANT1	802.11g	2462.00	16.982
NVNT	ANT1	802.11n(HT20)	2412.00	18.373
NVNT	ANT1	802.11n(HT20)	2437.00	18.318
NVNT	ANT1	802.11n(HT20)	2462.00	18.380


















3. Duty Cycle



Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	91.67	0.38
NVNT	ANT1	802.11b	2437.00	89.58	0.48
NVNT	ANT1	802.11b	2462.00	91.67	0.38
NVNT	ANT1	802.11g	2412.00	60.00	2.22
NVNT	ANT1	802.11g	2437.00	66.67	1.76
NVNT	ANT1	802.11g	2462.00	64.29	1.92
NVNT	ANT1	802.11n(HT20)	2412.00	71.43	1.46
NVNT	ANT1	802.11n(HT20)	2437.00	69.23	1.60
NVNT	ANT1	802.11n(HT20)	2462.00	64.29	1.92
















4. MAX. Output Power



Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	22.69	0.38	23.07	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	23.02	0.48	23.5	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	22.93	0.38	23.31	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	21.94	2.22	24.16	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	22.22	1.76	23.98	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	22.09	1.92	24.01	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	21.22	1.46	22.68	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	21.79	1.60	23.39	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	21.29	1.92	23.21	30	Pass



5. Power Spectral Density



Condition	Antenna	Modulation	Frequency (MHz)	PSD(dBm/30kHz)	Duty factor(dB)	RB factor(dB)	PSD(dBm/3kHz)	limit(dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	3.20	0.38	-10.00	-6.42	8	Pass
NVNT	ANT1	802.11b	2437.00	4.17	0.48	-10.00	-5.35	8	Pass
NVNT	ANT1	802.11b	2462.00	4.89	0.38	-10.00	-4.73	8	Pass
NVNT	ANT1	802.11g	2412.00	-2.64	2.22	-10.00	-10.42	8	Pass
NVNT	ANT1	802.11g	2437.00	-2.25	1.76	-10.00	-10.49	8	Pass
NVNT	ANT1	802.11g	2462.00	-2.46	1.92	-10.00	-10.54	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	-2.16	1.46	-10.00	-10.7	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-2.77	1.60	-10.00	-11.17	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-2.38	1.92	-10.00	-10.46	8	Pass













6. Bandedge

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark frequency(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2399.488	-34.849	-12.668	Pass
NVNT	ANT1	802.11b	2462.00	2483.968	-43.410	-12.346	Pass
NVNT	ANT1	802.11g	2412.00	2399.488	-38.127	-17.063	Pass
NVNT	ANT1	802.11g	2462.00	2484.592	-44.511	-17.362	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2399.936	-40.334	-18.079	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2483.872	-42.278	-17.929	Pass







2_Bandedge_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2462




2_Bandedge_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Bandedge_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Bandedge_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2412



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2462




7. Spurious Emission


Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark frequency(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	24832.701	-45.269	-12.668	Pass
NVNT	ANT1	802.11b	2437.00	24787.755	-44.240	-12.679	Pass
NVNT	ANT1	802.11b	2462.00	24780.264	-44.751	-12.346	Pass
NVNT	ANT1	802.11g	2412.00	2507.024	-51.146	-17.063	Pass
NVNT	ANT1	802.11g	2437.00	2534.491	-52.996	-17.322	Pass
NVNT	ANT1	802.11g	2462.00	2502.030	-52.207	-17.362	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	24737.815	-50.259	-18.079	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24702.857	-49.806	-18.286	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	24807.731	-50.966	-17.929	Pass




2_Spurious_Emission_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2437




2_Spurious_Emission_NVNT_ANT1_802_11b_2437




1_Reference_Level_NVNT_ANT1_802_11b_2462




2_Spurious_Emission_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Spurious_Emission_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2437




2_Spurious_Emission_NVNT_ANT1_802_11g_2437




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Spurious_Emission_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2437



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462



2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2462



- End of the Report -

