

规格承认书

客户 CUSTOMER	
客户料号 CUSTOMER NO.	MC68
供方品名 PART NAME	WIFI 天线
规格名称 SUPPLIER NO.	XH230052 (L=55mm)

客户确认 CUSTOMER APPROVED BY		
检验 APPROVAL	审核 CHIEF	批准 SUPERVISOR

设计 DESIGN	审核 CHECK	批准 APPROVAL
Luo	Robert	SHANG

Date:August 4,2023

DIRECTORY

NO.	Contents	Number of Page	Page Code
1	Spec Cover	1	1
2	DIRECTORY	1	2
3	Test Reports	1	3
4	Matching Circuits	1	4
5	DRAWING	1	5
6	Test Data	4	6~9
7	Antenna assembly position	1	10

电性测试报告


TEST REPORTS

频率 Frequency	WIFI(2400~2500MHz)
-----------------	--------------------

阻抗 Impedance	50 Ohm Nominal
驻波比 V.S.W.R	≤ 2.0
回波损耗 Return Loss	-10dB Max
辐射 Radiation	Omni-directional
增益 Gain(Peak)	2.06dBi
极化方式 Polarization	Linear,Vertical
功率 Admitted Power	1W
连接器 Connector	
Physical Properties	
天线材质 Antenna Material	FPC
线材类型 Cable Type	O.D.0.81mm
工作温度 Operating Temp.	-10-+60℃
存储温度 Storage Temp.	-10-+70℃
线材颜色 Cable Color	Black

匹配电路

Matching Circuits




匹配电路

Element	Value	Vender
E1(0402)		
E2(0402)	0Ω	
E3(0402)		
E4(0402)	0Ω	

原匹配电路无修改

The original matching circuit has not been modified




测试数据

Test Data


Freq (MHz)	Effi (%)	Gain (dBi)
2400	51.67	1.55
2410	50.24	1.34
2420	55.33	1.8
2430	52.16	1.46
2440	55.7	1.77
2450	52.08	1.48
2460	53.08	1.65
2470	52.87	1.66
2480	54.09	1.77
2490	58.29	2.06
2500	53.15	1.74

3D 方向图


2400.000MHz




2400.000MHz H




2400.000MHz E1




2400.000MHz E2




2450.000MHz




2450.000MHz H




2450.000MHz E1




2450.000MHz E2




2500.000MHz




2500.000MHz H




2500.000MHz E1



2500.000MHz E2



无源驻波



天线装配位置

Antenna assembly position

