

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Toy RC Rampage Renegade operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AAA batteries). For more details information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -5.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -5.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 90.8dB μ V/m at 3m in the frequency 2405MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -4.43dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 89.5dB μ V/m at 3m in the frequency 2445MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -5.73dBm
which is within the production variation.

The maximum conducted output power specified is -2.0dBm= 0.631mW

The source- based time-averaging conducted output power
=0.631mW

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 \cdot 5 / \text{sqrt} (2.475)$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.