



FCC RF Test Report

Report No.: JYTSZ-R12-2301493
Applicant: A.O.Smith (China) Water Heater Co. Ltd.
Address of Applicant: 336 Yaoxin Avenue NETDZ Nanjing China
Equipment Under Test (EUT)
Product Name: THR-Remote control
Model No.: THR-Remote control
Trade Mark: N/A
FCC ID: 2BDC5THR-RFCONTROL
Applicable Standards: FCC CFR Title 47 Part 15C (§15.231)
Date of Sample Receipt: 24 Oct., 2023
Date of Test: 25 Oct., to 01 Nov., 2023
Date of Report Issue: 02 Nov., 2023
Test Result: PASS

Tested by:

June Li
Project Engineer

Date:

02 Nov., 2023

Reviewed by:

Hetao Chang
Senior Engineer

Date:

02 Nov., 2023

Approved by:

Junet Wei
Manager

Date:

02 Nov., 2023

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	02 Nov., 2023	Original

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents	3
3 General Information	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions From the Method	5
3.7 Laboratory Facility	5
3.8 Laboratory Location	6
3.9 Test Instruments List	6
4 Measurement Setup and Procedure	8
4.1 Test Setup	8
4.2 Test Procedure	9
5 Test Results	10
5.1 Summary	10
5.1.1 Clause and Data Summary	10
5.1.2 Test Limit	11
5.2 Antenna Requirement	12
5.3 20dB Bandwidth	13
5.4 Field Strength of Fundamental	14
5.5 Field Strength of Spurious Emissions	16
5.6 Duration Time	20

3 General Information

3.1 Client Information

Applicant:	A.O.Smith (China) Water Heater Co. Ltd.
Address:	336 Yaoxin Avenue NETDZ Nanjing China
Manufacturer/Factory:	A.O.Smith (China) Water Heater Co. Ltd.
Address:	336 Yaoxin Avenue NETDZ Nanjing China

3.2 General Description of E.U.T.

Product Name:	THR-Remote control
Model No.:	THR-Remote control
Operation Frequency:	433.92 MHz
Channel Numbers:	1
Modulation Type:	FSK
Antenna Type:	Spring Antenna
Antenna Gain:	-3.555 dBi (declare by Applicant)
Power Supply:	DC 3V (CR2450 battery)
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode and Environment

Test Mode:	
Transmitting mode:	Keep the EUT in transmitting mode with modulation
Remark: The EUT was placed on three different polar directions tested: i.e. X axis, Y axis, Z axis, and found the test results are both the "worst case" and "worst setup": Y axis, so the report only reflects the test data of worst mode.	
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar

3.4 Description of Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
N/A	N/A	N/A	N/A	N/A

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Radiated Emission (9kHz ~ 30MHz) (3m SAC)	3.3 dB
Radiated Emission (30MHz ~ 200MHz) (3m SAC)	4.6 dB
Radiated Emission (200MHz ~ 1000MHz) (3m SAC)	5.8 dB
Radiated Emission (1GHz ~ 6GHz) (3m SAC)	4.5 dB
Radiated Emission (6GHz ~ 18GHz) (3m SAC)	4.7 dB
Radiated Emission (30MHz ~ 1GHz) (3m FAR)	3.43 dB
Radiated Emission (1GHz ~ 6GHz) (3m FAR)	4.95 dB
Radiated Emission (6GHz ~ 18GHz) (3m FAR)	5.23 dB

Remark: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.6 Additions to, Deviations, or Exclusions From the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	02-09-2023	02-08-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	02-09-2023	02-08-2024
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-10-2023	01-09-2024
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-10-2023	01-09-2024
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	01-11-2023	01-10-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-10-2023	01-09-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-18-2023	01-17-2024
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-18-2023	01-17-2024
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		


Radiated Emission(3m FAR):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m FAR	YUNYI	9m*6m*6m	WXJ097	06-15-2023	06-14-2028
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ097-2	07-13-2023	07-12-2024
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-02-2021	07-01-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ097-3	07-14-2023	07-13-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	01-09-2023	01-08-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	01-09-2023	01-08-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	01-09-2023	01-08-2024
Pre-amplifier (30MHz ~ 1GHz)	YUNYI	PAM-310N	WXJ097-5	05-14-2023	05-13-2024
Pre-amplifier (1GHz ~ 18GHz)	YUNYI	PAM-118N	WXJ097-6	05-14-2023	05-13-2024
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	01-11-2023	01-10-2024
EMI Test Receiver	Rohde & Schwarz	ESCI3	WXJ003	01-10-2023	01-09-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-10-2023	01-09-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ081-1	06-13-2023	06-12-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-13M	WXG097-1	08-01-2023	07-31-2024
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG097-2	08-01-2023	07-31-2024
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG097-3	08-01-2023	07-31-2024
High Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Low Band Reject Filter Group	Tonscend	JS0806-F	WXJ097-4	N/A	
Test Software	Tonscend	TS+	Version: 5.0.0		

4 Measurement Setup and Procedure


4.1 Test Setup

Radiated emission measurement:

30 MHz – 1000 MHz (3m SAC)



Above 1 GHz (3m SAC)



4.2 Test Procedure

Test method	Test step
Radiated emission	1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203	See Section 5.2	Pass
AC Power Line Conducted Emission	15.207	N/A	N/A
20dB Bandwidth	15.231 (c)	See Section 5.3	Pass
Field Strength of Fundamental	15.231 (b)	See Section 5.4	Pass
Field Strength of Spurious Emissions	15.209 15.231 (b)	See Section 5.5	Pass
Duration Time	15.231 (a)(1)	See Section 5.6	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable.			
Test Method:	ANSI C63.4-2014 ANSI C63.10-2013		

5.1.2 Test Limit

Test items	Limit																																												
20dB Bandwidth	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.																																												
Field Strength of Fundamental Field Strength of Spurious Emissions	<table><tr><th>Fundamental Frequency (MHz)</th><th>Field strength of fundamental (microvolts/meter)</th><th>Field strength of spurious emissions (microvolts/meter)</th></tr><tr><td>40.66 – 40.70</td><td>2250</td><td>225</td></tr><tr><td>70.00 – 130.00</td><td>1250</td><td>125</td></tr><tr><td>130.00 – 174.00</td><td>¹1250 to 3750</td><td>¹125 to 375</td></tr><tr><td>174.00 – 260.00</td><td>3750</td><td>375</td></tr><tr><td>260.00 – 470.00</td><td>¹3750 to 12500</td><td>¹375 to 1250</td></tr><tr><td>Above 470.00</td><td>12500</td><td>1250</td></tr></table> ¹Linear interpolations. (1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges. (2) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in § 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of § 15.205 shall be demonstrated using the measurement instrumentation specified in that section. (3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength: <table><tr><th>Frequency (MHz)</th><th>Limit (dBµV/m) @ 3m</th><th>Detector</th></tr><tr><td>30 – 88</td><td>40.0</td><td>Quasi-peak</td></tr><tr><td>88 – 216</td><td>43.5</td><td>Quasi-peak</td></tr><tr><td>216 – 960</td><td>46.0</td><td>Quasi-peak</td></tr><tr><td>960 – 1000</td><td>54.0</td><td>Quasi-peak</td></tr></table> Note: The more stringent limit applies at transition frequencies. <table><tr><th rowspan="2">Frequency</th><th colspan="2">Limit (dBµV/m) @ 3m</th></tr><tr><th>Average</th><th>Peake</th></tr><tr><td>Above 1 GHz</td><td>54.0</td><td>74.0</td></tr></table> Note: The measurement bandwidth shall be 1 MHz or greater.	Fundamental Frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)	40.66 – 40.70	2250	225	70.00 – 130.00	1250	125	130.00 – 174.00	¹ 1250 to 3750	¹ 125 to 375	174.00 – 260.00	3750	375	260.00 – 470.00	¹ 3750 to 12500	¹ 375 to 1250	Above 470.00	12500	1250	Frequency (MHz)	Limit (dBµV/m) @ 3m	Detector	30 – 88	40.0	Quasi-peak	88 – 216	43.5	Quasi-peak	216 – 960	46.0	Quasi-peak	960 – 1000	54.0	Quasi-peak	Frequency	Limit (dBµV/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0
Fundamental Frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)																																											
40.66 – 40.70	2250	225																																											
70.00 – 130.00	1250	125																																											
130.00 – 174.00	¹ 1250 to 3750	¹ 125 to 375																																											
174.00 – 260.00	3750	375																																											
260.00 – 470.00	¹ 3750 to 12500	¹ 375 to 1250																																											
Above 470.00	12500	1250																																											
Frequency (MHz)	Limit (dBµV/m) @ 3m	Detector																																											
30 – 88	40.0	Quasi-peak																																											
88 – 216	43.5	Quasi-peak																																											
216 – 960	46.0	Quasi-peak																																											
960 – 1000	54.0	Quasi-peak																																											
Frequency	Limit (dBµV/m) @ 3m																																												
	Average	Peake																																											
Above 1 GHz	54.0	74.0																																											
Duration Time	A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.																																												


5.2 Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The antenna of EUT is an Spring Antenna. See product internal photos for details.	

5.3 20dB Bandwidth

20dB bandwidth (MHz)	Limit (MHz)	Results
0.0342	1.0848	Passed
Note: Limit = Fundamental frequency×0.25%=433.92×0.25%=1.0848MHz.		


Test plot as follows:



5.4 Field Strength of Fundamental


Peak value						
Frequency (MHz)	Level (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Polarization
433.92	74.61	-9.81	64.80	100.83	36.03	Vertical
433.92	84.13	-9.81	74.32	100.83	26.51	Horizontal
Average value						
Frequency (MHz)	Level (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Polarization
433.92	64.80	-1.61	63.19	80.83	17.64	Vertical
433.92	74.32	-1.61	72.71	80.83	8.12	Horizontal
Duty Cycle Factor Calculate Formula:		Average value = Peak value + Duty Cycle Factor				
		Duty cycle factor = $20\log(\text{Duty cycle})$				
		Duty cycle = on time/100 milliseconds or period, whichever is less				
		T on time = 17.2(ms)				
		T period = 20.4(ms)				
		Duty cycle = 83.09%				
		Duty cycle factor = $20\log(\text{Duty cycle}) = -1.61$				

T period:




Date: 27.OCT.2023 18:24:50

T 150ms:



Date: 27.OCT.2023 18:28:16


T 100ms:



Date: 27.OCT.2023 18:31:11

5.5 Field Strength of Spurious Emissions

Product Name:	THR-Remote control	Product Model:	THR-Remote control
Test By:	Asher	Test mode:	Tx mode
Test Frequency:	30 MHz – 1000 MHz	Polarization:	Vertical
Test Voltage:	DC 3V		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	45.5216	29.40	-12.81	16.59	40.00	23.41	PK	Vertical
2	64.8265	31.25	-14.72	16.53	40.00	23.47	PK	Vertical
3	159.313	33.10	-17.90	15.20	43.50	28.30	PK	Vertical
4	272.524	34.90	-13.35	21.55	46.00	24.45	PK	Vertical
5	433.948	74.61	-9.81	64.80	100.83	36.03	PK	Vertical
6	867.678	29.21	-2.99	26.22	80.83	54.61	PK	Vertical


Suspected Data List

NO.	Freq. [MHz]	Level (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	433.948	64.80	-1.61	63.19	80.83	17.64	AV	Vertical
2	867.678	26.22	-1.61	24.61	60.83	36.22	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	THR-Remote control	Product Model:	THR-Remote control
Test By:	Asher	Test mode:	Tx mode
Test Frequency:	30 MHz – 1000 MHz	Polarization:	Horizontal
Test Voltage:	DC 3V		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	50.3720	29.46	-12.63	16.83	40.00	23.17	PK	Horizontal
2	107.898	31.53	-14.62	16.91	43.50	26.59	PK	Horizontal
3	262.338	28.26	-13.42	14.84	46.00	31.16	PK	Horizontal
4	433.948	84.13	-9.81	74.32	100.83	26.51	PK	Horizontal
5	725.462	31.70	-4.56	27.14	46.00	18.86	PK	Horizontal
6	867.872	38.65	-3.00	35.65	80.83	45.18	PK	Horizontal


Suspected Data List

NO.	Freq. [MHz]	Level (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit [dBμV/m]	Margin [dB]	Trace	olarity
1	433.948	74.32	-1.61	72.71	80.83	8.12	AV	Horizontal
2	867.872	35.65	-1.61	34.04	60.83	26.79	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	THR-Remote control	Product Model:	THR-Remote control
Test By:	Robin	Test mode:	Tx mode
Test Frequency:	1000 MHz – 5000 MHz	Polarization:	Vertical
Test Voltage:	DC 3V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1301.76	58.86	-20.39	38.47	74.00	35.53	160	PK	PASS	Vertical
2	1735.68	59.39	-19.77	39.62	80.83	41.21	326	PK	PASS	Vertical
3	2169.60	58.47	-18.25	40.22	80.83	40.61	222	PK	PASS	Vertical
4	2603.52	57.70	-16.72	40.98	80.83	39.85	298	PK	PASS	Vertical
5	3037.44	59.32	-14.40	44.92	80.83	35.91	188	PK	PASS	Vertical
6	3471.36	57.98	-12.23	45.75	80.83	35.08	104	PK	PASS	Vertical
7	3905.28	57.98	-10.08	47.90	74.00	26.10	167	PK	PASS	Vertical
8	4339.50	61.44	-9.06	52.38	74.00	21.62	104	PK	PASS	Vertical

Suspected Data List										
NO.	Freq. [MHz]	Level (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle[°]	Detector	Polarity
1	1301.76	28.93	-1.61	27.32	54.00	26.68	150	160	AV	Vertical
2	1735.68	29.53	-1.61	27.92	60.83	32.90	150	326	AV	Vertical
3	2169.60	30.89	-1.61	29.28	60.83	31.54	150	222	AV	Vertical
4	2603.52	31.89	-1.61	30.28	60.83	30.54	150	298	AV	Vertical
5	3037.44	34.40	-1.61	32.79	60.83	28.03	150	188	AV	Vertical
6	3471.36	36.08	-1.61	34.47	60.83	26.35	150	104	AV	Vertical
7	3905.28	37.99	-1.61	36.38	54.00	17.62	150	167	AV	Vertical
8	4339.50	47.72	-1.61	46.11	54.00	7.89	150	104	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	THR-Remote control	Product Model:	THR-Remote control
Test By:	Robin	Test mode:	Tx mode
Test Frequency:	1000 MHz – 5000 MHz	Polarization:	Horizontal
Test Voltage:	DC 3V		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1301.76	59.16	-20.39	38.77	74.00	35.23	159	PK	PASS	Horizontal
2	1735.68	59.56	-19.77	39.79	80.83	41.04	27	PK	PASS	Horizontal
3	2169.60	59.31	-18.25	41.06	80.83	39.77	13	PK	PASS	Horizontal
4	2603.52	59.09	-16.72	42.37	80.83	38.46	312	PK	PASS	Horizontal
5	3037.44	59.34	-14.40	44.94	80.83	35.89	62	PK	PASS	Horizontal
6	3471.36	57.76	-12.23	45.53	80.83	35.30	96	PK	PASS	Horizontal
7	3905.28	58.66	-10.08	48.58	74.00	25.42	83	PK	PASS	Horizontal
8	4339.50	64.59	-9.06	55.53	74.00	18.47	96	PK	PASS	Horizontal
Suspected Data List										
NO.	Freq. [MHz]	Level (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle[°]	Detector	Polarity
1	1301.76	29.42	-1.61	27.81	54.00	26.19	150	159	AV	Horizontal
2	1735.68	29.65	-1.61	28.04	60.83	32.78	150	27	AV	Horizontal
3	2169.60	31.24	-1.61	29.63	60.83	31.19	150	13	AV	Horizontal
4	2603.52	31.81	-1.61	30.20	60.83	30.62	150	312	AV	Horizontal
5	3037.44	34.82	-1.61	33.21	60.83	27.61	150	62	AV	Horizontal
6	3471.36	36.42	-1.61	34.81	60.83	26.01	150	96	AV	Horizontal
7	3905.28	38.45	-1.61	36.84	54.00	17.16	150	83	AV	Horizontal
8	4339.50	51.83	-1.61	50.22	54.00	3.78	150	96	AV	Horizontal


Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

5.6 Duration Time

Measurement monitoring	Result
The EUT automatically deactivate the transmitter within 5 seconds of switch being released.	Pass

Test plot as follows:



-----End of report-----