

User manual

Remote control + Remote control receiver board instructions

1. pairing

Within one minute after the remote control receiving board is powered on, long press the remote control button and the remote control button will blink. At this time, observe the remote control receiving board LED. When the remote control receiving board LED blinks, the remote control is successfully paired.

2. Activated zero cold water

Short press the button on the remote control with the distribution network will activate the zero cold water function of the remote control once, and press it again to activate it again, and so on.

3. Clear pairing

On the A07 screen of the display board, long press the pump key of the display board until the Zero cold water icon of the display board flashes, then all remote control pairing information will be cleared.

FCC Statement

This device complies with FCC Rules part 15. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference that may be received, including interference that may cause undesired operation. The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modification could void the

user's authority to use the equipment.

NOTE:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

Consult the dealer or an experienced radio/TV technician for help.