



## RF Exposure evaluation

According to 447498D01 and part 2.1093

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

### For BLE

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
2402	-5.24	0.29	5	0.09	3.0

### For 2.4G WIFI

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
2437	8.60	7.24	5	2.26	3.0

### For UNII-1

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
5240	6.69	4.67	5	2.14	3.0

### For UNII-3

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
5745	6.33	4.30	5	2.01	3.0

SAR test is not required.

BT & 2.4GWIFI and 5Gwifi use one antenna, So BT&2.4GWIFI and 5G WIFI cannot be used simultaneously.