



FCC TEST REPORT
FCC ID:2BDGQ-TABDIAG10

Report Number..... : ZHT-240410010E-1

Date of Test..... : Apr. 10, 2024 to Apr. 30, 2024

Date of issue : Apr. 30, 2024

Test Result : PASS

Testing Laboratory..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Applicant's name : Shenzhen Vident Technology Co., Ltd

Address : No. 42, HanTang 2nd Road, BaoAn Community, YuanShan Street, LongGang District, Shenzhen

Manufacturer's name : Shenzhen Vident Technology Co., Ltd

Address : No. 42, HanTang 2nd Road, BaoAn Community, YuanShan Street, LongGang District, Shenzhen

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Test procedure : KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2013

Non-standard test method : N/A

This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Product name..... : iSmart-Automotive Diagnostic System

Trademark : Vident

Model/Type reference : iSmart920, iSmart920IM

Model Difference : iSmart920 is tested model, other models are derivative models
The model is exactly the same in circuit, PCB layout, RF Chip, appearance, only different on the model names. So the test data of iSmart920 can represent the remaining models.

Ratings..... : Input: 100-240V~50-60Hz, 0.7A by adapter

Output: 12.0V 2A, 24W by adapter

Battery parameter: 7.4V, 5000mAh, 7PIN



Testing procedure and testing location:

Testing Laboratory.....: Guangdong Zhonghan Testing Technology Co., Ltd.

Address.....: Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tested by (name + signature): Leon Li

Leon Li

Reviewer (name + signature).....: Baret Wu

Baret Wu

Approved (name + signature): Levi Lee

Levi Lee



Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS.....	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT.....	8
3.2 DESCRIPTION OF TEST MODES.....	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED.....	10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE).....	10
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
4. EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION Limits.....	13
4.1.2 TEST PROCEDURE.....	13
4.1.3 DEVIATION FROM TEST STANDARD.....	13
4.1.4 TEST SETUP.....	14
4.1.5 EUT OPERATING CONDITIONS.....	14
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS.....	17
4.2.2 TEST PROCEDURE.....	17
4.2.3 DEVIATION FROM TEST STANDARD.....	18
4.2.4 TEST SETUP.....	18
4.2.5 EUT OPERATING CONDITIONS.....	19
4.2.6 TEST RESULTS	19
5. RADIATED BAND EMISSIONMEASUREMENT	24
5.1 TEST REQUIREMENT:.....	24
5.2 TEST PROCEDURE	24
5.3 DEVIATION FROM TEST STANDARD.....	24
5.4 TEST SETUP	25
5.5 EUT OPERATING CONDITIONS.....	25
5.6 TEST RESULT	26
6. POWER SPECTRAL DENSITY TEST	28
6.1 APPLIED PROCEDURES / LIMIT.....	28
6.2 TEST PROCEDURE	28
6.3 DEVIATION FROM STANDARD.....	28
6.4 TEST SETUP	28
6.5 EUT OPERATION CONDITIONS.....	28



- 6.6 TEST RESULT 29
- 7. CHANNEL BANDWIDTH 30
 - 7.1 APPLIED PROCEDURES / LIMIT..... 30
 - 7.2 TEST PROCEDURE 30
 - 7.3 DEVIATION FROM STANDARD..... 30
 - 7.4 TEST SETUP 30
 - 7.5 EUT OPERATION CONDITIONS..... 30
 - 7.6 TEST RESULT 31
- 8. PEAK OUTPUT POWER TEST 32
 - 8.1 APPLIED PROCEDURES/LIMIT..... 32
 - 8.2 TEST PROCEDURE 32
 - 8.3 DEVIATION FROM STANDARD..... 32
 - 8.4 TEST SETUP 32
 - 8.5 EUT OPERATION CONDITIONS..... 32
 - 8.6 TEST RESULT 32
- 9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 33
 - 9.1 APPLICABLE STANDARD..... 33
 - 9.2 TEST PROCEDURE 33
 - 9.3 DEVIATION FROM STANDARD..... 33
 - 9.4 TEST SETUP 33
 - 9.5 EUT OPERATION CONDITIONS..... 33
 - 9.6 TEST RESULTS 33
- 10. ANTENNA REQUIREMENT 34
- 11. APPENDIX WIFI 35
 - 11.1 DUTY CYCLE 35
 - 11.2 MAXIMUM AVERAGE CONDUCTED OUTPUT POWER 41
 - 11.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER..... 47
 - 11.4 -6DB BANDWIDTH 48
 - 11.5 OCCUPIED CHANNEL BANDWIDTH 54
 - 11.6 MAXIMUM POWER SPECTRAL DENSITY LEVEL..... 60
 - 11.7 BAND EDGE..... 66
 - 11.8 CONDUCTED RF SPURIOUS EMISSION 73
- 12. TEST SETUP PHOTO 83
- 13. EUT CONSTRUCTIONAL DETAILS 83



1. VERSION

Report No.	Version	Description	Approved
ZHT-240410010E-1	Rev.01	Initial issue of report	Apr. 30, 2024



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF conducted power	$\pm 0.16\text{dB}$
3	Conducted spurious emissions	$\pm 0.21\text{dB}$
4	All radiated emissions (9k-30MHz)	$\pm 4.68\text{dB}$
5	All radiated emissions (<1G)	$\pm 4.68\text{dB}$
6	All radiated emissions (>1G)	$\pm 4.89\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	Occupied Bandwidth	$\pm 4.96\%$



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	iSmart-Automotive Diagnostic System
Test Model No.:	iSmart920
Hardware Version:	V1.31
Software Version:	V1.2.7
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11, /802.11n(HT40):7
Operation Frequency:	802.11b/802.11g /802.11n(HT20): 2412-2462MHz/802.11n(HT40): 2422-2452MHz
Channel separation:	5MHz
Modulation technology:	IEEE 802.11b: DQPSK/DBPSK/DSSS/CCK IEEE 802.11g: QPSK/BPSK/16QAM/64QAM/OFDM IEEE 802.11n: QPSK/BPSK/16QAM/64QAM/OFDM
Antenna Type:	FPCB Antenna
Antenna gain:	2.99dBi
Power supply:	Input: 100-240V~50-60Hz, 0.7A by adapter

.....



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

Test channel	Frequency (MHz)
	802.11n(HT40)
Lowest channel	2422MHz
Middle channel	2437MHz
Highest channel	2452MHz


3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode			
Remark: EUT use new battery during the test,the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.				
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13.5Mbps




3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E1	iSmart-Automotive Diagnostic System	Shenzhen Vident Technology Co., Ltd	iSmart920	iSmart920IM	EUT
E2	AC/DC ADAPTER	Shenzhen Mingxin Power Technologies Co.,Ltd.	MX24Z1-1202000	/	EUT
E3	LCD Monitor	DELL	U3011t	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



Radiation Test equipment

Item	Equipment	Manufacturer	Model	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	May 12, 2023	May 11, 2024
2	Loop antenna	EMCI	LAP600	May 12, 2023	May 11, 2024
3	Amplifier	Schwarzbeck	BBV 9743 B	May 12, 2023	May 11, 2024
4	Amplifier	Schwarzbeck	BBV 9718 B	May 12, 2023	May 11, 2024
5	Bilog Antenna	Schwarzbeck	VULB9162	May 17, 2023	May 16, 2024
6	Horn Antenna	Schwarzbeck	BBHA9120D	May 17, 2023	May 16, 2024
7	Horn Antenna	A.H.SYSTEMS	SAS574	May 12, 2023	May 11, 2024
8	Amplifier	AEROFLEX	100KHz-40GHz	May 12, 2023	May 11, 2024
9	Spectrum Analyzer	R&S	FSV40	May 12, 2023	May 11, 2024
10	966 Anechoic Chamber	EMToni	9m6m6m	Nov. 25, 2021	Nov. 24, 2024
11	Spectrum Analyzer	KEYSIGHT	N9020A	May 12, 2023	May 11, 2024
12	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	May 12, 2023	May 11, 2024
13	Single Generator	Agilent	N5182A	May 12, 2023	May 11, 2024
14	Power Sensor	MWRfTest	MW100-RFCB	May 12, 2023	May 11, 2024
15	Audio analyzer	R&S	UPL	May 12, 2023	May 11, 2024
16	Single Generator	R&S	SMB100A	May 12, 2023	May 11, 2024
17	Power Amplifier Shielding Room	EMToni	2m3m3m	Nov. 25, 2021	Nov. 24, 2024



Equipment	Manufacturer	Model	Last Cal.	Next Cal.
Receiver	R&S	ESCI	May 12, 2023	May 11, 2024
LISN	R&S	ENV216	May 12, 2023	May 11, 2024
ISN CAT 6	Schwarzbeck	NTFM 8158	May 12, 2023	May 11, 2024
ISN CAT 5	Schwarzbeck	CAT5 8158	May 12, 2023	May 11, 2024
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	May 12, 2023	May 11, 2024
Current Transformer Clamp	Schwarzbeck	SW 9605	May 12, 2023	May 11, 2024
CE Shielding Room	EMToni	9m4m3m	Nov. 25, 2021	Nov. 24, 2024



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:


(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 test result

Temperature:	24.3°C	Relative Humidity :	50%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	31.63	9.52	41.15	66.00	-24.85	QP	P
2	0.1500	22.30	9.52	31.82	56.00	-24.18	AVG	P
3	0.1580	30.99	9.52	40.51	65.57	-25.06	QP	P
4	0.1580	17.40	9.52	26.92	55.57	-28.65	AVG	P
5	0.1770	28.88	9.53	38.41	64.63	-26.22	QP	P
6	0.1770	19.80	9.53	29.33	54.63	-25.30	AVG	P
7	0.1995	27.20	9.55	36.75	63.63	-26.88	QP	P
8	0.1995	18.09	9.55	27.64	53.63	-25.99	AVG	P
9	0.2353	22.64	9.56	32.20	62.26	-30.06	QP	P
10	0.2353	13.59	9.56	23.15	52.26	-29.11	AVG	P
11	0.4470	21.34	9.67	31.01	56.93	-25.92	QP	P
12 *	0.4470	13.85	9.67	23.52	46.93	-23.41	AVG	P

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor
- 4.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).



Temperature:	24.3°C	Relative Humidity :	50%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1 *	0.1500	36.39	9.52	45.91	66.00	-20.09	QP	P
2	0.1500	23.20	9.52	32.72	56.00	-23.28	AVG	P
3	0.1680	29.88	9.53	39.41	65.06	-25.65	QP	P
4	0.1680	16.16	9.53	25.69	55.06	-29.37	AVG	P
5	0.1949	25.97	9.54	35.51	63.83	-28.32	QP	P
6	0.1949	14.52	9.54	24.06	53.83	-29.77	AVG	P
7	0.2490	23.11	9.56	32.67	61.79	-29.12	QP	P
8	0.2490	15.31	9.56	24.87	51.79	-26.92	AVG	P
9	0.4153	23.35	9.65	33.00	57.54	-24.54	QP	P
10	0.4153	15.30	9.65	24.95	47.54	-22.59	AVG	P
11	0.4380	22.32	9.66	31.98	57.10	-25.12	QP	P
12	0.4380	11.32	9.66	20.98	47.10	-26.12	AVG	P

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).



Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS


Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz


Temperature :	25.2°C	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Horizontal
Test Voltage :	AC120V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.9940	23.48	-8.93	14.55	40.00	-25.45	QP
2	631.6883	22.17	-1.76	20.41	46.00	-25.59	QP
3	696.8567	22.89	-0.69	22.20	46.00	-23.80	QP
4	787.8512	22.19	0.51	22.70	46.00	-23.30	QP
5	872.1832	23.82	1.77	25.59	46.00	-20.41	QP
6 *	952.0937	26.06	2.66	28.72	46.00	-17.28	QP



Temperature :	25.2°C	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	AC120V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	52.3912	30.80	-8.99	21.81	40.00	-18.19	QP
2	142.8243	36.41	-13.77	22.64	43.50	-20.86	QP
3	157.5586	34.63	-13.59	21.04	43.50	-22.46	QP
4	872.1832	23.96	1.77	25.73	46.00	-20.27	QP
5	909.6666	21.93	2.28	24.21	46.00	-21.79	QP
6 *	958.7943	25.81	2.73	28.54	46.00	-17.46	QP

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).



1GHz~25GHz

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11b									
Low Channel:2412MHz									
V	4824.00	59.76	30.55	5.77	24.66	59.64	74	-14.36	Pk
V	4824.00	41.04	30.55	5.77	24.66	40.92	54	-13.08	AV
H	4824.00	59.17	30.33	6.32	24.55	59.71	74	-14.29	Pk
H	4824.00	42.58	30.33	6.32	24.55	43.12	54	-10.88	AV
Middle Channel:2437MHz									
V	4874.00	59.28	30.55	5.77	24.66	59.16	74	-14.84	Pk
V	4874.00	42.97	30.55	5.77	24.66	42.85	54	-11.15	AV
H	4874.00	58.51	30.33	6.32	24.55	59.05	74	-14.95	Pk
H	4874.00	44.04	30.33	6.32	24.55	44.58	54	-9.42	AV
High Channel:2462MHz									
V	4924.00	55.3	30.55	5.77	24.66	55.18	74	-18.82	Pk
V	4924.00	41.95	30.55	5.77	24.66	41.83	54	-12.17	AV
H	4924.00	59.43	30.33	6.32	24.55	59.97	74	-14.03	Pk
H	4924.00	43.59	30.33	6.32	24.55	44.13	54	-9.87	AV
802.11g									
Low Channel:2412MHz									
V	4824.00	55.8	30.55	5.77	24.66	55.68	74	-18.32	Pk
V	4824.00	41.66	30.55	5.77	24.66	41.54	54	-12.46	AV
H	4824.00	59.54	30.33	6.32	24.55	60.08	74	-13.92	Pk
H	4824.00	41.59	30.33	6.32	24.55	42.13	54	-11.87	AV
Middle Channel:2437MHz									
V	4874.00	56.1	30.55	5.77	24.66	55.98	74	-18.02	Pk
V	4874.00	41.84	30.55	5.77	24.66	41.72	54	-12.28	AV
H	4874.00	57.8	30.33	6.32	24.55	58.34	74	-15.66	Pk
H	4874.00	42.41	30.33	6.32	24.55	42.95	54	-11.05	AV
High Channel:2462MHz									
V	4924.00	59.23	30.55	5.77	24.66	59.11	74	-14.89	Pk
V	4924.00	41.9	30.55	5.77	24.66	41.78	54	-12.22	AV
H	4924.00	57.21	30.33	6.32	24.55	57.75	74	-16.25	Pk
H	4924.00	41.3	30.33	6.32	24.55	41.84	54	-12.16	AV
802.11n 20									
Low Channel:2412MHz									
V	4824.00	55.95	30.55	5.77	24.66	55.83	74	-18.17	Pk
V	4824.00	42	30.55	5.77	24.66	41.88	54	-12.12	AV
H	4824.00	58.46	30.33	6.32	24.55	59	74	-15	Pk
H	4824.00	44.77	30.33	6.32	24.55	45.31	54	-8.69	AV
Middle Channel:2437MHz									
V	4874.00	56.47	30.55	5.77	24.66	56.35	74	-17.65	Pk
V	4874.00	41.85	30.55	5.77	24.66	41.73	54	-12.27	AV
H	4874.00	59.48	30.33	6.32	24.55	60.02	74	-13.98	Pk
H	4874.00	41.64	30.33	6.32	24.55	42.18	54	-11.82	AV
High Channel:2462MHz									
V	4924.00	59.02	30.55	5.77	24.66	58.9	74	-15.1	Pk
V	4924.00	41.48	30.55	5.77	24.66	41.36	54	-12.64	AV
H	4924.00	58.84	30.33	6.32	24.55	59.38	74	-14.62	Pk
H	4924.00	42.48	30.33	6.32	24.55	43.02	54	-10.98	AV
802.11n 40									
Low Channel:2422MHz									
V	4844.00	59.28	30.55	5.77	24.66	59.16	74	-14.84	Pk
V	4844.00	41.87	30.55	5.77	24.66	41.75	54	-12.25	AV



H	4844.00	57.58	30.33	6.32	24.55	58.12	74	-15.88	Pk
H	4844.00	41.92	30.33	6.32	24.55	42.46	54	-11.54	AV
Middle Channel:2437MHz									
V	4874.00	59.77	30.55	5.77	24.66	59.65	74	-14.35	Pk
V	4874.00	41.76	30.55	5.77	24.66	41.64	54	-12.36	AV
H	4874.00	55.15	30.33	6.32	24.55	55.69	74	-18.31	Pk
H	4874.00	42.68	30.33	6.32	24.55	43.22	54	-10.78	AV
High Channel:2452MHz									
V	4904.00	56.05	30.55	5.77	24.66	55.93	74	-18.07	Pk
V	4904.00	41.79	30.55	5.77	24.66	41.67	54	-12.33	AV
H	4904.00	59.75	30.33	6.32	24.55	60.29	74	-13.71	Pk
H	4904.00	44.44	30.33	6.32	24.55	44.98	54	-9.02	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel


Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
802.11b	Low Channel 2412MHz										
	H	2390.00	60.71	30.22	4.85	23.98	59.32	74.00	-14.68	PK	PASS
	H	2390.00	48.46	30.22	4.85	23.98	47.07	54.00	-6.93	AV	PASS
	H	2400.00	61.42	30.22	4.85	23.98	60.03	74.00	-13.97	PK	PASS
	H	2400.00	46.10	30.22	4.85	23.98	44.71	54.00	-9.29	AV	PASS
	V	2390.00	62.37	30.22	4.85	23.98	60.98	74.00	-13.02	PK	PASS
	V	2390.00	48.12	30.22	4.85	23.98	46.73	54.00	-7.27	AV	PASS
	V	2400.00	60.59	30.22	4.85	23.98	59.20	74.00	-14.80	PK	PASS
	V	2400.00	46.74	30.22	4.85	23.98	45.35	54.00	-8.65	AV	PASS
	High Channel 2462MHz										
	H	2483.50	60.34	30.22	4.85	23.98	58.95	74.00	-15.05	AV	PASS
	H	2483.50	48.90	30.22	4.85	23.98	47.51	54.00	-6.49	PK	PASS
	H	2500.00	59.44	30.22	4.85	23.98	58.05	74.00	-15.95	AV	PASS
	H	2500.00	46.84	30.22	4.85	23.98	45.45	54.00	-8.55	PK	PASS
	V	2483.50	59.40	30.22	4.85	23.98	58.01	74.00	-15.99	AV	PASS
	V	2483.50	47.91	30.22	4.85	23.98	46.52	54.00	-7.48	PK	PASS
V	2500.00	59.80	30.22	4.85	23.98	58.41	74.00	-15.59	AV	PASS	
V	2500.00	47.26	30.22	4.85	23.98	45.87	54.00	-8.13	AV	PASS	
802.11g	Low Channel 2412MHz										
	H	2390.00	60.07	30.22	4.85	23.98	58.68	74.00	-15.32	PK	PASS
	H	2390.00	48.75	30.22	4.85	23.98	47.36	54.00	-6.64	AV	PASS
	H	2400.00	60.56	30.22	4.85	23.98	59.17	74.00	-14.83	PK	PASS
	H	2400.00	46.24	30.22	4.85	23.98	44.85	54.00	-9.15	AV	PASS
	V	2390.00	60.74	30.22	4.85	23.98	59.35	74.00	-14.65	PK	PASS
	V	2390.00	46.62	30.22	4.85	23.98	45.23	54.00	-8.77	AV	PASS
	V	2400.00	62.94	30.22	4.85	23.98	61.55	74.00	-12.45	PK	PASS
	V	2400.00	47.36	30.22	4.85	23.98	45.97	54.00	-8.03	AV	PASS
	High Channel 2462MHz										
	H	2483.50	60.29	30.22	4.85	23.98	58.90	74.00	-15.10	PK	PASS
	H	2483.50	47.70	30.22	4.85	23.98	46.31	54.00	-7.69	AV	PASS
	H	2500.00	59.56	30.22	4.85	23.98	58.17	74.00	-15.83	PK	PASS
	H	2500.00	48.10	30.22	4.85	23.98	46.71	54.00	-7.29	AV	PASS
	V	2483.50	60.77	30.22	4.85	23.98	59.38	74.00	-14.62	PK	PASS
	V	2483.50	46.45	30.22	4.85	23.98	45.06	54.00	-8.94	AV	PASS
V	2500.00	60.32	30.22	4.85	23.98	58.93	74.00	-15.07	PK	PASS	
V	2500.00	48.25	30.22	4.85	23.98	46.86	54.00	-7.14	AV	PASS	
802.11n20	Low Channel 2412MHz										
	H	2390.00	59.63	30.22	4.85	23.98	58.24	74.00	-15.76	PK	PASS
	H	2390.00	48.89	30.22	4.85	23.98	47.50	54.00	-6.50	AV	PASS
	H	2400.00	62.02	30.22	4.85	23.98	60.63	74.00	-13.37	PK	PASS
	H	2400.00	46.85	30.22	4.85	23.98	45.46	54.00	-8.54	AV	PASS
	V	2390.00	62.00	30.22	4.85	23.98	60.61	74.00	-13.39	PK	PASS
	V	2390.00	47.44	30.22	4.85	23.98	46.05	54.00	-7.95	AV	PASS
	V	2400.00	62.09	30.22	4.85	23.98	60.70	74.00	-13.30	PK	PASS
	V	2400.00	48.27	30.22	4.85	23.98	46.88	54.00	-7.12	AV	PASS
	High Channel 2462MHz										
	H	2483.50	61.50	30.22	4.85	23.98	60.11	74.00	-13.89	PK	PASS
	H	2483.50	48.94	30.22	4.85	23.98	47.55	54.00	-6.45	AV	PASS
	H	2500.00	61.83	30.22	4.85	23.98	60.44	74.00	-13.56	PK	PASS
	H	2500.00	46.15	30.22	4.85	23.98	44.76	54.00	-9.24	AV	PASS
	V	2483.50	61.32	30.22	4.85	23.98	59.93	74.00	-14.07	PK	PASS
	V	2483.50	47.35	30.22	4.85	23.98	45.96	54.00	-8.04	AV	PASS



	V	2500.00	62.99	30.22	4.85	23.98	61.60	74.00	-12.40	PK	PASS
	V	2500.00	47.35	30.22	4.85	23.98	45.96	54.00	-8.04	AV	PASS
	Low Channel 2422MHz										
	H	2390.00	60.60	30.22	4.85	23.98	59.21	74.00	-14.79	PK	PASS
	H	2390.00	46.27	30.22	4.85	23.98	44.88	54.00	-9.12	AV	PASS
	H	2400.00	62.54	30.22	4.85	23.98	61.15	74.00	-12.85	PK	PASS
	H	2400.00	46.65	30.22	4.85	23.98	45.26	54.00	-8.74	AV	PASS
	V	2390.00	60.10	30.22	4.85	23.98	58.71	74.00	-15.29	PK	PASS
	V	2390.00	46.39	30.22	4.85	23.98	45.00	54.00	-9.00	AV	PASS
	V	2400.00	62.81	30.22	4.85	23.98	61.42	74.00	-12.58	PK	PASS
	V	2400.00	46.93	30.22	4.85	23.98	45.54	54.00	-8.46	AV	PASS
	High Channel 2452MHz										
	H	2483.50	61.61	30.22	4.85	23.98	60.22	74.00	-13.78	PK	PASS
	H	2483.50	47.96	30.22	4.85	23.98	46.57	54.00	-7.43	AV	PASS
	H	2500.00	61.35	30.22	4.85	23.98	59.96	74.00	-14.04	PK	PASS
	H	2500.00	47.29	30.22	4.85	23.98	45.90	54.00	-8.10	AV	PASS
	V	2483.50	60.40	30.22	4.85	23.98	59.01	74.00	-14.99	PK	PASS
	V	2483.50	46.64	30.22	4.85	23.98	45.25	54.00	-8.75	AV	PASS
	V	2500.00	60.22	30.22	4.85	23.98	58.83	74.00	-15.17	PK	PASS
	V	2500.00	48.04	30.22	4.85	23.98	46.65	54.00	-7.35	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit



6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



Temperature :	25.9°C	Relative Humidity :	52%
Pressure :	101kPa	Test Voltage :	AC120V

Please refer to APPENDIX WIFI



7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Temperature :	25.8°C	Relative Humidity :	52%
Pressure :	101kPa	Test Voltage :	AC120V
Test Mode :	TX Mode		

Please refer to APPENDIX WIFI



8. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Spectrum analyzer

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1MHz. VBW =3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.6 TEST RESULT

Temperature :	25.3°C	Relative Humidity :	55%
Pressure :	101kPa	Test Voltage :	AC120V

Please refer to APPENDIX WIFI



9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidanceev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE


Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Please refer to APPENDIX WIFI



10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:	
The antenna is FPCB Antenna, the best case gain of the antenna is 2.99dBi, reference to the appendix II for details	




11. APPENDIX WIFI

11.1 DUTY CYCLE


Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
b	2412	99.76	0	0.08
b	2437	99.76	0	0.08
b	2462	99.76	0	0.08
g	2412	99.04	0	0.48
g	2437	98.56	0	0.49
g	2462	99.04	0	0.48
n20	2412	88.46	0.53	4.35
n20	2437	92	0.36	4.35
n20	2462	88.46	0.53	4.35





Test Graphs Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2437MHz Ant1








Duty Cycle NVNT g 2437MHz Ant1




Duty Cycle NVNT g 2462MHz Ant1







Duty Cycle NVNT n20 2412MHz Ant1



Duty Cycle NVNT n20 2437MHz Ant1








11.2 MAXIMUM AVERAGE CONDUCTED OUTPUT POWER


Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
b	2412	5.98	0	5.98	30	Pass
b	2437	6.39	0	6.39	30	Pass
b	2462	6.41	0	6.41	30	Pass
g	2412	-0.3	0	-0.3	30	Pass
g	2437	0.26	0	0.26	30	Pass
g	2462	0.22	0	0.22	30	Pass
n20	2412	1.56	0.53	2.09	30	Pass
n20	2437	0.3	0.36	0.66	30	Pass
n20	2462	0.15	0.53	0.68	30	Pass



Test Graphs Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2437MHz Ant1






Average Power NVNT b 2462MHz Ant1




Average Power NVNT g 2412MHz Ant1






Average Power NVNT g 2437MHz Ant1




Average Power NVNT g 2462MHz Ant1







Average Power NVNT n20 2412MHz Ant1



Average Power NVNT n20 2437MHz Ant1







11.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER

Mode	Frequency (MHz)	Total Power (dBm)	Limit (dBm)	Verdict
b	2412	7.76	30	Pass
b	2437	8.23	30	Pass
b	2462	8.36	30	Pass
g	2412	6.18	30	Pass
g	2437	6.69	30	Pass
g	2462	6.91	30	Pass
n20	2412	7.87	30	Pass
n20	2437	7.07	30	Pass
n20	2462	6.88	30	Pass




11.4 -6DB BANDWIDTH

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
b	2412	8.11	0.5	Pass
b	2437	9.054	0.5	Pass
b	2462	8.017	0.5	Pass
g	2412	15.397	0.5	Pass
g	2437	16.07	0.5	Pass
g	2462	14.72	0.5	Pass
n20	2412	16.426	0.5	Pass
n20	2437	16.637	0.5	Pass
n20	2462	15.902	0.5	Pass




Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1




-6dB Bandwidth NVNT b 2437MHz Ant1






-6dB Bandwidth NVNT b 2462MHz Ant1




-6dB Bandwidth NVNT g 2412MHz Ant1






-6dB Bandwidth NVNT g 2437MHz Ant1




-6dB Bandwidth NVNT g 2462MHz Ant1







-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1








11.5 OCCUPIED CHANNEL BANDWIDTH


Mode	Frequency (MHz)	99% OBW (MHz)
b	2412	11.086
b	2437	10.983
b	2462	10.893
g	2412	16.37
g	2437	16.408
g	2462	16.377
n20	2412	17.583
n20	2437	17.583
n20	2462	17.536



Test Graphs OBW NVNT b 2412MHz Ant1




OBW NVNT b 2437MHz Ant1






OBW NVNT b 2462MHz Ant1




OBW NVNT g 2412MHz Ant1






OBW NVNT g 2437MHz Ant1




OBW NVNT g 2462MHz Ant1







OBW NVNT n20 2412MHz Ant1



OBW NVNT n20 2437MHz Ant1








11.6 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
b	2412	-13.61	-13.61	8	Pass
b	2437	-12.73	-12.73	8	Pass
b	2462	-13.47	-13.47	8	Pass
g	2412	-15.64	-15.64	8	Pass
g	2437	-16.04	-16.04	8	Pass
g	2462	-15.92	-15.92	8	Pass
n20	2412	-15.97	-15.97	8	Pass
n20	2437	-15.63	-15.63	8	Pass
n20	2462	-15.17	-15.17	8	Pass




Test Graphs

PSD NVNT b 2412MHz Ant1




PSD NVNT b 2437MHz Ant1






PSD NVNT b 2462MHz Ant1




PSD NVNT g 2412MHz Ant1






PSD NVNT g 2437MHz Ant1




PSD NVNT g 2462MHz Ant1







PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1








11.7 BAND EDGE


Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-50.06	-30	Pass
b	2462	-55.05	-30	Pass
g	2412	-42.36	-30	Pass
g	2462	-48.09	-30	Pass
n20	2412	-41.22	-30	Pass
n20	2462	-48.31	-30	Pass



Test Graphs Band Edge NVNT b 2412MHz Ant1 Ref




Band Edge NVNT b 2412MHz Ant1 Emission






Band Edge NVNT b 2462MHz Ant1 Ref




Band Edge NVNT b 2462MHz Ant1 Emission






Band Edge NVNT g 2412MHz Ant1 Ref




Band Edge NVNT g 2412MHz Ant1 Emission










Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission












11.8 CONDUCTED RF SPURIOUS EMISSION

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-45.19	-30	Pass
b	2437	-45.54	-30	Pass
b	2462	-45.46	-30	Pass
g	2412	-41.89	-30	Pass
g	2437	-42.41	-30	Pass
g	2462	-40.91	-30	Pass
n20	2412	-43.14	-30	Pass
n20	2437	-43.34	-30	Pass
n20	2462	-42.77	-30	Pass










Tx. Spurious NVNT b 2437MHz Ant1 Ref







Tx. Spurious NVNT b 2437MHz Ant1 Emission















Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Tx. Spurious NVNT n20 2412MHz Ant1 Emission






Tx. Spurious NVNT n20 2437MHz Ant1 Ref




Tx. Spurious NVNT n20 2437MHz Ant1 Emission






Tx. Spurious NVNT n20 2462MHz Ant1 Ref



Tx. Spurious NVNT n20 2462MHz Ant1 Emission





12. TEST SETUP PHOTO

Reference to the appendix I for details.

13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****