

SPECIFICATION


Manufacturer	Shenzhen Chengrong Technology Co.,Ltd.
Address	Room707 Kangrui Time Square,Keyuan Business Building,Huarong Road 39,Gaofeng Community, Dalang Street,Longhua Disctrict,Shenzhen City.
Product name:	WPC A11 coil
Model name:	WPC A11 coil
DATE:	2023/08/06
Version:	A.0

Version Change History

[illegible]

SPECIFICATION

DESC	Φ 19.5x45-6.5uH-0.1x24PX2P-45mm	Rev:	A.0
------	---------------------------------	------	-----

一、 DIMENSION:(mm)	A	70±0.25
	B	17±1
	C	37±0.5
	D	40±0.5
二、 SCHEMATIC DIAGRAM:	Note:	
	1. Cross outgoing line;	
	2. Wrap 7mm (ref) wide high-temperature adhesive tape 1-2Ts around the outlet position;	
	3. The coil is attached to a circular hard magnetic disk with slots, with a magnetic disk size of 52 ± 0.25mm, and a thickness of 1.0 ± 0.1mm. The total thickness is 2.2 ± 0.2mm	

三、Winding Specification:

NO.	TERMINAL	WIRE	Turns	Winding Direction
1	S	F	Hot air line 0.1*24PX2	10Ts

四、ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
1	IND.	S-F	3.8uH ±20%Individual coil	100KHz/1.0V	LCZ METER 1062B
2	IND.	S-F	6.5uH ±10%Adding magnetic disks	100KHz/1.0V	LCZ METER 1062B
3	DCR	S-F	≤90m Ω	100KHz/1.0V	LCZ METER 502B
4	Q	S-F	≥39	100KHz/1.0V	LCZ METER 502B

PREPARED BY/DATE	CHECKED BY/DATE
2023/08/06	2023/08/06