



FCC Test Report

Report No: FCS202310362W01

Issued for

Applicant:	Xtuga E-COMMERCE CORP.
Address:	949 Constance Ln Unit E Sycamore IL 60178
Product Name:	WirelessGuitarPickup
Brand Name:	XTUGA
Model Name:	JTSY23
Series Model:	N/A
FCC ID:	2BDIS-JTSY23
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.fcs-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name.....: Xtuga E-COMMERCE CORP.
 Address.....: 949 Constance Ln Unit E Sycamore IL 60178
 Manufacture's Name.....: Enping Dekas Electroacoustic Equipment Co., Ltd
 Address.....: Card 1, 4F, Changchun Industrial Park, No. C10, Municipal
 Foreign-invested Industrial Zone, Enping

Product Description

Product Name.....: WirelessGuitarPickup
 Brand Name: XTUGA
 Model Name.....: JTSY23
 Series Model.....: N/A
 Test Standards.....: FCC Rules and Regulations Part 15 Subpart C section 15.236
 Test Procedure.....: ANSI C63.10:2013

This device described above has been tested FCS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of FCS, this document may be altered or revised by FCS, personal only, and shall be noted in the revision of the document..

Date of Test.....:

Date (s) of performance of tests.: Sep 25, 2023 ~ Oct 09, 2023

Date of Issue.....: Oct 09, 2023

Test Result.....: Pass

Tested by

:

Scott Shen

(Scott Shen)

Reviewed by

:

Duke Qian

(Duke Qian)

Approved by

:

Jack Wang

(Jack Wang)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	9
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	10
3 MAXIMUM RADIATED POWER	12
3.1 LIMIT	12
3.2 TEST PROCEDURE	12
3.3 TEST SETUP	12
3.4 TEST RESULTS	12
4. OCCUPIED BANDWIDTH	13
4.1 LIMIT	13
4.2 TEST PROCEDURE	13
4.3 TEST SETUP	13
4.4 TEST RESULTS	13
5. NECESSARY BANDWITH	16
5.1 LIMIT	16
5.2 TEST PROCEDURE	16
5.3 TEST SETUP	16
5.4 TEST RESULT	17
6. TRANSMITTER UNWANTED EMISSIONS	19
6.1 LIMIT	19
5.2 TEST PROCEDURE	19
5.3 TEST SETUP	19
6.4 TEST RESULTS	20
7. FREQUENCY STABILITY	27
7.1 LIMIT	27
7.2 TEST PROCEDURE	27
7.3 TEST SETUP	27
7.4 TEST RESULTS	28

Revision History

Rev.	Issue Date	Effect Page	Contents
00	Oct 09, 2023	All	Initial Issue

1. SUMMARY OF TEST RESULTS

FCC Part 15 Subpart C section 15.236			
Standard Section	Test Item	Judgment	Remark
FCC Part 15.236(d)	Maximum Radiated Power	PASS	--
FCC Part 15.236(f)(2)	Occupied Bandwidth	PASS	--
FCC Part 15.236(g)	Necessary bandwidth	PASS	--
FCC Part 15.236(f)(3)	Frequency stability	PASS	--
FCC Part 15.236(g)	Emission within the band and outside this band	PASS	--
FCC Part 207(a)	Conducted Emission	N/A	--

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) All tests are according to ANSI C63.10:2013

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number: 5545.01	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.71 \text{ dB}$
2	Unwanted Emissions, conducted	$\pm 2.98 \text{ dB}$
3	Conducted Emission (9KHz-150KHz)	$\pm 4.13 \text{ dB}$
4	Conducted Emission (150KHz-30MHz)	$\pm 4.74 \text{ dB}$
5	All emissions, radiated (<1G) 30MHz-1000MHz	$\pm 3.1 \text{ dB}$
6	All emissions, radiated (<1G) 30MHz-1000MHz	$\pm 3.2 \text{ dB}$
7	All emissions, radiated (1GHz -18GHz)	$\pm 3.66 \text{ dB}$
8	All emissions, radiated (18GHz -40GHz)	$\pm 4.31 \text{ dB}$
9	Occupied bandwidth	4(%)
10	Frequency stability	$\pm 2 \text{ ppm}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	WirelessGuitarPickup
Brand Name	XTUGA
Model Name	JTSY23
Series Model	N/A
Model Difference	N/A
Channel List	Please refer to the Note 2.
Operation frequency	520.5MHz-550.5MHz
Modulation Type	FM
Antenna Type	spring antenna
Antenna Gain (dBi)	-2.09
Power Supply	DC 5V
Battery	DC 3.7V,800mAh
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List

Channel			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	520.5	17	536.5
02	521.5	18	537.5
03	522.5	19	538.5
04	523.5	20	539.5
05	524.5	21	540.5
06	525.5	22	541.5
07	526.5	23	542.5
08	527.5	24	543.5
09	528.5	25	544.5
10	529.5	26	545.5
11	530.5	27	546.5
12	531.5	28	547.5
13	532.5	29	548.5
14	533.5	30	549.5
15	534.5	31	550.5
16	535.5		

Ant.	Atnenna Brand	Antenna Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	spring antenna	N/A	-2.09	Antenna

2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test software:FCC tools

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table, the following operating modes were applied for the related test items. All test modes were tested, only the result of the worst case was recorded in the report.

Tested mode, channel , information		
Mode	Channel	Frequency (MHz)
Channel	CH 01	520.5
Channel	CH 16	535.5
Channel	CH 31	550.5

Note: that use new battery during the test

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2023.08.29	2024.08.28
Signal Analyzer	R&S	FSV40-N	FCS-E012	2023.08.29	2024.08.28
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2023.08.29	2024.08.28
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2023.08.29	2024.08.28
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2023.08.29	2024.08.28
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2023.08.29	2024.08.28
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2023.08.29	2024.08.28
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2023.08.29	2024.08.28
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2023.08.29	2024.08.28
Temperature & Humidity	HTC-1	victor	FCS-E005	2023.08.29	2024.08.28
Signal generator	Agilent	E4421B	FCS-E025	2023.08.29	2024.08.28

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2023.08.29	2024.08.28
LISN	R&S	ENV216	FCS-E007	2023.08.29	2024.08.28
LISN	ETS	3810/2NM	FCS-E009	2023.08.29	2024.08.28
Temperature & Humidity	HTC-1	victor	FCS-E008	2023.08.29	2024.08.28

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
Spectrum Analyzer	Keysight	N9020A	FCS-E015	2023.08.29	2024.08.28
Spectrum Analyzer	Agilent	E4447A	MY50180039	2023.08.29	2024.08.28
Spectrum Analyzer	R&S	FSV-40	101499	2023.08.29	2024.08.28
Audio Analyzer	R&S	UPL	FCS-E39	2023.08.29	2024.08.28

3 MAXIMUM RADIATED POWER

3.1 LIMIT

Refer to FCC 15.236(d)

In the bands allocated and assigned for broadcast television and in the 600 MHz service band: 50 mW EIRP

3.2 TEST PROCEDURE

A · Connect each EUT's antenna output to power sensor by RF cable and attenuator

3.3 TEST SETUP



3.4 TEST RESULTS

Channel	Frequency (MHz)	Peak Output Power (dBm)	Antenna Gain (dBi)	Cable loss (dB)	EIRP(dBm)	Limit(dBm)	Verdict
CH 01	520.5	3.21	-2.09	0.8	1.91	16.99	PASS
CH 16	535.5	3.36	-2.09	0.8	2.07	16.99	PASS
CH 31	550.5	3.96	-2.09	0.8	2.67	16.99	PASS

4. OCCUPIED BANDWIDTH


4.1 LIMIT

One or more adjacent 25KHz segments within the assignable frequencies may be combined to form a channel whose maximum bandwidth shall not exceed 200 kHz. The operating bandwidth shall not exceed 200 kHz

4.2 TEST PROCEDURE

Parameter	Setting
Detector	Peak/AV
Sweep time	Auto
Resolution bandwidth	1 % to 5 % of the occupied bandwidth
Video bandwidth:	3 x resolution bandwidth
Span:	2 x emission bandwidth
Trace mode:	Max. hold
Analyzer function:	99% power occupied bandwidth function
EUT:	Modulated signal with max(FM,2.5kHz tone). frequency deviation

4.3 TEST SETUP



4.4 TEST RESULTS

Channel	Frequency (MHz)	20dB Bandwidth (KHz)	Limt(KHz)	Verdict
CH 01	520.5	101.4	200KHz	PASS
CH 16	535.5	112.7	200KHz	PASS
CH 31	550.5	102.2	200KHz	PASS

CHA

Low



Middle



High



5. NECESSARY BANDWIDTH

5.1 LIMIT





Figure 1: Spectrum mask for analogue systems in all bands

5.2 TEST PROCEDURE


EN300422-1 V1.4.2 Clause 8.3.

5.3 TEST SETUP




5.4 TEST RESULT


Low



Middle



High



6. TRANSMITTER UNWANTED EMISSIONS

6.1 LIMIT


Spurious emissions are emissions outside the frequency range(s) of the equipment. The power of the spurious emissions shall not exceed the limits of table as below:

State	Frequency		
	47MHz to 74MHz, 87.5MHz to 137MHz 174MHz to 230MHz, 470MHz to 862MHz	Other Frequencies below 1000MHz	Frequencies above 1000MHz
Operation	4nW	250nW	1uW
Standby	2nW	2nW	20nW

5.2 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 30MHz to 6000MHz with 100 KHz RBW and 300 KHz VBW
2. Please refer to ETSI EN 300 422-1 V1.4.2 (2011-08) clause 6.1 for the test conditions.
3. Please refer to ETSI EN 300 422-1 V1.4.2 (2011-08) clause 8.4.2 for the measurement method.


5.3 TEST SETUP



6.4 TEST RESULTS


01 CH-30MHZ-1000MHZ

Vertical



No.	Frequency (MHz)	Reading (dBm)	Correction (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	43.3534	-53.20	-16.92	-70.12	-36.00	-34.12	peak
2	65.1145	-48.58	-19.38	-67.96	-54.00	-13.96	peak
3	154.2786	-51.35	-19.28	-70.63	-36.00	-34.63	peak
4	237.4760	-53.78	-15.34	-69.12	-36.00	-33.12	peak
5	337.2155	-57.91	-12.88	-70.79	-36.00	-34.79	peak
6	912.8620	-70.77	-3.14	-73.91	-36.00	-37.91	peak

Horizontal




No.	Frequency (MHz)	Reading (dBm)	Correction (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	43.3534	-59.20	-16.92	-76.12	-36.00	-40.12	peak
2	80.9274	-52.68	-21.76	-74.44	-36.00	-38.44	peak
3	163.1818	-51.27	-18.68	-69.95	-36.00	-33.95	peak
4	237.4760	-53.28	-15.34	-68.62	-36.00	-32.62	peak
5	341.9786	-55.42	-12.78	-68.20	-36.00	-32.20	peak
6	821.7103	-70.45	-4.46	-74.91	-54.00	-20.91	peak

Note :

1. Result = Reading + Corrected Factor Note :


16 CH-30MHZ-1000MHZ

Vertical



No.	Frequency (MHz)	Reading (dBm)	Correction (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	43.3534	-60.70	-16.92	-77.62	-36.00	-41.62	peak
2	79.8002	-51.75	-21.90	-73.65	-36.00	-37.65	peak
3	104.9033	-53.10	-17.34	-70.44	-54.00	-16.44	peak
4	163.1818	-48.27	-18.68	-66.95	-36.00	-30.95	peak
5	341.9786	-57.92	-12.78	-70.70	-36.00	-34.70	peak
6	582.7423	-69.09	-8.58	-77.67	-54.00	-23.67	peak

Horizontal




No.	Frequency (MHz)	Reading (dBm)	Correction (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	43.3534	-59.20	-16.92	-76.12	-36.00	-40.12	peak
2	73.3593	-53.36	-21.00	-74.36	-54.00	-20.36	peak
3	104.9033	-53.10	-17.34	-70.44	-54.00	-16.44	peak
4	180.0165	-44.26	-19.44	-63.70	-54.00	-9.70	peak
5	341.9786	-52.42	-12.78	-65.20	-36.00	-29.20	peak
6	642.8613	-69.31	-6.97	-76.28	-54.00	-22.28	peak

Note :

2. Result = Reading + Corrected Factor Note :


31 CH-30MHZ-1000MHZ

Vertical



No.	Frequency (MHz)	Reading (dBm)	Correction (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	36.3813	-57.51	-16.50	-74.01	-36.00	-38.01	peak
2	75.1821	-51.07	-21.38	-72.45	-36.00	-36.45	peak
3	163.1818	-57.77	-18.68	-76.45	-36.00	-40.45	peak
4	237.4760	-60.28	-15.34	-75.62	-36.00	-39.62	peak
5	392.0951	-60.74	-12.84	-73.58	-36.00	-37.58	peak
6	716.6820	-70.99	-5.93	-76.92	-54.00	-22.92	peak

Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correction (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	52.3913	-53.47	-16.54	-70.01	-54.00	-16.01	peak
2	88.0327	-54.34	-20.60	-74.94	-54.00	-20.94	peak
3	135.9822	-56.26	-20.95	-77.21	-54.00	-23.21	peak
4	237.4760	-60.28	-15.34	-75.62	-36.00	-39.62	peak
5	431.0316	-62.24	-11.69	-73.93	-36.00	-37.93	peak
6	965.5421	-68.79	-2.32	-71.11	-36.00	-35.11	peak

Note :

3. Result = Reading + Corrected Factor Note :

1GHZ-6GHZ

Frequency	Reading	Correct	Result	Limit	Margin	Remark	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)		H/V
Channel 01 -520.5MHz							
1041.00	-53.68	8.27	-45.41	-30	-15.41	AVG	H
1561.50	-52.11	13.73	-38.38	-30	-8.38	AVG	H
1041.00	-50.36	8.27	-42.09	-30	-12.09	AVG	V
1561.50	-49.25	13.73	-35.52	-30	-5.52	AVG	V

Frequency	Reading	Correct	Result	Limit	Margin	Remark	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)		H/V
Channel 16 -535.5MHz							
1071.00	-51.35	9.65	-41.70	-30	-11.70	AVG	H
1606.50	-52.04	9.23	-42.81	-30	-12.81	AVG	H
1071.00	-51.26	9.65	-41.61	-30	-11.61	AVG	V
1606.50	-53.11	9.23	-43.88	-30	-13.88	AVG	V

Frequency	Reading	Correct	Result	Limit	Margin	Remark	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)		H/V
Channel 31 -550.5MHz							
1101.00	-53.48	9.05	-44.43	-30	-14.43	AVG	H
1651.50	-52.14	10.37	-41.77	-30	-11.77	AVG	H
1101.00	-53.07	9.05	-44.02	-30	-14.02	AVG	V
1651.50	-51.27	10.37	-40.90	-30	-10.90	AVG	V

7. FREQUENCY STABILITY

7.1 LIMIT

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.005\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C


7.2 TEST PROCEDURE

a. The EUT was connected to an external DC power supply and the RF output was connected to a frequency counter via feed through attenuators. The EUT was placed inside the temperature chamber. The DC leads and the RF output cable, exited the chamber through an opening made for that purpose.

After the temperature stabilized the frequency output was recorded from the counter. An external variable DC power supply was connected to the battery terminals of the equipment under test.

b. For hand carried, battery powered equipment primary supply voltage was reduced to the battery operating end point as specified by the manufacturer. The output frequency was recorded for each battery voltage.

7.3 TEST SETUP



7.4 TEST RESULTS

- (1) Frequency stability versus input voltage (Supply Nominal voltage is DC 5V)
- (2) Frequency stability versus input voltage (Supply battery operating end point which shall be specified by the manufacturer DC5V)

Refernce Frequency: 520.5MHz			
Power supply	Environment Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)
DC 4.25V	20	611	1.17
DC 5V	20	610	1.17
DC 5.75V	20	611	1.17

Refernce Frequency: 520.5MHz				
Frequency Deviation measured with time Elapse(30 minutes)				
Environment Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Results
50	611	1.17	50	Pass
40	590	1.13		
30	589	1.13		
20	598	1.15		
10	601	1.15		
0	602	1.16		
-10	605	1.16		
-20	609	1.17		

Refernce Frequency: 535.5MHz			
Power supply	Environment Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)
DC 4.25V	20	630	1.18
DC 5V	20	633	1.18
DC 5.75V	20	632	1.18

Refernce Frequency: 535.5MHz				
Frequency Deviation measured with time Elapse(30 minutes)				
Environment Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Results
50	631	1.18	50	Pass
40	611	1.14		
30	616	1.15		
20	625	1.17		
10	630	1.18		
0	628	1.17		
-10	629	1.17		
-20	619	1.16		

Reference Frequency: 550.5MHz			
Power supply	Environment Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)
DC 4.25V	20	648	1.17
DC 5V	20	649	1.18
DC 5.75V	20	646	1.17

Reference Frequency: 550.5MHz				
Frequency Deviation measured with time Elapse(30 minutes)				
Environment Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Results
50	623	1.13	50	Pass
40	616	1.12		
30	605	1.10		
20	611	1.11		
10	635	1.15		
0	638	1.16		
-10	624	1.13		
-20	629	1.14		

*****END OF THE REPORT*****