

# EMC TEST REPORT

**Applicant**      Roobuck Pty Ltd

**FCC ID**          2BDKTB6WB

**Product**        WiFi/BLE Belt Tag;  
WiFi/BLE Portable Tag

**Brand**            Roobuck

**Model**            RBT6A-WB; RPT6A-WB

**Report No.**      R2403A0239-E1

**Issue Date**      June 24, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2023)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

---

*Prepared by: Liu Wei*

*Approved by: Fan Guangchang*

**Eurofins TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## Table of Contents

1	Test Laboratory .....	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment Under Test .....	5
2.1	Applicant and Manufacturer Information .....	5
2.2	General Information .....	5
2.3	Applied Standards .....	7
2.4	Test Mode .....	8
3	Test Case Results .....	9
3.1	Radiated Emission.....	9
3.2	Conducted Emission.....	14
4	Uncertainty Measurement.....	16
5	Main Test Instruments .....	17
	ANNEX A: The EUT Appearance .....	18
	ANNEX B: Test Setup Photos .....	19

### Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	NA <sup>Note 1</sup>
Date of Testing: April 22, 2024 ~ May 27, 2024			
Date of Sample Received: April 15, 2024			
<p>Note: NA = Not Applicable.</p> <p>1. The equipment is not connected to the public network, so there is no need to test Conducted Emission.</p> <p>2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.</p>			

# 1 Test Laboratory

## 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

## 1.2 Test Facility

### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

### **A2LA (Certificate Number: 3857.01)**

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

## 1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Fan Guangchang  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <https://www.eurofins.com/electrical-and-electronics>  
E-mail: Jack.Fan@cpt.eurofinscn.com

## 2 General Description of Equipment Under Test

### 2.1 Applicant and Manufacturer Information

<b>Applicant</b>	Roobuck Pty Ltd
<b>Applicant address</b>	6/20 West Street, Brookvale, NSW, Australia
<b>Manufacturer</b>	Roobuck Pty Ltd
<b>Manufacturer address</b>	6/20 West Street, Brookvale, NSW, Australia

### 2.2 General Information

EUT Description			
Device Type	Portable Device		
Model	RBT6A-WB; RPT6A-WB		
Lab internal SN	R2403A0239/S01		
HW Version	V1.1		
SW Version	V1.1		
Power Rating	DC 3.6V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	PCB Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	NFC	/	13.56
	RFID	/	915 ~ 921
EUT Accessory			
Battery	Manufacturer: Panasonic Model: NCR18650GA DC 3.6V, 6Ah		
Auxiliary Test Equipment			
Phone	Manufacturer: SAMSUNG Model: Galaxy S5 Edge+ SN: R28H40J6DSE		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.			

The differences between models are as follows:

Item	RBT6A-WB	RPT6A-WB
Application	Carried on the belt for personal track	Put in a vehicle for vehicle track
Product label	For Belt tag name and model	For Portable tag name and model
Firmware	No effect on hardware and wireless	
Others	The same	
Note: This report only tested RBT6A-WB.		

## 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### Test standards

**FCC Code CFR47 Part15B (2023)**

**ANSI C63.4-2014**

## 2.4 Test Mode

Test Mode	
Mode 1	Battery Powered + EUT + Phone Bluetooth pairing + Working
Mode 2	Battery Powered + EUT+ Standby

Test Type	Test Mode	Worst Mode
Radiated Emission	Mode 1, 2	Mode 1
Conducted Emission	/	/
During the test, the preliminary test was performed in all modes, the test data of the worst-case condition was recorded in this report.		



### 3 Test Case Results

#### 3.1 Radiated Emission

##### Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

##### Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 10 meters below 1GHz; 3 meters for above 1GHz. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO


(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

**Test Setup**


**Below 1GHz**

**Distance 10m**



Note: Area side: 21m x 12m

**Above 1GHz**



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

**Limits**

**Class B**

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Detector
30 -88	30.0	Quasi-peak
88-216	33.5	Quasi-peak
216 – 960	36.0	Quasi-peak
960-1000	44.0	Quasi-peak
1000-5 <sup>th</sup> harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak


**Frequency range of radiated measurements**

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

**Test Results**

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier.


The following graphs display the maximum values of horizontal and vertical by software.  
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.



Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Polarization	Azimuth (deg)	Correct Factor (dB)
163.387	26.56	33.50	6.94	1.16	V	322.6	-12.46
168.297	30.51	33.50	2.99	1.91	V	220.1	-12.20
178.009	23.76	33.50	9.74	1.11	V	82.2	-11.76
195.104	20.18	33.50	13.32	1.75	V	254.8	-10.19
209.481	19.02	33.50	14.48	1.16	V	45.2	-9.68
419.761	26.59	36.00	9.41	4.00	V	41.2	-4.15

**Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss+amplifier gain)**  
**2. Margin = Limit – Quasi-Peak**



Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dB µ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1431.38	---	22.63	54.00	31.37	1000.00	110.0	H	353.00	-20
1514.25	35.08	---	74.00	38.92	1000.00	110.0	H	344.00	-20
2045.50	---	23.18	54.00	30.82	1000.00	198.0	H	12.00	-19
2060.38	34.88	---	74.00	39.12	1000.00	210.0	V	236.00	-19
2544.88	37.23	---	74.00	36.77	1000.00	197.0	V	320.00	-17
2561.88	---	24.64	54.00	29.36	1000.00	100.0	V	11.00	-17
3996.25	---	27.07	54.00	26.93	1000.00	210.0	V	242.00	-13
4017.50	40.82	---	74.00	33.18	1000.00	110.0	V	153.00	-13
6663.13	44.65	---	74.00	29.35	1000.00	198.0	H	238.00	-5
6767.25	---	32.25	54.00	21.75	1000.00	110.0	H	302.00	-5
10622.00	50.63	---	74.00	23.37	1000.00	210.0	H	319.00	0
11089.50	---	38.58	54.00	15.42	1000.00	198.0	H	58.00	1

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)  
 2. Margin = Limit –MAX Peak/ Average

### 3.2 Conducted Emission


#### Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

#### Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

#### Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

#### Limits

Frequency (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 to 56 *	56 to 46*
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50

\*: Decreases with the logarithm of the frequency.

Note: The EUT should meet CLASS B limit.

**Test Results**

The equipment doesn't connected to public network, therefore this requirement do not apply.

## 4 Uncertainty Measurement

Case	Uncertainty(3m)	Uncertainty(10m)	Factor k
Radiated Emission 30MHz – 200MHz	--	3.39 dB	1.96
Radiated Emission 200MHz – 1GHz	--	3.82 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	--	1.96



## 5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESR	102389	2023-05-12 2024-05-07	2024-05-11 2025-05-06
Signal Analyzer	R&S	FSV40	101186	2023-05-12 2024-05-07	2024-05-11 2025-05-06
EMI Test Receiver	R&S	ESR	102720	2023-09-19 2024-05-07	2024-09-18 2025-05-06
EMI Test Receiver	R&S	ESR	102721	2023-09-19 2024-05-07	2024-09-18 2025-05-06
Signal Analyzer	R&S	FSV3044	103495	2023-09-19 2024-05-07	2024-09-18 2025-05-06
Horn Antenna	R&S	HF907	102723	2021-07-24	2024-07-23
Amplifier	MicroWave	KLNA-18040050	220826001	2023-05-12 2024-05-08	2024-05-11 2025-05-07
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	01614	2023-09-13	2026-09-12
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	01615	2023-10-19	2026-10-18
Software	R&S	EMC32	9.26.01	/	/
Software	R&S	ELEKTRA	5.00.2	/	/

## **ANNEX A: The EUT Appearance**

The EUT Appearance are submitted separately.

## ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.

\*\*\*\*\* END OF REPORT \*\*\*\*\*