



ZHONGHAN

Project No.: ZHT-231027038E

Page 1 of 94

FCC TEST REPORT

FCC ID: 2BDLF-P2961

Report Number : ZHT-231027038E

Date of Test : Oct.27, 2023 to Nov. 07, 2023

Date of issue : Nov. 07, 2023

Test Result : PASS

Testing Laboratory : Guangdong Zhonghan Testing Technology Co., Ltd.

Address : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Applicant's name : Shenzhen WOSD Technology Co.

Address : Room 505, West Block, Building 405, Sanda Industrial Zone, Langguang Road, Huaqiangbei Street, Futian District, Shenzhen, China

Manufacturer's name : Shenzhen WOSD Technology Co.

Address : Room 505, West Block, Building 405, Sanda Industrial Zone, Langguang Road, Huaqiangbei Street, Futian District, Shenzhen, China

Test specification

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Test procedure : KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2013

Non-standard test method : N/A

This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Product name : Wireless headset

Trademark : WoSD , QiSiMiaoX

Model (s) : P2961

P2960, P2962, P2963, P2965, P2966,P2967,P2968, P2969, P2970, P7233, P202, P7236, P7235, P678, P733, P6065, P6066, H1,H2,H3,H4,H5,H6,H7,H8,H9,H10,SN-30,SN-31,SN-32,SN-33,SN-34,SN-35,SN-36, SN-37, SN-38,SN-39,SN-660,SY-T1, SY-T2, SY-T3, SY-4,SY-T5,SY-T6,SY-T7, SY-T8,SY-T9, SY-T10, SY-T11, SY-T12, SY-T13, SY-T14, SY-T25,SY-T15, SY-T30, SY-T30C, SY-T31, SY-T830, SY-T35, SY-T36,SY-T40, SY-T41, SY-T45, SY-T46, SY-T50, SY-T51, SY-T55,SY-T56, SY-T60, SY-T61, SY-T65, SY-T66, SY-T70, SY-T71, SY-G10, GM-1SY-G15, SY-G20, SY-G40,SY-830MV,SY950,Y08,Y08M,Y08R,SY28, RETRO-1, GM-110,BQ40,S20,P201,P202,P203,P204,P205,P206,P207,P208, P209,P101,P102,P103MSZ910,VJ901,CXT-02,M8

Model difference : Only the model name is difference.



ZHONGHAN

Project No.: ZHT-231027038E

Page 2 of 94

Ratings : DC 5V by adapter or DC 3.7V by battery

Testing procedure and testing location:

Testing Laboratory : Guangdong Zhonghan Testing Technology Co., Ltd.

Address : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tested by (name + signature) : Kevin Yang

Reviewer (name + signature) : Baret Wu

Approved (name + signature) : Levi Lee



Table of Contents

	Page
1. VERSION	5
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 Test Setup Configuration	10
3.3 Support Equipment	10
3.4 Test Mode	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	13
4.1 Conducted emissions.....	13
4.1.1 POWER LINE CONDUCTED EMISSION Limits	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD.....	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS.....	14
4.1.6 Test Result	15
4.2 Radiated emissions.....	17
4.2.1 Radiated Emission Limits.....	17
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD.....	18
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS.....	19
4.2.6 TEST RESULTS	20
5.1 Test Requirement:	25
5.2 TEST PROCEDURE	25
5.3 DEVIATION FROM TEST STANDARD	26
5.4 TEST SETUP	26
5.5 EUT OPERATING CONDITIONS	26
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	29
6.1 Limit.....	29
6.2 Test Setup	29
6.3 Test procedure	29
6.4 DEVIATION FROM STANDARD	29
6.5 Test Result	29
7. 20DB&99% BANDWIDTH.....	30
7.1 Test Setup	30
7.2 Limit.....	30
7.3 Test procedure	30
7.4 DEVIATION FROM STANDARD	30
7.5 Test Result	30
8. MAXIMUM PEAK OUTPUT POWER.....	31
8.1 Block Diagram Of Test Setup	31
8.2 Limit.....	31
8.3 Test procedure	31
8.4 DEVIATION FROM STANDARD	31
8.5 Test Result	31
9. HOPPING CHANNEL SEPARATION.....	32
9.1 Test Setup	32
9.2 Test procedure	32
9.3 DEVIATION FROM STANDARD	32
10. NUMBER OF HOPPING FREQUENCY.....	33
10.1 Test Setup	33
10.2 Test procedure	33



ZHONGHAN

10.3 DEVIATION FROM STANDARD	33
11.1 Test Setup	34
11.2 Test procedure	34
11.3 DEVIATION FROM STANDARD	34
11.4 Test Result.....	34
12. ANTENNA REQUIREMENT.....	35
13.APPENDIX BT	36
13.1 Maximum Peak Conducted Output Power	36
13.2 -20dB Bandwidth.....	42
13.3 Occupied Channel Bandwidth	48
13.4 Dwell Time	54
13.5 Band Edge	64
13.6 Band Edge(Hopping)	71
13.7 Conducted RF Spurious Emission.....	78
13.8 Carrier Frequencies Separation.....	88
13.9 Number of Hopping Channel	91
14. TEST SETUP PHOTO	94
15. EUT CONSTRUCTIONAL DETAILS	94



ZHONGHAN

1. VERSION

Report No.	Version	Description	Approved
ZHT-231027038E	Rev.01	Initial issue of report	Nov. 07, 2023



ZHONGHAN

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



ZHONGHAN

2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.

Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number: 255941

Designation Number: CN0325

IC Registered No.: 29832

CAB identifier: CN0143

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(9k-30MHz)	$\pm 4.68\text{dB}$
5	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
6	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	Occupied Bandwidth	$\pm 4.96\text{dB}$



ZHONGHAN

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Wireless headset
Model No.:	P2961
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz-2480MHz
Modulation technology:	GFSK, π/4DQPSK, 8DPSK
Antenna Type:	PCB Antenna
Antenna gain:	-0.58dBi
Ratings :	DC 5V by adapter or DC 3.7V by battery



ZHONGHAN

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz



ZHONGHAN


Project No.: ZHT-231027038E

Page 10 of 94

3.2 Test Setup Configuration Radiated Emission

EUT

Conducted Emission



3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	AC Adapter	Huawei	HW-050450C00	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	



ZHONGHAN

Project No.: ZHT-231027038E

Page 11 of 94

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	Mar 12, 2023	Mar 11, 2024
2	Loop antenna	EMCI	LAP600	Mar 12, 2023	Mar 11, 2024
3	Amplifier	Schwarzbeck	BBV 9743 B	Mar 12, 2023	Mar 11, 2024
4	Amplifier	Schwarzbeck	BBV 9718 B	Mar 12, 2023	Mar 11, 2024
5	Bilog Antenna	Schwarzbeck	VULB9162	Mar 17, 2023	Mar 16, 2024
6	Horn Antenna	Schwarzbeck	BBHA9120D	Mar 17, 2023	Mar 16, 2024
7	Horn Antenna	A.H.SYSTEMS	SAS574	Mar 12, 2023	Mar 11, 2024
8	Amplifier	AEROFLEX	100KHz-40GHz	Mar 12, 2023	Mar 11, 2024
9	Spectrum Analyzer	R&S	FSV40	Mar 12, 2023	Mar 11, 2024
11	966 Anechoic Chamber	EMToni	9m6m6m	Nov. 25, 2021	Nov. 24, 2024
12	Spectrum Analyzer	KEYSIGHT	N9020A	Mar 12, 2023	Mar 11, 2024
13	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	Mar 12, 2023	Mar 11, 2024
14	Single Generator	Agilent	N5182A	Mar 12, 2023	Mar 11, 2024
15	Power Sensor	MWRFtest	MW100-RFCB	Mar 12, 2023	Mar 11, 2024
16	Audio analyzer	R&S	UPL	Mar 12, 2023	Mar 11, 2024
17	Single Generator	R&S	SMB100A	Mar 12, 2023	Mar 11, 2024
18	Power Amplifier Shielding Room	EMToni	2m3m3m	Nov. 25, 2021	Nov. 24, 2024



ZHONGHAN

Project No.: ZHT-231027038E

Page 12 of 94

Conduction Test equipment

Equipment	Manufacturer	Model	Last Cal.	Next Cal.
Receiver	R&S	ESCI	Mar 12, 2023	Mar 11, 2024
LISN	R&S	ENV216	Mar 12, 2023	Mar 11, 2024
ISN CAT 6	Schwarzbeck	NTFM 8158	Mar 12, 2023	Mar 11, 2024
ISN CAT 5	Schwarzbeck	CAT5 8158	Mar 12, 2023	Mar 11, 2024
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	Mar 12, 2023	Mar 11, 2024
Current Transformer Clamp	Schwarzbeck	SW 9605	Mar 12, 2023	Mar 11, 2024
CE Shielding Room	EMToni	9m4m3m	Nov. 25, 2021	Nov. 24, 2024



ZHONGHAN

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


4.1.6 Test Result

Temperature:	26.1 °C	Relative Humidity:	52%
Pressure:	101.3kPa	Phase :	Live
Test Mode	Charging mode	Remark:	N/A



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2670	28.31	9.94	38.25	61.21	-22.96	QP	P	
2	0.2670	13.48	9.94	23.42	51.21	-27.79	AVG	P	
3	0.3390	27.99	9.96	37.95	59.23	-21.28	QP	P	
4	0.3390	12.27	9.96	22.23	49.23	-27.00	AVG	P	
5 *	0.4694	27.73	10.00	37.73	56.52	-18.79	QP	P	
6	0.4694	13.55	10.00	23.55	46.52	-22.97	AVG	P	
7	0.5280	27.17	10.02	37.19	56.00	-18.81	QP	P	
8	0.5280	12.92	10.02	22.94	46.00	-23.06	AVG	P	
9	0.5865	26.25	10.03	36.28	56.00	-19.72	QP	P	
10	0.5865	10.99	10.03	21.02	46.00	-24.98	AVG	P	
11	1.0590	25.35	10.06	35.41	56.00	-20.59	QP	P	
12	1.0590	8.07	10.06	18.13	46.00	-27.87	AVG	P	

Temperature:	26.1 °C	Relative Humidity:	52%
Pressure:	101.3kPa	Phase :	Neutral
Test Mode	Charging mode	Remark:	N/A



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2040	26.16	9.91	36.07	63.45	-27.38	QP	P	
2	0.2040	10.58	9.91	20.49	53.45	-32.96	AVG	P	
3	0.2670	25.78	9.94	35.72	61.21	-25.49	QP	P	
4	0.2670	11.93	9.94	21.87	51.21	-29.34	AVG	P	
5	0.3345	23.34	9.96	33.30	59.34	-26.04	QP	P	
6	0.3345	11.66	9.96	21.62	49.34	-27.72	AVG	P	
7 *	0.4694	24.34	10.00	34.34	56.52	-22.18	QP	P	
8	0.4694	11.47	10.00	21.47	46.52	-25.05	AVG	P	
9	0.5280	23.07	10.02	33.09	56.00	-22.91	QP	P	
10	0.5280	11.39	10.02	21.41	46.00	-24.59	AVG	P	
11	0.5865	22.58	10.03	32.61	56.00	-23.39	QP	P	
12	0.5865	8.18	10.03	18.21	46.00	-27.79	AVG	P	



ZHONGHAN

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


Between 30MHz – 1GHz

Temperature:	25.6°C	Relative Humidity:	47%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7 V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	122.8340	35.36	-13.07	22.29	43.50	-21.21	QP
2	737.0712	22.97	-0.16	22.81	46.00	-23.19	QP
3	821.7103	22.18	1.00	23.18	46.00	-22.82	QP
4	863.0561	22.46	1.63	24.09	46.00	-21.91	QP
5	916.0685	22.33	2.33	24.66	46.00	-21.34	QP
6	986.0715	23.88	2.98	26.86	54.00	-27.14	QP

Temperature:	25.6°C	Relative Humidity:	47%
Pressure:	101 kPa	Polarization:	Vertical
Test Voltage:	DC 3.7 V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	122.8340	42.81	-13.07	29.74	43.50	-13.76	QP
2	135.0318	35.72	-13.49	22.23	43.50	-21.27	QP
3	338.4000	31.28	-7.17	24.11	46.00	-21.89	QP
4	467.2350	30.48	-4.63	25.85	46.00	-20.15	QP
5	804.6027	23.31	0.75	24.06	46.00	-21.94	QP
6	909.6666	22.61	2.28	24.89	46.00	-21.11	QP



ZHONGHAN

Project No.: ZHT-231027038E

Page 22 of 94

1GHz~25GHz

GFSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	55.04	30.55	5.77	24.66	54.92	74	-19.08	Pk
V	4804	43.42	30.55	5.77	24.66	43.3	54	-10.7	AV
V	7206	56.81	30.33	6.32	24.55	57.35	74	-16.65	Pk
V	7206	42.89	30.33	6.32	24.55	43.43	54	-10.57	AV
H	4804	58.23	30.55	5.77	24.66	58.11	74	-15.89	Pk
H	4804	43.54	30.55	5.77	24.66	43.42	54	-10.58	AV
H	7206	58.43	30.33	6.32	24.55	58.97	74	-15.03	Pk
H	7206	41.89	30.33	6.32	24.55	42.43	54	-11.57	AV
Middle Channel:2441MHz									
V	4882	59.85	30.55	5.77	24.66	59.73	74	-14.27	Pk
V	4882	41.41	30.55	5.77	24.66	41.29	54	-12.71	AV
V	7323	57.41	30.33	6.32	24.55	57.95	74	-16.05	Pk
V	7323	41.47	30.33	6.32	24.55	42.01	54	-11.99	AV
H	4882	56.6	30.55	5.77	24.66	56.48	74	-17.52	Pk
H	4882	41.29	30.55	5.77	24.66	41.17	54	-12.83	AV
H	7323	58.53	30.33	6.32	24.55	59.07	74	-14.93	Pk
H	7323	41.57	30.33	6.32	24.55	42.11	54	-11.89	AV
High Channel:2480MHz									
V	4960	57.72	30.55	5.77	24.66	57.6	74	-16.4	Pk
V	4960	41.81	30.55	5.77	24.66	41.69	54	-12.31	AV
V	7440	55.14	30.33	6.32	24.55	55.68	74	-18.32	Pk
V	7440	43.78	30.33	6.32	24.55	44.32	54	-9.68	AV
H	4960	55.52	30.55	5.77	24.66	55.4	74	-18.6	Pk
H	4960	42.96	30.55	5.77	24.66	42.84	54	-11.16	AV
H	7440	57.53	30.33	6.32	24.55	58.07	74	-15.93	Pk
H	7440	43.77	30.33	6.32	24.55	44.31	54	-9.69	AV



ZHONGHAN

Project No.: ZHT-231027038E

Page 23 of 94

π/4DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli- fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	55.81	30.55	5.77	24.66	55.69	74	-18.31	Pk
V	4804	43.58	30.55	5.77	24.66	43.46	54	-10.54	AV
V	7206	55.36	30.33	6.32	24.55	55.9	74	-18.1	Pk
V	7206	41.65	30.33	6.32	24.55	42.19	54	-11.81	AV
H	4804	59.12	30.55	5.77	24.66	59	74	-15	Pk
H	4804	44.48	30.55	5.77	24.66	44.36	54	-9.64	AV
H	7206	60	30.33	6.32	24.55	60.54	74	-13.46	Pk
H	7206	44.12	30.33	6.32	24.55	44.66	54	-9.34	AV
Middle Channel:2441MHz									
V	4882	55.9	30.55	5.77	24.66	55.78	74	-18.22	Pk
V	4882	41.73	30.55	5.77	24.66	41.61	54	-12.39	AV
V	7323	55.95	30.33	6.32	24.55	56.49	74	-17.51	Pk
V	7323	41.96	30.33	6.32	24.55	42.5	54	-11.5	AV
H	4882	55.16	30.55	5.77	24.66	55.04	74	-18.96	Pk
H	4882	41.4	30.55	5.77	24.66	41.28	54	-12.72	AV
H	7323	59.51	30.33	6.32	24.55	60.05	74	-13.95	Pk
H	7323	41.3	30.33	6.32	24.55	41.84	54	-12.16	AV
High Channel:2480MHz									
V	4960	59.64	30.55	5.77	24.66	59.52	74	-14.48	Pk
V	4960	41.88	30.55	5.77	24.66	41.76	54	-12.24	AV
V	7440	56.76	30.33	6.32	24.55	57.3	74	-16.7	Pk
V	7440	41.08	30.33	6.32	24.55	41.62	54	-12.38	AV
H	4960	59.28	30.55	5.77	24.66	59.16	74	-14.84	Pk
H	4960	42.96	30.55	5.77	24.66	42.84	54	-11.16	AV
H	7440	59.49	30.33	6.32	24.55	60.03	74	-13.97	Pk
H	7440	44.59	30.33	6.32	24.55	45.13	54	-8.87	AV



ZHONGHAN

8DPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	55.27	30.55	5.77	24.66	55.15	74	-18.85	Pk
V	4804	41.02	30.55	5.77	24.66	40.9	54	-13.1	AV
V	7206	56.5	30.33	6.32	24.55	57.04	74	-16.96	Pk
V	7206	44.7	30.33	6.32	24.55	45.24	54	-8.76	AV
H	4804	58.85	30.55	5.77	24.66	58.73	74	-15.27	Pk
H	4804	42.43	30.55	5.77	24.66	42.31	54	-11.69	AV
H	7206	57.92	30.33	6.32	24.55	58.46	74	-15.54	Pk
H	7206	41.21	30.33	6.32	24.55	41.75	54	-12.25	AV
Middle Channel:2441MHz									
V	4882	59.87	30.55	5.77	24.66	59.75	74	-14.25	Pk
V	4882	41.53	30.55	5.77	24.66	41.41	54	-12.59	AV
V	7323	59.74	30.33	6.32	24.55	60.28	74	-13.72	Pk
V	7323	42.38	30.33	6.32	24.55	42.92	54	-11.08	AV
H	4882	57.29	30.55	5.77	24.66	57.17	74	-16.83	Pk
H	4882	41.64	30.55	5.77	24.66	41.52	54	-12.48	AV
H	7323	56.89	30.33	6.32	24.55	57.43	74	-16.57	Pk
H	7323	41.04	30.33	6.32	24.55	41.58	54	-12.42	AV
High Channel:2480MHz									
V	4960	56.03	30.55	5.77	24.66	55.91	74	-18.09	Pk
V	4960	41.09	30.55	5.77	24.66	40.97	54	-13.03	AV
V	7440	56.29	30.33	6.32	24.55	56.83	74	-17.17	Pk
V	7440	44.01	30.33	6.32	24.55	44.55	54	-9.45	AV
H	4960	55.82	30.55	5.77	24.66	55.7	74	-18.3	Pk
H	4960	44.74	30.55	5.77	24.66	44.62	54	-9.38	AV
H	7440	57.56	30.33	6.32	24.55	58.1	74	-15.9	Pk
H	7440	43	30.33	6.32	24.55	43.54	54	-10.46	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



ZHONGHAN

Project No.: ZHT-231027038E

Page 25 of 94

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:


- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP**Radiated Emission Test-Up Frequency Above 1GHz****5.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



ZHONGHAN

Project No.: ZHT-231027038E

Page 27 of 94

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margin (dB)	Detector Type	Result
Low Channel: 2402MHz											
GFSK	H	2390.00	60.79	30.22	4.85	23.98	59.40	74.00	-14.60	Pk	PASS
	H	2390.00	46.19	30.22	4.85	23.98	44.80	54.00	-9.20	AV	PASS
	H	2400.00	60.72	30.22	4.85	23.98	59.33	74.00	-14.67	Pk	PASS
	H	2400.00	46.20	30.22	4.85	23.98	44.81	54.00	-9.19	AV	PASS
	V	2390.00	62.45	30.22	4.85	23.98	61.06	74.00	-12.94	Pk	PASS
	V	2390.00	46.86	30.22	4.85	23.98	45.47	54.00	-8.53	AV	PASS
	V	2400.00	60.36	30.22	4.85	23.98	58.97	74.00	-15.03	Pk	PASS
	V	2400.00	47.95	30.22	4.85	23.98	46.56	54.00	-7.44	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	60.92	30.22	4.85	23.98	59.53	74.00	-14.47	PK	PASS
	H	2483.50	48.87	30.22	4.85	23.98	47.48	54.00	-6.52	AV	PASS
	H	2500.00	61.02	30.22	4.85	23.98	59.63	74.00	-14.37	PK	PASS
	H	2500.00	47.97	30.22	4.85	23.98	46.58	54.00	-7.42	AV	PASS
	V	2483.50	61.71	30.22	4.85	23.98	60.32	74.00	-13.68	PK	PASS
	V	2483.50	48.17	30.22	4.85	23.98	46.78	54.00	-7.22	AV	PASS
	V	2500.00	61.66	30.22	4.85	23.98	60.27	74.00	-13.73	PK	PASS
	V	2500.00	46.15	30.22	4.85	23.98	44.76	54.00	-9.24	AV	PASS
$\pi/4$ DQPSK	Low Channel: 2402MHz										
	H	2390.00	62.78	30.22	4.85	23.98	61.39	74.00	-12.61	PK	PASS
	H	2390.00	48.89	30.22	4.85	23.98	47.50	54.00	-6.50	AV	PASS
	H	2400.00	61.09	30.22	4.85	23.98	59.70	74.00	-14.30	PK	PASS
	H	2400.00	46.77	30.22	4.85	23.98	45.38	54.00	-8.62	AV	PASS
	V	2390.00	61.24	30.22	4.85	23.98	59.85	74.00	-14.15	PK	PASS
	V	2390.00	46.70	30.22	4.85	23.98	45.31	54.00	-8.69	AV	PASS
	V	2400.00	59.24	30.22	4.85	23.98	57.85	74.00	-16.15	PK	PASS
	V	2400.00	48.31	30.22	4.85	23.98	46.92	54.00	-7.08	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	61.29	30.22	4.85	23.98	59.90	74.00	-14.10	PK	PASS
	H	2483.50	46.50	30.22	4.85	23.98	45.11	54.00	-8.89	AV	PASS
	H	2500.00	60.38	30.22	4.85	23.98	58.99	74.00	-15.01	PK	PASS
	H	2500.00	48.77	30.22	4.85	23.98	47.38	54.00	-6.62	AV	PASS
	V	2483.50	60.42	30.22	4.85	23.98	59.03	74.00	-14.97	PK	PASS
	V	2483.50	46.74	30.22	4.85	23.98	45.35	54.00	-8.65	AV	PASS
	V	2500.00	62.81	30.22	4.85	23.98	61.42	74.00	-12.58	PK	PASS
	V	2500.00	46.17	30.22	4.85	23.98	44.78	54.00	-9.22	AV	PASS
8DPSK	Low Channel: 2402MHz										
	H	2390.00	59.44	30.22	4.85	23.98	58.05	74.00	-15.95	PK	PASS
	H	2390.00	47.80	30.22	4.85	23.98	46.41	54.00	-7.59	AV	PASS
	H	2400.00	62.85	30.22	4.85	23.98	61.46	74.00	-12.54	PK	PASS
	H	2400.00	47.73	30.22	4.85	23.98	46.34	54.00	-7.66	AV	PASS
	V	2390.00	59.77	30.22	4.85	23.98	58.38	74.00	-15.62	PK	PASS
	V	2390.00	46.77	30.22	4.85	23.98	45.38	54.00	-8.62	AV	PASS
	V	2400.00	60.18	30.22	4.85	23.98	58.79	74.00	-15.21	PK	PASS
	V	2400.00	48.67	30.22	4.85	23.98	47.28	54.00	-6.72	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	62.02	30.22	4.85	23.98	60.63	74.00	-13.37	PK	PASS
	H	2483.50	46.09	30.22	4.85	23.98	44.70	54.00	-9.30	AV	PASS
	H	2500.00	60.17	30.22	4.85	23.98	58.78	74.00	-15.22	PK	PASS
	H	2500.00	46.44	30.22	4.85	23.98	45.05	54.00	-8.95	AV	PASS



ZHONGHAN

	V	2483.50	60.44	30.22	4.85	23.98	59.05	74.00	-14.95	PK	PASS
	V	2483.50	47.28	30.22	4.85	23.98	45.89	54.00	-8.11	AV	PASS
	V	2500.00	59.46	30.22	4.85	23.98	58.07	74.00	-15.93	PK	PASS
	V	2500.00	47.52	30.22	4.85	23.98	46.13	54.00	-7.87	AV	PASS

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD

No deviation.

6.5 Test Result

Please refer to the Appendix BT

7. 20DB&99% BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013

7.1 Test Setup



7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.

7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Please refer to the Appendix BT



ZHONGHAN

8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013

8.1 Block Diagram Of Test Setup



8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W.

8.3 Test procedure

The EUT was directly connected to the Power meter

8.4 DEVIATION FROM STANDARD

No deviation.

8.5 Test Result

Please refer to the Appendix BT

9. HOPPING CHANNEL SEPARATION

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=30KHz, VBW=100KHz, detector=Peak
Limit:	GFSK: 20dB bandwidth $\pi/4$ -DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup



9.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

9.3 DEVIATION FROM STANDARD

No deviation.


9.4 Test Result

Please refer to the Appendix BT

10. NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

10.1 Test Setup



10.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD

No deviation.


10.4 Test Result

Please refer to the Appendix BT

11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

11.3 DEVIATION FROM STANDARD

No deviation.

11.4 Test Result

Please refer to the Appendix BT



ZHONGHAN

Project No.: ZHT-231027038E

Page 35 of 94

12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna: The antenna is PCB Antenna, the best case gain of the antennas is -0.58dBi, reference to the appendix II for details	



ZHONGHAN

Project No.: ZHT-231027038E


Page 36 of 94

13.Appendix BT


13.1 Maximum Peak Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	-3.14	21	Pass
NVNT	1-DH5	2441	Ant1	-1.18	21	Pass
NVNT	1-DH5	2480	Ant1	-1.36	21	Pass
NVNT	2-DH5	2402	Ant1	-1.17	21	Pass
NVNT	2-DH5	2441	Ant1	-0.35	21	Pass
NVNT	2-DH5	2480	Ant1	-0.7	21	Pass
NVNT	3-DH5	2402	Ant1	-0.81	21	Pass
NVNT	3-DH5	2441	Ant1	0.02	21	Pass
NVNT	3-DH5	2480	Ant1	-0.3	21	Pass
















ZHONGHAN


13.2 -20dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	Ant1	1.008	Pass
NVNT	1-DH5	2441	Ant1	1.057	Pass
NVNT	1-DH5	2480	Ant1	1.044	Pass
NVNT	2-DH5	2402	Ant1	1.341	Pass
NVNT	2-DH5	2441	Ant1	1.321	Pass
NVNT	2-DH5	2480	Ant1	1.311	Pass
NVNT	3-DH5	2402	Ant1	1.295	Pass
NVNT	3-DH5	2441	Ant1	1.307	Pass
NVNT	3-DH5	2480	Ant1	1.304	Pass














ZHONGHAN


Project No.: ZHT-231027038E


Page 48 of 94


13.3 Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH5	2402	Ant1	0.916
NVNT	1-DH5	2441	Ant1	0.934
NVNT	1-DH5	2480	Ant1	0.947
NVNT	2-DH5	2402	Ant1	1.213
NVNT	2-DH5	2441	Ant1	1.205
NVNT	2-DH5	2480	Ant1	1.228
NVNT	3-DH5	2402	Ant1	1.211
NVNT	3-DH5	2441	Ant1	1.22
NVNT	3-DH5	2480	Ant1	1.219














ZHONGHAN


Project No.: ZHT-231027038E


Page 54 of 94


13.4 Dwell Time


Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2402	Ant1	2.88	313.92	109	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.88	282.24	98	31600	400	Pass
NVNT	1-DH5	2480	Ant1	2.879	305.174	106	31600	400	Pass
NVNT	2-DH5	2402	Ant1	2.878	307.946	107	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.878	328.092	114	31600	400	Pass
NVNT	2-DH5	2480	Ant1	2.886	288.6	100	31600	400	Pass
NVNT	3-DH5	2402	Ant1	2.887	332.005	115	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.888	303.24	105	31600	400	Pass
NVNT	3-DH5	2480	Ant1	2.887	303.135	105	31600	400	Pass


























ZHONGHAN


Project No.: ZHT-231027038E


Page 64 of 94


13.5 Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-47.91	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-52.63	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-50.77	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-51.17	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-50.36	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-53.2	-20	Pass


















ZHONGHAN


13.6 Band Edge(Hopping)


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-47.96	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-48.51	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-48.69	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-48.7	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-48.69	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-48.41	-20	Pass
















ZHONGHAN


Project No.: ZHT-231027038E


Page 78 of 94


13.7 Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-45.25	-20	Pass
NVNT	1-DH5	2441	Ant1	-46.09	-20	Pass
NVNT	1-DH5	2480	Ant1	-46.44	-20	Pass
NVNT	2-DH5	2402	Ant1	-48.18	-20	Pass
NVNT	2-DH5	2441	Ant1	-46.77	-20	Pass
NVNT	2-DH5	2480	Ant1	-48.22	-20	Pass
NVNT	3-DH5	2402	Ant1	-46.33	-20	Pass
NVNT	3-DH5	2441	Ant1	-46.92	-20	Pass
NVNT	3-DH5	2480	Ant1	-47.77	-20	Pass



























ZHONGHAN

13.8 Carrier Frequencies Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2440.85	2442.018	1.168	0.705	Pass
NVNT	2-DH5	Ant1	2440.996	2442.346	1.35	0.881	Pass
NVNT	3-DH5	Ant1	2440.852	2442.016	1.164	0.871	Pass









ZHONGHAN

13.9 Number of Hopping Channel

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass







ZHONGHAN

14. Test Setup Photo

Reference to the appendix I for details.

15. EUT Constructional Details

Reference to the appendix II for details.

***** END OF REPORT *****