

	TEST REPOR	T		
FCC ID:	2BDNT-FX-770			
Test Report No::	TCT231115E002	(3)		
Date of issue::	Jan. 29, 2024			
Testing laboratory:	SHENZHEN TONGCE TESTING	S LAB		
Testing location/ address:	2101 & 2201, Zhenchang Factor Fuhai Subdistrict, Bao'an District 518103, People's Republic of Ch	, Shenzhen, Guangdon		
Applicant's name::	Jiangmen Purevox Science and	Technology Co., Ltd.		
Address::	Floor 3, Building 5, No. 46-1, Xiyongli, Pengjiang District, Jiangmen, Guangdong, China			
Manufacturer's name:	Jiangmen Purevox Science and	Technology Co., Ltd.		
Address::	Floor 3, Building 5, No. 46-1, Xiyongli, Pengjiang District, Jiangmen, Guangdong, China			
Standard(s)::	FCC CFR Title 47 Part 1.1307			
Product Name::	CAR STEREO WITH AM FM RA	DIO		
Trade Mark:	QFX			
Model/Type reference:	FX-770			
Rating(s)::	DC 12V			
Date of receipt of test item:	Nov. 15, 2023			
Date (s) of performance of test:	Nov. 15, 2023 ~ Jan. 29, 2024			
Tested by (+signature):	Onnado YE	Onnado Jaiges		
Check by (+signature):	Beryl ZHAO	BoyC TCT		
Approved by (+signature):	Tomsin	Jomsin's si		

### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





# **Table of Contents**

2. (2 2. (3 3. I	General Pro  1.1. EUT deso  1.2. Model(s)  General Info  2.1. Test envi  2.2. Descripti  Facilities au  3.1. Facilities	cription listormation ironment a ion of Sup nd Accre	and mode. port Units ditations			3444
	3.2. Location Test Result					5 6



Report No.: TCT231115E002

# 1. General Product Information

# 1.1. EUT description

Product Name:	CAR STEREO WITH AM FM RADIO	(3)
Model/Type reference:	FX-770	
Sample Number:	TCT231115E001-0101	
Operation Frequency:	2402MHz~2480MHz	
Modulation Type:	GFSK, π/4-DQPSK, 8DPSK	
Antenna Type:	External Antenna	(c)
Antenna Gain:	-3.74dBi	
Rating(s):	DC 12V	

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

# 1.2. Model(s) list None.



Report No.: TCT231115E002

# 2. General Information

### 2.1. Test environment and mode

Item	Normal condition				
Temperature	+25°C				
Voltage	DC 12V				
Humidity	56%				
Atmospheric Pressure:	1008 mbar				
Test Mode:					
Transmitting Mode:	Keep the EUT in continuous transmitting by select channel				

# 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
1		1	1	1

### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



TESTING CENTRE TECHNOLOGY Report No.: TCT231115E002

# 3. Facilities and Accreditations

### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

**Designation Number: CN1205** 

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

## 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





Report No.: TCT231115E002

# 4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) The maximum output power for antenna is 3.43dBm (2.20mW) at 2480MHz, -3.74dBi antenna gain(with 0.42 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

### Calculation

Given

$$E = \sqrt{\frac{30 \times P \times G}{d}} \quad \& \quad S = \frac{E^2}{3770}$$

Where

E = Field Strength in Volts / meter

P = Power in Watts

G=Numeric antenna gain

d=Distance in meters

S=Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using d=20cm into above equation.

Yields: S=0.000199\*P\*G

Mode	Power(mW)	numeric antenna gain	Power density (mW/cm²)	Limit (mW/cm²)	Result
ВТ	2.20	0.42	0.000184	1.0	PASS

# \*\*\*\*\*END OF REPORT\*\*\*\*\*

