




FCC RADIO TEST REPORT

Applicant	: Hypertechnologie Ciara Inc. Ciara Technologies Inc
Address	: 9300 Transcanadienne St-Laurent, Quebec H4S 1K5 Canada
Equipment	: Notebook PC
Model No.	: CRIUS CO310-G1, CRIUS CO310-G1-BL, CRIUS N320-G1, CRIUS N320-G1-BL, CRIUS N310-G1, CRIUS N310-G1-BL
Trade Name	: 
FCC ID.	: 2BDS2-CRIUS
Standard	: FCC part 15 Subpart C §15.247

I HEREBY CERTIFY THAT:

The sample was received on Nov. 07, 2023 and the testing was completed on Nov. 30, 2023 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:


Leevin Li / Supervisor



CONTENTS

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test	6
2.2 Carrier Frequency of Channels	7
2.3 Test Mode and Test Software	8
2.4 Power Parameter Value of the test software	10
2.5 Description of Test System	11
2.6 General Information of Test	12
2.7 Measurement Uncertainty	12
3. Test Equipment and Ancillaries Used for Tests	13
4. Antenna Requirements	15
4.1 Standard Applicable	15
4.2 Antenna Construction and Directional Gain	15
5. Test of AC Power Line Conducted Emission	16
5.1 Test Limit	16
5.2 Test Procedures	16
5.3 Typical Test Setup	17
5.4 Test Result and Data	18
6. Test of Spurious Emission (Radiated)	20
6.1 Test Limit	20
6.2 Test Procedures	20
6.3 Typical Test Setup	21
6.4 Test Result and Data (9KHz ~ 30MHz)	22
6.5 Test Result and Data (30MHz ~ 1GHz)	22
6.6 Test Result and Data (1GHz ~ 25GHz)	26
6.7 Restricted Bands of Operation	98
6.8 Restrict Band Emission Measurement Data	99
7. Test of Conducted Spurious Emission	147
7.1 Test Limit	147
7.2 Test Procedure	147
7.3 Test Setup Layout	147
7.4 Test Result and Data	147
8. On Time, Duty Cycle and Measurement methods	162
8.1 Test Limit	162
8.2 Test Procedure	162
8.3 Test Setup Layout	162
8.4 Test Result and Data	162
9. 6dB Bandwidth Measurement Data	164
9.1 Test Limit	164
9.2 Test Procedures	164
9.3 Test Setup Layout	164
9.4 Test Result and Data	165
10.Maximum Peak Output Power	173



10.1 Test Limit 173

10.2 Test Procedures 173

10.3 Test Setup Layout..... 173

10.4 Test Result and Data 174

11. Power Spectral Density 176

11.1 Test Limit 176

11.2 Test Procedures 176

11.3 Test Setup Layout..... 176

11.4 Test Result and Data 177



History of this test report

Version No.	Report No	Date	Description
Rev.01	DEF12310067	Dec. 06, 2023	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
FCC CFR Title 47 Part 15 Subpart C: Section 15.203/15.247 (b)	. Antenna Requirement	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.207	. AC Power Line Conducted Emission	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.205/15.209;	. Spurious Emission(Radiated)	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(d);	. Spurious Emission(Conducted)	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(a)(2);	. 6dB Bandwidth	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(b);	. Maximum Peak Output Power	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(e)	. Power Spectral Density	Pass
Note: Deviations Yes ☐ No ☒ *The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.		



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Equipment	Notebook PC
Model Name	CRIUS CO310-G1, CRIUS CO310-G1-BL, CRIUS N320-G1, CRIUS N320-G1-BL, CRIUS N310-G1, CRIUS N310-G1-BL
Model Discrepancy	The Motherboard and Circuit principle are identical except different antenna gain, antenna location, HVIN, appearance, keyboard, Interface Board, battery. More details please refer to Product Similarity Declaration.
Module	AX211NGW
Frequency Range	BT/BLE/ WIFI 2.4G: 2400MHz-2483.5MHz WIFI 5G: 5150MHz-5250MHz, 5250MHz-5350MHz, 5470MHz -5725MHz, 5725MHz -5850MHz
Modulation Type	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK 2.4GHz 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM 5GHz 802.11a/n: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Data Rate	BT: GFSK:1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK:3Mbps BLE: GFSK: 1Mbps WIFI 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0-MCS15, HT20/HT40 802.11ax: MCS0-MCS11, HE20/HE40 WIFI 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0-MCS15, HT20/HT40 802.11ac: MCS0-MCS9, VHT20/40/80/160 802.11ax: MCS0-MCS11, HE20/HE40/HE80/HE160
Working Temperature	0°C to 35°C
EUT Power Rating:	DC IN Input: 19V $\approx$ 3.42A from adapter type -C port Input: 20V $\approx$ 3.25A from adapter

Note:

1. The EUT not support TPC Function.
2. EUT support Client mode without radar detection.
3. 11AX supports FULL RU only.
4. For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT 20, 802.11ax HE20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
*01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	*11	2462
*06	2437	---	---

802.11n HT40 , 802.11ax HE40 (2422MHz~2452MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
*03	2422	*09	2452
04	2427	---	---
05	2432	---	---
*06	2437	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- The complete test system included support units and EUT for RF test.
- An executive program, "DRTU.exe (Ver.: N/A)" under Windows 11 system was executed to transmit and receive data via WLAN.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	802.11b for 120V for CRIUS N310-G1
2	802.11g for 120V for CRIUS N310-G1
3	802.11n HT20 for 120V for CRIUS N310-G1
4	802.11n HT40 for 120V for CRIUS N310-G1
5	802.11ax HE20 for 120V for CRIUS N310-G1
6	802.11ax HE40 for 120V for CRIUS N310-G1
7	802.11ax HE40 for 120V for CRIUS CO310-G1
8	802.11ax HE40 for 120V for CRIUS N320-G1
9	802.11ax HE40 for 240V for CRIUS N310-G1
10	802.11ax HE40 for 240V for CRIUS CO310-G1
11	802.11ax HE40 for 240V for CRIUS N320-G1
caused "Test Mode 6 at CH3:2422" generated the worst case, it was reported as the final data.	
Radiated emission (Below 1GHz)	
Test Mode	Operating Description
1	802.11b for CRIUS N310-G1
2	802.11g for CRIUS N310-G1
3	802.11n HT20 for CRIUS N310-G1
4	802.11n HT40 for CRIUS N310-G1
5	802.11ax HE20 for CRIUS N310-G1
6	802.11ax HE40 for CRIUS N310-G1
7	802.11ax HE40 for CRIUS CO310-G1
8	802.11ax HE40 for CRIUS N320-G1
caused "Test Mode 6 at CH3:2422 for 1TX-Ant A and Test Mode 6 at CH6:2437 for 2TX" generated the worst case, it was reported as the final data.	
Radiated emission (1GHz ~ 25GHz) for 1TX	
1	802.11b (1Mbps) for CRIUS N310-G1
2	802.11g (6Mbps) for CRIUS N310-G1
3	802.11n HT20 (6.5Mbps) for CRIUS N310-G1
4	802.11n HT40 (13.5Mbps) for CRIUS N310-G1
5	802.11ax HE20 (7.3Mbps) for CRIUS N310-G1
6	802.11ax HE40 (14.6Mbps) for CRIUS N310-G1
7	802.11b (1Mbps) for CRIUS CO310-G1
8	802.11g (6Mbps) for CRIUS CO310-G1
9	802.11n HT20 (6.5Mbps) for CRIUS CO310-G1
10	802.11n HT40 (13.5Mbps) for CRIUS CO310-G1
11	802.11ax HE20 (7.3Mbps) for CRIUS CO310-G1
12	802.11ax HE40 (14.6Mbps) for CRIUS CO310-G1
13	802.11b (1Mbps) for CRIUS N320-G1
14	802.11g (6Mbps) for CRIUS N320-G1
15	802.11n HT20 (6.5Mbps) for CRIUS N320-G1
16	802.11n HT40 (13.5Mbps) for CRIUS N320-G1
17	802.11ax HE20 (7.3Mbps) for CRIUS N320-G1
18	802.11ax HE40 (14.6Mbps) for CRIUS N320-G1
caused "Test Mode 1~6 ant Ant A" generated the worst case, it was reported as the final data.	
Radiated emission (1GHz ~ 25GHz) for 2TX	
1	802.11n HT20 (13Mbps) for CRIUS N310-G1



2	802.11n HT40 (27Mbps) for CRIUS N310-G1
3	802.11ax HE20 (14.6Mbps) for CRIUS N310-G1
4	802.11ax HE40 (29.2Mbps) for CRIUS N310-G1
5	802.11n HT20 (13Mbps) for CRIUS CO310-G1
6	802.11n HT40 (27Mbps) for CRIUS CO310-G1
7	802.11ax HE20 (14.6Mbps) for CRIUS CO310-G1
8	802.11ax HE40 (29.2Mbps) for CRIUS CO310-G1
9	802.11n HT20 (13Mbps) for CRIUS N320-G1
10	802.11n HT40 (27Mbps) for CRIUS N320-G1
11	802.11ax HE20 (14.6Mbps) for CRIUS N320-G1
12	802.11ax HE40 (29.2Mbps) for CRIUS N320-G1
caused "Test Mode 1~4,6,10" generated the worst case, it was reported as the final data.	

Note: For Radiated emission (1GHz ~ 25GHz), Model CRIUS N310-G1 is the worst, Model CRIUS CO310-G1 and CRIUS N320-G1 only put the worst mode data

Modulation Type	TX CONFIGURATION
802.11b	1TX
802.11g	1TX
802.11n HT20	1TX/2TX
802.11n HT40	1TX/2TX
802.11ax HE20	1TX/2TX
802.11ax HE40	1TX/2TX



2.4 Power Parameter Value of the test software


Mode	Frequency (MHz)	Setting level			
		1TX		2TX	
		Ant 1	Ant 2	Ant 1	Ant 2
802.11b	2412	18.25	18.25	N/A	N/A
	2437	18.25	18.25	N/A	N/A
	2462	18.25	18.25	N/A	N/A
802.11g	2412	19	19	N/A	N/A
	2437	19	19	N/A	N/A
	2462	19	19	N/A	N/A
802.11n (20MHz)	2412	18	18	16	16
	2437	18	18	16	16
	2462	18	18	16	16
802.11n (40MHz)	2422	17	17	16	16
	2442	17	17	16	16
	2452	17	17	16	16
802.11ax (20MHz)	2412	18	18	16	16
	2437	18	18	16	16
	2462	18	18	16	16
802.11ax (40MHz)	2422	17	17	16	16
	2442	17	17	16	16
	2452	17	17	16	16



2.5 Description of Test System

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Adapter	Aoda	A869-200325C-Uus1	5019043	N/A

Connection Diagram





2.6 General Information of Test

Test Site	CerpPASS Technology Corporation(CerpPASS Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-DG	2023/11/20~2023/11/23	22~24℃ / 51~54%	Amos Zhang
Radiated Emissions	3M02-DG	2023/11/17~2023/12/23	22~24℃ / 48~54%	Amos Zhang
AC Power Line Conducted Emission	CON01-DG	2023/11/30	23℃ / 54%	Amos Zhang

2.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±2.60dB
Radiated Spurious Emission(9KHz~30MHz)	±4.10dB
Radiated Spurious Emission(30MHz~1GHz)	±4.51dB
Radiated Spurious Emission(1GHz~18GHz)	±5.36dB
Radiated Spurious Emission(18GHz~40GHz)	±5.43dB
6dB Bandwidth&20dB Bandwidth	±4.8%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±0.94dB
Power Spectral Density	±1.01dB
Dwell Time / Deactivation Time	±3.5%



3. Test Equipment and Ancillaries Used for Tests

AC Power Line Conducted Emission					
Test Site	CON01-DG				
Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100564	2023/01/06	2024/01/05
LISN	SCHWARZBECK	NSLK 8127	8127749	2023/08/03	2024/08/02
LISN	R&S	ENV216	100024	2023/01/06	2024/01/05
Cable	Aoda	RG214	Cable-06	2023/01/06	2024/01/05
Pulse Limiter with 10dB Attenuation	SCHWARZBECK	VTSD 9561-F	9561-F106	2023/01/06	2024/01/05
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2023/08/03	2024/08/02

Radiated Emissions					
Test Site	3M01-DG				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Test Receiver	R&S	ESCI	100565	2023/08/03	2024/08/02
Amplifier	EMCI	EMC330	980082	2023/05/06	2024/05/05
Loop Antenna	R&S	HFH2-Z2	100150	2022/05/11	2024/05/10
Bilog Antenna	Sunol Science	JB1	A072414-3	2022/06/09	2024/06/08
Preamplifier	Agilent	8449B	3008A02342	2023/08/03	2024/08/02
Preamplifier	COM-POWER	PA-840	711885	2023/05/06	2024/05/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120 D	9120D-619	2022/05/22	2024/05/21
Standard Gain Horn Antenna	TRC	HA-2640	18050	2022/05/09	2024/05/08
Standard Gain Horn Antenna	TRC	HA-1726	18051	2022/05/09	2024/05/08
FSQ Signal Analyzer	R&S	FSQ40	200012	2023/05/06	2024/05/05
Cable	EMCI	EM104-NM SM-8.5M	Cable-03	2023/08/03	2024/08/02
Cable	Jiuzhoubona	T-SMA	SMA48AL-7000	2023/08/03	2024/08/02
Cable	CH-CoDesigh	CCXA40-2.92-2.92-1M	21071954	2023/08/03	2024/08/02
Cable	CH-CoDesigh	CCX40-2.92 M-2.92M-9 M	21070892	2023/08/03	2024/08/02
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2023/08/03	2024/08/02



RF Conducted					
Test Site	RFCON01-DG				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
MXA Signal Analyzer	KEYSIGHT	N9020A	US46220290	2023/05/06	2024/05/05
EXA Signal Analyzer	KEYSIGHT	N9010A	MY53400169	2023/05/06	2024/05/05
ESG VECTOR SIGNAL GENERATOR	Agilent	E4438C	MY45092582	2023/05/06	2024/05/05
MXG VECTOR SIGNAL GENERATOR	Agilent	N5182B	MY53050127	2023/05/06	2024/05/05
USB Wideband Power Sensor	Boonton	55006	9778	2023/08/03	2024/08/02
Temperature/ Humidity Meter	mingle	ETH529	N/A	2023/01/06	2024/01/05



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

WIFI 2.4G:

For Model CRIUS N310-G1/ CRIUS N310-G1-BL

Antenna Type	FPC Antenna
Antenna Gain	Antenna A:4.27dBi (Aux) Antenna B:3.83dbi (Main)

(Non-Beamforming)

2400MHz-2483.5MHz

For 2TX

For Power/PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$
= 7.06(dBi)

For model CRIUS CO310-G1/ CRIUS CO310-G1-BL

Antenna Type	FPC Antenna
Antenna Gain	Antenna A: -0.4dBi (Aux) Antenna B: 2.06dbi (Main)

(Non-Beamforming)

2400MHz-2483.5MHz

For 2TX

For Power/PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$
= 3.93(dBi)

For model CRIUS N320-G1/ CRIUS N320-G1-BL

Antenna Type	FPC Antenna
Antenna Gain	Antenna A: -0.46dBi (Aux) Antenna B: 2.27dbi (Main)

(Non-Beamforming)

2400MHz-2483.5MHz

For 2TX

For Power/PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$
= 4.02(dBi)



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 6.2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

The EUT was setup according to ANSI C63.10, 2013 and tested according to DTS test procedure of Oct 2014 KDB558074 for compliance to FCC 47CFR 15.247 requirements. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.




5.3 Typical Test Setup






5.4 Test Result and Data



Note: Measurement Level = Reading Level + Correct Factor



Note: Measurement Level = Reading Level + Correct Factor



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

6.2 Test Procedures


- The EUT was placed on a rotatable table top 0.8 meter for frequency below 1GHz and 1.5meter for frequency above 1GHz above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than AVG limit (that means the emission level in peak mode also complies with the limit in AVG mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in AVG mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.
Note: The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions sch that emissions from the EUT are maximized.

(X-AXIS is the worst.)




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup








6.4 Test Result and Data (9KHz ~ 30MHz)


The 9kHz-30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)














6.6 Test Result and Data (1GHz ~ 25GHz)


Model CRIUS N310-G1


SISO-1TX















































































































MIMO-2TX






































































Model CRIUS CO310-G1

MIMO

