

RF Exposure Requirements

1.1 General Information

Client Information

Applicant : RADIOSHACK WORLDWIDE CORP.
Address of applicant : Building AFRA ,Ave. Samuel Lewis and street 54, Panama City,
Panama 5, Republic of Panama
Manufacturer : GUANGDONG KEGAO ELECTRONICS CO., LTD.
Address of manufacturer : No.39 East Science & Technology Ave. Zone A Shishan Science
&Technology Industrial Park, Nanhai District, Foshan,
Guangdong, P.R.China.

General Description of E.U.T

FCC ID : 2BDURAU50-06B
Product Name : Aroma Diffuser
Model No. : AU50-06B
Model Description : ---
Rated Voltage : DC 24V
Battery Capacity : ---
Power Adapter : HCX1201-2400500U
Input: 100-240V~, 50-60Hz, 0.5A; Output: DC 24V, 0.5A

Technical Characteristics of EUT

Support Standards : 802.11b, 802.11g, 802.11n
Frequency Range : 2412-2462MHz for 802.11b/g/n(HT20)
2422-2452MHz for 802.11n(HT40)
RF Output Power : 15.78dBm (Conducted)
Modulation : 802.11b: DSSS(DBPSK/DQPSK/CCK)
802.11g/n: OFDM (BPSK/QPSK/16QAM/64QAM)
Data Rate : 1-11Mbps, 6-54Mbps, up to 300Mbps
Quantity of Channels : 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation : 5MHz
Type of Antenna : PCB Printed Antenna
Antenna Gain : -0.24dBi

2 Applicable Standard

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalent power density

3 Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm), R=20cm.

4 MPE Calculation Result

Frequency (MHz)	Antenna Gain (dBi)	Numeric gain	Conducted Power (dBm)	Maximum Tune-up output power		PD (mW/cm ²)	Limit (mW/cm ²)
				(dBm)	(mW)		
2462	-0.24	0.95	15.78	16.00	39.81	0.00749	1

Result: Pass

=====End of Report=====