

# FCC Test Report

# Report No.: AGC00803240101FR01

FCC ID	:	2BDUU-MD190
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Wireless Mouse
BRAND NAME	:	B.O.W
MODEL NAME	:	MD190
APPLICANT	:	Shenzhen Hangshi Technology Co., Ltd.
DATE OF ISSUE	:	Jan. 15, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
<b>REPORT VERSION</b>	:	V1.0







# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Jan. 15, 2024	Valid	Initial Release	



# **Table of Contents**

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	
2.2 Test Frequency List	
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Receiver Input Bandwidth	7
2.6 Equally Average Use of Frequencies And Behaviour	7
2.7 Pseudorandom Frequency Hopping Sequence	
2.8 Special Accessories	
2.9 Equipment Modifications	
2.10 Antenna Requirement	
3. Test Environment	
3.1 Address of The Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	
3.4 Measurement Uncertainty	11
3.5 List of Equipment Used	
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. RF Output Power Measurement	
6.1 Provisions Applicable	
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	
6.4 Measurement Result	
7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Results	
8. Conducted Band Edge and Out-of-Band Emissions	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
	05



9. Radiated Spurious Emission	
9.1 Measurement Limit	
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Result	
10. Number of Hopping Frequency Measurement	45
10.1 Provisions Applicable	45
10.2 Measurement Procedure	45
10.3 Measurement Setup (Block Diagram of Configuration)	45
10.4 Measurement Result	45
11. Time of Occupancy (Dwell Time) Measurement	47
11.1 Provisions Applicable	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	
11.4 Measurement Result	
12. Frequency Separation Measurement	51
12.1 Provisions Applicable	51
12.2 Measurement Procedure	51
12.3 Measurement Setup (Block Diagram of Configuration)	51
12.4 Measurement Result	51
13. AC Power Line Conducted Emission Test	53
13.1 Measurement Limit	53
13.2 Measurement Setup (Block Diagram of Configuration)	53
13.3 Preliminary Procedure of Line Conducted Emission Test	54
13.4 Final Procedure of Line Conducted Emission Test	54
13.5 Measurement Results	54
Appendix I: Photographs of Test Setup	57
Appendix II: Photographs of Test EUT	



# **1. General Information**

Applicant	Shenzhen Hangshi Technology Co., Ltd.			
Address	2nd Floor, Building A1, Zone G, Minzhu West Industrial Zone, Minzhu Community, Shajing Street, Bao'an District, Shenzhen, 518104, China			
Manufacturer	Shenzhen Hangshi Electronic Technology Co., Ltd			
Address	2nd Floor, A1 Building, G Area, Democracy West Industry Area, Shajing Town, Bao'an District, Shenzhen, China.			
Factory	Shenzhen Hangshi Electronic Technology Co., Ltd			
Address	2nd Floor, A1 Building, G Area, Democracy West Industry Area, Shajing Town, Bao'an District, Shenzhen, China.			
Product Designation	Wireless Mouse			
Brand Name	B.O.W			
Test Model	MD190			
Series Model(s)	N/A			
Difference Description	N/A			
Date of receipt of test item	Jan. 08, 2024			
Date of Test	Jan. 08, 2024 to Jan. 15, 2024			
Deviation from Standard	No any deviation from the test method			
Condition of Test Sample	Normal			
Test Result	Pass			
Test Report Form No	AGCER-FCC-BR_EDR-V1			
NUMBER THAN A STATE OF A DATA OF A				

Note: The test results of this report relate only to the tested sample identified in this report.

Thea Yuang Prepared By Thea Huang Jan. 15, 2024 (Project Engineer) **Reviewed By** Calvin Liu Jan. 15, 2024 (Reviewer) Approved By

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Max Zhang

(Authorized Officer)

Jan. 15, 2024



# 2. Product Information

# 2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.0
Modulation Type	BR 🖾 GFSK, EDR 🗌 $\pi$ /4-DQPSK, $\square$ 8DPSK
Number of channels	79 Channels
Channel Separation	1 MHz
Maximum Transmitter Power	-0.898dBm
Hardware Version	V:1.0
Software Version	V1.0
Antenna Designation	PCB Antenna
Antenna Gain	2.34dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter
Adapter Information	N/A

# 2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
	0	2402 MHz		
	1	2403 MHz		
	:	:		
2400~2483.5MHz	39	2441MHz		
	:	:		
	77	2479 MHz		
	78	2480 MHz		
Note: f = 2402 + 1k MHz, k = 0,, 78 ; "f "is the operating frequency (MHz); "k" is the operating channel.				



# 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2BDUU-MD190**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

## 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title	
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations	
2	2 FCC 47 CFR Part 15 Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices	
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules	

## 2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

## 2.6 Equally Average Use of Frequencies And Behaviour

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:


The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



## 2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

44	35	78	03	20	76	02	19		21	64	75
						1		]			$\square$
			i						1		
			1			1			i		
			. !	<u>`</u>		<u>'i</u>		1			

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



## 2.8 Special Accessories

Not available for this EUT intended for grant.

## 2.9 Equipment Modifications

Not available for this EUT intended for grant.

## 2.10 Antenna Requirement

## Standard Requirement

## 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

#### EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.34dBi.



# 3. Test Environment

## 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

## CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

## A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

## IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



## **3.3 Environmental Conditions**

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V

## **3.4 Measurement Uncertainty**

The reported uncertainty of measurement y  $\pm$ U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



## 3.5 List of Equipment Used

• R	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
$\boxtimes$	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2023-06-01	2024-05-31		
$\boxtimes$	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2023-03-03	2024-03-02		
$\boxtimes$	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2023-03-03	2024-03-02		
	AGC-EM-A152	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08		
$\boxtimes$	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		

• F	Radiated Spurious Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\boxtimes$	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023-02-18	2024-02-17
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023-06-03	2024-06-02
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2022-03-12	2024-03-11
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
$\boxtimes$	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2024-03-22
$\boxtimes$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03
$\boxtimes$	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2023-06-01	2024-05-31
$\square$	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08

• A	AC Power Line Conducted Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\boxtimes$	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023-06-03	2024-06-02
$\boxtimes$	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023-06-03	2024-06-02
$\square$	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2024-06-08



• Te	Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information	
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71	
$\boxtimes$	AGC-EM-S003	RE-Test System	FARA	EZ-EMC	VRA-03A	
	AGC-ER-S012	BT/WIFI-Test System	Tonscend	JS1120-2	2.6	
$\square$	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0	



# **4.System Test Configuration**

## **4.1 EUT Configuration**


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

# 4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## 4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



# 4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

# ☑ Test Accessories Come From The Laboratory

No	Equipment	Model No.	Manufacturer	Specification Information	Cabl e
1	Control Box	USB-TTL			
2	Adapter	HW-200440C 00	Huawei	Input(AC):100V-240V 50/60Hz 2.4A Output(DC):USB-C(5V/3A;9V/3A;10V/4A;11V/ 6A;12V/3A;15V/3A;20V4.4A) USB-A(5V/2A;10V/4A;11V/6A;20V/4.4A)	

☑ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	ID/Specification Information	Cable
1	Wireless Mouse	MD190	Shenzhen Hangshi Electronic Technology Co., Ltd	2BDUU-MD190	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



## 4.5 Summary of Test Results

Item	FCC Rules	Description of Test Result	
1	§15.203&15.247(b)(4)	Antenna Equipment Pas	
2	§15.247 (b)(1)	RF Output Power Pass	
3	§15.247 (a)(1)	20 dB Bandwidth Pas	
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
5	§15.209	Radiated Spurious Emission Pa	
6	§15.247 (a)(1)(iii)	Number of Hopping Frequency Pa	
7	§15.247 (a)(1)(iii)	Time of Occupancy Pa	
8	§15.247 (a)(1)	Frequency Separation Pas	
9	§15.207	AC Power Line Conducted Emission	Pass



# 5. Description of Test Modes

	Summary table of Test Cases				
Test Item	Data Rate / Modulation				
iest item	Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)				
Radiated & Conducted Test Cases Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (Battery powered or AC/De Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (Battery powered or AC/De Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (Battery powered or AC/De					
AC Conducted Emission Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adap					
<ul> <li>2. The battery is full-cha</li> <li>3. For Radiated Emission</li> <li>4. For Conducted Test no set of the set of</li></ul>	Image: Strain of the string for each applicable mode.         nethod, a temporary antenna connector is provided by the manufacture.         Software Setting Diagram         en(Built On Mer 28 2022)             Image: Strain of the				
a1 a4 □□□□ [CMD] config.d_m [RCV:=]04 0E 06 01 1F 2	ode:1,freq:38, power:0, p_mode:1, hopping:0, rx_mode:0, aff:0, jpn:0, ble:1,dr:1Mbps.				

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

a1 a4

 Import
 [RCV:=]04 0E 06 01 1F 20 00 00 00

 [RCV:=]04 0E 06 01 1F 20 0C 3D 30



# 6. RF Output Power Measurement

# 6.1 Provisions Applicable

The maximum out power permissible output power is 1 Watt for all frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

The maximum out power permissible output power is 0.125 watts for all other frequency hopping systems in the 2400-2483.5 MHz band.

## **6.2 Measurement Procedure**

⊠For Peak power test:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW  $\geq$ RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

# $\boxtimes$ For Average power test:

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required


# 6.3 Measurement Setup (Block Diagram of Configuration)

 $\boxtimes$ For Average power test setup





# For peak power test setup




## 6.4 Measurement Result

Test Data of Conducted Output Power				
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2402	-1.012	≤21	Pass
GFSK	2441	-0.898	≤21	Pass
	2480	-0.963	≤21	Pass

# Test Result of Average Output Power (Reporting Only)

Test Data of Conducted Output Power				
Test Mode	Test Frequency (MHz)	Average Power (dBm)	Limits (dBm)	Pass or Fail
	2402	-3.215	≤21	Pass
GFSK	2441	-2.748	≤21	Pass
	2480	-2.632	≤21	Pass





#### **Test Graphs of Conducted Output Power**







# 7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement

## 7.1 Provisions Applicable


There is no corresponding limit requirement for this test item.

## 7.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 6.9.2 (20dB BW).

- The 20dB bandwidth spectrum analyzer setting reference is as follows:
- 1. Set RBW ≥ 1% to 5% of the 20dB bandwidth
- 2. VBW = Approximately three times RBW
- 3. Span = Approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated
- 9. with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20
- 10. dB relative to the maximum level in the fundamental emission.
- The 99% bandwidth spectrum analyzer setting reference is as follows:
- 1. Span = 1.5 times to 5 times the OBW
- 2. Set RBW = 1% to 5% the OBW
- 3. VBW  $\geq$  3 × RBW
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace was allowed to stabilize


# 7.3 Measurement Setup (Block Diagram of Configuration)






## 7.4 Measurement Results

Test Data of Occupied Bandwidth and -20dB Bandwidth					
Test Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail
	2402	0.869	0.910	N/A	Pass
GFSK	2441	0.872	0.915	N/A	Pass
	2480	0.852	0.885	N/A	Pass



## Test Graphs of Occupied Bandwidth and -20 Bandwidth







# 8. Conducted Band Edge and Out-of-Band Emissions

## **8.1 Provisions Applicable**


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

## 8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.10.4 and 7.8.8:


- Reference level measurement
- 1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- Emission level measurement
- 1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Trace was allowed to stabilize
- 8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

## 8.3 Measurement Setup (Block Diagram of Configuration)






#### **8.4 Measurement Results**




## Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

























## Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands







# 9. Radiated Spurious Emission

## 9.1 Measurement Limit

#### 15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

## 9.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection"

Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

#### The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting		
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP		
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP		



## • Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

#### Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

#### Average Measurements above 1GHz (Method VB)


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle  $\ge$  98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW  $\geq$  1/T. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize




## 9.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



peak

peak

-10.21

-8.57

46.00

46.00

#### 9.4 Measurement Result

5

6 \* 524.5541

903.3094

## **Radiated Emission Below 30MHz**

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz							
EUT Name	Wireless Mouse			Model	Name	MD190	
Temperature	<b>23.8</b> °C			Relativ	e Humidity	60.5%	
Pressure	960hPa			Test Vo	oltage	Normal Voltage	
Test Mode	Mode 2			Anten	na Polarity	Horizontal	
72.0 dBuV/m							
-8 30.000	1	70 80	(MHz)				
	0 40 30 60	Reading	Correct	Measure-			
No.	Mk. Freq.	Level	Factor	ment		Over	
	MHz	dBuV	dB	dBuV/m	dB/m	dB Detector	
1	211.5265	18.80	14.44	33.24	43.50 -1	0.26 peak	
2	227.6906	16.62	14.78	31.40	46.00 -1	4.60 peak	
3	441.7426	6.67	25.04	31.71	46.00 -1	4.29 peak	
4	504.7062	10.85	22.83	33.68	46.00 -1	2.32 peak	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

24.90

31.34

35.79

37.43

10.89

6.09



		F	Radia	tea E	miss		esults at 30	MHz-1GH	Z	
EUT Name	Wireles	Wireless Mouse				Mode	el Name	Ν	1D190	
Temperature	<b>23.8℃</b>				Relat	tive Humid	l <b>ity</b> 6	0.5%		
Pressure	960hPa	а					Test	Voltage	Ν	lormal Voltage
Test Mode	Mode 2	2					Ante	nna Polari	ty V	'ertical
72.0 di	BuV/m						l			
72.0 u	544711								Lin Ma	it: <u>—</u> rgin: <u>—</u>
32							2		3.4 X X	
-8 30.000	40	50 60		80	der Straffe	(MHz)		00 <b>400</b>	500 600	
-8 30.000		50 60	- 70 - F	80 Readi	ing	(MHz)	Measure	00 400		700 1000.000
-8 30.000	40		70 F	80	ing 31	(MHz)	3	00 400	500 600	700 1000.000
-8 30.000	40 Mk.	50 60 Freq	70 : F	® Readi Leve	ing >I	(MH2) Correct Factor	Measure ment	00 400	500 600 Over	700 1000.000 Detector
-8 30.000 No.	40 Mk. 189	50 60 Freq MHz	70 : F  . 4	80 Readi Leve dBuV	ing ≱I √ 5	(MH2) Correct Factor dB	Measure ment dBuV/m	00 400 	500 600 Over dB	Detector
-8 30.000 No.	40 Mk. 189 230	50 60 Freq MHz 9.7384	- 70 - 1  . 4	80 Readi Leve dBuV 12.2	ing el v 5 2	(MHz) Correct Factor dB 18.21	Measure ment dBuV/m 30.46	00 400 Limit dB/m 43.50	500 600 Over dB -13.04	Detector peak
-8 30.000 No. 1 2	40 Mk. 189 230 482	<sup>50</sup> 60 Freq MHz 9.7384 0.0985	1 70 F	80 Readi Leve dBuV 12.25 13.82	ing 9	(MHz) Correct Factor dB 18.21 16.31	Measure ment dBuV/m 30.46 30.13	00 400 Limit dB/m 43.50 46.00	500 600 Over dB -13.04 -15.87	Detector peak peak peak
-8 30.000 No. 1 2 3	40 Mk. 189 230 482 500	50 60 Freq MHz 9.7384 0.0985 2.2155	1 70 F	80 Readi Leve dBuV 12.25 13.82 12.65	ing 2 2 9	(MH2) Correct Factor dB 18.21 16.31 23.83	Measure ment dBuV/m 30.46 30.13 36.52	00 400 Limit dB/m 43.50 46.00 46.00	500 600 Over dB -13.04 -15.87 -9.48	Detector peak peak peak peak

### **RESULT: Pass**

- Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.
  - 2. All test modes had been pre-tested. The mode 2 is the worst case and recorded in the report.



Radiated Emissions Test Results Above 1 GH
--

Femperature Pressure Fest Mode	23.8°C 960hPa			Dalat					
Test Mode				Relat	ive Humidity	60.5%			
· · · · · · · · · · · · · · · · · · ·		960hPa			Voltage	Normal \	Normal Voltage		
Froguerou	Mode 1	Mode 1		Anter	nna Polarity	Horizont	al		
Frequencia									
Frequency	Meter Reading	Factor	Emission	n Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV	/m)	(dBµV/m)	(dB)	value Type		
4804.000	46.28	0.08	46.3	6	74	-27.64	peak		
4804.000	37.41	0.08	37.4	9	54	-16.51	AVG		
7206.000	41.69	2.21	43.9	9	74	-30.1	peak		
7206.000	32.32	2.21	34.5	3	54	-19.47	AVG		
Remark:									
Factor = Antenn	a Factor + Cable	e Loss – Pre-	amplifier.						
EUT Name	Wireless Mo	use		Mode	I Name	MD190			
<b>F</b> emperature	<b>23.8</b> ℃			Relat	ive Humidity	60.5%			
Pressure	960hPa			Test V	Voltage	Normal \	/oltage		
Test Mode	Mode 1			Anter	nna Polarity	Vertical			
r			<u> </u>				1		
Frequency	Meter Reading	<u> </u>		n Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV		(dBµV/m)	(dB)	ncali		
4804.000	46.84	0.08	46.9		74	-27.08	peak		
4804.000	37.17	0.08	37.2		54	-16.75	AVG		
7206.000	41.56	2.21	43.7		74	-30.23	peak		
7206.000	32.49	2.21	34.7	1	54	-19.3	AVG		
Remark:			•				•		
	a Factor + Cable	Loss – Pre-	amplifier.						

## **RESULT: Pass**



EUT Name		Wireless I	Nouse		Mode	el Name		MD	0190	
Temperature		<b>23.8</b> ℃			Relative Humidity 60.5%			5%		
Pressure		960hPa			Test	Test Voltage Nor			rmal Voltage	
Test Mode		Mode 2			Ante	nna Pola	rity	Ho	rizontal	
Freque	ncy	Meter Reading	Facto	or Emissio	n Level	Limits		Margin	N Value Ty	
(MHz	)	(dBµV)	(dB)	) (dBµ'	V/m)	(dBµV/n	ı)	(dB)	value ry	pe
4882.0	00	45.58	0.14	45.	72	74		-28.28	s peak	
4882.0	00	38.74	0.14	38.	88	54		-15.12	2 AVG	
7323.0	00	40.62	2.36	i 42.	98	74		-31.02		
7323.0	00	33.82	2.36	36.	18	54		-17.82	2 AVG	
Remark:										
Factor =	Antenna	a Factor + C	able Loss –	Pre-amplifier.		-				
EUT Name		Wireless I	Nouse		Mode	el Name		MD	0190	
Temperature		<b>23.8</b> ℃			Relat	tive Hum	idity	60.	5%	
Pressure		960hPa			Test	Voltage		No	rmal Voltage	
Test Mode		Mode 2			Ante	nna Pola	rity	Ver	rtical	
Fraguanay	Mata	r Reading	Factor	Emission Lev		imits	Morai			
Frequency (MHz)		dBµV)	(dB)	(dBµV/m)		BµV/m)	Margi (dB)		Value Type	
4882.000		45.57	0.14	45.71	,u	5μν/m) 74	-28.2		peak	
4882.000	-	37.48	0.14	37.62		74 54	-16.3		AVG	
7323.000		40.26	2.36	42.62		74	-31.3		peak	
7323.000		33.41	2.36	35.77		54	-18.2		AVG	
			v					-		
Remark:										

### Radiated Emissions Test Results for Above 1 GHz

### **RESULT: Pass**



EUT Name	Wireless Mou	se	Mode	I Name	MD190		
Temperature	<b>23.8</b> ℃		Relati	ve Humidity	60.5%	60.5%	
Pressure	960hPa		Test V	/oltage	Normal	Voltage	
Test Mode	Mode 3		Anten	na Polarity	Horizon	tal	
	·		·		·		
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4960.000	46.63	0.22	46.85	74	-27.15	peak	
4960.000	38.48	0.22	38.7	54	-15.3	AVG	
7440.000	41.52	2.64	44.16	74	-29.84	peak	
7440.000	32.51	2.64	35.15	54	-18.85	AVG	
Remark:							
Factor = Anter	nna Factor + Cable						
Factor = Anter	nna Factor + Cable Wireless Mou			I Name	MD190		
Factor = Anter			Mode	I Name ive Humidity	MD190 60.5%		
Factor = Anter EUT Name Temperature	Wireless Mou		Mode Relati			Voltage	
Factor = Anter EUT Name Temperature Pressure	Wireless Mou		Mode Relati Test V	ve Humidity	60.5%	Voltage	
Factor = Anter EUT Name Temperature Pressure Test Mode	Wireless Mou 23.8°C 960hPa Mode 3		Mode Relati Test V	ve Humidity /oltage	60.5% Normal Vertical	1	
Factor = Anter EUT Name Temperature Pressure	Wireless Mou 23.8°C 960hPa	Se	Mode Relati Test V Anten	ive Humidity /oltage ana Polarity	60.5% Normal	Voltage Value Type	
Factor = Anter	Wireless Mou 23.8°C 960hPa Mode 3 Meter Reading	Se Factor	Mode Relati Test V Anten Emission Level	Voltage	60.5% Normal Vertical	1	
Factor = Anter	Wireless Mou 23.8°C 960hPa Mode 3 Meter Reading (dBµV)	ISE Factor (dB)	Mode Relati Test V Anten Emission Level (dBµV/m)	ive Humidity /oltage ana Polarity Limits (dBµV/m)	60.5% Normal Vertical Margin (dB)	- Value Type	
Factor = Anter         EUT Name         Temperature         Pressure         Test Mode         Frequency         (MHz)         4960.000	Wireless Mou 23.8°C 960hPa Mode 3 Meter Reading (dBµV) 46.89	Factor (dB) 0.22	Mode Relati Test V Anten Emission Level (dBµV/m) 47.11	Limits       (dBµV/m)       74	60.5% Normal Vertical Margin (dB) -26.89	Value Type	
Factor = Anter	Wireless Mou           23.8°C           960hPa           Mode 3           Meter Reading           (dBµV)           46.89           38.48	Se Factor (dB) 0.22 0.22	Mode Relati Test V Anten Emission Level (dBµV/m) 47.11 38.7	Limits       (dBµV/m)       74       54	60.5% Normal Vertical Margin (dB) -26.89 -15.3	- Value Type peak AVG	
Factor = AnterEUT NameTemperaturePressureTest ModeFrequency(MHz)4960.0004960.0007440.000	Wireless Mou           23.8°C           960hPa           Mode 3           Meter Reading           (dBµV)           46.89           38.48           40.62	Factor (dB) 0.22 0.22 2.64	Mode Relati Test V Anten Emission Level (dBµV/m) 47.11 38.7 43.26	Limits       (dBµV/m)       74       54       74	60.5% Normal Vertical Margin (dB) -26.89 -15.3 -30.74	Value Type peak AVG peak	
Factor = AnterEUT NameTemperaturePressureTest ModeFrequency(MHz)4960.0004960.0007440.000	Wireless Mou           23.8°C           960hPa           Mode 3           Meter Reading           (dBµV)           46.89           38.48           40.62	Factor (dB) 0.22 0.22 2.64	Mode Relati Test V Anten Emission Level (dBµV/m) 47.11 38.7 43.26	Limits       (dBµV/m)       74       54       74	60.5% Normal Vertical Margin (dB) -26.89 -15.3 -30.74	Value Type peak AVG peak	

### **RESULT: Pass**

Note:


- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.




EUT Name	Wireless Mouse	Model Name	MD190
Temperature	<b>23.8℃</b>	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Horizontal

#### Band Edge Emission Test Results for Restricted Bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




## **RESULT: Pass**




Band Edge Emission Test R	esults for Restricted Bands
---------------------------	-----------------------------

EUT Name	Wireless Mouse	Model Name	MD190
Temperature	<b>23.8℃</b>	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



## **RESULT: Pass**




Band Edge Emission	Test Results for Restricted Bands
--------------------	-----------------------------------

EUT Name	Wireless Mouse	Model Name	MD190
Temperature	<b>23.8</b> ℃	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




## **RESULT: Pass**




Band Edge Emission Test R	esults for Restricted Bands
---------------------------	-----------------------------

EUT Name	Wireless Mouse	Model Name	MD190
Temperature	<b>23.8</b> ℃	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



# **RESULT: Pass**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



# **10. Number of Hopping Frequency Measurement**

### **10.1 Provisions Applicable**


This frequency hopping system must employ a minimum of 15 hopping channels.

### **10.2 Measurement Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span = The frequency band of operation. Depending on the number of channels the device
- 2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 3. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 4. VBW  $\geq$  RBW
- 5. Sweep time = Auto couple
- 6. Detector = Peak
- 7. Trace mode = Max hold
- 8. Allow the trace to stabilize


## 10.3 Measurement Setup (Block Diagram of Configuration)



#### **10.4 Measurement Result**

	Test Data of Number of Hopping	Frequency	
Test Mode	Number of Hopping Frequency	Limits	Pass or Fail
GFSK Hopping	79	>=15	Pass





## Test Graphs of Number of Hopping Frequency



# 11. Time of Occupancy (Dwell Time) Measurement

### **11.1 Provisions Applicable**


The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

### **11.2 Measurement Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span = Zero span, centered on a hopping channel.
- 2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. VBW  $\geq$  RBW
- 4. Sweep time = As necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = Free Run
- 7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.


### 11.3 Measurement Setup (Block Diagram of Configuration)



#### **11.4 Measurement Result**


		Test Data of D	well Time		
Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)	Pass or Fail
2402	2.853	28.0*4	319.536	400	Pass
2441	2.854	28.0*4	319.648	400	Pass
2480	2.854	28.0*4	319.648	400	Pass






**Test Graphs of Dwell Time** 











## **12. Frequency Separation Measurement**

### **12.1 Provisions Applicable**

When the power is less than 0.125W: The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.


When the power is less than 1W: The minimum permissible channel separation for this system is 20dB BW.

### **12.2 Measurement Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- 1. Span: Wide enough to capture the peaks of two adjacent channels.
- 2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3. Video (or average) bandwidth (VBW)  $\geq$  RBW.
- 4. Sweep: Auto.
- 5. Detector function: Peak.
- 6. Trace: Max hold. g) Allow the trace to stabilize.
- 7. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

## 12.3 Measurement Setup (Block Diagram of Configuration)




### **12.4 Measurement Result**

	Test Data of Frequency Separa	tion	
Test Mode	Channel Separation (MHz)	Limits	Pass or Fail
GFSK Hopping	0.989	>= 2/3 -20dB BW	Pass







### **Test Graphs of Number of Hopping Frequency**



# **13. AC Power Line Conducted Emission Test**

### 13.1 Measurement Limit


Frequency	Maximum RF Line Voltage			
Frequency	Q.P. (dBµV)	Average (dBµV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 13.2 Measurement Setup (Block Diagram of Configuration)





## **13.3 Preliminary Procedure of Line Conducted Emission Test**

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

## **13.4 Final Procedure of Line Conducted Emission Test**

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

## **13.5 Measurement Results**






#### MEASUREMENT RESULT: "agc\_fin"

2024/1/11 10:	2024/1/11 10:55					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.310000 0.582000 1.106000 2.162000 12.146000 13.062000	21.20 19.80 21.00 15.50 18.10 18.40	6.1 6.2 6.2 6.2 6.8 6.8	60 56 56 60 60	38.8 36.2 35.0 40.5 41.9 41.6	QP QP	L1 L1 L1 L1 L1 L1

### MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.354000	16.80	6.1	49	32.1	AV	L1
0.778000	18.90	6.2	46	27.1	AV	L1
1.306000	16.00	6.2	46	30.0	AV	L1
2.134000	11.00	6.2	46	35.0	AV	L1
12.166000	9.70	6.8	50	40.3	AV	L1
12.902000	9.90	6.8	50	40.1	AV	L1





### MEASUREMENT RESULT: "agc\_fin"

2024/1/11 10:58 Frequency Level Transd Limit Margin Detector Line MHz dBµV dB dBµV dB 0.358000 20.50 6.1 59 38.3 QP N 0.790000 22.70 6.2 56 33.3 QP Ν 1.362000 20.00 6.2 56 36.0 Ν QP 15.10 56 2.294000 6.3 40.9 QP Ν 6.3 6.8 4.246000 10.30 56 45.7 QP Ν 13.682000 14.90 60 45.1 QP Ν

#### MEASUREMENT RESULT: "agc\_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.358000	16.60	6.1	49	32.2	AV	N
0.778000	19.60	6.2	46	26.4	AV	N
1.350000	15.10	6.2	46	30.9	AV	N
2.182000	10.90	6.3	46	35.1	AV	N
12.346000	6.40	6.8	50	43.6	AV	N
13.522000	6.90	6.8	50	43.1	AV	N



Report No.: AGC00803240101FR01 Page 57 of 57

## **Appendix I: Photographs of Test Setup**

Refer to the Report No.: AGC00803240101AP02

## Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC00803240101AP03

-----End of Report-----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.