RF Exposure Requirements

1.1 Product Description for Equipment Under Test (EUT)

Client Information	
Applicant:	Guangdong Xinxun Technology Co., Ltd.
Address of applicant:	Room 101, Building 5, No. 128 Donghuan Road,
	Donghuan Street, Panyu District, Guangzhou
Manufacturer:	Guangdong Xinxun Technology Co., Ltd.
Address of Manufacturer:	Room 101, Building 5, No. 128 Donghuan Road,
	Donghuan Street, Panyu District, Guangzhou

General Description of EUT	
Product Name:	Smart Watch T10
Brand Name:	1
Model No.:	T10
Adding Model(s):	/
Rated Voltage:	DC 3.7V
Power Adapter:	/
Software Version:	1
Hardware Version:	/
Serial Number:	2JDLP2033
FCC ID:	2BE35-T10

Technical Characteristics of EUT	
Bluetooth Version:	V5.0 BLE
Frequency Range:	2402-2480MHz
RF Output Power:	-10.12dBm
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Integral antenna
Antenna Gain:	-1.24dBi

1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, the following RF exposure evaluation shall to demonstrate RF exposure compliance.

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$

Where

- -f(GHz) is the RF channel transmit frequency in GHz
- -Power and distance are rounded to the nearest mW and mm before calculation
- -The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

1.3 Calculation Method

Bluetooth

Tx frequency range: 2402~2480MHz Min. test separation distance: 5mm

Maximum Conducted Output Power: -10.12Bm Maximum Tune-up Conducted Output Power: -9dBm

RF channel transmit frequency: 2440MHz

Result: 0.039 Limit: 3.0

So the transmitter complies with the RF exposure requirements and the SAR is not required.