

承 認 書

SPECIFICATION FOR APPROVAL

客 戶:	Dongguan Hechuang Green Energy Electronic Technology Co., Ltd
CUSTOMER:	
客 戶 料 號:	
CUST P/N:	
音 澤 料 號:	G43.5*0.75-20.5-0.08*48P-10TS-6.8UH-W38.3-L8MM+
FINE P/N:	BJ
產 品 型 號:	
DESC:	Φ 43.5MMX0.75MM
日 期:	
DATE:	2024/1/23
版 本:	
Version:	A.0

擬 制 PREPARED BY	審 核 CHECKED BY	批 准 APPROVED BY	客 戶 承 認 CUSTOMER APPROVE
何立成	马莉	但可清	

Dongguan yinze Electronic technology Co., Ltd

Address: Building D, No. 40 Fulong Education Road, Shipai Town, Dongguan City

但可清 TEL: 18617251159

版本變更履歷


Version Change History

[illegible]

SPECIFICATION

產品型號: DESC	G43.5*0.75-20.5-0.08*48P-10 TS-6.8UH-L8MM+BJ	版本 Rev: A.0	客戶 CUST:	伟高域
			客戶料号 CUST P/N:	

一、尺寸 DIMENSION:(mm)



A	43.5±0.5
B	38.3±0.5
C	20.5±0.5
D	8 ±2
E	3±2
F	5.3±0.2
G	0.75±0.05
H	1.7±0.1
I	
K	

注：
1.交叉出线;
2.线圈贴双槽磁片，磁片尺寸
43.5±0.5mm,，厚度为
0.75±0.05mm.
3.磁片背面贴背胶

二、原理图 SCHEMATIC DIAGRAM:

三、绕线参数 Winding Specification:

序号 NO.	端子 TERMINAL		线径 WIRE	圈数 Turns	绕线方向 Winding Direction
1	S	F	热风线 0.08*48P	10Ts	CCW

四、电气特性 ELECTRICAL CHARACTERISTICS:

温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20%

序号 NO.	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND.	S-F	3.7uH ±10%单独线圈	100KHz/1.0V	LCZ METER 1062B
2	IND.	S-F	6.8uH ±10%加磁片	100KHz/1.0V	LCZ METER 1062B
3	DCR	S-F	≤100mΩ		LCZ METER 502B

擬制/日期 PREPARED BY/DATE	審核/日期 CHECKED BY/DATE
何立成 2024.1.23	

