

FCC EMC Test Report

Report No.: JYTSZ-R01-2400087
Applicant: PEEQ LLC
Address of Applicant: 215 S Broadway Unit 253 Salem, NH 03079, USA
Equipment Under Test (EUT)
Product Name: GPS tracker
Model No.: POM1
Trade Mark: N/A
FCC ID: 2BE9Z-POM1
Applicable Standards: FCC CFR Title 47 Part 15B
Date of Sample Receipt: 12 Mar., 2024
Date of Test: 13 Mar., to 25 Mar., 2024
Date of report Issued: 26 Mar., 2024
Test Result: PASS

Project by:

Logan Li

Date:

26 Mar., 2024

Reviewed by:

Jeta Yang

Date:

26 Mar., 2024

Approved by:

James Wei

Date:

26 Mar., 2024

Manager

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	26 Mar., 2024	Original

2 Contents

	Page
Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode	4
3.4 Description of Test Auxiliary Equipment	5
3.5 Description of Cable Used.....	5
3.6 Measurement Uncertainty	5
3.7 Additions to, Deviations, or Exclusions from the Method	5
3.8 Laboratory Facility	5
3.9 Laboratory Location.....	6
3.10 Test Instruments List.....	6
4 Measurement Setup and Procedure	7
4.1 Test Setup	7
4.2 Test Procedure	9
5 Test Results.....	10
5.1 Summary	10
5.1.1 Clause and data summary	10
5.1.2 Test Limit.....	10
5.2 Conducted Emission	11
5.3 Radiated Emission	13

3 General Information

3.1 Client Information

Applicant:	PEEQ LLC
Address:	215 S Broadway Unit 253 Salem, NH 03079, USA
Manufacturer:	PEEQ LLC
Address:	215 S Broadway Unit 253 Salem, NH 03079, USA
Factory:	KONKA Smart Technology Co.,Ltd.
Address:	No.12, West Section of Gangyuan Road, Guoxing Avenue, Lingang Economic Development ZoneYibin, Sicuan, P.R.CHINA

3.2 General Description of E.U.T.

Product Name:	GPS tracker
Model No.:	POM1
Power Supply:	Rechargeable Li-ion Battery DC3.7V, 5200mAh
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode

Operating Mode	Detail Description
Working mode	Keep the EUT in Working mode
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

3.4 Description of Test Auxiliary Equipment

Manufacturer	Description	Model	S/N	FCC ID/DoC
ADAPTER	ADAPTER	KA1501A-050300US	/	DoC

3.5 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Shielding	1.0m	EUT	PC/Adapter

3.6 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	3.57 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	3.14 dB
Radiated Emission (30MHz ~ 200MHz) (3m SAC)	4.6 dB
Radiated Emission (200MHz ~ 1000MHz) (3m SAC)	5.8 dB
Radiated Emission (1GHz ~ 6GHz) (3m SAC)	4.5 dB
Radiated Emission (6GHz ~ 18GHz) (3m SAC)	4.7 dB
Radiated Emission (30MHz ~ 200MHz) (10m SAC)	4.3 dB
Radiated Emission (200MHz ~ 1000MHz) (10m SAC)	4.3 dB

Note: All the measurement uncertainty value were shown with a coverage $k=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.7 Additions to, Deviations, or Exclusions from the Method

No

3.8 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.9 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.10 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	01-09-2024	01-08-2025
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	01-05-2024	01-04-2025
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	12-27-2023	12-26-2024
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	12-27-2023	12-26-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-27-2023	12-26-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-17-2024	01-16-2025
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-17-2024	01-16-2025
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		


Radiated Emission(10m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
10m SAC	ETS	RFSD-100-F/A	WXJ090	04-28-2021	04-27-2024
BiConiLog Antenna	SCHWARZBECK	VULB 9168	WXJ090-1	12-28-2023	12-27-2024
BiConiLog Antenna	SCHWARZBECK	VULB 9168	WXJ090-2	12-28-2023	12-27-2024
EMI Test Receiver	R&S	ESR 3	WXJ090-3	12-27-2023	12-26-2024
EMI Test Receiver	R&S	ESR 3	WXJ090-4	12-27-2023	12-26-2024
Low Pre-amplifier	Bost	LNA 0920N	WXJ090-6	12-27-2023	12-26-2024
Low Pre-amplifier	Bost	LNA 0920N	WXJ090-7	12-27-2023	12-26-2024
Cable	Bost	JYT10M-1G-NN-10M	WXG002-7	01-17-2024	01-16-2025
Cable	Bost	JYT10M-1G-NN-10M	WXG002-8	01-17-2024	01-16-2025
Test Software	R&S	EMC32	Version: 10.50.40		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	07-05-2023	07-04-2024
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	12-27-2023	12-26-2024
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	12-27-2023	12-26-2024
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	01-17-2024	01-16-2025
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

4 Measurement Setup and Procedure

4.1 Test Setup


1) Conducted emission measurement:




Note: The detailed descriptions please refer to Figure 8 of ANSI C63.4:2014.

2) Radiated emission measurement:

Below 1GHz (10m SAC)





4.2 Test Procedure

Test method	Test step
Conducted emission	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement.
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 10 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 10 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

5 Test Results

5.1 Summary


5.1.1 Clause and data summary

Test items	Standard clause	Test data	Result
Conducted Emission	Part 15.107	See Section 5.2	Pass
Radiated Emission	Part 15.109	See Section 5.3	Pass
Remark: 1. The EUT is a Class B digital device. 2. Pass: The EUT complies with the essential requirements in the standard. 3. N/A: Not Applicable.			
Test Method:	ANSI C63.4:2014		

5.1.2 Test Limit

5.2 Conducted Emission

Product name:	GPS tracker	Product model:	POM1
Test by:	Asher	Test mode:	Working mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Aux Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	9.80	0.20	0.00	9.88	0.01	19.89	56.00	-36.11	Average
2	0.150	30.26	0.20	0.00	9.88	0.01	40.35	66.00	-25.65	QP
3	0.270	22.26	0.20	0.00	9.88	0.02	32.36	61.12	-28.76	QP
4	0.435	5.62	0.20	0.00	9.88	0.03	15.73	47.15	-31.42	Average
5	3.025	20.84	0.30	0.00	9.89	0.07	31.10	56.00	-24.90	QP
6	3.107	11.34	0.30	0.00	9.89	0.07	21.60	46.00	-24.40	Average
7	4.158	21.69	0.30	0.00	9.89	0.08	31.96	56.00	-24.04	QP
8	4.180	11.36	0.30	0.00	9.89	0.08	21.63	46.00	-24.37	Average
9	4.926	10.22	0.30	0.00	9.89	0.09	20.50	46.00	-25.50	Average
10	5.249	19.66	0.30	0.00	9.89	0.09	29.94	60.00	-30.06	QP
11	9.809	5.79	0.39	0.00	9.91	0.13	16.22	50.00	-33.78	Average
12	10.019	14.48	0.40	0.00	9.91	0.13	24.92	60.00	-35.08	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	GPS tracker	Product model:	POM1
Test by:	Asher	Test mode:	Working mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



Trace: 1

	Freq	Read Level	LISN Factor	Aux Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB	
1	0.152	28.72	0.20	0.00	9.88	0.01	38.81	65.87	-27.06	QP
2	0.182	11.51	0.20	0.00	9.88	0.01	21.60	54.42	-32.82	Average
3	0.277	8.65	0.20	0.00	9.88	0.02	18.75	50.90	-32.15	Average
4	0.277	25.04	0.20	0.00	9.88	0.02	35.14	60.90	-25.76	QP
5	0.421	20.37	0.20	0.00	9.88	0.04	30.49	57.42	-26.93	QP
6	0.497	7.67	0.20	0.00	9.88	0.03	17.78	46.05	-28.27	Average
7	3.058	21.55	0.30	0.00	9.89	0.07	31.81	56.00	-24.19	QP
8	4.114	13.87	0.30	0.00	9.89	0.08	24.14	46.00	-21.86	Average
9	4.224	22.85	0.30	0.00	9.89	0.08	33.12	56.00	-22.88	QP
10	5.058	12.86	0.30	0.00	9.89	0.09	23.14	50.00	-26.86	Average
11	13.551	11.99	0.40	0.00	9.92	0.12	22.43	50.00	-27.57	Average
12	13.551	19.46	0.40	0.00	9.92	0.12	29.90	60.00	-30.10	QP


Remark:

1. Level = Read level + LISN Factor + Cable Loss.

5.3 Radiated Emission

Below 1GHz:

Product Name:	GPS tracker	Product Model:	POM1
Test By:	Asher	Test mode:	Working mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



Critical Freqs


Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
554.867000	22.87	36.00	13.13	100.0	V	75.0	-7.7
46.538500	14.20	30.00	15.80	100.0	V	91.0	-16.5
160.610500	13.90	33.50	19.60	100.0	V	229.0	-15.4
58.518000	11.81	30.00	18.19	100.0	V	254.0	-16.9
945.874000	30.69	36.00	5.31	100.0	V	278.0	-0.3
240.005000	21.50	36.00	14.50	100.0	V	295.0	-17.4

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	GPS tracker	Product Model:	POM1
Test By:	Asher	Test mode:	Working mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		

Full Spectrum



— Preview Result 1H-PK+ * Critical_Freqs PK+
— FCC PART 15 Class B 10m ◆ Final_Result QPK

Critical_Freqs


Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
201.302000	11.90	33.50	21.60	100.0	H	2.0	-18.8
47.896500	12.23	30.00	17.77	100.0	H	8.0	-16.5
56.626500	11.39	30.00	18.61	100.0	H	20.0	-16.7
554.285000	23.42	36.00	12.58	100.0	H	133.0	-7.8
944.516000	31.54	36.00	4.46	100.0	H	235.0	-0.3
152.705000	13.89	33.50	19.61	100.0	H	240.0	-15.2

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Product Name:	GPS tracker	Product Model:	POM1
Test By:	Robin	Test mode:	Working mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	3689.71	48.15	33.18	-14.97	54.00	20.82	AV	Vertical
2	3704.71	58.50	43.57	-14.93	74.00	30.43	PK	Vertical
3	4231.65	58.82	46.17	-12.65	74.00	27.83	PK	Vertical
4	4266.03	47.82	35.30	-12.52	54.00	18.70	AV	Vertical
5	5546.19	57.41	52.12	-5.29	74.00	21.88	PK	Vertical
6	5596.19	46.24	41.82	-4.42	54.00	12.18	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	GPS tracker	Product Model:	POM1
Test By:	Robin	Test mode:	Working mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	3619.07	59.21	44.07	-15.14	74.00	29.93	PK	Horizontal
2	3632.20	48.24	33.14	-15.10	54.00	20.86	AV	Horizontal
3	4267.28	47.75	35.24	-12.51	54.00	18.76	AV	Horizontal
4	4284.16	58.49	46.04	-12.45	74.00	27.96	PK	Horizontal
5	5601.82	46.29	41.92	-4.37	54.00	12.08	AV	Horizontal
6	5664.95	58.19	53.23	-4.96	74.00	20.77	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

-----End of report-----