

## INTERTEK TESTING SERVICES

---

### RF Exposure

The Equipment Under Test (EUT) is a Skeleton Dog operating at 433.92MHz. The EUT is powered by DC 3.0V (2 x 1.5V AAA batteries). For more detailed features description, please refer to the user's manual.

Antenna Type: Integral Antenna

Modulation: FSK

Antenna Gain: 0.9dBi

The normal peak radiated output power (e.i.r.p) is: -26.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is -26.9dBm (tolerance: +/- 3dB).

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 68.9 dB $\mu$ V/m at 3m in the frequency 433.92MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -26.33dBm

which is within the production variation.

The maximum conducted output power specified is -23.9dBm = 0.00407mW

The source- based time-averaging conducted output power

=0.00407mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt}(433.92)$  mW

= 22.77mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: 2BEA3-24171