

# TEST REPORT

**Product Name** : Tablet  
**Model Number** : M12, TPC12-PS  
**Contains FCC ID** : 2BEA6TPC121

**Prepared for** : Vantron Technology, Inc.  
**Address** : 48434 Milmont Drive Fremont, California 94538-7324, United States

**Prepared by** : EMTEK (SHENZHEN) CO., LTD.  
**Address** : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26954280  
Fax: (0755) 26954282

**Report Number** : ENS2410220034W01004R  
**Date(s) of Tests** : October 23, 2024 to November 6, 2024  
**Date of issue** : November 6, 2024

## 1 TEST RESULT CERTIFICATION

Applicant : Vantron Technology, Inc.

Address : 48434 Milmont Drive Fremont, California 94538-7324, United States

Manufacturer : Vantron Technology, Inc.

Address : 48434 Milmont Drive Fremont, California 94538-7324, United States

EUT : Tablet

Model Name : M12, TPC12-PS

Trademark : Vantron

Measurement Procedure Used:

| APPLICABLE STANDARDS                                                                |             |
|-------------------------------------------------------------------------------------|-------------|
| STANDARD                                                                            | TEST RESULT |
| FCC 47 CFR Part 2, Subpart J<br>FCC 47 CFR Part 15, Subpart E                       | PASS        |
| IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021)<br>IC RSS-247 Issue 3(08-2023) | PASS        |

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2, Part 15.407, IC RSS-247 Issue 3 and IC RSS-GEN, Issue 5.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : October 23, 2024 to November 6, 2024

Prepared by :   
Una Yu/Editor

Reviewer :   
Joe Xia/Supervisor

Approve & Authorized Signer :   
Lisa Wang/Manager

## Modified History

| Version                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Report No.           | Revision Date | Summary         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------|-----------------|
| Ver.1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ENS2410220034W01004R | /             | Original Report |
| <p>Note: This change is to request approval for mobile category specific host product, Antenna Type is FPC antenna, According to the requirements for antenna Change in KDB178919 D01 Permissive Change Policy v06, the antenna types are different and the gain value is greater than the original, Radiated Spurious Emission tests were performed to verify RF compliance, and the results of other test items remained unchanged based on the module report.</p> |                      |               |                 |



## TABLE OF CONTENTS

|          |                                                  |           |
|----------|--------------------------------------------------|-----------|
| <b>1</b> | <b>TEST RESULT CERTIFICATION .....</b>           | <b>2</b>  |
| <b>2</b> | <b>EUT TECHNICAL DESCRIPTION .....</b>           | <b>5</b>  |
| <b>3</b> | <b>SUMMARY OF TEST RESULT .....</b>              | <b>6</b>  |
| <b>4</b> | <b>TEST METHODOLOGY .....</b>                    | <b>7</b>  |
| 4.1      | GENERAL DESCRIPTION OF APPLIED STANDARDS .....   | 7         |
| 4.2      | MEASUREMENT EQUIPMENT USED .....                 | 7         |
| 4.3      | DESCRIPTION OF TEST MODES .....                  | 8         |
| <b>5</b> | <b>FACILITIES AND ACCREDITATIONS .....</b>       | <b>12</b> |
| 5.1      | FACILITIES .....                                 | 12        |
| 5.2      | EQUIPMENT .....                                  | 12        |
| 5.3      | LABORATORY ACCREDITATIONS AND LISTINGS .....     | 12        |
| <b>6</b> | <b>TEST SYSTEM UNCERTAINTY .....</b>             | <b>13</b> |
| <b>7</b> | <b>SETUP OF EQUIPMENT UNDER TEST .....</b>       | <b>14</b> |
| 7.1      | RADIO FREQUENCY TEST SETUP .....                 | 14        |
| 7.2      | RADIO FREQUENCY TEST SETUP .....                 | 14        |
| 7.3      | CONDUCTED EMISSION TEST SETUP .....              | 17        |
| 7.4      | BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM ..... | 18        |
| 7.5      | SUPPORT EQUIPMENT .....                          | 18        |
| 7.6      | UNDESIRABLE RADIATED SPURIOUS EMISSION .....     | 19        |

## 2 EUT TECHNICAL DESCRIPTION

| Characteristics           | Description                                                                                                                                                |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product:</b>           | Tablet                                                                                                                                                     |
| <b>Model Number:</b>      | M12, TPC12-PS<br>(The same product, different names sold to different customers or regions)                                                                |
| <b>Sample Number:</b>     | 2#                                                                                                                                                         |
| <b>Wifi Type:</b>         | Wifi 5G with 5150MHz-5250MHz Band<br>Wifi 5G with 5250MHz-5350MHz Band<br>Wifi 5G with 5470MHz-5725MHz Band<br>Wifi 5G with 5725MHz-5850MHz Band           |
| <b>WLAN Supported:</b>    | 802.11a/n/ac                                                                                                                                               |
| <b>Data Rate :</b>        | 802.11a: 54/48/36/24/18/12/9/6Mbps<br>802.11n: MCS0-MCS15<br>802.11ac: MCS0-MCS9                                                                           |
| <b>Modulation:</b>        | OFDM with BPSK/QPSK/16QAM/64QAM for 802.11a/n<br>OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11ac                                                       |
| <b>Frequency Range:</b>   | UNII-1: 5150MHz-5250MHz Band<br>5180-5240MHz for 802.11a/n(HT20)/ac(VHT20)<br>5190-5230MHz for 802.11n(HT40)/ac(VHT40)<br>5210MHz for 802.11ac(VHT80)      |
|                           | UNII-2A: 5250MHz-5350MHz Band<br>5260-5320MHz for 802.11a/n(HT20)/ac(VHT20)<br>5270-5310MHz for 802.11n(HT40)/ac(VHT40)<br>5290MHz for 802.11ac(VHT80)     |
|                           | UNII-2C: 5470MHz-5725MHz Band<br>5500-5700MHz for 802.11a/n(HT20)/ac(VHT20)<br>5510-5670MHz for 802.11n(HT40)/ac(VHT40)<br>5530MHz for 802.11ac(VHT80)     |
|                           | UNII-3 with 5725MHz-5850MHz Band<br>5745-5825MHz for 802.11a/n(HT20)/ac(VHT20)<br>5755-5795MHz for 802.11n(HT40)/ac(VHT40)<br>5775MHz for 802.11ac(VHT80); |
| <b>Antenna Type:</b>      | FPC Antenna                                                                                                                                                |
| <b>Antenna Gain:</b>      | Ant1: 4.3 dBi<br>Ant2: 5.7 dBi<br>(Note: The antenna information is provided by the customers, which will have a certain impact on the test results.)      |
| <b>Power Supply:</b>      | AC 230V/50Hz, AC 120V/60Hz,<br>DC 7.6V from Internal Battery                                                                                               |
| <b>Temperature Range:</b> | 0-40℃                                                                                                                                                      |

**Note:** For more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

| FCC PartClause                                                                                                                                                                                                                                                                                  | IC Part Clause                                              | Test Parameter            | Verdict | Remark |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------|---------|--------|
| 15.407 (b)<br>15.209<br>15.205                                                                                                                                                                                                                                                                  | RSS-247, 6.2<br>RSS-Gen 8.9<br>RSS-Gen 8.10<br>RSS-Gen 6.13 | RadiatedSpurious Emission | PASS    |        |
| NOTE1:N/A (Not Applicable)<br>NOTE2:According to FCC OET KDB 789033, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits. |                                                             |                           |         |        |

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for **ContainsFCC ID:2BEA6TPC121** filing to comply with Section 15.407 of the FCC Part 15, Subpart C Rules.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart E

IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021)

IC RSS-247 Issue 3(08-2023)

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D2 General UNII Test Procedures New Rules v02r01

### 4.2 MEASUREMENT EQUIPMENT USED

#### For Spurious Emissions Test

| Equipment                   | Manufacturer    | Model No.                    | Serial No.         | Last Cal.  | Cal. Interval |
|-----------------------------|-----------------|------------------------------|--------------------|------------|---------------|
| Pre-Amplifier               | Bonn            | BLMA<br>011001N              | 2213967A           | 2024/10/23 | 1Year         |
| EMI Test Receiver           | Rohde & Schwarz | ESR7                         | 102551             | 2024/10/23 | 1Year         |
| Bilog Antenna               | Schwarzbeck     | VULB9163                     | 9163142            | 2024/7/8   | 2Year         |
| Horn antenna                | Schwarzbeck     | BBHA9120D                    | 9120D-1198         | 2023/6/2   | 2Year         |
| Pre-Amplifier               | Bonn            | BLMA 0118-5G                 | 2213967B-01        | 2024/10/23 | 1Year         |
| Spectrum Analyzer           | Rohde & Schwarz | FSV3044                      | 101290             | 2024/10/23 | 1Year         |
| Horn antenna                | Schwarzbeck     | BBHA9170                     | 9170-399           | 2023/5/12  | 2Year         |
| Pre-Amplifier               | Lunar EM        | LNA18G26-40                  | J1012131010<br>001 | 2024/5/11  | 1Year         |
| Pre-Amplifier               | Lunar EM        | LNA26G40-40                  | J1013131028<br>001 | 2024/5/11  | 1Year         |
| Loop Antenna                | Schwarzbeck     | FMZB1519                     | 1519-012           | 2023/5/12  | 2Year         |
| Cable                       | H+B             | NmSm-05-C150<br>52           | N/A                | 2024/5/15  | 1 Year        |
| Cable                       | H+B             | NmSm-2-C1520<br>1            | N/A                | 2024/5/15  | 1 Year        |
| Cable                       | H+B             | NmNm-7-C1570<br>2            | N/A                | 2024/5/15  | 1 Year        |
| Cable                       | H+B             | SAC-40G-1                    | 414                | 2024/5/15  | 1 Year        |
| Cable                       | H+B             | SUCOFLEX104                  | MY14871/4          | 2024/5/15  | 1 Year        |
| Cable                       | H+B             | BLU18A-NmSm-<br>6500         | D8501              | 2024/5/15  | 1 Year        |
| Band reject<br>Filter(50dB) | WI/DE           | WRCGV-2400(2<br>400-2485MHz) | 2                  | 2024/5/15  | 1 Year        |

### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11a: 54 Mbps; 802.11n(HT20): MCS0; 802.11ac(VHT20): MCS0; 802.11n(HT40): MCS0; 802.11ac(VHT40): MCS0; 802.11ac(VHT80): MCS0;) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

☒ Wifi 5G with U-NII - 1

Frequency and Channel list for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 36      | 5180            | 44      | 5220            |         |                 |
| 40      | 5200            | 48      | 5240            |         |                 |

Frequency and Channel list for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 38      | 5190            | 46      | 5230            |         |                 |

Frequency and Channel list for 802.11ac (VHT80):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 42      | 5210            |         |                 |         |                 |

**Test** Frequency and Channel for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 36               | 5180            | 40               | 5200            | 48                | 5240            |

**Test** Frequency and channel for 802.11n (HT40), 802.11ac (VHT40):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 38               | 5190            | N/A              | N/A             | 46                | 5230            |

**Test** Frequency and channel for 802.11ac (VHT80):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 42               | 5210            | N/A              | N/A             | N/A               | N/A             |

☒ Wifi 5G with U-NII -2A

Frequency and Channel list 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 52      | 5260            | 60      | 5300            |         |                 |
| 56      | 5280            | 64      | 5320            |         |                 |

Frequency and Channel list for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 54      | 5270            |         |                 |         |                 |
| 62      | 5310            |         |                 |         |                 |

Frequency and Channel list for 802.11ac (VHT80):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 58      | 5290            |         |                 |         |                 |

Test Frequency and Channel for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 52               | 5260            | 56               | 5280            | 64                | 5320            |

Test Frequency and channel for 802.11n (HT40), 802.11ac (VHT40):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 54               | 5270            | N/A              | N/A             | 62                | 5310            |

Test Frequency and channel for 802.11ac (VHT80):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 58               | 5290            |                  |                 |                   |                 |

☒ Wifi 5G with U-NII -2C

Frequency and Channel list for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 100     | 5500            | 116     | 5580            | 132     | 5660            |
| 104     | 5520            | 120     | 5600            | 136     | 5680            |
| 108     | 5540            | 124     | 5620            | 140     | 5700            |
| 112     | 5560            | 128     | 5640            |         |                 |

Frequency and Channel list for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 102     | 5510            | 118     | 5590            | 134     | 5670            |
| 110     | 5550            | 126     | 5630            |         |                 |

Frequency and Channel list for 802.11ac (VHT80):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 106     | 5530            | 122     | 5610            |         |                 |
|         |                 |         |                 |         |                 |

**Test** Frequency and Channel for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 100              | 5500            | 120              | 5600            | 140               | 5700            |

**Test** Frequency and channel for 802.11n (HT40), 802.11ac (VHT40):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 102              | 5510            |                  |                 | 134               | 5670            |

**Test** Frequency and channel for 802.11ac (VHT80):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 106              | 5530            |                  |                 |                   |                 |

☒ Wifi 5G with U-NII -3

Frequency and Channel list for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 149     | 5745            | 157     | 5785            | 165     | 5825            |
| 153     | 5765            | 161     | 5805            |         |                 |

Frequency and Channel list for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 151     | 5755            | 159     | 5795            |         |                 |

Frequency and Channel list for 802.11ac (VHT80):

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 155     | 5775            |         |                 |         |                 |

Test Frequency and Channel for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 149              | 5745            | 157              | 5785            | 165               | 5825            |

Test Frequency and channel for 802.11n (HT40), 802.11ac (VHT40):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 151              | 5755            | N/A              | N/A             | 159               | 5795            |

Test Frequency and channel for 802.11ac (VHT80):

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 155              | 5775            |                  |                 |                   |                 |

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.3 LABORATORY ACCREDITATIONS AND LISTINGS

#### Site Description

EMC Lab. : **Accredited by CNAS**  
The Certificate Registration Number is L2291.  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

**Accredited by FCC**  
Designation Number: CN1204  
Test Firm Registration Number: 882943

**Accredited by A2LA**  
The Certificate Number is 4321.01.

Accredited by Industry Canada  
The Conformity Assessment Body Identifier is CN0008

Name of Firm : EMTEK (SHENZHEN) CO., LTD.  
Site Location : Building 69, Majialong Industry Zone,  
Nanshan District, Shenzhen, Guangdong, China

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


| Test Parameter                 | Measurement Uncertainty |
|--------------------------------|-------------------------|
| Radio Frequency                | $\pm 1 \times 10^{-5}$  |
| Maximum Peak Output Power Test | $\pm 1.0\text{dB}$      |
| Conducted Emissions Test       | $\pm 2.0\text{dB}$      |
| Radiated Emission Test         | $\pm 2.0\text{dB}$      |
| Power Density                  | $\pm 2.0\text{dB}$      |
| Occupied Bandwidth Test        | $\pm 1.0\text{dB}$      |
| Band Edge Test                 | $\pm 3\text{dB}$        |
| All emission, radiated         | $\pm 3\text{dB}$        |
| Antenna Port Emission          | $\pm 3\text{dB}$        |
| Temperature                    | $\pm 0.5^\circ\text{C}$ |
| Humidity                       | $\pm 3\%$               |

Measurement Uncertainty for a level of Confidence of 95%

## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:

(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Measurements shall be taken, using the following steps, at a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment (see RSS-Gen for applicable versions of ANSI and CISPR standards).

- (1) Line the ground plane with absorbers between the transmitter and the receive antenna to minimize reflections. The absorbers used should have a minimum-rated attenuation of 20 dB through the measurement frequency range of interest. The absorbers shall be positioned to replicate the layout used when compliance with the applicable acceptability criterion was achieved, as set forth in the aforementioned standards on site validation.
- (2) Set the height of the receive antenna to 1.5 m. The receive antenna must be one that was designed and fabricated to operate over the entire frequency range of interest, for example, an appropriate standard gain horn.
- (3) The distance between the receive antenna and the radiating source shall be sufficient in order to ensure far-field conditions.
- (4) Mount the transmitter at a height of 1.5 m.
- (5) Configure the device under test (DUT) to produce the maximum power spectral density as measured while assessing compliance with Section 6.2.2 (i.e. channel frequency, modulation type and data rate). If the DUT is equipped with a detachable antenna and the antenna is intended for remote installation (i.e. tower-mounted), the DUT may be substituted with a suitable signal generator. The level and frequency settings on the generator shall be set so as to reproduce the maximum power spectral density, measured within a 1 MHz bandwidth, obtained while assessing compliance to Section 6.2.2.

(6) Position the transmitter or the radiating antenna so that elevation pattern measurements can be taken.  
(7) Find the 0° reference point in the horizontal plane.

(8) Care should be taken when positioning the receive antenna to avoid cross-polarization. Antennas of known mounting polarization should be assessed with the receive antenna oriented in the same polarity. If the polarization of the transmit antenna is unknown or the transmit antenna can be mounted in either polarization, e.i.r.p. measurements should be performed to find which mounting polarity provides the highest e.i.r.p. value. Testing shall be carried out with the receive antenna and the DUT mounted in each polarity.

(9) The emission shall be centred on the display of the spectrum analyzer with the following settings:

i. If the power spectral density of the DUT was assessed with a peak detector and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

ii. If the power spectral density of the DUT was assessed using a sample detector with power averaging and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a sample detector, configured to produce 100 power averages and set with a resolution bandwidth, as well as a video bandwidth of 1 MHz.

iii. If the antenna can be detached from the DUT, a continuous wave (CW) signal equal to that of the power spectral density measurement may be used, the spectrum analyzer shall be set to peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

(10) Rotate the turntable 360° recording the field strength at each step. Throughout the main beam of the antenna, the step size shall be kept to a maximum of 1°.

Once outside the main beam of the antenna, the maximum step size shall be as follows, when compared to the requirements of Section 6.2.2:

i. Between 0° and 8°, maximum step size of 2°;

ii. Between 8° and 40°, maximum step size of 4°;

iii. Between 40° and 45°, maximum step size of 1°;

iv. Between 45° and 90°, maximum step size of 5°.

Once the mask reaches 90°, the mask will be inverted and the step size will follow in the same manner as above.

For the purpose of this procedure, the main beam of the antenna is defined as the 3 dB beamwidth.

(11) Convert the measured field strength values in terms of e.i.r.p. density (dBW/1 MHz) using the following equation:

$$\text{e.i.r.p. density (dBW/MHz)} = 10 \log((E \cdot r)^2 / 30)$$

E = field strength in V/m

r = measurement distance in metres

(12) Plot the results against the emission mask with reference to the horizontal plane.


(13) Using the plot, the 0° can be rotated to determine the worst-case installation tilt angle.

(14) Testing shall be performed using the highest gain antenna for every antenna type, if applicable.


(15) Antenna type(s), antenna model number(s), and worst-case tilt angle(s) necessary to remain compliant with the elevation mask requirement set forth in Section 6.2.2(3) of RSS-247 shall be clearly indicated in the user manual.

The following figure is an example of a polar elevation mask measured using the Method 1 reference to dBμV/m at 3 m.


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



## 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



## 7.5 SUPPORT EQUIPMENT

| EUT Cable List and Details |            |                     |                        |
|----------------------------|------------|---------------------|------------------------|
| Cable Description          | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                          | /          | /                   | /                      |

| Auxiliary Cable List and Details |            |                     |                        |
|----------------------------------|------------|---------------------|------------------------|
| Cable Description                | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                                | /          | /                   | /                      |

| Auxiliary Equipment List and Details |              |       |               |
|--------------------------------------|--------------|-------|---------------|
| Description                          | Manufacturer | Model | Serial Number |
| /                                    | /            | /     | /             |

### Notes:

- 1.All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2.Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 7.6 UNDESIRABLE RADIATED SPURIOUS EMISSION

### 7.6.1 Applicable Standard

According to FCC Part 15.407 (b), 15.209, 15.205

According to 789033 D02 SectionII(G)

According to RSS-GEN 8.9, 8.10 and 6.13

### 7.6.2 Conformance Limit

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

| Restricted Frequency(MHz) | Field Strength (μV/m) | Field Strength (dBμV/m) | Measurement Distance |
|---------------------------|-----------------------|-------------------------|----------------------|
| 0.009-0.490               | 2400/F(KHz)           | 20 log (uV/m)           | 300                  |
| 0.490-1.705               | 24000/F(KHz)          | 20 log (uV/m)           | 30                   |
| 1.705-30                  | 30                    | 29.5                    | 30                   |
| 30-88                     | 100                   | 40                      | 3                    |
| 88-216                    | 150                   | 43.5                    | 3                    |
| 216-960                   | 200                   | 46                      | 3                    |
| Above 960                 | 500                   | 54                      | 3                    |

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| 10.495-0.505      | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25          | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6             | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | (2)         |
| 13.36-13.41       |                     |               |             |

- Remark:
1. Emission level in dBuV/m =  $20 \log (\mu\text{V/m})$
  2. Measurement was performed at an antenna to the closed point of EUT distance of     meters.
  3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

### 7.6.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

### 7.6.4 Test Procedure

#### ■ Unwanted Emissions Measurements below 1000 MHz

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

The EUT was placed on a turn table which is 0.8m above ground plane.

And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Repeat above procedures until all frequency measured was complete.

We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes have been tested and the worst result was reported.

Use the following spectrum analyzer settings:

Set RBW = 120kHz for  $f < 1 \text{ GHz}$  (30MHz to 1GHz), 200Hz for  $f < 150\text{kHz}$  (9kHz to 150kHz), 9kHz for  $f > 150\text{kHz}$  (150kHz to 30kHz).

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Repeat above procedures until all frequency measured was complete.

#### ■ Unwanted Maximumpeak Emissions Measurements above 1000 MHz

Maximum emission levels are measured by setting the analyzer as follows:

RBW = 1 MHz.

VBW  $\geq$  3 MHz.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately  $1/x$ , where  $x$  is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

#### ■ Unwanted Average Emissions Measurements above 1000 MHz

Method VB (Averaging using reduced video bandwidth): Alternative method.

RBW = 1 MHz.

Video bandwidth. • If the EUT is configured to transmit with duty cycle  $\geq 98$  percent, set  $\text{VBW} \leq \text{RBW}/100$  (i.e., 10 kHz) but not less than 10 Hz.

• If the EUT duty cycle is  $< 98$  percent, set  $\text{VBW} \geq 1/T$ , where  $T$  is defined in section II.B.1.a).

Video bandwidth mode or display mode • The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).

• As an alternative, the analyzer may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some analyzers require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of  $1/x$ , where  $x$  is the duty cycle. For example, use at least 200 traces if the duty cycle is 25 percent. (If a specific emission is demonstrated to be continuous—i.e., 100 percent duty cycle—rather than turning on and off with the transmit cycle, at least 50 traces shall be averaged.)

#### ■ Band edge measurements.

Unwanted band-edge emissions may be measured using either of the special band-edge measurement techniques (the marker-delta or integration methods) described below. Note that the marker-delta method is primarily a radiated measurement technique that requires the 99% occupied bandwidth edge to be within 2 MHz of the authorized band edge, whereas the integration method can be used in either a radiated or conducted measurement without any special requirement with regards to the displacement of the unwanted emission(s) relative to the authorized bandwidth.

Marker-Delta Method.

The marker-delta method, as described in ANSI C63.10, can be used to perform measurements of the radiated unwanted emissions level of emissions provided that the 99% occupied bandwidth of the fundamental is within 2 MHz of the authorized band-edge.

#### 7.6.5 Test Results

|                    |           |
|--------------------|-----------|
| Temperature:       | 22° C     |
| Relative Humidity: | 43%       |
| ATM Pressure:      | 1011 mbar |

#### ■ Spurious Emission below 30MHz(9KHz to 30MHz)

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission<br>Level(dBuV/m) |    | Limit 3m(dBuV/m) |    | Over(dB) |    |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
|                |                 | PK                        | AV | PK               | AV | PK       | AV |
| --             | --              | --                        | -- | --               | -- | --       | -- |

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance/ test distance})$  (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

# ■ For Undesirable radiatedSpurious Emission in U-NII - 1

●Undesirable radiated Spurious Emission Above 1GHz(1GHz to 40GHz)

All the antenna(Antenna 1&2) and modes(802.11a/n/ac) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

| Test mode:  |          | 802.11a                 |               | Frequency:  |          | Channel 36: 5180MHz |  |
|-------------|----------|-------------------------|---------------|-------------|----------|---------------------|--|
| Freq. (MHz) | Ant.Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Over(dB) |                     |  |
| 8696.348    | V        | 42.76                   | -52.47        | -27         | -25.47   |                     |  |
| 10737.36    | V        | 44.96                   | -50.27        | -27         | -23.27   |                     |  |
| 17566.28    | V        | 46.35                   | -48.88        | -27         | -21.88   |                     |  |
| 8713.356    | H        | 43.05                   | -52.18        | -27         | -25.18   |                     |  |
| 9988.994    | H        | 41.82                   | -53.41        | -27         | -26.41   |                     |  |
| 15899.44    | H        | 44.20                   | -51.03        | -27         | -24.03   |                     |  |

| Test mode:  |          | 802.11a                 |               | Frequency:  |          | Channel 40: 5200MHz |  |
|-------------|----------|-------------------------|---------------|-------------|----------|---------------------|--|
| Freq. (MHz) | Ant.Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Over(dB) |                     |  |
| 8135.067    | V        | 40.88                   | -54.35        | -27         | -27.35   |                     |  |
| 11120.06    | V        | 44.51                   | -50.72        | -27         | -23.72   |                     |  |
| 16579.78    | V        | 44.57                   | -50.66        | -27         | -23.66   |                     |  |
| 8679.339    | H        | 42.57                   | -52.66        | -27         | -25.66   |                     |  |
| 11069.03    | H        | 44.10                   | -51.13        | -27         | -24.13   |                     |  |
| 17838.41    | H        | 47.05                   | -48.18        | -27         | -21.18   |                     |  |

| Test mode:  |          | 802.11a                 |               | Frequency:  |          | Channel 48: 5240MHz |  |
|-------------|----------|-------------------------|---------------|-------------|----------|---------------------|--|
| Freq. (MHz) | Ant.Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Over(dB) |                     |  |
| 7437.718    | V        | 39.83                   | -55.40        | -27         | -28.40   |                     |  |
| 11077.53    | V        | 44.08                   | -51.15        | -27         | -24.15   |                     |  |
| 16316.15    | V        | 44.23                   | -51.00        | -27         | -24.00   |                     |  |
| 10091.04    | H        | 46.99                   | -48.24        | -27         | -21.24   |                     |  |
| 12990.99    | H        | 46.16                   | -49.07        | -27         | -22.07   |                     |  |
| 17311.15    | H        | 45.29                   | -49.94        | -27         | -22.94   |                     |  |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).  
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
(3)EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77  
d is the measurement distance in 3 meters

Test mode: 802.11a Frequency: Channel 36: 5180MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8696.348       | V        | 57.96                     | 42.76 | 74               | 54 | 16.04    | 11.24 |
| 10737.36       | V        | 62.23                     | 44.96 | 74               | 54 | 11.77    | 9.04  |
| 17566.28       | V        | 64.12                     | 46.35 | 74               | 54 | 9.88     | 7.65  |
| 8713.356       | H        | 57.96                     | 43.05 | 74               | 54 | 16.04    | 10.95 |
| 9988.994       | H        | 61.27                     | 41.82 | 74               | 54 | 12.73    | 12.18 |
| 15899.44       | H        | 63.16                     | 44.20 | 74               | 54 | 10.84    | 9.80  |

Test mode: 802.11a Frequency: Channel 40: 5200MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8135.067       | V        | 57.55                     | 40.88 | 74               | 54 | 16.45    | 13.12 |
| 11120.06       | V        | 61.55                     | 44.51 | 74               | 54 | 12.45    | 9.49  |
| 16579.78       | V        | 63.58                     | 44.57 | 74               | 54 | 10.42    | 9.43  |
| 8679.339       | H        | 57.50                     | 42.57 | 74               | 54 | 16.50    | 11.43 |
| 11069.03       | H        | 60.80                     | 44.10 | 74               | 54 | 13.20    | 9.90  |
| 17838.41       | H        | 63.50                     | 47.05 | 74               | 54 | 10.50    | 6.95  |

Test mode: 802.11a Frequency: Channel 48: 5240MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 7437.718       | V        | 56.91                     | 39.83 | 74               | 54 | 17.09    | 14.17 |
| 11077.53       | V        | 61.03                     | 44.08 | 74               | 54 | 12.97    | 9.92  |
| 16316.15       | V        | 63.67                     | 44.23 | 74               | 54 | 10.33    | 9.77  |
| 10091.04       | H        | 60.45                     | 46.99 | 74               | 54 | 13.55    | 7.01  |
| 12990.99       | H        | 62.09                     | 46.16 | 74               | 54 | 11.91    | 7.84  |
| 17311.15       | H        | 62.86                     | 45.29 | 74               | 54 | 11.14    | 8.71  |

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge

All the antenna( Antenna 1&2 ) and modes( 802.11a/n/ac ) has been tested and the worst( Antenna 1,802.11ac(VHT20)) result recorded was report as below:

| Test mode:  |          | 802.11ac(VHT20)                      |               | Frequency:  | Channel 36: 5180MHz |
|-------------|----------|--------------------------------------|---------------|-------------|---------------------|
| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict             |
| 5138.62     | H        | 45.13                                | -50.10        | -27         | Pass                |
| 5126.925    | V        | 44.64                                | -50.59        | -27         | Pass                |

| Test mode:  |          | 802.11ac(VHT20)                      |               | Frequency:  | Channel 48: 5240MHz |
|-------------|----------|--------------------------------------|---------------|-------------|---------------------|
| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict             |
| 5360.14     | H        | 44.89                                | -50.34        | -27         | Pass                |
| 5356.43     | V        | 44.99                                | -50.24        | -27         | Pass                |


**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77  
 d is the measurement distance in 3 meters

| Test mode:      |          | 802.11ac(VHT20)       |                   | Frequency:            | Channel 36: 5180MHz |
|-----------------|----------|-----------------------|-------------------|-----------------------|---------------------|
| Frequency (MHz) | Polarity | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m)   |
| 5138.62         | H        | 55.38                 | 74                | 45.13                 | 54                  |
| 5126.925        | V        | 55.09                 | 74                | 44.64                 | 54                  |


| Test mode:      |          | 802.11ac(VHT20)       |                   | Frequency:            | Channel 48: 5240MHz |
|-----------------|----------|-----------------------|-------------------|-----------------------|---------------------|
| Frequency (MHz) | Polarity | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m)   |
| 5360.14         | H        | 53.95                 | 74                | 44.89                 | 54                  |
| 5356.43         | V        | 53.86                 | 74                | 44.99                 | 54                  |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| U-NII - 1  |                      |                      |                                |   |
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 36: 5180MHz  | Ant.Pol                        | H |




|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| U-NII - 1  |                      |                      |                                |   |
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 36: 5180MHz  | Ant.Pol                        | V |




U-NII - 1

|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 48: 5240MHz  | Ant.Pol                        | H |



U-NII - 1

|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 48: 5240MHz  | Ant.Pol                        | V |



■ For Undesirable Radiated Spurious Emission in U-NII -2A

● Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All the antenna (Antenna 1&2) and modes (802.11a/n/ac) has been tested and the worst (Antenna 1, 802.11a) result recorded was report as below:

| Test mode: 802.11a |           | Frequency:              |               | Channel 52: 5260MHz |           |
|--------------------|-----------|-------------------------|---------------|---------------------|-----------|
| Freq. (MHz)        | Ant. Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm)         | Over (dB) |
| 8050.025           | V         | 40.52                   | -54.71        | -27                 | -27.71    |
| 10745.87           | V         | 44.82                   | -50.41        | -27                 | -23.41    |
| 17778.88           | V         | 46.58                   | -48.65        | -27                 | -21.65    |
| 8670.835           | H         | 42.47                   | -52.76        | -27                 | -25.76    |
| 12531.76           | H         | 47.48                   | -47.75        | -27                 | -20.75    |
| 16214.10           | H         | 44.15                   | -51.08        | -27                 | -24.08    |

| Test mode: 802.11a |           | Frequency:              |               | Channel 56: 5280MHz |           |
|--------------------|-----------|-------------------------|---------------|---------------------|-----------|
| Freq. (MHz)        | Ant. Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm)         | Over (dB) |
| 8696.348           | V         | 43.01                   | -52.22        | -27                 | -25.22    |
| 10737.36           | V         | 44.65                   | -50.58        | -27                 | -23.58    |
| 16528.76           | V         | 45.01                   | -50.22        | -27                 | -23.22    |
| 8696.348           | H         | 43.11                   | -52.12        | -27                 | -25.12    |
| 11052.02           | H         | 44.06                   | -51.17        | -27                 | -24.17    |
| 17914.95           | H         | 46.92                   | -48.31        | -27                 | -21.31    |

| Test mode: 802.11a |           | Frequency:              |               | Channel 64: 5320MHz |           |
|--------------------|-----------|-------------------------|---------------|---------------------|-----------|
| Freq. (MHz)        | Ant. Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm)         | Over (dB) |
| 8721.860           | V         | 42.58                   | -52.65        | -27                 | -25.65    |
| 11103.051          | V         | 44.27                   | -50.96        | -27                 | -23.96    |
| 15168.08           | V         | 44.13                   | -51.10        | -27                 | -24.10    |
| 9291.645           | H         | 43.88                   | -51.35        | -27                 | -24.35    |
| 11094.54           | H         | 44.51                   | -50.72        | -27                 | -23.72    |
| 16409.70           | H         | 45.02                   | -50.21        | -27                 | -23.21    |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
(3) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77  
d is the measurement distance in 3 meters

Test mode: 802.11a Frequency: Channel 52: 5260MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8050.025       | V        | 57.56                     | 40.52 | 74               | 54 | 16.44    | 13.48 |
| 10745.87       | V        | 61.15                     | 44.82 | 74               | 54 | 12.85    | 9.18  |
| 17778.88       | V        | 63.41                     | 46.58 | 74               | 54 | 10.59    | 7.42  |
| 8670.835       | H        | 57.99                     | 42.47 | 74               | 54 | 16.01    | 11.53 |
| 12531.76       | H        | 62.35                     | 47.48 | 74               | 54 | 11.65    | 6.52  |
| 16214.10       | H        | 63.07                     | 44.15 | 74               | 54 | 10.93    | 9.85  |

Test mode: 802.11a Frequency: Channel 56: 5280MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8696.348       | V        | 57.58                     | 43.01 | 74               | 54 | 16.42    | 10.99 |
| 10737.36       | V        | 61.62                     | 44.65 | 74               | 54 | 12.38    | 9.35  |
| 16528.76       | V        | 63.86                     | 45.01 | 74               | 54 | 10.14    | 8.99  |
| 8696.348       | H        | 57.93                     | 43.11 | 74               | 54 | 16.07    | 10.89 |
| 11052.02       | H        | 61.64                     | 44.06 | 74               | 54 | 12.36    | 9.94  |
| 17914.95       | H        | 64.28                     | 46.92 | 74               | 54 | 9.72     | 7.08  |

Test mode: 802.11a Frequency: Channel 64: 5320MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8721.860       | V        | 57.89                     | 42.58 | 74               | 54 | 16.11    | 11.42 |
| 11103.051      | V        | 61.86                     | 44.27 | 74               | 54 | 12.14    | 9.73  |
| 15168.08       | V        | 64.30                     | 44.13 | 74               | 54 | 9.70     | 9.87  |
| 9291.645       | H        | 57.41                     | 43.88 | 74               | 54 | 16.59    | 10.12 |
| 11094.54       | H        | 61.31                     | 44.51 | 74               | 54 | 12.69    | 9.49  |
| 16409.70       | H        | 64.28                     | 45.02 | 74               | 54 | 9.72     | 8.98  |

**Note:**

- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
- (2) Emission Level= Reading Level+Correct Factor.
- (3) Correct Factor= Ant\_F + Cab\_L - Preamp
- (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge

All the antenna( Antenna 1&2 ) and modes( 802.11a/n/ac ) has been tested and the worst( Antenna 1,802.11ac(VHT20)) result recorded was report as below:

| Test mode:  |          | 802.11ac(VHT20)                      |               | Frequency:  | Channel 52: 5260MHz |
|-------------|----------|--------------------------------------|---------------|-------------|---------------------|
| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict             |
| 5084.67     | H        | 44.27                                | -50.96        | -27         | Pass                |
| 5098.56     | V        | 44.55                                | -50.68        | -27         | Pass                |

| Test mode:  |          | 802.11ac(VHT20)                      |               | Frequency:  | Channel 64: 5320MHz |
|-------------|----------|--------------------------------------|---------------|-------------|---------------------|
| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict             |
| 5357.49     | H        | 45.56                                | -49.67        | -27         | Pass                |
| 5357.98     | V        | 45.07                                | -50.16        | -27         | Pass                |


**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77  
 d is the measurement distance in 3 meters

| Test mode:      |          | 802.11ac(VHT20)       |                   | Frequency:            | Channel 52: 5260MHz |
|-----------------|----------|-----------------------|-------------------|-----------------------|---------------------|
| Frequency (MHz) | Polarity | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m)   |
| 5084.67         | H        | 64.58                 | 74.00             | 44.27                 | 54.00               |
| 5098.56         | V        | 64.49                 | 74.00             | 44.55                 | 54.00               |


| Test mode:      |          | 802.11ac(VHT20)       |                   | Frequency:            | Channel 64: 5320MHz |
|-----------------|----------|-----------------------|-------------------|-----------------------|---------------------|
| Frequency (MHz) | Polarity | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m)   |
| 5357.49         | H        | 63.65                 | 74.00             | 45.56                 | 54.00               |
| 5357.98         | V        | 64.13                 | 74.00             | 45.07                 | 54.00               |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


|            |                                      |                                          |                                        |   |
|------------|--------------------------------------|------------------------------------------|----------------------------------------|---|
| Test Model | U-NII -2A                            |                                          |                                        |   |
|            | Undesirable radiated 802.11ac(VHT20) | Undesirable radiated Channel 52: 5260MHz | Spurious Emission in Band Edge Ant.Pol | H |




|            |                                      |                                          |                                        |   |
|------------|--------------------------------------|------------------------------------------|----------------------------------------|---|
| Test Model | U-NII -2A                            |                                          |                                        |   |
|            | Undesirable radiated 802.11ac(VHT20) | Undesirable radiated Channel 52: 5260MHz | Spurious Emission in Band Edge Ant.Pol | V |



| U-NII -2A  |                                      |                                          |                                        |   |
|------------|--------------------------------------|------------------------------------------|----------------------------------------|---|
| Test Model | Undesirable radiated 802.11ac(VHT20) | Undesirable radiated Channel 64: 5320MHz | Spurious Emission in Band Edge Ant.Pol | H |



| U-NII -2A  |                                      |                                          |                                        |   |
|------------|--------------------------------------|------------------------------------------|----------------------------------------|---|
| Test Model | Undesirable radiated 802.11ac(VHT20) | Undesirable radiated Channel 64: 5320MHz | Spurious Emission in Band Edge Ant.Pol | V |



■ For Undesirable radiated Spurious Emission in U-NII -2C

● Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All the antenna (Antenna 1&2) and modes (802.11a/n/ac) has been tested and the worst (Antenna 1, 802.11a) result recorded was report as below:

| Test mode: 802.11a |           | Frequency:              |               | Channel 100: 5500MHz |          |
|--------------------|-----------|-------------------------|---------------|----------------------|----------|
| Freq. (MHz)        | Ant. Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm)          | Over(dB) |
| 8747.373           | V         | 42.53                   | -52.70        | -27                  | -25.70   |
| 10992.49           | V         | 44.48                   | -50.75        | -27                  | -23.75   |
| 16766.88           | V         | 45.03                   | -50.20        | -27                  | -23.20   |
| 8670.835           | H         | 41.80                   | -53.43        | -27                  | -26.43   |
| 11026.51           | H         | 44.46                   | -50.77        | -27                  | -23.77   |
| 17761.88           | H         | 46.97                   | -48.26        | -27                  | -21.26   |

| Test mode: 802.11a |           | Frequency:              |               | Channel 120: 5600MHz |          |
|--------------------|-----------|-------------------------|---------------|----------------------|----------|
| Freq. (MHz)        | Ant. Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm)          | Over(dB) |
| 8645.322           | V         | 41.97                   | -53.26        | -27                  | -26.26   |
| 12582.79           | V         | 45.06                   | -50.17        | -27                  | -23.17   |
| 17506.75           | V         | 45.41                   | -49.82        | -27                  | -22.82   |
| 8670.835           | H         | 42.47                   | -52.76        | -27                  | -25.76   |
| 10660.83           | H         | 44.36                   | -50.87        | -27                  | -23.87   |
| 17778.88           | H         | 46.56                   | -48.67        | -27                  | -21.67   |

| Test mode: 802.11a |           | Frequency:              |               | Channel 140: 5700MHz |          |
|--------------------|-----------|-------------------------|---------------|----------------------|----------|
| Freq. (MHz)        | Ant. Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm)          | Over(dB) |
| 8653.826           | V         | 42.33                   | -52.90        | -27                  | -25.90   |
| 9997.498           | V         | 41.59                   | -53.64        | -27                  | -26.64   |
| 16588.29           | V         | 45.09                   | -50.14        | -27                  | -23.14   |
| 8135.067           | H         | 40.79                   | -54.44        | -27                  | -27.44   |
| 9903.952           | H         | 41.51                   | -53.72        | -27                  | -26.72   |
| 17727.86           | H         | 46.41                   | -48.82        | -27                  | -21.82   |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3)  $EIRP[dBm] = E[dBuV/m] + 20 \log(d[meters]) - 104.77$   
 d is the measurement distance in 3 meters

Test mode: 802.11a Frequency: Channel 100: 5500MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8747.373       | V        | 57.89                     | 42.53 | 74               | 54 | 16.11    | 11.47 |
| 10992.49       | V        | 60.97                     | 44.48 | 74               | 54 | 13.03    | 9.52  |
| 16766.88       | V        | 63.99                     | 45.03 | 74               | 54 | 10.01    | 8.97  |
| 8670.835       | H        | 57.90                     | 41.80 | 74               | 54 | 16.10    | 12.20 |
| 11026.51       | H        | 61.41                     | 44.46 | 74               | 54 | 12.59    | 9.54  |
| 17761.88       | H        | 63.56                     | 46.97 | 74               | 54 | 10.44    | 7.03  |

Test mode: 802.11a Frequency: Channel 116: 5580MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8645.322       | V        | 57.96                     | 41.97 | 74               | 54 | 16.04    | 12.03 |
| 12582.79       | V        | 62.32                     | 45.06 | 74               | 54 | 11.68    | 8.94  |
| 17506.75       | V        | 64.53                     | 45.41 | 74               | 54 | 9.47     | 8.59  |
| 8670.835       | H        | 57.72                     | 42.47 | 74               | 54 | 16.28    | 11.53 |
| 10660.83       | H        | 61.22                     | 44.36 | 74               | 54 | 12.78    | 9.64  |
| 17778.88       | H        | 64.06                     | 46.56 | 74               | 54 | 9.94     | 7.44  |

Test mode: 802.11a Frequency: Channel 140: 5700MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |    | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|----|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV | PK       | AV    |
| 8653.826       | V        | 57.68                     | 42.33 | 74               | 54 | 16.32    | 11.67 |
| 9997.498       | V        | 61.50                     | 41.59 | 74               | 54 | 12.50    | 12.41 |
| 16588.29       | V        | 63.29                     | 45.09 | 74               | 54 | 10.71    | 8.91  |
| 8135.067       | H        | 56.99                     | 40.79 | 74               | 54 | 17.01    | 13.21 |
| 9903.952       | H        | 61.27                     | 41.51 | 74               | 54 | 12.73    | 12.49 |
| 17727.86       | H        | 63.85                     | 46.41 | 74               | 54 | 10.15    | 7.59  |

**Note:**

- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
- (2) Emission Level= Reading Level+Correct Factor.
- (3) Correct Factor= Ant\_F + Cab\_L - Preamp
- (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge

All the antenna( Antenna 1&2 ) and modes( 802.11a/n/ac ) has been tested and the worst( Antenna 1,802.11ac(VHT20)) result recorded was report as below:

| Test mode:  |          | 802.11ac(VHT20)                      |               | Frequency:  | Channel 100: 5500MHz |
|-------------|----------|--------------------------------------|---------------|-------------|----------------------|
| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict              |
| 5468.51     | H        | 54.58                                | -40.65        | -27         | Pass                 |
| 5466.76     | V        | 55.32                                | -39.91        | -27         | Pass                 |

| Test mode:  |          | 802.11ac(VHT20)                      |               | Frequency:  | Channel 140: 5700MHz |
|-------------|----------|--------------------------------------|---------------|-------------|----------------------|
| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict              |
| 5727.67     | H        | 55.12                                | -40.11        | -27         | Pass                 |
| 5725.50     | V        | 55.94                                | -39.29        | -27         | Pass                 |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77  
 d is the measurement distance in 3 meters


| Test mode:      |          | 802.11ac(VHT20)       |                   | Frequency:            | Channel 100: 5500MHz |
|-----------------|----------|-----------------------|-------------------|-----------------------|----------------------|
| Frequency (MHz) | Polarity | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m)    |
| 5469.56         | H        | 56.75                 | 74.00             | 45.81                 | 54.00                |
| 5469.23         | V        | 54.82                 | 74.00             | 46.08                 | 54.00                |

| Test mode:      |          | 802.11ac(VHT20)       |                   | Frequency:            | Channel 140: 5700MHz |
|-----------------|----------|-----------------------|-------------------|-----------------------|----------------------|
| Frequency (MHz) | Polarity | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m)    |
| 5725.47         | H        | 55.32                 | 74.00             | 46.28                 | 54.00                |
| 5727.15         | V        | 55.02                 | 74.00             | 45.89                 | 54.00                |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


**U-NII -2C**

|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 100: 5500MHz | Ant.Pol                        | H |




**U-NII -2C**


|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 100: 5500MHz | Ant.Pol                        | V |



Test Model U-NII -2C  
Undesirable radiated 802.11ac(VHT20) Undesirable radiated Channel 140: 5700MHz Spurious Emission in Band Edge Ant.Pol H



Test Model U-NII -2C  
Undesirable radiated 802.11ac(VHT20) Undesirable radiated Channel 140: 5700MHz Spurious Emission in Band Edge Ant.Pol V



■ For Undesirable radiated Spurious Emission in U-NII -3

● Undesirable radiated Spurious Emission Above 1GHz(1GHz to 40GHz)

All the antenna(Antenna 1&2) and modes(802.11a/n/ac) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

Test mode: 802.11a Frequency: Channel 149: 5745MHz

| Freq. (MHz) | Ant.Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Over(dB) |
|-------------|----------|-------------------------|---------------|-------------|----------|
| 8721.860    | V        | 46.37                   | -48.86        | -27         | -21.86   |
| 11842.92    | V        | 45.32                   | -49.91        | -27         | -22.91   |
| 17608.80    | V        | 45.10                   | -50.13        | -27         | -23.13   |
| 8466.733    | H        | 40.26                   | -54.97        | -27         | -27.97   |
| 10728.86    | H        | 45.17                   | -50.06        | -27         | -23.06   |
| 17285.64    | H        | 44.79                   | -50.44        | -27         | -23.44   |

Test mode: 802.11a Frequency: Channel 157: 5785MHz

| Freq. (MHz) | Ant.Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Over(dB) |
|-------------|----------|-------------------------|---------------|-------------|----------|
| 8687.843    | V        | 42.79                   | -52.44        | -27         | -25.44   |
| 10754.37    | V        | 44.74                   | -50.49        | -27         | -23.49   |
| 17336.66    | V        | 44.77                   | -50.46        | -27         | -23.46   |
| 7922.461    | H        | 39.12                   | -56.11        | -27         | -29.11   |
| 10023.01    | H        | 41.73                   | -53.50        | -27         | -26.50   |
| 17974.48    | H        | 46.69                   | -48.54        | -27         | -21.54   |

Test mode: 802.11a Frequency: Channel 165: 5825MHz

| Freq. (MHz) | Ant.Pol. | Field Strength (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Over(dB) |
|-------------|----------|-------------------------|---------------|-------------|----------|
| 8687.843    | V        | 42.59                   | -52.64        | -27         | -25.64   |
| 9903.952    | V        | 41.10                   | -54.13        | -27         | -27.13   |
| 15601.80    | V        | 42.77                   | -52.46        | -27         | -25.46   |
| 8577.288    | H        | 40.92                   | -54.31        | -27         | -27.31   |
| 10737.36    | H        | 44.98                   | -50.25        | -27         | -23.25   |
| 17617.30    | H        | 46.85                   | -48.38        | -27         | -21.38   |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).  
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
(3) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77  
d is the measurement distance in 3 meters

Test mode: 802.11a Frequency: Channel 149: 5745MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|-------|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV    | PK       | AV    |
| 8721.860       | V        | 58.11                     | 46.37 | 74.00            | 54.00 | 15.89    | 11.37 |
| 11842.92       | V        | 60.92                     | 45.32 | 74.00            | 54.00 | 13.08    | 10.30 |
| 17608.80       | V        | 64.01                     | 45.10 | 74.00            | 54.00 | 9.99     | 7.18  |
| 8466.733       | H        | 57.63                     | 40.26 | 74.00            | 54.00 | 16.37    | 13.74 |
| 10728.86       | H        | 61.50                     | 45.17 | 74.00            | 54.00 | 12.50    | 8.83  |
| 17285.64       | H        | 64.51                     | 44.79 | 74.00            | 54.00 | 9.49     | 9.21  |

Test mode: 802.11a Frequency: Channel 157: 5785MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|-------|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV    | PK       | AV    |
| 8687.843       | V        | 57.85                     | 42.79 | 74.00            | 54.00 | 16.15    | 11.21 |
| 10754.37       | V        | 60.93                     | 44.74 | 74.00            | 54.00 | 13.07    | 9.26  |
| 17336.66       | V        | 63.39                     | 44.77 | 74.00            | 54.00 | 10.61    | 9.23  |
| 7922.461       | H        | 56.45                     | 39.12 | 74.00            | 54.00 | 17.55    | 14.88 |
| 10023.01       | H        | 61.09                     | 41.73 | 74.00            | 54.00 | 12.91    | 12.27 |
| 17974.48       | H        | 64.11                     | 46.69 | 74.00            | 54.00 | 9.89     | 7.31  |

Test mode:: 802.11a Frequency: Channel 165: 5825MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |       |
|----------------|----------|---------------------------|-------|------------------|-------|----------|-------|
|                | H/V      | PK                        | AV    | PK               | AV    | PK       | AV    |
| 8687.843       | V        | 57.40                     | 42.59 | 74.00            | 54.00 | 16.60    | 11.41 |
| 9903.952       | V        | 61.34                     | 41.10 | 74.00            | 54.00 | 12.66    | 12.90 |
| 15601.80       | V        | 63.49                     | 42.77 | 74.00            | 54.00 | 10.51    | 11.23 |
| 8577.288       | H        | 57.42                     | 40.92 | 74.00            | 54.00 | 16.58    | 13.08 |
| 10737.36       | H        | 61.74                     | 44.98 | 74.00            | 54.00 | 12.26    | 9.02  |
| 17617.30       | H        | 64.03                     | 46.85 | 74.00            | 54.00 | 9.97     | 7.15  |

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge

All the antenna( Antenna 1&2 ) and modes( 802.11a/n/ac ) has been tested and the worst( Antenna 1,802.11ac(VHT20)) result recorded was report as below:

Test mode: 802.11ac(VHT20) Frequency: Channel 149: 5745MHz

| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict |
|-------------|----------|--------------------------------------|---------------|-------------|---------|
| 5725        | H        | 80.20                                | -15.03        | 27          | Pass    |
| 5724.81     | V        | 64.74                                | -30.49        | 26.57       | Pass    |


Test mode: 802.11ac(VHT20) Frequency: Channel 165: 5825MHz

| Freq. (MHz) | Ant.Pol. | Field Strength (RBW=100KHz) (dBuV/m) | E.I.R.P (dBm) | Limit (dBm) | Verdict |
|-------------|----------|--------------------------------------|---------------|-------------|---------|
| 5850.31     | H        | 71.81                                | -23.42        | 26.29       | Pass    |
| 5851.00     | V        | 60.11                                | -35.12        | 24.72       | Pass    |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3) $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$   
 d is the measurement distance in 3 meters


**U-NII-3**

|            |                                      |                                           |                                        |   |
|------------|--------------------------------------|-------------------------------------------|----------------------------------------|---|
| Test Model | Undesirable radiated 802.11ac(VHT20) | Undesirable radiated Channel 149: 5745MHz | Spurious Emission in Band Edge Ant.Pol | H |
|------------|--------------------------------------|-------------------------------------------|----------------------------------------|---|




**U-NII-3**

|            |                                      |                                           |                                        |   |
|------------|--------------------------------------|-------------------------------------------|----------------------------------------|---|
| Test Model | Undesirable radiated 802.11ac(VHT20) | Undesirable radiated Channel 149: 5745MHz | Spurious Emission in Band Edge Ant.Pol | V |
|------------|--------------------------------------|-------------------------------------------|----------------------------------------|---|




**U-NII-3**

|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 165: 5825MHz | Ant.Pol                        | H |




**U-NII-3**

|            |                      |                      |                                |   |
|------------|----------------------|----------------------|--------------------------------|---|
| Test Model | Undesirable radiated | Undesirable radiated | Spurious Emission in Band Edge |   |
|            | 802.11ac(VHT20)      | Channel 165: 5825MHz | Ant.Pol                        | V |



- Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)  
All the antenna( Antenna 1&2 ) and modes( 802.11a/n/ac ) has been tested and the worst( Antenna 1,802.11ac(VHT20)) result recorded was report as below:

|       |             |
|-------|-------------|
| Mode: | 11AC20 5180 |
|-------|-------------|




## Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| 1   | 65.9259     | 38.50          | -18.24        | 20.26          | PK       | 40.00          | 19.74       | Vertical |
| 2   | 72.7227     | 37.42          | -19.21        | 18.21          | PK       | 40.00          | 21.79       | Vertical |
| 3   | 166.9069    | 52.24          | -19.17        | 33.07          | PK       | 43.50          | 10.43       | Vertical |
| 4   | 590.2503    | 32.67          | -6.97         | 25.70          | PK       | 46.00          | 20.30       | Vertical |
| 5   | 705.7958    | 31.26          | -6.14         | 25.12          | PK       | 46.00          | 20.88       | Vertical |
| 6   | 836.8769    | 31.16          | -4.74         | 26.42          | PK       | 46.00          | 19.58       | Vertical |

## Final Data List

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 65.9259     | -18.24        | 19.56             | 40.00             | 20.44          |
| 2   | 72.7227     | -19.21        | 16.23             | 40.00             | 23.77          |
| 3   | 166.9069    | -19.17        | 31.80             | 43.50             | 11.70          |
| 4   | 590.2503    | -6.97         | 24.43             | 46.00             | 21.57          |
| 5   | 705.7958    | -6.14         | 23.53             | 46.00             | 22.47          |
| 6   | 836.8769    | -4.74         | 25.55             | 46.00             | 20.45          |

|       |             |
|-------|-------------|
| Mode: | 11AC20 5180 |
|-------|-------------|




## Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| 1   | 159.1391    | 50.49          | -19.47        | 31.02          | PK       | 43.50          | 12.48       | Horizontal |
| 2   | 162.0521    | 52.48          | -19.37        | 33.11          | PK       | 43.50          | 10.39       | Horizontal |
| 3   | 356.2462    | 38.51          | -12.35        | 26.16          | PK       | 46.00          | 19.84       | Horizontal |
| 4   | 420.3303    | 38.70          | -11.87        | 26.83          | PK       | 46.00          | 19.17       | Horizontal |
| 5   | 453.3433    | 40.10          | -10.64        | 29.46          | PK       | 46.00          | 16.54       | Horizontal |
| 6   | 810.6607    | 34.83          | -5.32         | 29.51          | PK       | 46.00          | 16.49       | Horizontal |

## Final Data List

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 159.1391    | -19.47        | 29.67             | 43.50             | 13.83          |
| 2   | 162.0521    | -19.37        | 32.47             | 43.50             | 11.03          |
| 3   | 356.2462    | -12.35        | 25.20             | 46.00             | 20.80          |
| 4   | 420.3303    | -11.87        | 25.87             | 46.00             | 20.13          |
| 5   | 453.3433    | -10.64        | 29.22             | 46.00             | 16.78          |
| 6   | 810.6607    | -5.32         | 29.27             | 46.00             | 16.73          |

|       |             |
|-------|-------------|
| Mode: | 11AC20 5200 |
|-------|-------------|




## Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| 1   | 63.984      | 37.32          | -17.98        | 19.34          | PK       | 40.00          | 20.66       | Vertical |
| 2   | 70.7808     | 37.23          | -18.90        | 18.33          | PK       | 40.00          | 21.67       | Vertical |
| 3   | 166.9069    | 52.75          | -19.17        | 33.58          | PK       | 43.50          | 9.92        | Vertical |
| 4   | 582.4825    | 32.96          | -7.34         | 25.62          | PK       | 46.00          | 20.38       | Vertical |
| 5   | 714.5345    | 31.30          | -6.14         | 25.16          | PK       | 46.00          | 20.84       | Vertical |
| 6   | 722.3023    | 32.03          | -6.14         | 25.89          | PK       | 46.00          | 20.11       | Vertical |

## Final Data List

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 63.984      | -17.98        | 18.38             | 40.00             | 21.62          |
| 2   | 70.7808     | -18.90        | 17.37             | 40.00             | 22.63          |
| 3   | 166.9069    | -19.17        | 33.34             | 43.50             | 10.16          |
| 4   | 582.4825    | -7.34         | 24.10             | 46.00             | 21.90          |
| 5   | 714.5345    | -6.14         | 23.64             | 46.00             | 22.36          |
| 6   | 722.3023    | -6.14         | 24.04             | 46.00             | 21.96          |

|       |             |
|-------|-------------|
| Mode: | 11AC20 5200 |
|-------|-------------|




## Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| 1   | 159.1391    | 49.81          | -19.47        | 30.34          | PK       | 43.50          | 13.16       | Horizontal |
| 2   | 172.7327    | 51.82          | -18.92        | 32.90          | PK       | 43.50          | 10.60       | Horizontal |
| 3   | 420.3303    | 38.97          | -11.87        | 27.10          | PK       | 46.00          | 18.90       | Horizontal |
| 4   | 452.3724    | 39.00          | -10.68        | 28.32          | PK       | 46.00          | 17.68       | Horizontal |
| 5   | 574.7147    | 33.79          | -7.73         | 26.06          | PK       | 46.00          | 19.94       | Horizontal |
| 6   | 840.7608    | 33.09          | -4.63         | 28.46          | PK       | 46.00          | 17.54       | Horizontal |

## Final Data List

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 159.1391    | -19.47        | 28.90             | 43.50             | 14.60          |
| 2   | 172.7327    | -18.92        | 31.14             | 43.50             | 12.36          |
| 3   | 420.3303    | -11.87        | 25.34             | 46.00             | 20.66          |
| 4   | 452.3724    | -10.68        | 26.56             | 46.00             | 19.44          |
| 5   | 574.7147    | -7.73         | 25.01             | 46.00             | 20.99          |
| 6   | 840.7608    | -4.63         | 28.13             | 46.00             | 17.87          |

|       |             |
|-------|-------------|
| Mode: | 11AC20 5240 |
|-------|-------------|




## Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| 1   | 65.9259     | 37.98          | -18.24        | 19.74          | PK       | 40.00          | 20.26       | Vertical |
| 2   | 70.7808     | 37.60          | -18.90        | 18.70          | PK       | 40.00          | 21.30       | Vertical |
| 3   | 166.9069    | 51.72          | -19.17        | 32.55          | PK       | 43.50          | 10.95       | Vertical |
| 4   | 589.2793    | 32.81          | -7.02         | 25.79          | PK       | 46.00          | 20.21       | Vertical |
| 5   | 647.5375    | 32.84          | -7.31         | 25.53          | PK       | 46.00          | 20.47       | Vertical |
| 6   | 844.6446    | 31.15          | -4.45         | 26.70          | PK       | 46.00          | 19.30       | Vertical |

## Final Data List

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 65.9259     | -18.24        | 18.30             | 40.00             | 21.70          |
| 2   | 70.7808     | -18.90        | 17.98             | 40.00             | 22.02          |
| 3   | 166.9069    | -19.17        | 31.83             | 43.50             | 11.67          |
| 4   | 589.2793    | -7.02         | 24.74             | 46.00             | 21.26          |
| 5   | 647.5375    | -7.31         | 25.20             | 46.00             | 20.80          |
| 6   | 844.6446    | -4.45         | 26.37             | 46.00             | 19.63          |

|       |             |
|-------|-------------|
| Mode: | 11AC20 5240 |
|-------|-------------|



## Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| 1   | 159.1391    | 49.80          | -19.47        | 30.33          | PK       | 43.50          | 13.17       | Horizontal |
| 2   | 169.8198    | 53.56          | -19.06        | 34.50          | PK       | 43.50          | 9.00        | Horizontal |
| 3   | 420.3303    | 39.01          | -11.87        | 27.14          | PK       | 46.00          | 18.86       | Horizontal |
| 4   | 452.3724    | 37.99          | -10.68        | 27.31          | PK       | 46.00          | 18.69       | Horizontal |
| 5   | 841.7317    | 32.59          | -4.58         | 28.01          | PK       | 46.00          | 17.99       | Horizontal |
| 6   | 946.5966    | 31.92          | -3.17         | 28.75          | PK       | 46.00          | 17.25       | Horizontal |

## Final Data List

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 159.1391    | -19.47        | 29.59             | 43.50             | 13.91          |
| 2   | 169.8198    | -19.06        | 33.43             | 43.50             | 10.07          |
| 3   | 420.3303    | -11.87        | 26.07             | 46.00             | 19.93          |
| 4   | 452.3724    | -10.68        | 26.96             | 46.00             | 19.04          |
| 5   | 841.7317    | -4.58         | 26.38             | 46.00             | 19.62          |
| 6   | 946.5966    | -3.17         | 27.12             | 46.00             | 18.88          |

----- END OF REPORT -----