

Test Report

Report No.: MTi240103011-03E1

Date of issue: 2024-04-24

Applicant: Dongguan Lingdu Electronic Technology Co.,Ltd

Product: Dash Cam

Model(s): LD2K, LD4K, LD03, LD05, E21, E22, PG17, PG19X,
PG02S-R, PG18S, PG16S-3CH

FCC ID: 2BEAP-LD2K

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.



Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Environmental Conditions	7
1.4	Description of support units	7
1.5	Measurement uncertainty	7
2	Summary of Test Result	8
3	Test Facilities and accreditations	9
3.1	Test laboratory	9
4	List of test equipment.....	10
5	Evaluation Results (Evaluation).....	11
5.1	Antenna requirement	11
6	Radio Spectrum Matter Test Results (RF)	12
6.1	Occupied Bandwidth	12
6.2	Maximum Conducted Output Power.....	13
6.3	Power Spectral Density	14
6.4	RF conducted spurious emissions and band edge measurement	15
6.5	Band edge emissions (Radiated)	16
6.6	Radiated emissions (below 1GHz)	33
6.7	Radiated emissions (above 1GHz).....	37
	Photographs of the test setup	44
	Photographs of the EUT.....	45
	Appendix A: DTS Bandwidth	47
	Appendix B: Maximum conducted output power.....	52
	Appendix C: Maximum power spectral density.....	53
	Appendix D: Band edge measurements	58
	Appendix E: Conducted Spurious Emission	61
	Appendix F: Duty Cycle	73


Test Result Certification	
Applicant:	Dongguan Lingdu Electronic Technology Co.,Ltd
Address:	No.1, Longcheng Street, Qingxi Town, Dongguan City, Guangdong Province, China
Manufacturer:	Dongguan Lingdu Electronic Technology Co.,Ltd
Address:	No.1, Longcheng Street, Qingxi Town, Dongguan City, Guangdong Province, China
Product description	
Product name:	Dash Cam
Trade mark:	N/A
Model name:	LD2K
Series Model(s):	LD4K, LD03, LD05, E21, E22, PG17, PG19X, PG02S-R, PG18S, PG16S-3CH
Standards:	47 CFR Part 15.247
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02
Date of Test	
Date of test:	2024-03-19 to 2024-04-23
Test result:	Pass

Test Engineer :




(Yanice Xie)

Reviewed By: :



(David Lee)

Approved By: :



(Leon Chen)

1 General Description

1.1 Description of the EUT

Product name:	Dash Cam
Model name:	LD2K
Series Model(s):	LD4K, LD03, LD05, E21, E22, PG17, PG19X, PG02S-R, PG18S, PG16S-3CH
Model difference:	All the models are the same circuit and module, except the model name.
Electrical rating:	Input:DC 12-24V Output:DC 5V/2.5A
Accessories:	1. Rear camera(6m cable) *1 2. USB Car charger(3.5m cable)*1 3. Cable clips*5 4. Wire Trim tool*1
Hardware version:	V0.2
Software version:	LD2K-DA380-230612LDCVRX1
Test sample(s) number:	MTi240103011-03S1001
RF specification	
Operating frequency range:	802.11b/g/n20:2412~2462 MHz 802.11n40:2422~2452 MHz
Channel number:	11
Modulation type:	IEEE 802.11b : DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna(s) type:	FPC Antenna
Antenna(s) gain:	4.6dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX-802.11b
Mode2	TX-802.11g
Mode3	TX-802.11N20
Mode4	TX-802.11N40

1.2.1 Operation channel list

Test Channel List

Operation Band: 2400-2483.5 MHz

Bandwidth (MHz)	Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
20	2412	2437	2462
40	2422	2437	2452

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software:

For power setting, refer to below table.

Mode	2412MHz	2437MHz	2462MHz
802.11b	50	50	50
802.11g	60	60	60
802.11n20	60	60	60
Mode	2422MHz	2437MHz	2452MHz
802.11n40	41	41	41

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
Accumulator	6-QW-45(370)-L	/	Camzel Group Co., Ltd.
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Occupied channel bandwidth	±3 %
RF output power, conducted	±1 dB
Power Spectral Density, conducted	±1 dB
Unwanted Emissions, conducted	±1 dB
Radiated spurious emissions (above 1GHz)	±5.3dB
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Requirement	Result
1	Antenna requirement	47 CFR 15.203	Pass
2	Occupied Bandwidth	47 CFR 15.247(a)(2)	Pass
3	Maximum Conducted Output Power	47 CFR 15.247(b)(3)	Pass
4	Power Spectral Density	47 CFR 15.247(e)	Pass
5	RF conducted spurious emissions and band edge measurement	47 CFR 15.247(d), 15.209, 15.205	Pass
6	Band edge emissions (Radiated)	47 CFR 15.247(d), 15.209, 15.205	Pass
7	Radiated emissions (below 1GHz)	47 CFR 15.247(d), 15.209, 15.205	Pass
8	Radiated emissions (above 1GHz)	47 CFR 15.247(d), 15.209, 15.205	Pass
9	Conducted Emission at AC power line	47 CFR 15.207(a)	N/A

Notes:

1.N/A means not applicable.

Since the EUT power by DC supply, therefore AC power line conducted emissions test is not required.

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2023-04-26	2024-04-25
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2023-04-25	2024-04-24
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2023-04-25	2024-04-24
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2023-04-25	2024-04-24
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2023-04-26	2024-04-25
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2023-04-26	2024-04-25
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2023-05-05	2024-05-04
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2023-04-25	2024-04-24
9	DC Power Supply	Agilent	E3632A	MY40027695	2023-05-05	2024-05-04
Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2023-06-17	2025-06-16
3	Amplifier	Agilent	8449B	3008A01120	2023-06-26	2024-06-25
4	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
5	MXA signal analyzer	Agilent	N9020A	MY54440859	2023-06-01	2024-05-31
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2023-06-11	2025-06-10
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2023-04-25	2024-04-24
5	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached. The EUT complies with the requirement of FCC PART 15.203.
--

6 Radio Spectrum Matter Test Results (RF)


6.1 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	a) Set RBW = 100 kHz. b) Set the VBW \geq [3 × RBW]. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	59 %	Atmospheric Pressure:	98 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.1.2 Test Setup Diagram:



6.1.3 Test Data:

Please Refer to Appendix for Details.


6.2 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	59 %	Atmospheric Pressure:	98 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	59 %	Atmospheric Pressure:	98 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.3.2 Test Setup Diagram:



6.3.3 Test Data:


Please Refer to Appendix for Details.

6.4 RF conducted spurious emissions and band edge measurement

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	59 %	Atmospheric Pressure:	98 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.4.2 Test Setup Diagram:

6.4.3 Test Data:

Please Refer to Appendix for Details.


6.5 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.		
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	54 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.					

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2310.000	51.49	-12.83	38.66	74.00	-35.34	peak
2		2310.000	42.27	-12.83	29.44	54.00	-24.56	AVG
3		2390.000	54.80	-12.42	42.38	74.00	-31.62	peak
4	*	2390.000	45.81	-12.42	33.39	54.00	-20.61	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2310.000	51.97	-12.83	39.14	74.00	-34.86	peak
2		2310.000	42.08	-12.83	29.25	54.00	-24.75	AVG
3		2390.000	54.07	-12.42	41.65	74.00	-32.35	peak
4	*	2390.000	43.52	-12.42	31.10	54.00	-22.90	AVG

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2483.500	58.70	-12.44	46.26	74.00	-27.74	peak
2	*	2483.500	51.20	-12.44	38.76	54.00	-15.24	AVG
3		2500.000	56.41	-12.35	44.06	74.00	-29.94	peak
4		2500.000	46.58	-12.35	34.23	54.00	-19.77	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2483.500	58.67	-12.44	46.23	74.00	-27.77	peak
2	*	2483.500	50.41	-12.44	37.97	54.00	-16.03	AVG
3		2500.000	55.42	-12.35	43.07	74.00	-30.93	peak
4		2500.000	46.09	-12.35	33.74	54.00	-20.26	AVG

Mode2 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	52.12	-12.83	39.29	74.00	-34.71	peak
2		2310.000	42.82	-12.83	29.99	54.00	-24.01	AVG
3		2390.000	64.54	-12.42	52.12	74.00	-21.88	peak
4	*	2390.000	48.88	-12.42	36.46	54.00	-17.54	AVG

Mode2 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	52.15	-12.83	39.32	74.00	-34.68	peak
2		2310.000	41.76	-12.83	28.93	54.00	-25.07	AVG
3		2390.000	64.87	-12.42	52.45	74.00	-21.55	peak
4	*	2390.000	49.76	-12.42	37.34	54.00	-16.66	AVG

Mode2 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2483.500	74.89	-12.44	62.45	74.00	-11.55	peak
2	*	2483.500	61.84	-12.44	49.40	54.00	-4.60	AVG
3		2500.000	66.89	-12.35	54.54	74.00	-19.46	peak
4		2500.000	51.40	-12.35	39.05	54.00	-14.95	AVG

Mode2 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2483.500	73.78	-12.44	61.34	74.00	-12.66	peak
2	*	2483.500	61.06	-12.44	48.62	54.00	-5.38	AVG
3		2500.000	63.92	-12.35	51.57	74.00	-22.43	peak
4		2500.000	49.83	-12.35	37.48	54.00	-16.52	AVG

Mode3 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	52.39	-12.83	39.56	74.00	-34.44	peak
2		2310.000	42.43	-12.83	29.60	54.00	-24.40	AVG
3		2390.000	66.69	-12.42	54.27	74.00	-19.73	peak
4	*	2390.000	51.64	-12.42	39.22	54.00	-14.78	AVG

Mode3 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	51.62	-12.83	38.79	74.00	-35.21	peak
2		2310.000	41.65	-12.83	28.82	54.00	-25.18	AVG
3		2390.000	64.37	-12.42	51.95	74.00	-22.05	peak
4	*	2390.000	48.85	-12.42	36.43	54.00	-17.57	AVG

Mode3 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2483.500	74.91	-12.44	62.47	74.00	-11.53	peak
2	*	2483.500	61.65	-12.44	49.21	54.00	-4.79	AVG
3		2500.000	65.93	-12.35	53.58	74.00	-20.42	peak
4		2500.000	51.43	-12.35	39.08	54.00	-14.92	AVG

Mode3 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2483.500	73.25	-12.44	60.81	74.00	-13.19	peak
2	*	2483.500	60.22	-12.44	47.78	54.00	-6.22	AVG
3		2500.000	63.90	-12.35	51.55	74.00	-22.45	peak
4		2500.000	49.14	-12.35	36.79	54.00	-17.21	AVG

Mode4 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 40 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	51.08	-12.83	38.25	74.00	-35.75	peak
2		2310.000	42.12	-12.83	29.29	54.00	-24.71	AVG
3		2390.000	62.49	-12.42	50.07	74.00	-23.93	peak
4	*	2390.000	49.66	-12.42	37.24	54.00	-16.76	AVG

Mode4 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 40 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	51.37	-12.83	38.54	74.00	-35.46	peak
2		2310.000	41.75	-12.83	28.92	54.00	-25.08	AVG
3		2390.000	62.00	-12.42	49.58	74.00	-24.42	peak
4	*	2390.000	48.33	-12.42	35.91	54.00	-18.09	AVG

Mode4 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 40 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2483.500	66.49	-12.44	54.05	74.00	-19.95	peak
2	*	2483.500	56.01	-12.44	43.57	54.00	-10.43	AVG
3		2500.000	58.90	-12.35	46.55	74.00	-27.45	peak
4		2500.000	49.80	-12.35	37.45	54.00	-16.55	AVG

Mode4 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 40 / CH: H


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2483.500	64.49	-12.44	52.05	74.00	-21.95	peak
2	*	2483.500	54.97	-12.44	42.53	54.00	-11.47	AVG
3		2500.000	56.96	-12.35	44.61	74.00	-29.39	peak
4		2500.000	45.68	-12.35	33.33	54.00	-20.67	AVG


6.6 Radiated emissions (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.6.1 E.U.T. Operation:


Operating Environment:			
Temperature:	24 °C	Humidity:	54 %
		Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4		
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report		
Note:	The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.		

6.6.2 Test Setup Diagram:





6.6.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		72.0843	44.73	-11.27	33.46	40.00	-6.54	QP	
2		96.0985	46.41	-10.55	35.86	43.50	-7.64	QP	
3	*	119.8556	48.02	-9.22	38.80	43.50	-4.70	QP	
4	!	191.7450	47.61	-9.86	37.75	43.50	-5.75	QP	
5		239.9873	46.19	-6.89	39.30	46.00	-6.70	QP	
6	!	348.0274	44.71	-4.37	40.34	46.00	-5.66	QP	

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		47.9940	40.93	-7.51	33.42	40.00	-6.58	QP	
2		96.0986	46.73	-10.55	36.18	43.50	-7.32	QP	
3	!	119.8556	47.95	-9.22	38.73	43.50	-4.77	QP	
4	*	131.7577	50.85	-11.77	39.08	43.50	-4.42	QP	
5		191.7450	45.04	-9.86	35.18	43.50	-8.32	QP	
6	!	287.9904	46.48	-5.60	40.88	46.00	-5.12	QP	

6.7 Radiated emissions (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.7.1 E.U.T. Operation:

Operating Environment:			
Temperature:	24 °C	Humidity:	54 %
		Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4		
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report		
Note: Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported.			

6.7.2 Test Setup Diagram:


6.7.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4824.000	58.06	-7.42	50.64	74.00	-23.36	peak
2		4824.000	56.63	-7.42	49.21	54.00	-4.79	AVG
3		7236.000	46.97	0.75	47.72	74.00	-26.28	peak
4		7236.000	45.60	0.75	46.35	54.00	-7.65	AVG
5		9648.000	48.18	2.34	50.52	74.00	-23.48	peak
6	*	9648.000	46.98	2.34	49.32	54.00	-4.68	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4824.000	53.07	-7.42	45.65	74.00	-28.35	peak
2		4824.000	51.74	-7.42	44.32	54.00	-9.68	AVG
3		7236.000	50.28	0.75	51.03	74.00	-22.97	peak
4	*	7236.000	48.93	0.75	49.68	54.00	-4.32	AVG
5		9648.000	47.88	2.34	50.22	74.00	-23.78	peak
6		9648.000	46.67	2.34	49.01	54.00	-4.99	AVG

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4874.000	54.80	-7.44	47.36	74.00	-26.64	peak
2		4874.000	53.56	-7.44	46.12	54.00	-7.88	AVG
3		7311.000	48.85	0.70	49.55	74.00	-24.45	peak
4		7311.000	47.62	0.70	48.32	54.00	-5.68	AVG
5		9748.000	48.39	3.03	51.42	74.00	-22.58	peak
6	*	9748.000	47.18	3.03	50.21	54.00	-3.79	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4874.000	55.64	-7.44	48.20	74.00	-25.80	peak
2		4874.000	54.56	-7.44	47.12	54.00	-6.88	AVG
3		7311.000	50.96	0.70	51.66	74.00	-22.34	peak
4	*	7311.000	49.75	0.70	50.45	54.00	-3.55	AVG
5		9748.000	47.97	3.03	51.00	74.00	-23.00	peak
6		9748.000	46.65	3.03	49.68	54.00	-4.32	AVG

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4924.000	53.11	-7.37	45.74	74.00	-28.26	peak
2		4924.000	51.72	-7.37	44.35	54.00	-9.65	AVG
3		7386.000	49.32	1.06	50.38	74.00	-23.62	peak
4		7386.000	48.19	1.06	49.25	54.00	-4.75	AVG
5		9848.000	48.42	2.75	51.17	74.00	-22.83	peak
6	*	9848.000	47.37	2.75	50.12	54.00	-3.88	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4924.000	54.21	-7.37	46.84	74.00	-27.16	peak
2		4924.000	52.72	-7.37	45.35	54.00	-8.65	AVG
3		7386.000	50.38	1.06	51.44	74.00	-22.56	peak
4	*	7386.000	49.26	1.06	50.32	54.00	-3.68	AVG
5		9848.000	47.70	2.75	50.45	74.00	-23.55	peak
6		9848.000	46.41	2.75	49.16	54.00	-4.84	AVG

Photographs of the test setup

Refer to Appendix - Test Setup Photos for MTi240103011-03E1.docx

Photographs of the EUT

Refer to Appendix - EUT Photos


Appendix


Appendix A: DTS Bandwidth

Test Result


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	9.080	0.5	PASS
		2437	9.040	0.5	PASS
		2462	9.040	0.5	PASS
11G	Ant1	2412	16.560	0.5	PASS
		2437	16.560	0.5	PASS
		2462	16.560	0.5	PASS
11N20SISO	Ant1	2412	16.560	0.5	PASS
		2437	16.520	0.5	PASS
		2462	16.560	0.5	PASS
11N40SISO	Ant1	2422	36.400	0.5	PASS
		2437	36.320	0.5	PASS
		2452	36.320	0.5	PASS

Test Graphs







11G Ant1_2437




11G Ant1_2462



11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO Ant1_2437



11N40SISO Ant1_2452



Appendix B: Maximum conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Peak Power [dBm]	Conducted Limit [dBm]	Verdict
11B	Ant1	2412	15.19	≤30.00	PASS
		2437	15.67	≤30.00	PASS
		2462	15.53	≤30.00	PASS
11G	Ant1	2412	13.35	≤30.00	PASS
		2437	14.03	≤30.00	PASS
		2462	14.21	≤30.00	PASS
11N20SISO	Ant1	2412	13.29	≤30.00	PASS
		2437	14.00	≤30.00	PASS
		2462	14.20	≤30.00	PASS
11N40SISO	Ant1	2422	6.48	≤30.00	PASS
		2437	7.01	≤30.00	PASS
		2452	7.20	≤30.00	PASS


Appendix C: Maximum power spectral density

Test Result


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-13.35	≤8.00	PASS
		2437	-13.69	≤8.00	PASS
		2462	-14.16	≤8.00	PASS
11G	Ant1	2412	-15.14	≤8.00	PASS
		2437	-14.39	≤8.00	PASS
		2462	-14.50	≤8.00	PASS
11N20SISO	Ant1	2412	-15.12	≤8.00	PASS
		2437	-14.47	≤8.00	PASS
		2462	-14.78	≤8.00	PASS
11N40SISO	Ant1	2422	-20.88	≤8.00	PASS
		2437	-20.06	≤8.00	PASS
		2452	-19.75	≤8.00	PASS

Test Graphs







11G Ant1_2437




11G Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437



11N20SISO_Ant1_2462






11N40SISO_Ant1_2422




Appendix D: Band edge measurements

11B Ant1 Low 2412


11B Ant1 High 2462

11G Ant1 Low 2412

11G Ant1 High 2462




11N20SISO Ant1 Low 2412




11N20SISO Ant1 High 2462




11N40SISO Ant1 Low 2422




11N40SISO Ant1 High 2452




Appendix E: Conducted Spurious Emission







11B_Ant1_2437_30~1000




11B_Ant1_2437_1000~26500




11B_Ant1_2462_0~Reference




11B Ant1_2462_30~1000




11B Ant1_2462_1000~26500




11G Ant1_2412_0~Reference



11G Ant1_2412_30~1000




11G Ant1_2412_1000~26500




11G Ant1_2437_0~Reference



11G Ant1_2437_30~1000




11G Ant1_2437_1000~26500




11G Ant1_2462_0~Reference




11G Ant1_2462_30~1000




11G Ant1_2462_1000~26500




11N20SISO Ant1_2412_0~Reference




11N20SISO Ant1 2412 30~1000




11N20SISO Ant1 2412 1000~26500




11N20SISO Ant1 2437 0~Reference




11N20SISO Ant1 2437_30~1000




11N20SISO Ant1 2437_1000~26500




11N20SISO Ant1 2462_0~Reference




11N20SISO Ant1 2462 30~1000




11N20SISO Ant1 2462 1000~26500




11N40SISO Ant1 2422 0~Reference




11N40SISO Ant1 2422 30~1000




11N40SISO Ant1 2422 1000~26500




11N40SISO Ant1 2437 0~Reference




11N40SISO Ant1 2437 30~1000




11N40SISO Ant1 2437 1000~26500




11N40SISO Ant1 2452 0~Reference



11N40SISO Ant1 2452 30~1000



11N40SISO Ant1 2452 1000~26500



Appendix F: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Factor
11B	Ant1	2437	19.00	19.00	100.00	0.00
11G	Ant1	2437	19.00	19.00	100.00	0.00
11N20SISO	Ant1	2437	19.00	19.00	100.00	0.00
11N40SISO	Ant1	2437	19.00	19.00	100.00	0.00

Notes:

Duty Cycle [%] = Transmission Duration [ms] / Transmission Period [ms] * 100

Factor = 10 * log (Duty Cycle)

----End of Report----