

# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

## 1.1 Client Information

### Client Information

Applicant: Guangzhou Yiming Electronic Technology Co., LTD  
Address of applicant: 302, Building 2, Meidong Industrial Park, Tieshanhe Road, Sandong Avenue,

Manufacturer: Guangzhou Yiming Electronic Technology Co., LTD  
Address of manufacturer: 302, Building 2, Meidong Industrial Park, Tieshanhe Road, Sandong Avenue,

### General Description of EUT

Product Name: Projector  
Trade Name: /  
Model No.: Q9  
Q3, Q7, Q8, Q10, M1 pro, M2 pro, M3 pro, M4 pro, M5 pro, M6 pro, M7 pro, M8 pro, M9 pro, V1 pro, V2 pro, V3 pro, V4 pro, V5 pro, V6 pro, V7 pro, V8 pro, V9 pro, A1, A2, A3, A4, A5, A6, A7, A8, A9, ZX1, ZX6, ZX7, ZX8, ZX9, Z9, Z10, i5, i6, i7, i8, i9, F1, F2, F3, F6, F8, F9, X1-PRO, X1-MAX, X6, X6-PRO, X6-MAX, X8, X8-PRO, X8-MAX, X9, X9-PRO, X9-MAX, X10, X10-PRO, X10-MAX, S6, S7, S8, S9, S10, Q6 Pro, A8X, A8X Pro  
Adding Model(s):  
Rated Voltage: AC 120V/60Hz  
Power Adapter Model: /  
Serial number: S-01  
FCC ID: 2BEB5-Q9

### Technical Characteristics of EUT

Support Standards: 802.11b, 802.11g, 802.11n  
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)  
2422-2452MHz for 802.11n(HT40)  
RF Output Power: 16.15dBm (Conducted)  
Type of Modulation: DBPSK, BPSK, DQPSK, QPSK, 16QAM, 64QAM  
Quantity of Channels: 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)  
Channel Separation: 5MHz  
Type of Antenna: Integral Antenna  
Antenna Gain: 2.32dBi

## 1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

### (a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

### (b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: \* = Plane-wave equivalents power density

## 1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 1.4 MPE Calculation Result

Maximum peak output power: 16.15 (dBm)

Tune-Up output power: 17(dBm), 50.12(mW)

Prediction distance: >20(cm)

Prediction frequency: 2412 (MHz)

Antenna gain: 2.32 (dBi)

Directional gain: 1.71(numeric)

The worst case is power density at prediction frequency at 20cm: 0.017(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

$0.017(\text{mw}/\text{cm}^2) < 1 (\text{mw}/\text{cm}^2)$

So the transmitter complies with the RF exposure requirements and the SAR is not required.